ZZ-R-765/8


21 February 1986

FEDERAL SPECIFICATION SHEET

RUBBER, SILICONE; CHANNEL, NONMETALLIC

This specification is approved by the Assistant Administrator, Office of Federal Supply and Services, General Services Administration, for the use of all Federal agencies.

The complete requirements for procuring the channels described herein shall consist of this document and the latest issue of ZZ-R-765/GEN.



PART NO. ZZR765/8-	LENGTH
001B6	4.90
002A6	5.62
003B6	1.00

NOTES:
1. Dimensions are in inches.
2. Nonmetallic Hardness Rating: 55.0 min. and 65.0 max. Shore Durometer A.
3. Minimum Tensile Strength: 650 psi.
4. Material Transparency: Any Acceptable.
5. Color: Natural.
6. Temperature Rating: -73°C to 218.5°C (-100°F and 425°F).
7. When metric units are required, units for inch and psi may be converted to the metric equivalent as follows:

English	Multiply by	Equals	Metric unit
inch	2.54	=	centimeter (cm)
psi	6.894 X 10-3	=	mega pascal (MPa)


AMSC: N/A

/FSC 9320/

DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:26Z
Check the source to verify that this is the current version before use.

PART NUMBERING SYSTEM FOR FEDERAL SPECIFICATION ZZ-R-765/GEN



MILITARY INTERESTS:

Custodians

Army -- MR
Navy -- AS
Air Force -- 20

Review activity

DLA -- GS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA -- FSS

PREPARING ACTIVITY:

Army -- MR

Project No. 9320-0360

(KBWP# ID-7059A/DISK-0555A. FOR AMMRC USE ONLY).

☆U S GOVERNMENT PRINTING OFFICE 1986 — 605 036/40979

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:26Z
Check the source to verify that this is the current version before use.