INCH-POUND


MIL-PRF-27/146D
w/AMENDMENT 1
1 November 2016
SUPERSEDING
MIL-PRF-27/146D
28 September 2012


PERFORMANCE SPECIFICATION SHEET

TRANSFORMERS AND INDUCTORS (AUDIO, POWER, AND HIGH-POWER PULSE), INDUCTORS, HIGH Q

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the transformer described herein shall consist of this specification sheet and MIL-PRF-27.






ALTITUDE 75.000 FT. MAX.

(SEE TABLE I FOR VALUE OF "X")

CIRCUIT DIAGRAM AND MARKING



Dim	Inches	mm
A	.360 Dia. Max	9.14 Dia. Max
B	.200 ±.010	5.08 ±.25
C	.025 Dia. lead (2 required)	.64 Dia. lead (2 required)
D	1.250 ±.125	31.75 ±3.18
E	.250 Max	6.35 Max

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking shall be on the side of the case.

FIGURE 1. Dimensions and configurations

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:38Z
Check the source to verify that this is the current version before use.

REQUIREMENTS: (When numbers in parentheses, such as (1-2) are used, they indicate the winding and the extreme terminals of the winding.)

Electrical ratings: See table I.

Inductance (1-2): Table I, at 0.1 V rms, 1 kHz, 0 dc.

Working voltage: 175 volts peak.

Design and construction:

Dimensions and configuration: See figure 1.

Case: Epoxy molded.

Material: Diallyl phthalate.

Terminals: Tin-lead plated type D4 in accordance with MIL-STD-1276.

Weight: 1.3 grams, maximum.

Altitude: 75,000 feet, maximum.

Operating temperature range: -55°C to +105°C.

Terminal strength: MIL-STD-202-211, test condition A, 2 pounds.

Dielectric withstanding voltage:

At sea level: 500 volts rms.

At reduced barometric pressure: 300 V rms.

Vibration (high frequency): MIL-STD-202-204, test condition D.

TABLE I Electrical ratings.

Dash Number 1/	(1-2) Inductance (max) mH ±2%	(1-2) DC current (max) mA 2/	(1-2) DC resistance (max) at 25˚C Ohms	(1-2) Quality factor		
				Q Min	Voltage (rms)	Frequency (kHz)
01	1	60	1.4	26	1.0	15
02	5	28	7	30	1.0	15
03	10	20	11	32	1.0	15
04	25	13	38	32	1.0	15
05	50	9	75	32	1.0	15
06	100	6	132	32	1.0	15

1/ Qualification testing and approval to M27/146-06 shall be sufficient to grant qualification approval to M27/146-01 through M27/146-06.
2/ The dc current is the amount of current that will reduce the inductance 10 percent maximum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:38Z
Check the source to verify that this is the current version before use.

Marking location: See figure 1.

Part or Identification Number (PIN): M27/146-(dash number from table I).

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-PRF-27, this document references the following:

MIL-STD-202-204 MIL-STD-202-211 MIL-STD-1276

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5950-2016-025)

Review Activities:
Army - AR, CR4, MI
Navy - AS, MC, OS, SH
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:38Z
Check the source to verify that this is the current version before use.