MIL-C-48115A(AR)
AMENDMENT 3
26 July 1985
SUPERSEDING
AMENDMENT 2
4 March 1985

MILITARY SPECIFICATION

CARTRIDGE, 40mm. HEDP,M430;
SPITBACK ASSEMBLY FOR METAL PARTS AND
LOADING, ASSEMBLING AND PACKAGING

This amendment forms a part of Military Specification MIL-C-48115A(AR), dated 29 March 1976, and is approved for use by the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

Delete preamble and substitute the following:

"This specification is approved for use by the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense."

PAGE 2

Delete: "DRAWINGS (see 6.6) US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND" and substitute "DRAWINGS (see 6.6) US ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER"

PAGE 3

* 4.3.1 Delete:

"Loading Composition 9276547 8oz."
Unconsolidated Material

PAGE 4

* TABLE I Delete:

"Loading Composition

| | |
|---|---|
| Determination of Calcium Resinate | 4.5.2.1 |
| Determination of Graphite Content | 4.5.2.2 |
| Determination or RDX | 4.5.2.3 |
| Moisture Content | 4.5.3" |

FSC 1310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

PAGE 8

4.4.2.3

* Delete: "Major 101" in its entirety.

* Major 102, Change "RDX" to CH6"

Delete "Minor 201" in its entirety.

PAGE 9

4.4.2.4

* Delete "Major 104" in its entirety

Change Major 105 to read "charge above or below flush"

PAGE 10

* Delete "4.5.2., 4.5.2.1" in their entirety

PAGE 11

* Delete "4.5.2.2" in its entirety

PAGE 12

* Delete 4.5.2.3 and 4.5.3" in their entirety

4.5.4 Delete in its entirety and substitute the following:

"4.5.4 Functioning. The spitback assembly shall be assembled to a HE loaded cartridge for which it is standard. The cartridge shall be fired from a launcher for which it is standard to impact on sand placed at 200 meters from the launcher. Observation shall be made for proper functioning (see 3.5). If any fuze duds occur, replacement samples must be fired."

5.1.1 Delete "Level C" and substitute "Level B"

5.2.1 Delete "Level C" and substitute "Level B"



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

6.3 Delete "DRDAR-QAA-I, ARRADCOM" and substitute "ARDC, ATTN: AMSMC-QAF-S(D)"

Add the following new paragraph:

"6.6 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Research and Development Center (ARDC), may also include drawings prepared by and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or ARRADCOM drawings. Technicla data originally prepared by these activities is now under tha cognizance ARDC."

This admendment is marked with an asterick to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Goverment assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous amendment.

Custodian:
Army-AR

Preparing Activity
Army-AR

(Project 1310-A365)



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.