INCH-POUND
MIL-C-48139B (AR)
AMENDMENT 4
09 August 1996
SUPERSEDING
AMENDMENT 3
07 August 1995

MILITARY SPECIFICATION

CARTRIDGE, 105MM, TPDS-T, M724A1
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-C-48139B (AR), dated 15 March 1990, and is approved for use by the U.S. Army Armament Research, Development and Engineering Center and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.2: Add "12935041 - Cartridge, 105MM, TPDS-T, M724A1, (SWCC) Assembly and Marking Diagram."

PAGE 3

3.2: After "9278500" add "12935041".

3.3: Between last two words, "propellant" and "used" add "and type of cartridge case".

3.4: Delete: "...at a load between 1300 pounds and 4,000 pounds." and substitute:

"...between the following loads: Deep Drawn Cartridge Case, Dwg. 9278500 - 1,300 to 4,000 lbs.; Spiral Wrapped Cartridge Case, Dwg. 12935041 - 1,000 to 4,000 lbs."

3.5 Delete in its entirety.

3.6 Delete in its entirety and substitute:

"3.6 Rotating band seating. the gap between the sabot and the rotating band shall not exceed the maximum requirement as stated on drawing 11738367."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

PAGE 7

Table I Drawing Number block, add: “/12935041”.

PAGE 8

Table I: Drawing Number block, add: “/12935041”.

PAGE 9

Table I: Drawing Number block, add: “/12935041”.

PAGE 12

4.4.2.1: Next Higher Assembly block, add: “/12935041”.

PAGE 13

4.4.2.2: Drawing Number block, add: “/12935041”.

PAGE 14

4.4.2.3: Next Higher Assembly block, add: “/12935041”.

Add: “107 Gap between rotating band and sabot 100% 3.1 Gage”.

PAGE 15

4.4.2.4: Delete major characteristic 105 in its entirety.

Drawing Number block, add: “/12935041”.

* Add the following Major defects:

“107	Maximum gap between the projectile lip and the case lip after crimping	100%	3.1	Gage
108	Cartridge case crimped on top of projectile lip	100%	3.1	Visual”.

PAGE 19

4.4.3.3: first sentence, delete “...drawing 9278500.” and substitute “...drawings 9278500 and 12935041.”

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.

PAGE 22

4.5.3: Delete in its entirety.

4.5.4: Delete in its entirety and substitute:

"4.5.4 Rotating Band Seating. a feeler gage shall be inserted between the forward edge of the rotating band and the rear edge of the sabot flange. The gage must not enter more than one fourth (90° - 5°) of the projectile circumference in total. Any assembly which fails this requirement must be retightened and reinspected."

PAGE 23

4.5.6.1.1: delete in its entirety and substitute the following:

"4.5.6.1.1 General. Sample cartridges shall be fired from a fixed-type facility mount with an M1 or M60A3 recoil utilizing a muzzle boresight or from an M1 or M60A3 tank with a gunner's auxiliary sight. An M68A1 gun tube shall be utilized as specified in Table I. All fixed type facility mounts and tank systems must be properly maintained and validated prior to testing."

PAGE 29

6.11: Delete the definition for secondary land wear limits:

"Between 70° and 40° of primary land wear"

and substitute:

"Between 70° and 140° of primary land wear".

NOTE: the margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1315-0140)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.