MILITARY SPECIFICATION

GUN, MACHINE, BROWNING, CALIBER .30, M1919A6 (WITH SPARE PARTS)

1. SCOPE

1.1 This specification covers one type of Browning, Caliber .30, Machine Gun, with shoulder stock and bipod mount, and known as Gun, Machine, Browning, Caliber .30, M1919A6.

2. APPLICABLE DOCUMENTS

2.1 The following specifications, standards, drawings, and publications, of the issue in effect on date of invitation for bids, form a part of this specification:

SPECIFICATIONS

MILITARY

MIL-P-12362 - Packaging of Machine Gun Browning, Caliber .30, M1919A6

U. S. ARMY

52-O-1 - General Specification Governing the Manufacture and Inspection of Small Arms Weapons, Spare and Replacement Parts, and Accessories

DRAWING

ORDNANCE CORPS

D7142395 - Gun, Machine, Caliber .30, Browning, M1919A6

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:59Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

ORDNANCE CORPS

ORD-SIP-S6 - Ordnance Standard Inspection Procedure for Guns, Machine, Caliber .30, Browning, M1917A1, M1919A4 Fixed and Flexible, M1919A5 Fixed, and M1919A6

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Parts.

3.1.1 Materials.- Materials shall conform to the applicable drawings and specifications, or shall be approved by the procuring agency.

3.1.2 Manufacture.

3.1.2.1 General.- Braxing, welding, heat-treatment, protective coatings for corrosion protection, riveting, staking, and other manufacturing processes shall be as specified in the applicable drawings and Specification 52-0-1.

3.1.3 Additional specific requirements.

3.1.3.1 Barrel.- The enlargement of the chamber due to proof-firng shall not exceed 0.001 inch. After proof-firing, the dimensions of the chamber and bore shall not exceed the limits shown on the applicable drawing.

3.1.3.2 Bolt.- Following proof-firing, dimensions of the bolt shall be within the limits shown on applicable drawing, with no set-back of the face. All operating surfaces shall be smooth and free from any defects which may affect its functioning. The T-slot shall be free from any roughness which may intensify the collection of brass particles during feeding or extraction of cartridge cases.

3.1.3.3 Cover assembly.- The belt feed lever, slide, and pawl shall function smoothly when assembled to feed from either left-hand or right-hand side.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:59Z
Check the source to verify that this is the current version before use.

3.1.3.4 Extractor assembly. The extractor assembly shall pivot smoothly in the bolt. The ejector and the extractor cam plunger shall act freely under their spring tension.

3.1.3.5 Driving spring rod assembly. The driving spring rod assembly shall move freely in the bolt when both are assembled in the casing assembly.

3.1.3.6 Firing pin assembly. The firing pin assembly shall slide freely in the bolt. There shall be no hand-stoning of the striker point. The sear engaging notch shall have a fine finish and the forward edge shall be sharp and free of wire edges and burrs.

3.1.3.7 Springs.- All springs shall be capable of gymnastication testing in accordance with the applicable drawings.

3.1.3.8 Locking devices. All locking devices shall maintain proper adjustment during firing and during handling of the weapon.

3.1.3.9 Other parts.- All other parts shall conform to the dimensions within the limits shown on the applicable drawings.

3.2 Manufacturing assemblies.- An assembly consisting of two or more parts combined for machining or other operations shall conform to the requirements specified for individual parts.

3.3 Spare parts. - When specified, machine guns shall be accompanied by a proportional quantity of spare parts. The quantity of each part furnished shall be as specified by the procuring activity. (See 6.1.)

3.4 Assembled guns.

3.4.1 The gun shall be assembled as shown on the applicable drawings and in a manner to meet the following requirements before and after all firing tests.

3.4.1.1 Cocking lever. The cocking lever shall retract the sear engaging notch of the firing pin not less than 0.010 inch beyond the engaging point of the sear.

3.4.1.2 Firing pin protrusion. The firing pin shall protrude from the face of the bolt 0.060 to 0.068 inch when in the forward or firing position.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:59Z
Check the source to verify that this is the current version before use.

3.4.1.3 Timing. The timing of the gun shall be such that the firing pin cannot be released when the distance between the forward edge of the barrel extension and the trunnion block is 0.120 inch, and such that the firing pin can be released before this distance is reduced to 0.030 inch.

3.4.1.4 Trigger pull. The trigger pull necessary to operate the gun shall be 7 to 12 pounds when measured at the center of the bow in a line at right angles to the bore and parallel with the side plates. The measurement may be made with the back plate removed. The weapons submitted to the endurance test specified herein shall be capable of meeting at least 75 percent of the original specified trigger pull upon completion of the endurance test.

3.4.1.5 Headspace.- Each completed weapon shall be within the proper headspace requirements when gaged with a .123-inch "go" and .128-inch "not go" gage.

3.4.1.6 Cyclic rate.- The rate of fire shall be within the range of 425 to 550 rounds per minute using U. S. Government caliber .30 standard service ball ammunition when firing from the bipod mount. The normal rate may be expected to be within the range of 500 to 650 rounds per minute when mounted on a rigid test stand approved by the Government inspector.

3.5 Marking.

3.5.1 Completed weapons.- Unless otherwise specified, each gun shall be marked in the position and size specified on the drawings and as specified in Specification 52-0-1.

3.5.2 Components.- Components and assemblies shall be marked with the manufacturer's symbol, the Ordnance part number only, or both, as specified on the part number identification drawing or the individual part drawing.

3.6 Gymnastication.- Each completed gun shall be placed in a gymnastication fixture furnished by the contractor and mechanically gymnasticated for a minimum of 500 cycles prior to any firing tests.

3.7 Proof-firing.

3.7.1 Assembled guns.- Each gun shall be capable of withstanding proof-firing with one U. S. Government high pressure proof cartridge without structural failures or distortions that would affect functioning of the weapon.

3.7.2 Spare barrels, barrel extensions, and bolts. – Each barrel, barrel extension, and bolt intended as spare parts shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:59Z
Check the source to verify that this is the current version before use.

be proof-fired using one proof cartridge each. Fixtures for proof-firing these parts shall be provided by the contractor. Following proof-firing, these parts shall meet the requirements specified herein and on the drawings.

3.8 Function firing.- Each assembled gun shall be capable of withstanding the function firing test specified herein, with no breakages or malfunctions of the gun or bipod mount, using standard U. S. Government caliber .30 ball ammunition in metallic belts.

3.9 Endurance firing.- Assembled guns shall be capable of withstanding an endurance test of 10,000 rounds when tested as specified herein. Breakages and malfunctions shall be limited to those specified in table I. U. S. Government standard caliber .30 ball ammunition, in metallic belts, shall be used in the test.

3.10 Accuracy.- Accuracy of the weapons shall be such that at least nine rounds of a 10-round burst, fired full machine gun action, shall group within a 3-inch circle when fired at a 100-foot range. Rounds that cut the edge of the 3 inch circle shall be considered as acceptable.

3.11 Lubrication.- Each machine gun shall be adequately lubricated throughout all firing tests and prior to Government acceptance. (See 6.3.)

3.12 Workmanship.- Standards of workmanship shall be such that equipment will meet the requirements of 3.1 through 3.11. All components, subassemblies, parts, and the final assembly shall meet the inspection requirements for defects in quality and dimensions as specified in 4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:59Z
Check the source to verify that this is the current version before use.

TABLE I.- Malfunctions, broken parts, and nonacceptable conditions

Malfunctions and nonacceptable conditions	Number permitted in the endurance test	
	First 5000 rounds	Second 5000 rounds
Enlarged firing pin hole	0	0
Extruded primers, enlarged firing pin hole	0	2
Failure of latch	1	1
Failure to close, due to any gun component	0	1
Failure to eject	1	2
Failure to extract cartridge case from chamber	0	1
Failure to extract cartridge from feed belt	0	1
Failure to feed, bullet striking face of barrel	0	1
Failure to feed, insufficient recoil	0	0
Failure of trigger to release	0	0
Faulty trigger pull	0	NP[1].
Hangfire, noticeable	0	0
Misfire	1	2
Pierced primer	0	1
Partial ignition	0	0
Ruptured cartridge case	0	1
Uncontrolled fire	0	0
Other malfunctions, total	3	6
Broken or Unserviceable Parts		
Accelerator, broken	0	0
Barrels, eroded	0	NP[1].
Barrel extension, broken	0	0
Belt, broken	0	0
Cocking lever, broken, burred, or worn	0	0
Cams, broken	0	0
Ejector, broken	0	1
Extractor assembly, broken, burred, or deformed	0	0
Extractor cam, broken or burred	0	0
Firing pin, broken	1	1
Firing pin spring, broken or set	0	1
Rivets, loose	0	0
Belt feed pawl, broken or burred	0	0
Belt feed slide, broken or burred	0	0
Sear, broken	0	1
Sear contacts, defective	0	1
Side or bottom plates, spread or broken	0	0
Striker point, defective	0	NP[1].
Setback in face of bolt	0	0
All other broken parts	0	8

[1]. NP indicates no penalty if encountered during the endurance test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:59Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Lot size.

4.1.1 Guns.- The lot size of completely assembled guns, or complete sets of parts, components, and assemblies therefor submitted for inspection, shall be as determined by the Government inspector and contractor based upon existing conditions and facilities.

4.1.2 Spare parts.- When spare parts are specified by the contract, the lot size of those parts submitted for inspection shall be any quantity, but not less than a quantity proportional to the lot of completely assembled guns submitted for final inspection.

4.2 Sampling.

4.2.1 Guns.- Unless otherwise specified herein for firing tests, inspection and functional tests shall be performed on each gun. Unless otherwise specified; non-conformance to drawings and all specified requirements shall constitute a critical defect and shall result in the rejection of the gun, until such defect has been corrected.

4.2.2 Parts.- Sampling procedures for less than 100 percent inspection shall be in accordance with the standard sampling procedures of ORD-SIP-S6.

4.2.3 Acceptance or rejection.- The classification of defects and acceptable quality levels (AQL's) of ORD-SIP-S6 shall be used as the basis for acceptance or rejection of an inspection lot.

4.3 Inspection.- Inspection shall be performed in accordance with Specification 52-O-1, ORD-SIP-S6, and this specification.

4.4 Gaging.

4.4.1 Firing pin protrusion.- Each machine gun shall be gaged to determine conformance with firing pin protrusion requirement. The guns shall be gaged before and after the firing tests. Any gun not meeting this requirement shall be rejected.

4.4.2 Headspace.- Each gun shall be gaged to determine that the specified headspace requirement has been met. The guns shall meet this requirement before and after proof-firing, after each 4,000 rounds in the endurance test, and upon completion of the endurance test without further adjustment. Any gun not meeting this requirement shall be rejected.

Source: https://assist.dla.mil - Downloaded: 2026-10-18T00:59Z
Check the source to verify that this is the current version before use.

4.4.3 Trigger pull.- The trigger pull of each machine gun shall be measured to determine compliance with the trigger pull requirement specified herein. Any gun not meeting this requirement shall be rejected.

4.5 Tests.- Tests shall be performed in accordance with Specification 52-0-1, ORD-SIP-S6, and this specification.

4.5.1 Proof-firing test.- Each assembled machine gun and each spare barrel, barrel extension, and bolt shall be proof-fired using one caliber .30 M1 high pressure test cartridge for each gun or part tested.

4.5.1.1 Any stoppage or failure of any part shall be cause for rejection of the gun or of the part being tested. The chamber and the bore of the barrel shall be gaged after proof-firing to determine compliance with the requirements specified herein and on the drawings. If the parts specified above are found acceptable, proof marks shall be stamped in the locations specified on the drawings.

4.5.2 Function firing test.- All weapons that have successfully completed the specified proof-firing test shall be function fired according to the following schedule.

4.5.2.1 The first 100 guns produced under each contract shall be fired 100 rounds each. Firing shall be in interrupted bursts except that one continuous burst of 25 rounds shall be fired from each weapon.

4.5.2.2 Every tenth gun produced thereafter shall be fired 75 rounds each with not less than 20 rounds fired in one continuous burst.

4.5.2.3 All other guns produced shall be fired a total of 35 rounds each in interrupted or continuous bursts.

4.5.2.4 Any breakage or malfunction of any of the guns shall be cause for rejection of the gun being function fired. In addition, if the breakage or malfunction occurs in a weapon being fired in the 35 round schedule, the next 10 weapons shall be function fired in the 75 round schedule as specified herein. If these 10 weapons pass the 75 round test successfully, the original schedule specified herein shall be reapplied.

4.5.2.4.1 Malfunctions or stoppages resulting from defective ammunition or links in any firing test shall not be charged against the weapon being tested.

4.5.3 Rate of fire.- The cyclic rate of fire shall be determined for every tenth gun produced, the test shall be conducted concurrently with the function firing test. The rate of fire

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:59Z
Check the source to verify that this is the current version before use.

shall be within the ranges specified herein. Failure to meet the cyclic rate requirements shall be cause for determining the cyclic rate on the next ten guns. If the 10 guns pass the test successfully, the test procedure shall revert back to schedule specified above. Failure to meet the cyclic rate with each of the 10 guns shall reject the lot represented by the test weapons.

4.5.4 Endurance test.- The endurance test shall be conducted according to the following schedule.

4.5.4.1 One gun from the first 100 weapons produced shall be subjected to an endurance test of 10,000 rounds. Firing shall be at the rate of approximately 50 rounds per minute, in bursts not exceeding 20 rounds. The test weapon shall be allowed to air-cool for 5 minutes after each 500 rounds and for 10 minutes after each 1000 rounds.

4.5.4.2 When the test weapon representing the initial 100 guns has successfully passed the above test, one gun from each succeeding tenth lot of 500 weapons shall also be fired in the 10,000 round schedule specified in 4.5.4.1.

4.5.4.3 All other lots shall be tested by subjecting one weapon from each lot to a 5,000 round endurance test. The conditions of firing shall be the same as for the 10,000 round test.

4.5.4.4 Test weapons shall be cleaned and oiled after every 500 rounds but no parts shall be altered or replaced except for broken parts or those parts worn to the extent of unserviceability. A record shall be kept of each replacement.

4.5.4.5 The lot from which the test weapon was drawn shall be acceptable if the test weapon withstands the endurance test within the limits specified in table I.

4.5.4.6 The test weapons submitted to the endurance test shall not be accepted by the Government until they have been thoroughly reconditioned by the contractor.

4.5.5 Accuracy test.- One gun from each lot of guns shall be submitted to an accuracy test. The gun shall be mounted on a fixed rest approved by the inspector or on a standard caliber .30 tripod mount fastened to a suitable base. The gun shall be fired on a 100 foot range to determine compliance with accuracy requirements. Guns which fail to meet this requirement shall be rejected and the lot shall be screened for the defect. One additional gun from the same lot shall then be tested for accuracy with the lot accepted or rejected on the performance of this second gun.

4.6. Retests.- Weapons rejected in any inspection or test, except in the endurance test, may be conditioned and resubmit-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:59Z
Check the source to verify that this is the current version before use.

ted for the inspection or test in which failure occurred. The Government inspector may, in addition, subject the resubmitted guns to such other tests as he deems necessary. If resubmission is allowed, the entire lot of guns shall be checked and conditioned for the failure or failures.

4.6.1 A retest shall be allowed in the case of guns rejected because of failure in the endurance test unless, in the opinion of the Government inspector, the failure or failures indicate serious defects in the lot of guns. In such a case, a retest shall be made only if authorized by the contracting officer and after the entire lot has been reconditioned where necessary. In the event that a retest is made, the Government inspector shall take at random from the rejected lot a weapon to be subjected to the same endurance test. Failure of the weapon in retest shall be cause for final rejection of the lot.

4.7 Final acceptance.- The weapons shall be finally accepted after having passed the inspections and tests specified herein, been stamped with the inspector's stamp and with the Ordnance Inspection Stamp, and packed for shipment as specified herein.

5. PREPARATION FOR DELIVERY

5.1 Weapons.- The assembled weapons shall be prepared for shipment as specified in Specification MIL-P-12362.

5.2 Spare parts.- Spare parts shall be packaged and packed in accordance with the spare parts packaging drawing furnished by the contracting officer. (See 6.1)

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Title, number, and date of applicable drawings.
c. List of spare parts, when required. (See 3.3.)
d. Site of inspections and tests.
e. Spare parts packaging drawings. (See 5.2.)

6.2 Suggested contractural features.

6.2.1 Serial numbers.- The contractor should be furnished a block of serial numbers to be used for weapon identification. (See 3.5.1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:59Z
Check the source to verify that this is the current version before use.

6.2.2 Description of manufacture. Upon request, the contractor should be furnished a description of manufacture previously employed in the manufacture of this weapon.

6.2.3 Additional drawings and specifications. Upon request, with reasons therefor, the contractor should be furnished any referenced drawings and specifications he may desire, in addition to those originally furnished by the contracting officer as necessary for the materiel contracted for.

6.3 Lubrication. Lubrication Order L09-244 should be furnished the contractor to facilitate correct lubrication.

6.4 Safety during firing. Care is essential to assure safety during firing. The chamber and bore should be dry, clean, and free of obstructions. Proof cartridges should be shaken to verify that the powder is loose before using. In the event of a hangfire, the action of the gun should not be opened for at least 30 seconds, and then should be opened rapidly by means of a lanyard taking precautions for the safety of personnel.

6.5 Defective ammunition. If defective ammunition of any type is encountered in any firing test, the Commanding Officer, Frankford Arsenal, should be notified and samples submitted for examination and information.

6.6 Defective belt links. If defective belt links are encountered in any firing test, the Commanding Officer, Rock Island Arsenal, should be notified and samples submitted for examination and information.

Notice: This specification, together with specifications and drawings pertaining to it and bearing a "NOTICE" of similar restrictions, is intended for use only in connection with procurement by the United States Government, and shall not be reproduced either wholly or in part except when authorized in connection with Government procurement, nor be used for any other purpose except when specifically authorized by the Chief of Ordnance.

Custodian:

Army - Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:59Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

COMMANDING OFFICER
FRANKFORD ARSENAL
ATTN: SMUFA-N1100
PHILA., PA. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:59Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)* | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT
$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE C-8278

Source: https://assistdocs.com - Downloaded: 2026/01/18T00:59Z
Check the source to verify that this is the current version before use.