MILITARY SPECIFICATION

MOUNT, TELESCOPE, T191

1. SCOPE

1.1 This specification covers a mount used to support Telescope T156 in Tank, 90MM Gun, M48.

2. APPLICABLE DOCUMENTS

2.1 The following specification and drawing, and specifications and drawings referenced thereon, of the issue in effect on date of invitation for bids, form a part of this specification.

SPECIFICATION

U. S. ARMY

51-7 Instruments, Fire-Control; General Specification Governing the Manufacture and Inspection of

DRAWING

ORDNANCE CORPS

F8201501 Mount, Telescope, T191

(Copies of specifications standards drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer)

3. REQUIREMENTS

3.1 General requirements - General requirements and associated tests common to all fire control instruments as specified in Specification 51-7 shall be mandatory.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:58Z
Check the source to verify that this is the current version before use.

3.2 Materials - Materials shall be in accordance with the applicable drawings, and specifications forming part of this specification.

3.3 Movement - The horizontal and vertical knobs of the Housing Assembly shall be set at the (2) position (mid-point) when the rear bracket is set at center of travel. The mount assembly then shall have sufficient movement to accommodate maximum and minimum travel of the knobs from their midpoints.

3.4 Backlash - Backlash in either of the boresight knobs shall not exceed 3/8 inch movement as measured on the periphery of the knob scales.

3.5 Torque

3.5.1 The torque required to rotate the unlocked boresite knobs shall not exceed 10 pound-inches.

3.5.2 Illumination - The signal light shall be checked for functional requirement when connected to a 24 volt source.

3.6 Temperature - Temperature requirements and test Type III in Specification 51-7 shall apply, except minus 40°F shall be substituted for minus 45°F. The torque value specified herein shall apply at all temperatures.

3.7 Workmanship - Workmanship shall be in accordance with Specification 51-7.

4. QUALITY ASSURANCE PROVISIONS

4.1 Unless otherwise specified, each mount shall be inspected for conformance with this specification and with Specification 51-7.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking - Packaging, packing, and marking shall be in accordance with instructions forming part of the contract or furnished by the contracting officer in connection with the contract.

6. NOTES

6.1 Ordering data - Invitation for bids and contracts should specify the title, number, date of this specification and type of packing.

PATENT NOTICE: This specification, together with specifications and drawings pertaining to it and bearing a "NOTICE" of similar restrictions is intended for use only in connection with procurement by the United States Government; and shall not be reproduced either wholly or in part except

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:58Z
Check the source to verify that this is the current version before use.

when authorized in connection with Government procurement, nor be used for any other purpose except when specifically authorized by the Chief of Ordnance

CUSTODIAN:

Army - Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:58Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:58Z
Check the source to verify that this is the current version before use.