MIL-C-60810(MU)
20 July 1969

SUPERSEDING
FA-PD-MI-2680
8 July 1965

MILITARY SPECIFICATION
CATAPULT, AIRCRAFT EJECTION SEAT: M10
REMANUFACTURED METAL PARTS ASSEMBLY

1. SCOPE

1.1 This specification covers Catapult, Aircraft Ejection Seat, M10, Remanufactured Metal Parts Assembly. The assembly will ultimately be loaded and used in conjunction with other propellant actuated devices in aircrew emergency escape systems.

1.2 Items to be re-worked under this specification to the remanufactured M10 Catapult configuration shall be limited to XM10, XM10E1 and M10 Catapults.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS
Military

MIL-A-2550	- Ammunition and Special Weapons, General Specification for
MIL-C-5541	- Chemical Films and Chemical Film Materials for Aluminum and Aluminum Alloys

STANDARDS
Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-1167	- Ammunition Data Card

DRAWINGS
Munitions Command

F8596929	- Catapult, Aircraft Ejection Seat, M10, Metal Parts Assembly

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

2.1 (Cont'd)

DRAWINGS
Munitions Command

C8826676	- Box, Packing, Ammunition, for Catapult, M10 in Fiber Container, M425
C8826681	- Container, Ammunition, Fiber, M425 for Catapult, M10
IEL-8596929	- Inspection Equipment List for Catapult, Aircraft Ejection Seat, M10, Metal Parts Assembly

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2. Other publications.- The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

ASA B46.1 - Surface Texture,

(Application for copies should be addressed to the American Standards Association, 10 East 40th Street, New York, N.Y. 10016)

3. REQUIREMENTS

3.1 General.- Materials, parts and assemblies shall comply with the requirements specified on the applicable drawings and referenced specifications.

3.2 Hydrostatic pressure.- The components listed in table 1 shall withstand the corresponding internal pressure for 15 seconds, minimum, without application of any external load and shall show no evidence of leakage or mechanical failure (see 6.2).

TABLE I

Component	Hydrostatic Pressure (psi,min)
Tube, Motor	3500
Tube, Launcher	1200
Cylinder, Slider Valve and Tube, Booster Assembly	1200
Can, Bottom	1200

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

3.2.1 The launcher trunnion breech shall withstand an internal pressure of 1200 psi, minimum, for 15 seconds, minimum, without application of any external load and shall show no evidence of leakage or mechanical failure (see 6.2). The pressure shall be confined to an area such that no pressure is applied to the bottom surface of the breech.

3.3 Air pressure.- The nozzle cups in nozzle assembly shall withstand an internal pressure of 100 psi, minimum, for 15 seconds, minimum, without application of any external load and shall show no evidence of leakage or mechanical failure (see 6.2). Pressure shall be applied to inlet side of nozzle.

3.4 Metal parts assembly.- Parts shall be combined to produce an assembly which conforms to the requirements of the metal parts assembly drawing and the following:

3.4.1 Remanufactured metal parts assembly shall contain the following new components:

Ring, Retaining	MS16631-1150
O-ring	MS29513-12
O-ring	MS29513-18
O-ring	MS29513-19 (2 required)
O-ring	MS29513-147
O-ring	MS29513-228 (2 required)
O-ring	MS29513-230
O-ring	B8596908
Screw, Set	MS51963-35
Screw, Set	AN565C8H3
Screw, Set	A8597934
Spring, Can	D8596889
Pin, Valve Shear	C8596901 (4 required)
Pin, Shear	C8596910
Spring, Grain	D8596916
Wire, Lock	D8596918
Wire, Lock	D8596919
Cup, Nozzle	C8597583 (6 required) (See 6.4.2)
Can, Bottom	F8597937 (See 6.4.3)

3.4.2 Conversion of the XM10 Catapult to the latest M10 Catapult configuration shall be accomplished by replacing the following components, in addition to replacing the components listed under 3.4.1 and by modifying the following components as noted:

Delete base plate attached to nozzle

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

3.4.2 (Cont'd.)

Delete nozzle plug and plug retainer located in nozzle exit port.

Delete grain disc.

Add grain collar, Dwg. C8597664 as required by dwg. F8596929

Modify nozzle as noted in 6.4.2.

Assembly nozzle cups to nozzle as required by dwg. F8596938.

3.5 Protective finish.- Protective finish shall be in accordance with applicable specifications and drawings and shall apply to all surfaces of the component regardless of configuration. Remanufactured exterior components shall have the existing protective finish stripped and the specified protective finish re-applied(see 6.5).

3.6 Residual magnetism.- The metal parts assembly shall not deflect the indicator of the compass more than three degrees in either direction when passed in front of the compass at a distance of 6 inches (see 6.3).

3.7 Workmanship.- The requirements for workmanship are as specified on the applicable drawings, referenced specifications and the following:

3.7.1 Metal defects.- The part shall be free from cracks, splits, or other metal defects.

3.7.2 Burr.- The part shall not have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.7.3 Foreign matter.- The part or assembly shall not contain chips, dirt, grease, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

4.1.1 Quality assurance terms and definitions.- Reference shall be made to MIL-STD-109 to define the quality assurance terms used.

4.1.2 Inspection.- Inspection shall be in accordance with MIL-A-2550.

4.2 Inspection Provisions.

4.2.1 Lot.

4.2.11 Submission of Product.- The product shall be submitted in accordance with MIL-STD-105.

4.2.1.2 Size of Lot.- The shipping lots of metal parts assemblies shall consist of 1200 catapults, maximum, exclusive of test samples, provided the homogeneity requirements of inspection lots have been retained. A smaller lot may be shipped upon approval of the contracting officer.

4.2.2 Examination.- The roughness comparison specimens prescribed in ASA B46.1 shall be used as a basis of comparison for surface roughness determination. Four power (4X) magnification may be used in performing visual examination for such defects as burr and foreign matter.

4.2.2.1 Reclaimed parts.- Examination of reuseable parts, which require no reprocessing, shall be limited to inspection of defects that require visual type inspection. One hundred percent examination shall be performed for such defects. All nonconforming parts shall be reprocessed or rejected.

4.2.2.2 Reprocessed parts.- One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects contained herein, using the sampling plan and associated criteria in Tables II and III. For an individual defect (single characteristic) the criteria in Table II shall be used. For total defects within a major or minor group, the criteria in Table III shall be used. All nonconforming material shall be rejected.

TABLE II

Lot Size	Sample Size	Major		Minor	
		Accept	Reject	Accept	Reject
1 - 300	100% Examination				
301 - 1,300	110	1	2	2	3
1,301 - 3,200	150	2	3	3	4
3,201 - 8,000	225	3	4	4	5
8,001 - 22,000	300	4	5	5	6

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

TABLE III

Total allowable Defects Per Sample Size

Sample Size for Major Defects Number of Defects in Class	110	150	225	300
2 - 3	1	2	3	4
4 - 7	2	3	4	5
8 - 19	3	4	5	7
20 - 43	4	5	8	10
over 43	6	8	11	14

Sample Size for Minor Defects Number of Defects in Class	110	150	225	300
2 - 3	2	3	4	5
4 - 7	3	4	5	7
8 - 16	4	5	8	10
17 - 48	6	8	11	14
over 48	8	11	17	20

4.2.2.3 Holder, Cable, Lower, Dwg. C8596890, covering a detail of Dwg. F8596929.

Defect	Method of Inspection
CRITICAL	
None defined.	
MAJOR	
101. Pitch diameter of thread, min.	Gage
102. Major diameter of thread, min.	Gage
103. Thread damaged	Visual
104. Metal defective	Visual
105. Protective finish inadequate or defective	Visual
106. Burr or sharp corner	Visual
107. Foreign matter	Visual
MINOR	
None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

4.2.2.4 Piston Slider Valve, Drawing F8596902, covering a detail of Drawing F8596929.

Defect	Method of Inspection
CRITICAL	
None defined.	
MAJOR	
101. Metal defective	Visual
102. Protective finish, inadequate or defective	Visual
103. Burr or sharp corner, except as required	Visual
104. Foreign matter	Visual
MINOR	
None defined.	

4.2.2.5 Cap, Igniter Retaining, Drawing C8596903, covering a detail of Drawing F8596929.

CRITICAL	
None defined.	
MAJOR	
101. Thickness, max.	Gage
102. Metal defective	Visual
103. Protective finish inadequate or defective	Visual
104. Burr or sharp corner	Visual
105. Foreign matter	Visual
MINOR	
None defined.	

4.2.2.6 Pin, Firing, Dwg. D8596909, covering a detail of Drawing F8596929.

CRITICAL	
None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

4.2.2.6 (Cont'd.)

Defect	Method of Inspection
MAJOR	
101. Metal defective	Visual
102. Protective finish inadequate or defective	Visual
103. Burr or sharp corner, except as required	Visual
104. Foreign matter	Visual
MINOR	
None defined.	

4.2.2.7 Sleeve, Firing Pin, Drawing C8596915, covering a detail of Drawing F8596929.

CRITICAL	
None defined.	
MAJOR	
101. Metal defective	Visual
102. Protective finish inadequate or defective	Visual
103. Burr	Visual
104. Foreign matter	Visual
MINOR	
None defined.	

4.2.2.8 Breech, Launcher Trunnion, Drawing F8596930, covering a detail of Drawing F8596929.

CRITICAL	
None defined.	
MAJOR	
101. Pitch diameter of thread, max.	Gage
102. Minor diameter of thread, max.	Gage
103. Diameter of lug	Gage
104. Thread damaged	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

4.2.2.8 (Cont'd.)

Defect	Method of Inspection
MAJOR	
105. Metal defective	Visual
106. Protective finish inadequate or defective	Visual
107. Burr or sharp corner	Visual
108. Foreign matter	Visual
MINOR	
None defined.	

4.2.2.9 Head, Motor Tube, Drawing F8596937 covering a detail of Drawing F8596929.

CRITICAL	
None defined.	
MAJOR	
101. Pitch diameter of large thread, max.	Gage
102. Minor diameter of large thread, max.	Gage
103. Pitch diameter gas intake port thread	Gage
104. Minor diameter gas intake port thread	Gage
105. Diameter of mounting hole	Gage
106. Thread damaged	Visual
107. Metal defective	Visual
108. Protective finish inadequate or defective	Visual
109. Surface finish of chamfer on gas intake port mouth, improper	Visual
110. Burr or sharp corner	Visual
111. Foreign matter	Visual
MINOR	
None defined.	

4.2.2.10 Tube, Motor, Dwg. F8596940 covering a detail of Dwg. F8596929.

CRITICAL	
None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

4.2.2.10 (Cont'd.)

Defect	Method of Inspection
MAJOR	
101. Diameter, inside	Visual
102. Metal defective	Visual
103. Protective finish inadequate or defective	Visual
104. Burr or sharp corner	Visual
105. Foreign matter	Visual
MINOR	
None defined.	

4.2.2.11 Sleeve, Head, Dwg. F8596941, covering a detail of Dwg. F8596929.

CRITICAL	
None defined.	
MAJOR	
101. Metal defective	Visual
102. Protective finish, inadequate or defective	Visual
103. Burr or sharp corner	Visual
104. Foreign matter	Visual
MINOR	
None defined.	

4.2.2.12 Tube, Launcher, Dwg. F8596942, covering a detail of Dwg. F8596929.

CRITICAL	
None defined.	
MAJOR	
101. Pitch diameter of thread, min.	Gage
102. Major diameter of thread, min.	Gage
103. Thread damaged	Visual
104. Metal defective	Visual
105. Protective finish, inadequate or defective	Visual
106. Burr or sharp corner	Visual
107. Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

4.2.2.12 (Cont'd.)

Defect	Method of Inspection

MINOR

None defined.

4.2.2.13 Plate, Orifice, Dwg. D8597584, covering a detail of Dwg. F8596929.

CRITICAL

None defined.

MAJOR

101.	Metal defective	Visual
102.	Protective finish inadequate or defective	Visual
103.	Burr or sharp corner	Visual
104.	Foreign matter	Visual

MINOR

None defined.

4.2.2.14 Collar, Grain, Dwg. D8597664, covering a detail of Dwg. F8596929.

CRITICAL

None defined.

MAJOR.

101.	Metal defective	Visual
102.	Protective finish, inadequate or defective	Visual
103.	Burr	Visual
104.	Foreign matter	Visual

MINOR

None defined.

4.2.2.15 Can, Bottom, Dwg. F8597937, covering a detail of Dwg. F8596929.

CRITICAL

None defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

4.2.2.15 (Cont'd.)

Defect	Method of Inspection
MAJOR	
101. Pitch diameter of thread, max.	Gage
102. Minor diameter of thread, max.	Gage
103. Thread damaged	Visual
104. Metal defective	Visual
105. Protective finish inadequate or defective	Visual
106. Burr or sharp corner	Visual
107. Foreign matter	Visual
MINOR	
None defined.	

4.2.2.16 Cylinder, Slider Valve and Booster Tube Assembly, Dwg. F8596932, covering a detail of Dwg. F8596929.

CRITICAL	
None defined.	
MAJOR	
101. Metal defective	Visual
102. Protective finish inadequate or defective	Visual
103. Burr	Visual
104. Foreign matter	Visual
MINOR	
None defined.	

4.2.2.17 Nozzle, Assembly, Dwg. F8596938, covering a detail of Dwg. F8596929.

CRITICAL	
None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

4.2.2.17 (Cont'd.)

Defect	Method of Inspection
MAJOR	
101. Diameter of undercut on nozzle body, max.	Gage
102. Metal defective	Visual
103. Protective finish, inadequate or defective	Visual
104. Burr	Visual
105. Foreign matter	Visual
MINOR	
201. Diameter of undercut on nozzle body, min.	Gage
202. Cup protruding above groove in nozzle	Visual

4.2.2.18 Catapult, Aircraft Ejection Seat, M10, Metal Parts Assembly, Drawing F8596929.

CRITICAL	
None defined.	
MAJOR	
101. Any part missing, except as otherwise classified	Visual
102. Improper assembly	Visual
103. "O" Ring not lubricated	Visual
104. Thread damaged	Visual
105. Burr	Visual
106. Foreign matter	Visual
MINOR	
201. Shipping plug missing	Visual
202. Protective finish inadequate or defective	Visual

4.2.2.19 Container, Ammunition, Fiber, Drawing C8826681.

CRITICAL	
None defined.	
MAJOR	
None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

4.2.2.19 (Cont'd.)

Defect	Method of Inspection
MINOR	
201. Gap between body and cover, max.	Manual
202. Contents loose	Manual
203. Metal ends loose or distorted	Manual
204. Cut or damaged through all impregnated layers	Visual
205. Marking missing, incorrect or illegible	Visual
206. Tape incomplete or badly wrinkled	Visual
207. Length of tear tab, min.	Visual
208. Color of tape, incorrect	Visual

4.2.2.20 Box, Packing, Ammunition, Drawing C8826676.

CRITICAL

None defined.

MAJOR

None defined.

MINOR

201. Contents loose	Manual
202. Hardware missing, loose, broken or improperly engaged	Manual and Visual
203. Strapping missing, loose, broken or improperly assembled	Manual and Visual
204. Contents of box exposed	Visual
205. Box damaged	Visual
206. Marking, missing, incorrect or illegible	Visual
207. Number of units incorrect	Visual
208. Car seal missing, unsealed or improperly positioned	Visual

4.2.3 Inspection Testing.- The following tests shall be performed in accordance with the provisions of 4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

4.2.3.1 Hydrostatic pressure.- Each component listed in 3.2 shall be subjected to an internal hydrostatic pressure. Failure of any component to comply with the requirements of 3.2 shall be cause for rejection of the component.

4.2.3.1.1 Breech, launcher trunnion.- Each breech, launcher trunnion shall be subjected to a hydrostatic pressure. Failure of any component to comply with the requirements of 3.2.1 shall be cause for rejection of the component.

4.2.3.2 Air pressure.- Each nozzle assembly shall be subjected to an air pressure test. Failure of any assembly to comply with the requirements of 3.3 shall be cause for rejection of the assembly.

4.2.3.3 Protective finish, Replated components.- The number of specimens and acceptance criteria for protective finish test shall be in accordance with the applicable military standard listed on the drawing.

4.2.3.4 Residual magnetism.- Each catapult shall be tested for excessive residual magnetism. Failure of any unit to comply with 3.6 shall be cause for rejection of the catapult.

4.2.4 Inspection Equipment.- The examination and tests shall be made using equipment listed on IEL-8596929.

4.3 Test Methods and Procedures.

4.3.1 Hydrostatic pressure.- Each component listed in 3.2 and 3.2.1 shall be individually mounted in the device, using the fixtures for sealing all openings and subjected to the hydrostatic pressure to determine compliance with the requirements listed in 3.2 and 3.2.1. The breech, launcher trunnion shall be sealed such that the pressure shall be applied to an area $2\frac{1}{4}$ inches minimum, from the open end of the breech and transmit no load to the bottom surface.

4.3.2 Air Pressure.- The cup in the nozzle assembly shall be subjected to the air pressure test. The nozzle assembly shall be so placed in the fixture as to seal all openings before the air pressure is applied so that each cup will be subjected equally to the required pressure.

4.3.3 Protective finish, replated components.- Test procedures for protective finish shall be in accordance with the applicable military standard referenced on the drawing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

4.3.4 Residual Magnetism.- The catapult shall be tested for excessive residual magnetism in an area free of local magnetic effects by placing the catapult 6 inches from, and at the same height as the compass, in a north-south horizontal position with the compass set in an east-west heading. The catapult shall be moved slowly past the compass in a longitudinal direction for its entire length, rotated 180 degrees in the horizontal position and moved slowly back past the compass.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking.- (Level A).- Packing and marking shall be in accordance with drawings C8826676 and C8826681.

5.2 Data cards.- Data card information shall be as specified in MIL-STD-1167.

6. NOTES

6.1 Ordering data.- Procurement documents should specify the title, number and date of this specification.

6.2 A mechanical failure is defined as any deformation or breakage of a part, the occurrence of which is other than a design function.

6.3 When remanufacturing and loading of assembly are performed by the same facility, the residual magnetism requirement shall be performed on the loaded assembly only.

6.4 Special instructions covering modification, repair and assembly of remanufactured components are as follows:

6.4.1 Nozzle assemblies which do not contain the undercut on the nozzle body shall be modified to contain an undercut of 2.490 - .010 diameter to a length of 1.0 as shown on drawing F8596944, Section A-A and top view.

6.4.2 The nozzle cups shall be removed from the nozzle assembly and the nozzle exit port area shall be thoroughly cleaned. New nozzle cups shall be assembled in accordance with drawing F8596938.

6.4.3 The two-piece steel bottom can shall be replaced with the one-piece impact extruded aluminum can conforming to the requirements of drawing F8597937.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

6.5 Protective finish.

6.5.1 The remanufactured exterior components are as follows:

Motor tube head, drawing F8596937.

Head sleeve, drawing F8596941.

Launcher tube, drawing F8596942.

Launcher trunnion breech, drawing F8596930

6.5.2 Exposure of base metal on internal aluminum components shall be treated with a Chemical Film, Grade A or B, Class 1, MIL-C-5541.

6.6 Supersession data.- This specification includes the requirements of Purchase Description FA-PD-MI-2680 dated 8 July 1965.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1377-A202

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army

Frankford Arsenal
Philadelphia, Pa. 19137

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
Department of the Army

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-N1100
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:57Z
Check the source to verify that this is the current version before use.