MILITARY SPECIFICATION

DECONTAMINATING AND RE-IMPREGNATING KIT,

INDIVIDUAL, M13

1. SCOPE

1.1 This specification covers one type of decontaminating and re-impregnating kit.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

TT-W-572	-	Wood Preservative, Water Repellent.
PPP-B-621	-	Boxes, Wood, Nailed, and Lock Corners.
PPP-B-636	-	Box, Fiberboard.
PPP-F-320	-	Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.

MILITARY

MIL-P-116	-	Preservation, Methods of.
MIL-P-15011	-	Pallet, Material Handling, Wood, Post Construction, 4-Way Entry.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-147	-	Palletized and Containerized Unit Loads.
MIL-STD-1235	-	Single and Multi-Level Continuous Sampling.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:54Z
Check the source to verify that this is the current version before use.

DRAWINGS

US ARMY MUNITIONS COMMAND

EDGEWOOD ARSENAL

DL5-77-763 - Decontaminating and Re-Impregnating Kit, Individual, M13.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with procurement functions, should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies of these ratings, rules and regulations, should be addressed to the Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard Chicago, Illinois 60606.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing DL5-77-763 shall conform to the specifications listed thereon or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the M13 decontaminating and re-impregnating kit shall conform to the specifications and drawings listed on Drawing DL5-77-763 and subsidiary drawings.

3.1.2.1 Packet leakage. The large and small packets (Drawings C5-77-979 and C5-77-946), after filling and sealing, shall not leak when tested as specified in 4.4.4.1 and 4.4.4.2.

3.1.2.2 Dye capsule leakage. After filling and sealing, the capsule shall not leak when tested as specified in 4.4.4.3.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:54Z
Check the source to verify that this is the current version before use.

3.1.2.3 Dye capsule, damage. The dye capsule Drawing C5-77-765 shall show no evidence of damage (crushed, cracked or separated) when examined and tested as specified in 4.4.4.4.

3.1.2.4 Impregnite, weight of fill. The weight of fill of impregnite for the large bag shall be as specified on Drawing C5-77-769 when tested in accordance with 4.4.4.5.

3.1.2.5 Fuller's earth, weight of fill. The weight of fill of Fuller's earth shall be as specified on Drawing C5-77-766 when tested in accordance with 4.4.4.6.

3.1.2.6 Dye, weight of fill. The weight of fill of the dye shall be as specified on Drawing C5-77-765 when tested in accordance with 4.4.4.7.

3.1.2.7 Fuller's earth pad, heat seal. The Fuller's earth pad Drawing C5-77-766 shall show no separation or tearing when tested as specified in 4.4.4.8.

3.2 Manufacture and assembly. The kit shall be manufactured and assembled in accordance with Drawing C5-77-763.

3.3 Preproduction. Prior to the start of regular production, a preproduction lot of kits shall be produced in accordance with this specification for examination and test (see 4.3).

3.4 Workmanship. The kit and contents shall be free from damage (breaks, scratches, cracks, tears, holes, burrs, or mold protrusions) and contamination (grease, oil or dirt) that may affect the intended use of the kit. All marking or lettering shall be legible.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:54Z
Check the source to verify that this is the current version before use.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3)
(b) Quality conformance inspection (see 4.4)

4.3 Preproduction inspection.

4.3.1 Sample. A preproduction sample of 100 kits shall be manufactured using the same methods, materials, equipment and processes as will be used during regular production.

4.3.2 Examination and tests. The preproduction sample shall be examined and tested for all the requirements of the drawings and this specification.

4.3.3 Acceptance/rejection criteria. The preproduction sample shall meet all the requirements of this specification to be acceptable.

4.4 Quality conformance inspection.

4.4.1 Lotting. A lot shall consist of the kits produced by one manufacturer, at one plant, from the same materials, under essentially the same manufacturing conditions. However, no more than one lot of dye shall be represented in any one lot of finished kits.

4.4.2 Sampling.

4.4.2.1 For examination. Sampling of kits shall be conducted in accordance with MIL-STD-105.

4.4.2.2 For destructive tests. Sampling of kits shall be conducted in accordance with MIL-STD-105, level S-4.

4.4.3 Inspection procedure.

4.4.3.1 For examination. Sample components shall be examined in accordance with the classification of defects and MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:54Z
Check the source to verify that this is the currenversion before use.

4.4.3.2 For destructive tests. Sample kits shall be tested in accordance with table I and accepted in accordance with MIL-STD-105, level S-4, using an AQL as indicated.

Table I. Component tests

Item	Component	Drawing	Test	AQL
a	Packet, Large, Filled	C5-77-979	Leakage 4.4.4.1	4.0
b	Bag, Plastic, Small	C5-77-946	Leakage 4.4.4.2	1.5
c	Dye Capsule	C5-77-765	Leakage 4.4.4.3*	2.5
d	Dye Capsule	C5-77-765	Damage 4.4.4.4*	0.65
e	Impregnite	C5-77-769	Weight of fill 4.4.4.5*	4.0
f	Fullers Earth	C5-77-766	Weight of fill 4.4.4.6	2.5
g	Dye	C5-77-765	Weight of fill 4.4.4.7	2.5
h	Fuller's Earth Pad	C5-77-766	Heat seal 4.4.4.8	2.5

*Perform test on one-half of the kits selected.

Note: (1) Items b, c, e, f, g and h may be tested in-process for acceptance purposes.

(2) Items e, f and h may be accepted in accordance with MIL-STD-1235 in lieu of MIL-STD-105, level S-4. The same AQL shall apply.

4.4.3.3 Classification of defects.

(a) Decontaminating and re-impregnating kit, individual, M13 (Dwg C5-77-763).

Categories	Defects
Critical:	None defined
Major:	AQL 2.5 percent defective
101	Component missing
102	Marking incorrect or missing
103	Workmanship (3.4)

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:54Z
Check the source to verify that this is the currentversion before use.

4.4.3.3 Classification of defects (continued).

(b) Case (Dwg C5-77-836).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Outer dimensions over maximum

(c) Cover, case (Dwg C5-77-977).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Inside width
102	Inside length
103	Radius

4.4.4 Tests. Tests shall be conducted as follows:

4.4.4.1 Leakage, packet, large, filled, Dwg C5-77-979. Carefully remove the packet from the kit. Using a wire screen or similar device submerge the packet under water to a depth of 1/2-inch and draw a vacuum on the container of 10 ± 1 inch of mercury and hold for 10 - 15 seconds. Release vacuum and keep component under water for an additional 10 - 15 seconds. Remove from container and observe for water absorption in bag. Leaks resulting from tears or damage to the polyethylene bag due to removal from the can shall be disregarded.

4.4.4.2 Leakage, bag, plastic, small, filled, Dwg C5-77-946. Using a wire screen or similar device submerge the bag under water to a depth of 1/2-inch and draw a vacuum on the container of 10 ± 1 inch of mercury and hold for 10 - 15 seconds. Release vacuum and keep component under water for an additional 10 - 15 seconds. Remove from container, tear open bag and observe for water abosorption on Fuller's earth.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:54Z
Check the source to verify that this is the currentversion before use.

4.4.4.3 Leakage, dye, capsule, Dwg C5-77-765. Carefully remove the dye capsule from the cloth bags. Using a wire screen or similar device submerge the capsule under water to a depth of 1/2-inch and draw a vacuum on the container of 10 ± 1 inch of mercury and hold for 30 ± 5 seconds. Release vacuum and keep under water for an additional 30 ± 5 seconds. Remove from the container and observe for absorption of water in the capsule.

4.4.4.4 Damage, dye, capsule, Dwg C5-77-765. Carefully remove the dye capsule from the cloth bags. The capsule shall be visually inspected for damage (crushed, cracked or separated) which will allow dye to spill out when the capsule is shaken by hand.

4.4.4.5 Weight of fill, impregnite. Weigh the entire amount of impregnite from each sample bag. Record the results.

4.4.4.6 Weight of fill, Fuller's earth. Weight the Fuller's earth in the two halves of each sample separately. Record the results.

4.4.4.7 Weight of fill, dye. Wieght the entire amount of dye from each sample capsule. Record the results.

4.4.4.8 Heat seal. Insert the three middle fingers inside the loop of the Fuller's earth pad and apply tension to the heat seal area by moving the fingers apart. Any separation or tearing of the heat sealed area shall be considered cause for rejection.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Level shall be as specified (see 6.2).

5.1.1 Level A. Ten kits shall be packaged in an upright position and arranged in the most compact two by five kit pattern in a snug fitting fiberboard box. The box shall conform to a style RSC, grade W6c box of PPP-B-636. The box shall be closed as prescribed for closure of class weather-resistant boxes in the appendix to PPP-B-636.

5.1.2 Level C. The kits shall be packaged to provide adequate protection from the supply source to the first receiving activity for immediate use.

5.2 Packing. Level shall be as specified (see 6.2).

5.2.1 Level A. Ten packages of kits, packaged as specified in 5.1 and arranged in the most compact configuration, shall be packed in either a fiberboard or wood box as specified (see para 6.2). The fiberboard box shall conform to style RSC, grade V3c of PPP-B-636. The fiberboard box shall be closed by taping, reinforced by tape banding, in accordance with appendix to PPP-B-636. The wood box shall conform to style 4 1/2, class 2 overseas type 2 average load, of PPP-B-621.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:54Z
Check the source to verify that this is the currentversion before use.

The wood box shall be closed and strapped, using galvanized strapping, in accordance with appendix to PPP-B-621. All inside faces of the wood box shall be lined with fiberboard pads conforming to grade W5c or W6c of PPP-F-320. The wood box, or the finished wood parts thereof, shall have been completely immersed for a minimum period of three minutes in a water-repellent wood preservative conforming to type II composition A or TT-W-572.

5.2.2 Level C. Ten packages of kits, packaged as specified in 5.1, shall be packed to insure carrier acceptance and safe delivery to the first domestic destination. Containers shall be in accordance with Uniform Freight Classification rules and regulations of other carriers applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages and shipping containers shall be marked in accordance with MIL-STD-129.

5.4 Palletization. When specified (see 6.2) shipping containers shall be palletized in a two by three container arrangement stacked in four tiers as specified for a load type I of MIL-STD-147, using a style 1, type optional, class 1 pallet of MIL-P-15011. Wood treatment of the pallet as specified in MIL-P-15011 shall be required unless otherwise specified (see 6.2). The minimum width and thickness of the strapping specified in MIL-STD-147 shall be reissued to 1-1/4 inch and 0.035 inch respectively.

6. NOTES

6.1 Intended use. The kit covered by this specification is intended for use by the individual for decontaminating clothing and skin and for impregnating clothing against CW agents.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Level of packaging and packing required.
(c) Palletization when required.
(d) Type of shipping container required.
(e) Elimination of wood treatment for pallet, when treatment is not required.
(f) Preproduction.

(1) Time allowed for supplier submission of samples for Government test and evaluation after award of contract.
(2) Name and address of test facilities and shipping instructions when testing is performed by the Government.
(3) Time required for the Government to notify the supplier whether or not to proceed with production.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:54Z
Check the source to verify that this is the currentversion before use.

6.3 Component specifications. The specifications for the components of the M13 Decontaminating and re-impreganting kit are listed below:

MIL-I-285B - Impregnite, Unstabilized (CC2) and Stablized (XXCC3)
MIL-C-51245(MU) - Cloth, Knitted Acrylic Fiber
MIL-C-51247(MU) - Cloth, Plain Weave, Synthetic Fiber
MIL-D-51248(MU) - Dye, Chemical Agent Indicator
PROVISIONAL SPECIFICATION T. S. 600 (British Specification) - Fuller's Earth

Custodian:

Army - MU

Preparing activity:

Army - MU(EA)

Project No. 4230-A029

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:54Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:54Z
Check the source to verify that this is the current version before use.