MILITARY SPECIFICATION

PRIMER, PERCUSSION, MARK 2A4
METAL PARTS FOR

1. SCOPE

1.1 This specification covers the metal parts for one type of artillery primer designated as Primer, Percussion Mark 2A4.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons; General Specification for
MIL-I-45607 - Inspection Equipment, Supply and Maintenance of

STANDARDS

FEDERAL

TEST METHOD STANDARD NO. 151 - Metals; Test Methods.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105).
MIL-STD-109 - Quality Assurance Terms and Definitions.

FSC: 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:37Z
Check the source to verify that this is the current version before use.

MIL-STD-1168 - Lot Numbering of Ammunition.
MIL-STD-1169 - Packaging, Packing and Marking for Shipment Of Inert Ammunition Components
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes.

DRAWINGS

ARMY

8840358 - Metal Parts Assembly

PUBLICATIONS

ARMY

ET-8840358 - Equipment Tabulation

(Copies of specifications, sta dards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with applicable drawings and specifications.

3.2 Parts.-The parts shall comply with all requirements specified on Drawing (dwg.) 8840358 as applicable, and with all requirements specified in applicable specifications.

3.3 Mercurous Nitrate test.-The primer bodies shall exhibit no cracks when subjected to the mercurous nitrate test specified in 4.4.3.

3.4 Workmanship.-All parts shall be fabricated and finished in a thorough, workmanlike manner. They shall be clean and free of burrs, sharp edges, unblended radii, cracks, surface defects, chips, dirt, grease, rust and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:37Z
Check the source to verify that this is the currenversion before use.

3.5 First article inspection.-This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define the terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all quality assurance provisions specified within this specification.
b. Number of units of product inspected.
c. Results obtained, by defect code, for all inspections performed.
d. Drawing, specification number and date, together with an identification and date of changes.
e. Certificates of conformance on all material purchased by the contractor when such material is controlled by Government or commercial specifications referenced in any of the contractual documents.
f. Number of items in the lot.
g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:37Z
Check the source to verify that this is the current version before use.

4.1.2 Government verification.-Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records.

4.2 First article inspection

4.2.1 Submission.-The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with the provisions of 4.2.2. The first article sample shall consist of twenty-five assemblies and twenty-five each of every component which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including statements of findings for materials, processes and tests. A sample containing known defects will not be submitted unless specifically authorized, by the Contracting Officer. A first article sample, or portion thereof, as directed by the contracting officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

4.2.2 Inspections to be performed.-Assemblies and components will be subjected by the Government to any or all the examinations or tests specified in 4.3.2 and 4.3.3 of this specification and any or all requirements of the applicable drawings.

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:37Z
Check the source to verify that this is the current version before use.

4.2.3 Rejection.-If any assembly or component fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an assembly or component to comply with any of the stated requirements.

4.3 Inspection provisions

4.2.1 Lot formation.-The term "lot" as used throughout this specification refers to an inspection lot, which is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance of the lot with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Changes to the process, specification, or drawing not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of the lot. Inspection lots shall comply with MIL-STD-105 and shall be numbered in accordance with MIL-STD-1168. Unless otherwise approved by the contracting officer, the inspection lot size of end items deliverable under the contract shall be not less than the smallest weekly estimate of quantities contractually scheduled for production during the contract period nor more than the largest monthly quantity contractually scheduled for delivery during the contract period. Inspection lots for components or subassemblies, other than the items of delivery, shall be homogeneous and of a size mutually convenient to both the contractor and the Government inspector.

4.3.2 Examination.-Inspection for Critical defects (and Major defects, when so specified,) shall be 100 percent. Sampling plans and procedures for Major and Minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to individual characteristics listed using an AQL of 0.65 percent for each Minor defect and an AQL of 0.40 percent for each Major defect, except where 100 percent inspection is specified. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:37Z
Check the source to verify that this is the current version before use.

4.3.2.1 Body (see dwg. 8840359 covering a detail of dwg. 8840358).

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical:	None defined.		
Major:	AQL 1.5 percent		
101.	Diameter of cone cavity	Gage	01001
102.	Angle of cone seat	Gage	01002
103.	Diameter of flash hole	Gage	01003
104.	Diameter of flange	Gage	01004
105.	Diameter of primer cavity	Gage	01005
106.	Diameter under flange	Gage	01006
107.	Outside diameter at mouth	Gage	01007
108.	Profile of flange	Gage	01008
109.	Depth of primer cavity	Gage	01009
110.	Depth of charge cavity	Gage	01010
111.	Total length	Gage	01011
112.	Thickness of flange	Gage	01012
Minor:	AQL 2.5 percent		
201.	Diameter of plug cavity	Gage	01013
202.	Depth of plug cavity	Gage	01014
203.	Concentricity of primer cavity within the outside cylindrical surface	Gage	01015
204.	Concentricity of flash hole with primer cavity	Gage	01016
205.	Thickness at mouth of charge cavity	Gage	01017
206.	Evidence of poor workmanship (see 3.4)	Visual	01018

4.3.2.2 Cone (see dwg. 8840360 covering a detail of dwg. 8840358).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:37Z
Check the source to verify that this is the current version before use.

Major:	AQL 0.40 percent		
101.	Angle	Gage	02001
Minor:	AQL 1.5 percent		
201.	Total length	Gage	02002
202.	Distance from base to taper ..	Gage	02003
203.	Evidence of poor workmanship (see 3.4)	Visual	02004

4.3.2.3 Plug (see dwg. 8840361 covering a detail of dwg. 8840358).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Hole missing	Gage	03001
Minor:	AQL 1.5 percent		
201.	Diameter of hole	Gage	03002
202.	Thickness	Gage	03003
203.	Diameter	Gage	03004
204.	Location of hole	Gage	03005

4.3.2.4 Assembly (see dwg. 8840358).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Total length, max.	Gage	04001
102.	Crimp of plug not adequate ...	Visual	04002
103.	Crack or split	Visual	04003
104.	Cone not free	Manual	04004
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.4)	Visual	04005

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:37Z
Check the source to verify that this is the current version before use.

4.3.3 Testing

4.3.3.1 Hardness (see dwg. 8840359) Major defect - Code No. 01018.-Ten bodies shall be randomly selected for this test. If any sample fails to comply with the applicable requirement the lot shall be rejected. The test shall be performed as specified in 4.4.1.

4.3.3.2 Crimp of plug to body (see dwg. 8840358) Major defect - Code No. 04007.-Twenty-five assemblies shall be randomly selected for this test. If any sample fails to comply with the applicable requirement the lot shall be rejected. The test shall be performed as specified in 4.4.2.

4.3.3.3 Mercurous nitrate test. (See 3.3) Major defect - Code No. 01019.-Twenty-five bodies shall be randomly selected for this test. If any sample fails to comply with the applicable requirement the lot shall be rejected. The test shall be performed as specified in 4.4.3.

4.3.4 Inspection Equipment.-Equipment Tabulation Number ET-8840358 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.3.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspect on equipment drawings are needed.

4.3.4.2 Supply and maintenance.-Supply and maintenance of the equipment listed on the ET shall be in accordance with Specification MIL-I-45607.

4.3.4.3 Government use of contractor's inspection and test equipment.-The contractor shall make available to the Government all inspection and test equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment, and verification of its accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:37Z
Check the source to verify that this is the currentversion before use.

4.4 Test methods

4.4.1 Rockwell Hardness Test.-The primer bodies shall be tested in accordance with Federal Test Method Standard No. 151, Method 243.1.

4.4.2 Crimp of plug to body.-The assemblies shall be cut so the cone can be removed and the plug is exposed. Using equipment in accordance with 4.3.4 determine the security of the crimp of the plug to the body by applying a load in the axial direction. The rate of travel of the testing machine head shall be .100 to .125 inch per minute and record the load required to break crimp.

4.4.3 Mercurious nitrate test.-The primer bodies shall be tested in accordance with Federal Test Method Standard No. 151, Method 831. Each body shall be examined for cracks.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking

5.1.1 Level C.-Packing and marking shall be in accordance with MIL-STD-1169.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

c. First article inspection provision.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the referenced inspection equipment Lists (EL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:37Z
Check the source to verify that this is the current version before use.

6.3.1 Inspection equipment lists.-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications; mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:37Z
Check the source to verify that this is the current version before use.

and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category E, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit one copy of final designs as a rolled set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of contractor designs.-Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND7. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

Custodian:
Army-MU

Preparing activity:
Army-MU

Project Number: 1390-A589

•U.S. GOVERNMENT PRINTING OFFICE: 1967-301-509/204

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:37Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE.

To detach this form, cut along this line

DD FORM 1 OCT 64 1426

ESC-FM 2011-66

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:37Z
Check the source to verify that this is the current version before use.