MILITARY SPECIFICATION
STATIC TUBE CONTAINER H-483

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of container entitled Static Tube Container H-483 which is used with the Nike Hercules warhead section.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by by Attributes.
MIL-STD-810	- Environmental Test Methods.
MIL-STD-1168	- Lot Numbering of Ammunition.
MIL-STD-1169	- Packaging, Packing and Marking for Shipment of Inert Ammunition Components.

DRAWINGS

ORDNANCE CORPS

8785903 - Insert, Container.
8785904 - Static Tube Container H-483.
8785905 - Disk.
8785906 - Plastic Grommet.
8785907 - Externally Threaded Ring.
8785908 - Center Support.
8785913 - Shock Pad.
8785914 - Static Tube Retainer.
8785915 - Base Reinforcement.
8791666 - Humidity Indicator.
8791668 - Gasket.
8791669 - Dial Window.
8791670 - Gasket.
8791671 - Hexagon Plain Nut.
8791672 - Indicator Plate.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

8791673 - Retaining Ring.
8791682 - Indicator Housing.
8804050 - Shipping Lock.
8804060 - Open End Wrench.
8804078 - Swivel Lock.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The container shall comply with all requirements specified on the drawing (dwg) 8785904, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Environmental testing. The container shall comply with MIL-STD-810, visual inspection and failure criteria, section 3.

3.4.1 High temperature. The container shall be capable of withstanding a 240 hour storage period at a temperature of 160 ± 10°F without evidence of damage such as cracking, splitting, bulging or other deleterious deformation when tested as specified in 4.4.1.1.

3.4.2 Humidity. The container shall show no evidence of deterioration such as swelling, corrosion, erosion, pitting, loosening of parts or other damage when subjected to humidity conditions averaging from 30 to 105 percent relative humidity, and/or condensations ranging from -65 ± 5°F to 85 ± 5°F and relative humidities decreasing linearly from 30 percent at 85 ± 5°F to 5 percent at 160 ± 5°F when tested as specified in 4.4.1.2.

3.4.3 Low temperature. The container shall be capable of withstanding a 48 hour period at -80 ± 5°F and 24 hours at -65 ± 5°F without evidence of damage such as cracking, splitting or other deleterious deformation when tested as specified in 4.4.1.3.

3.5 Workmanship.

3.5.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.5.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

3.5.3 Burrs. Parts shall be free from burrs.

3.5.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.5.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 3 complete assemblies (see dwg 8785904) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table I. Tests need not be conducted in order specified in Table I.

Table I

First article inspection and tests

Inspection or Test	Dest	Non-Dest
1. Classification of characteristics (see 4.3.2.1)		X
2. High temperature (see 3.4.1)		X
3. Humidity (see 3.4.2)	X	
4. Low temperature (see 3.4.3)		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table II and Table III), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

Table II
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table III
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Hexagon plain nut (see dwg 8791671 covering details of dwg 8785904).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Width across flat surfaces (1.625 - 0.002)	Gage
Minor:		
	201. Thickness	Gage
	202. Depth of counterbore	Gage
	203. Diameter of counterbore	Gage
	204. Radius at thread and counterbore (max.)	Gage
	205. Chamfer at counterbore improper	Visual
	206. Finish improper	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

4.3.2.1.2 Indicator plate prior to forming (see dwg 8791672 covering details of dwg 8785904).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major: None defined.		
Minor:		
	201. Location of holes	Gage
	202. Diameter of holes	Gage
	203. Outside diameter	Gage

4.3.2.1.3 Indicator plate (see dwg 8791672 covering details of dwg 8785904).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
	101. Thickness	Gage
Minor:		
	201. Height	Gage
	202. Width of flange	Gage
	203. Large radius improper	Gage

4.3.2.1.4 Retaining ring (see dwg 8791673 covering details of dwg 8785904).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major: None defined.		
Minor:		
	201. Inside diameter of groove	Gage
	202. Inside diameter	Gage
	203. Total length	Gage
	204. Width of groove	Gage
	205. Location of groove	Gage
	206. Depth of slot	Gage
	207. Width of slot	Gage
	208. Finish improper	Visual
	209. Threads improperly formed	Visual
	210. Any radius improper	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

4.3.2.1.5 Indicator housing (see dwg 8791682 covering details of dwg 8785904).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Depth of groove in inside cavity shoulder	Gage
102.	Width of groove in inside cavity shoulder	Gage
103.	Finish improper on groove inside cavity shoulder surface	Gage
104.	Finish improper on groove shoulders located in the flange	Gage
105.	Inside thread improperly formed	Visual
106.	Outside thread improperly formed	Visual
Minor:		
201.	Width of outside thread undercut	Gage
202.	Depth of outside thread undercut	Gage
203.	Width of groove in flange	Gage
204.	Depth of groove in flange	Gage
205.	Width of slot	Gage
206.	Depth of slot	Gage
207.	Diameter of hole	Gage
208.	Diameter of flange	Gage
209.	Location of groove in flange	Gage
210.	Location of groove in inside cavity shoulder surface	Gage
211.	Thickness between bottom of groove at flange and forward surface of flange	Gage
212.	Location of outside thread undercut	Gage
213.	Distance between inside thread and flange shoulder	Gage
214.	Thickness between inside cavity shoulder and forward surface of flange	Gage
215.	Thickness of flange	Gage
216.	Chamfer improper at thread end (max.) (when applicable)	Gage
217.	Angle of countersink improper	Gage
218.	Corners at bottom of groove in flange not sharp	Visual
219.	Finish improper	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

4.3.2.1.6 Dial window (see dwg 8791669 covering details of dwg 8785904).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Edges chipped or cracked	Visual
Minor:		
	201. Outside diameter	Gage
	202. Thickness	Gage
	203. Taper on outside diameter (max.)	Gage
	204. Chamfer on all edges (max.) (when applicable)	Gage

4.3.2.1.7 Gasket (see dwg 8791670 and 8791668 covering details of dwg 8785904).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Thickness (min.)	Gage
	102. Split, scraped or broken	Visual
Minor:		
	201. Outside diameter (to be controlled by tool manufacturer)	Gage
	202. Inside diameter (to be controlled by tool manufacturer)	Gage

4.3.2.1.8 Humidity indicator (see dwg 8791666 covering details of dwg 8785904).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Window cracked or broken	Visual
Minor:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

4.3.2.1.9 Open end wrench (see dwg 8804060 covering details of dwg 8785904).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major: None defined.		
Minor:		
201.	Thickness	Gage
202.	Width of opening	Gage
203.	Length of opening from end to large inside radius	Gage
204.	Location of open end	Gage
205.	Location of hole	Gage
206.	Total length (min)	Gage
207.	Diameter of hole (min)	Gage
208.	Length of chamfers on edge of handle section	Gage
209.	Chamfer missing at handle end corners	Visual
210.	Any radius missing	Visual

4.3.2.1.10 Plastic grommet (see dwg 8785906 covering details of dwg 8785904).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major: None defined.		
Minor:		
201.	Outside diameter of mold	Gage
202.	Small inside mount diameter of mold	Gage
203.	Large inside mount diameter of mold	Gage
204.	Locations of disk in mold	Gage
205.	Total length	Gage
206.	Mold loose	Visual/Manual
207.	Thickness of disk	Gage

4.3.2.1.11 Disk (see dwg 8785905 covering details of dwg 8785904).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major: None defined.		
Minor:		
201.	Location of fastener holes	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

4.3.2.1.12 Externally threaded ring (see dwg 8785907 covering details of dwg 8785904).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:	None defined.	
Minor:		
201.	Thread undercut (max)	Gage
202.	Diameter of centerhole	Gage
203.	Location of rivet holes	Gage
204.	Thickness of flange	Gage
205.	Width of slot	Gage
206.	Location of slot	Gage
207.	Length of diameter between thread undercut and flange	Gage
208.	Diameter of flange	Gage
209.	Diameter of shoulder between thread undercut and flange	Gage
210.	Length from thread and surface to flange	Gage
211.	Finish improper	Gage

4.3.2.1.13 Center support (see dwg 8785908 covering details of dwg 8785904).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:	None defined.	
Minor:		
201.	Outside diameter of plastic grommet	Gage
202.	Small inside diameter of plastic grommet	Gage
203.	Large inside diameter of plastic grommet	Gage
204.	Location of disk in plastic grommet	Gage
205.	Total length	Gage
206.	Thickness of disk	Gage
207.	Plastic grommet loosely moulded to disk	Visual/Manual
208.	Cam action fastener grommet loosely assembled	Visual/Manual
209.	Retaining ring loosely assembled	Visual/Manual
210.	Assembly stud excessively loose or damaged	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

4.3.2.1.14 Shock pad (see dwg 8785913 covering details of dwg 8785904).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:	None defined.	
Minor:		
	201. Total height	Gage
	202. Outside large diameter	Gage
	203. Outside diameter at small end	Gage
	204. Thickness between inside cavity bottom and small end surface	Gage
	205. Diameter of cavity (max)	Gage
	206. Diameter of hole (max)	Gage
	207. Outside end angle missing	Visual
	208. In excess of two pieces of stock	Visual

4.3.2.1.15 Static tube retainer (see dwg 8785914 covering details of dwg 8785904).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:	None defined.	
Minor:		
	201. Width (all sides)	Gage
	202. Location of partially spherical corners	Gage
	203. Thickness	Gage
	204. Location of receptacle holes	Gage
	205. Large radius at open side missing	Visual

4.3.2.1.16 Base reinforcement (see dwg 8785915 covering details of dwg 8787905).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:	None defined.	
Minor:		
	201. Location of small holes	Gage
	202. Diameter of small holes (max)	Gage
	203. Diameter of center hole (max)	Gage
	204. Outside diameter (min)	Gage
	205. Thickness (min)	Gage
	206. Total length	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

4.3.2.1.17 Container insert (see dwg 8785903 covering details of dwg 8785904).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:	None defined.	
Minor:		
	201. Total length	Gage
	202. Length from base reinforcement to static tube retainer	Gage
	203. Length from base end to base reinforcement	Gage
	204. Outside diameter of container insert base (both ends)	Gage
	205. Length of container insert base (both ends)	Gage
	206. Diameter of hole in container insert base (both ends)	Gage
	207. Outside diameter of each support tube	Gage
	208. Location of static tube retainer with support tubes	Gage
	209. Externally threaded ring loosely riveted (including rivet missing)	Visual/Manual
	210. Any weld container undercut, crack, porosity or is inadequately formed	Visual/Manual
	211. Receptacle loosely riveted to static tube retainer	Visual/Manual
	212. Thread damaged or externally threaded ring	Visual
	213. Any support tube excessively damaged	Visual
	214. Coating improper (including bare spot or excessive scratches)	Visual
	215. Top marking improper (including incorrect color)	Visual

4.3.2.1.18 Static tube containers H483 prior to assembling humidity indicator, cover metal drum and metal drum cover locking ring (see dwg 8785904).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

Minor:

201. Diameter of humidity indicator hole....Gage
202. Depth of humidity indicator dimple.....Gage
203. Diameter at bottom of dimple.....Gage
204. Width across top of elliptical shape of dimple.....Gage
205. Radius at bottom of dimple between bottom and angled surface (max).....Gage
206. Location of humidity indicator hole from open end.....Gage
207. Location of bolt welded to bottom.....Gage
208. Any bare spots or scratches (in excess of 1/4 square inch total).....Visual

4.3.2.1.19 Static tube container H-483 prior to assembling cover metal drum and metal drum cover locking ring (see dwg 8785904).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Humidity indicator inadequately assembled (not fully seated)	Gage
	102. Center support loosely assembled to receptacles to static tube retainer	Visual/Manual
	103. Small wrench missing	Visual
	104. Open end wrench missing	Visual
Minor:		
	201. Shock pad missing (top or bottom)	Visual
	202. Container insert dented or damaged	Visual
	203. Marking incorrect, incomplete or illegible	Visual

4.3.2.1.20 Static tube container H-483 (see dwg 8785904).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Metal drum cover improperly assembled	Visual/Manual
	102. Metal drum cover locking ring improperly assembled	Visual/Manual
	103. Objective evidence relative to material missing or improper (see 3.1)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

Minor:

201.	Location of humidity indicator from welded seam	Visual
202.	Evidence of poor workmanship (see 3.5)	Visual

4.3.2.1.21 Shipping lock (see dwg 8804050 covering details of dwg 8785904).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Threads not full	Visual
102.	Evidence of poor workmanship (see 3.5)	Visual
Minor:		
201.	Angle on outside diameter of flange	Gage
202.	Width of slot	Gage
203.	Forward diameter of flange	Gage
204.	Diameter of counterbore at forward end	Gage
205.	Depth of counterbore	Gage
206.	Location of two small holes	Gage
207.	Location of threaded hole	Gage
208.	Large diameter of flange	Gage
209.	Outside diameter of rear of flange,(min)	Gage
210.	Total length, (min)	Gage
211.	Thickness of flange,(min)	Gage
212.	Radius under flange	Gage
213.	Diameter of small holes	Gage
214.	Finish improper	Visual
215.	Anodic coating improper (including color)	Visual

4.3.2.1.22 Swivel lock (see dwg 8804078 covering defects of dwg 8785904).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Adjustment screw loose or inadequate	Visual/Manual
102.	Indicating streamer insecurely attached with drive screws	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

Minor:
201. Color of indicating streamer improper.....Visual
202. Coating damaged (including bare spots or scratches in excess of 1/4 square inch).....Visual

4.3.2.1.23 Preparation for delivery (see 5).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Preservation, packaging and packing not in accordance with MIL-STD-1169	Visual
102.	Marking not in accordance with MIL-STD-1169	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.5)	Visual

4.3.3 Testing. There are no production tests applicable to the container.

4.3.4 Acceptance inspection equipment. Inspection and testing shall be performed with the acceptance test equipment, operating instructions and calibration instructions prepared by the contractor. The contractor shall obtain approval of such designs, operating instructions and special calibration instructions as specified in 6.3 prior to use on the contract.

4.3.4.1 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Environmental testing (see 3.4).

4.4.1.1 High temperature test. The static tube container shall be placed in a suitable chamber and the following 24 hour cycle shall be performed 10 times with no lapse of time between cycles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

Cumulative time (hours)	Temperature (°F)
0 - 10	90
10 - 15	Change to 160
15 - 19	160
19 - 24	Change to 90

The relative humidity shall be maintained at 15 percent or less. Upon return to room conditions, visual inspection shall reveal no evidence of deterioration or damage to the static tube container.

4.4.1.2 Humidity test.

4.4.1.2.1 Preconditioning. The static tube container shall be disassembled to the extent required to ensure thorough drying. It shall be placed in a chamber which has been preheated to 130°F and has a relative humidity of 15 percent. The static tube container shall remain in the chamber for a period of 24 hours. Immediately upon withdrawal the static tube container shall be reassembled and placed in a suitable humidity chamber and subjected to ten humidity cycles in accordance with 4.4.1.2.2 with no lapse of time between cycles.

4.4.1.2.2 Humidity cycle. While the static tube container is in the chamber, the humidity shall be maintained at 90 to 98 percent relative humidity throughout the following cycle:

a. The temperature shall be raised to 149°F within four hours and maintained at this point for eight hours.

b. The temperature shall then be reduced to 86°F within four hours and maintained at this point for 21 hours.

c. The temperature shall be reduced to 68°F within one hour and maintained at the point for four hours.

d. The temperature shall then be raised to 86°F within one hour and maintained at this point for five hours.

4.4.1.2.3 Inspection following test. Upon completion of the above tests, parts of the assembly shall be inspected for deterioration of materials, such as corrosion and potential deterioration because of accumulation of moisture.

4.4.1.3 Low temperature. The static tube assembly shall be placed in a suitable chamber. Control of humidity is not significant. The chamber temperature shall be reduced to -65°F and maintained until the temperature of the static tube assembly stabilizes (see 6.4). The temperature shall then be reduced to -80°F and held for 48 hours after which it shall be visually inspected to ensure that no damage has occurred which might ultimately result in malfunction. It shall be raised to -65°F and maintained for 24 hours or until the assembly temperature stabilizes whichever is the longer. Visual inspection shall reveal no evidence of deterioration or damage to the static tube assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The container shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.2 Level C. The container shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.2 Packing.

5.2.1 Levels A and C. The container shall be packed in accordance with the applicable instructions contained in MIL-STD-1169(MU).

5.3 Marking. Marking shall be in accordance with MIL-STD-1169(MU).

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-T.

6.4 Temperature stabilization. The temperature is considered stabilized when the greatest peaks (both highest and lowest) continually observed over 5 minutes min. do not exceed the nominal temperature plus tolerance specified.

6.5 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-1033 dated 6 June 1962.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. NUOR-A032

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-N-Q
Dover, New Jersey 07801

FOLD

3622

88%

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:30Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 2 AUG 62 WHICH MAY BE USED

Source: https://assist.dla.mil - Downloaded: 2026-02-27 19:30:07
Check the source to verify that this is the current version before use.