MILITARY SPECIFICATION

CARTRIDGE, ARMOR-PIERCING, CALIBER .30, M2

This amendment forms a part of Military Specification MIL–C–1217A, dated 20 September 1950, and was approved by the Department of the Army, the Navy, and the Air Force for use of procurement services of the respective Departments.

Page 1, paragraph 1.1: Delete "againts" and substitute "against."

Page 1, paragraph 2.2: Delete "JAN–STD–105 Sampling Inspection Tables for Inspection by attributes" and substitute "MIL–STD–105 Sampling Procedures and Tables for Inspection by Attributes."

Page 2, paragraph 3.1.3, last two lines: Delete and substitute: ", table III of Standard MIL–STD–105, as follows:"

Page 3, table I, under "*weighing*": Delete "Complete round."

Page 4, paragraph 3.2: Delete "Bulletin" and substitute "Bullet."

Page 4, paragraph 3.8: Delete "bullets" and substitute "cores of bullets."

Page 5, paragraph 4.1.1.2: Delete "of Standard MIL–STD–105" and substitute ", table III of Standard MIL–STD–105."

Page 6, paragraph 4.6: Delete "section 7–11" and substitute "section 7–13."

Page 7, paragraph 4.10: Delete "Drawing 51–74–4" and substitute "Drawing D7690962."

Page 7, paragraph 4.12: Delete and substitute:

> **"4.12 Stripping test.**—If any strips or tumbles, or both, occur, or are suspected of occurring in the accuracy, velocity, or pressure tests, a test for stripping shall be made as follows: Fire the cartridges from rifle, U. S. caliber .30, M1903A3, held in rest conforming to Drawing 49–6–40, against paper screens placed 10 feet and 50 feet in front of the muzzle of the gun. For this test, the rifle shall have been fired previously between 4,000 and 6,000 times. The headspace shall be from 1.940 to 1.946 inches, inclusive."

Custodian:
Army—Ordnance Corps
Other interest:
Army—T
Navy—O*MC*
Air Force.

905073—51—No. 464

U. S. GOVERNMENT PRINTING OFFICE: 1951

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:57Z
Check the source to verify that this is the current version before use.