MIL–L–1225A
19 SEPTEMBER 1952
SUPERSEDING
MIL–L–1225
22 July 1949

MILITARY SPECIFICATION

LAUNCHERS, GRENADE, M7A2 AND M7A3

This specification has been approved by the Departments of the Army, the Navy, and the Air Force

1. SCOPE

1.1 Scope.—This specification covers grenade launchers used with the U. S. rifle, cal. .30, M1 in discharging the rifle grenade.

1.2 Classification.—Launchers shall be of one type in the following models, as specified (see 6.1):

Launcher, grenade, M7A2
Launcher, grenade, M7A3

2. APPLICABLE SPECIFICATIONS, STANDARD, AND DRAWINGS

2.1 The following specifications, standard, and drawings, of the issue in effect on date of invitation for bids, form a part of this specification:

SPECIFICATIONS

FEDERAL

NN–B–621 —Boxes, Wood, Nailed and Lock-Corner.
UU–T–116 —Tape; Paper, Gummed, Water-Resistant.
LLL–B–631 —Boxes, Fibre, Corrugated (for Domestic Shipment).

MILITARY

JAN–P–106 —Packaging and Packing for Overseas Shipment—Boxes; Wood, Nailed.
JAN–P–108 —Packaging and Packing for Overseas Shipment—Boxes, Fiberboard (V-Board and W-Board), Exterior and Interior.
MIL–P–116 —Preservation, Methods of.
JAN–P–117 —Packaging and Packing for Overseas Shipment—Bags, Interior Packing.
JAN–B–121 —Barrier - Materials, Greaseproof.
JAN–P–125 —Packaging and Packing for Overseas Shipment — Barrier-Materials, Waterproof, Flexible.
JAN–P–133 —Packaging and Packing for overseas Shipment—Boxes, Set-up, Paperboard.
MIL–A–140 —Adhesive, Water-Resistant, Waterproof Barrier-Material.
JAN–B–148 —Barrier-Material, Aluminum-Foil.
MIL–L–644 —Lubricating-Oil, Preservative, Special.
MIL–P–3420 —Packaging Materials, Volatile Corrosion Inhibitor Treated.

STANDARD

MIL–STD–129 —Marking of Shipments.

DRAWINGS

ORDNANCE CORPS

C7265949 —Launcher, Grenade, M7A2 List of Drawings and Specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:01Z
Check source to verify that this is the current version before use.

C7266167 —Launcher, Grenade, M7A3 List of Drawings and Specifications.

U. S. ARMY

52–0–1 —General Specification Governing The Manufacture and Inspection of Small Arms Weapons, Spare and Replacement Parts, and Accessories.

57–0–2 —Finishes, Protective, For Iron and Steel Parts.

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Design and manufacture.

3.1.1 *General.*—Components and assemblies shall conform to the materials, dimensions, tolerance limits, heat treatment, degree of surface roughness, and final protective finish specified on the drawings. All surfaces shall be smooth and finished in accordance with Specification 52–0–1.

3.1.2 *Final protective finishes.*—Final protective finishes shall be as prescribed on the drawings and shall conform to the requirements of Specification 57–0–2.

3.1.3 *Markings.*—Unless otherwise specified, each launcher shall be marked in the position and of the type size specified on the drawings, and in accordance with Specification 52–0–1.

3.1.4 *Workmanship.*—Finished launchers shall be free of defects which may affect serviceability, functioning, operation, or appearance.

3.2 Pull.—Launchers shall be released from a tube or cylinder having an inside diameter equal to the maximum diameter of the grenade sleeve, by a steady pull within the range specified on the applicable drawing.

3.3 Functioning.—Grenade launchers shall withstand firing test as prescribed in 4.3.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 General procedures and inspection.

4.1.1 *Sampling.*

4.1.1.1 *Lot.*—Unless otherwise specified, a lot shall consist of not more than 2000 launchers.

4.1.1.2 *Size of inspection sample.*—The inspector may subject all or part of any lot of components or assemblies to such inspection as he deems necessary to determine compliance with this specification.

4.1.1.3 *Size of test samples.*—Unless otherwise specified, the size of test samples shall be as specified for each test.

4.1.2 *Inspection and tests, general.*

4.1.2.1 *Place.*—Unless otherwise specified, inspection and tests, excepting the function firing test, shall be performed at the plant of the prime contractor. The function firing test shall be accomplished at a Government installation to be named by the procuring agency.

4.1.2.2 *Contractor's responsibility.*

4.1.2.2.1 *Inspection.*—The contractor shall maintain an adequate system of processing, inspection, and lot identification. Only such lots which meet the requirements of this specification shall be submitted for final Government inspection.

4.1.2.2.2 *Tests.*—Unless otherwise specified, all tests specified herein, other than the function firing test, shall be performed by the contractor under the supervision of a Government inspector.

4.1.2.3 *Test rifles.*—All rifles used in the tests shall be equipped with screw, gas cylinder lock with valve, assembly (Dwg B7310079) and lock, gas cylinder (Dwg B7265871).

4.1.2.4 *Reinspection and retests.*—Launchers rejected individually or by lots because of inspection or test shall be returned to the contractor. After conditioning they may be resubmitted for inspection or test in which failure occurred and such other inspection and tests as the inspector may consider necessary.

4.1.3 *Inspection.*—Launchers shall be visually inspected for completeness of manufac-

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:01Z
Check the source to verify that this is the current version before use.

ture, assembly, finish, and workmanship. Components shall be inspected as necessary to assure compliance with drawing requirements. The functioning of latch and latch pin, chamfer of sleeve, proper staking, freedom of burrs on sleeve, and markings on bracket and sleeve shall be especially noted. Before final acceptance of any lot, the inspector shall make whatever final visual inspection deemed necessary to assure that the launchers have undergone all inspection and tests prescribed therefor, and that they have been thoroughly cleaned and prepared for shipment as required by section 5.

4.2 **Pull test.**—Each launcher shall be submitted to a pull test as specified on the applicable drawing.

4.3 **Function firing test.**—From the initial lot of launchers fabricated and found satisfactory in other tests, the inspector shall select the number of launchers specified by the procuring agency for shipment to the responsible Ordnance Corps technical center for function firing test. The function firing test shall consist of firing the number of rounds of grenades and cartridges deemed necessary by the technical center to determine the suitability of the launchers. Acceptance of the launchers shall be deferred pending the successful completion of the function firing test.

5. PREPARATION FOR DELIVERY

5.1 **Preservation.**

5.1.1 *General.*—Methods and procedures used in cleaning, preserving, and packaging launchers, gas cylinder locks, and spare parts shall conform to the general requirements of Specification MIL–P–116. Operational procedures specified herein for cleaning, preserving, and packaging shall be accomplished with a minimum of delay between steps. Fingerprint remover or gloves are not required in cleaning and preserving operations.

5.1.2 *Cleaning.*—Components and assemblies shall be thoroughly cleaned and rinsed by agitation in a two-step solvent bath conforming to method C–3 of Specification MIL–P–116. All items shall be thoroughly drained and dried before preserving.

5.1.3 *Preservative method.*

5.1.3.1 Each launcher, gas cylinder lock, and spare part shall be dipped in a bath of special preservative lubricating oil conforming to Specification MIL–L–644, maintained at a temperature of 120° F., and shall remain submerged long enough to receive a complete coating. The excess oil shall be allowed to drain thoroughly by gravity before packing.

5.2 **Packaging.**

5.2.1 *Moldable volatile corrosion inhibitor material.*—Moldable volatile corrosion inhibitor (VCI) material referred to herein shall be a light duty volatile corrosion inhibitor coated on a material that will adhere to itself, or when wrapped to conform to the contour of an object it will hold this shape in a "dead fold." The vapor corrosion inhibitor shall conform to paragraph 6.5 of Specification MIL–P–3420, and shall be laminated to a type I, grade C, greaseproof barrier-material conforming to Specification JAN–B–121 or to aluminum-foil conforming to type III or IV of Specification JAN–B–148.

5.2.2 *Launcher, grenade.*—Each launcher, with the latch folded inward, shall be completely wrapped with moldable VCI material in such a manner as to conform to the shape of the item and prevent sharp edges from puncturing the wrapper. Particular care shall be taken to prevent rupturing of the wrap around the area of the latch ends by forming sufficient thicknesses of the material around the protuberances.

5.2.3 *Lock, gas cylinder.*—Each gas cylinder lock shall be individually wrapped with moldable VCI material and inserted in a type II, class A, greaseproof bag conforming to Specification JAN–P–117. The bag shall be sealed and marked with the identification of the gas cylinder lock.

5.2.4 *Unit packages.*

5.2.4.1 *Launcher.*—One grenade launcher (wrapped) and one gas cylinder lock (bagged) shall be packaged together in a setup paperboard box conforming to Specification JAN–P–133, and shall be sealed with 60 pound kraft gummed tape. The parts shall fit snugly in the box and shall be cushioned as necessary, to prevent any free movement. The box shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:01Z
Check the source to verify that this is the current version before use.

overwrapped with waterproof barrier material conforming to Specification JAN–P–125, and all seams shall be sealed with waterproof adhesive conforming to Specification MIL–A–140.

5.2.4.2 *Spare parts.*

5.2.4.2.1 *Latch.*—Each latch shall be wrapped with a moldable VCI material. Ten wrapped latches shall be packaged in a type II, class A, greaseproof bag conforming to Specification JAN–P–117, as a unit package.

5.2.4.2.2 *Spring, retaining.*—Ten springs shall be wrapped together with a moldable VCI material, and packaged in a type II, class A, greaseproof bag conforming to Specification JAN–P–117, as a unit package.

5.2.5 *Intermediate packages.*

5.2.5.1 *Launcher and gas cylinder lock.*—Fifty unit packages containing the launcher and gas cylinder lock shall be packaged in a corrugated fiberboard box conforming to Specification JAN–P–108. Closure of the box shall be made with either water-resistant gummed tape conforming to Specification UU–T–116 or waterproof adhesive conforming to Specification MIL–A–140.

5.2.5.2 *Latch.*—Twenty unit packages (200 latches) shall be packaged in a corrugated fiberboard box conforming to Specification JAN–P–108. Closure of the box shall be made with either water-resistant gummed tape conforming to Specification UU–T–116 or waterproof adhesive conforming to Specification MIL–A–140.

5.2.5.3 *Spring, retaining.*—Twenty unit packages (200 springs) shall be packaged in a setup paperboard box conforming to Specification JAN–P–133, and the closure sealed with 60 pound kraft gummed tape. The box shall be overwrapped with waterproof barrier material conforming to Specification JAN–P–125, and all seams shall be sealed with waterproof adhesive conforming to Specification MIL–A–140.

5.3 Packing.

5.3.1 *For domestic shipment.*—Intermediate packages shall be packed in exterior shipping containers not to exceed 200 pounds gross weight. The exterior container shall be a corrugated fibre or wood box conforming to Specification LLL–B–631 or NN–B–621.

5.3.2 *For oversea shipment.*—Intermediate packages shall be packed in a style IV nailed wood box constructed in accordance with Specification JAN–P–106. Gross weight shall not exceed 70 pounds.

5.4 Labeling and marking.

5.4.1 *Identification.*—Each unit package and intermediate package shall be clearly marked in accordance with Standard MIL–STD–129.

5.4.2 *Shipping containers.*—In addition to any special markings required by the procurement documents, shipping containers shall be marked in accordance with Standard MIL–STD–129, except that type of preservative used shall be included.

5.5 Pilot pack.—When specified in procurement documents, a pilot pack shall be submitted for approval to the authorized Government representative to determine conformance with this specification. Approval of the pilot pack through error or omission shall not relieve the contractor of his obligations to package, pack, and mark in accordance with this specification.

6. NOTES

6.1 Ordering data.—Procurement documents should specify:

(a) Title, number, and date of this specification.
(b) Model of launcher (see 1.2).
(c) Whether domestic or oversea packing is required (see 5.3).

Notice.—This specification, together with specifications and drawings pertaining to it and bearing a "Notice" of similar restrictions, is intended for use only in connection with procurement by the United States Government, and shall not be reproduced either wholly or in part except when authorized in connection with Government procurement, nor be used for any other purpose except when specifically authorized by the Chief of Ordnance.

Custodians:
Army—Ordnance Corps
Navy—Bureau of Ordnance
Other interest:
Army—T
Navy—*MC*.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:01Z
Check the source to verify that this is the current version before use.