MIL-R-1284E
16 Feburary 1982
SUPERSEDING
MIL-R-1284D
20 May 1974

MILITARY SPECIFICATION

ROLLERS, TOWED, SHEEPSFOOT, 2 OR 3 DRUMS IN LINE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a sheepsfoot roller consisting of 2 or 3 drums side-by-side in line. The roller is an item of construction equipment.

1.2 Classification. Rollers shall be furnished in the following types and classes, as specified (see 6.2):

Type I - 40- thru 48-inch diameter drums.
Type II - 60-inch diameter drums.

Class 1 - 2 drums in line, side-by-side.
Class 2 - 3 drums in line (type I only), side-by-side.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 3895

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:04Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

QQ-S-781	- Strapping, Steel, Flat and Seals.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-P-40	- Packaging and Packing of Hand Tools.

MILITARY

MIL-P-116	- Preservation, Methods of.
MIL-P-514	- Plates, Identification, Instruction and Marking, Blank.
MIL-T-704	- Treatment and Painting of Materiel.
MIL-F-3541	- Fitting, Lubrication.
MIL-G-3859	- Grease Gun, Hand Operated, Lever, Push and Screw Type.
MIL-G-10924	- Grease, Automotive and Artillery.
MIL-T-22085	- Tape, Pressure-Sensitive, Adhesive, Preservation and Sealing.
MIL-C-46168	- Coating, Aliphatic Polyurethane, Chemical Agent Resistant.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-209	- Sling and Tiedown Provisions for Lifting and Tying Down Military Equipment.
MIL-STD-1188	- Commercial Packaging of Supplies and Equipment.

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.1.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:04Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Department, 1616 P Street NW, Washington, DC 20036.)

NATIONAL ASSOCIATION OF METAL NAME PLATE MANUFACTURERS (NAME)

Metal Name Plate Industry Standards and Practices.

(Application for copies should be addressed to the National Association of Metal Name Plate Manufacturers, Inc., 1000 Vermont Avenue, NW, Washington, DC 20005.)

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

SAE Handbook

(Application for copies should be addressed to the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096.)

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code, Section IX - Welding Qualifications.

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

AMERICAN WELDING SOCIETY, (AWS)

AWS D1.1 Structural Welding Code, Section 5, Qualifications
AWS Welding Handbook.

(Application for copies should be addressed to the American Welding Society, Inc., 2501 N.W. Seventh Street, Miami, FL 33125.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Description. The sheepsfoot earth compaction roller shall consist of either a double drum (class 1) or a triple drum (class 2) earth compaction roller assembly, as specified (see 1.2 and 6.2). The drums shall be arranged

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:04Z
Check the source to verify that this is the current version before use.

side-by-side in an equallizing frame that will permit independant oscillation of each drum. The roller shall be equipped with a drawbar with a front tractor hitch clevis, and a rear towing clevis. The drums shall be equipped with tamping feet having replaceable tips. When towed and when pushed by construction equipment prime movers, the rollers shall withstand rough operations encountered on land-fills, ripped rocky ground, and construction job sites. The rollers shall withstand towing and pushing operations at speeds up to 5 mph without permanent deformation or damage. The roller shall, as a minimum, be in accordance with the requirements of this specification for Commercial Construction Equipment (CCE) and shall be the roller manufacturer's standard commercial product line. The commercial standard product line is one which has been fielded and sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's publications and represents the latest production model.

3.1.1 Dimensions and weights. The sheepsfoot roller shall conform to table I, as follows:

TABLE I. Dimensions and Weights.

Requirement	Type I	Type II
Overall length, including drawbar, feet.	12 min., 15 max.	15 min., 21.25 max.
Overall width, Class 1 roller, feet-inches.	10-6 max.	13-0 max.
Overall width, Class 2 roller, feet.	15 max.	- - -
Length of each drum, inches	48 ± 1 inch.	60 ± 1 inch.
Diameter of each drum without tamping feet, inches.	40 Min., 44 max.	60 ± 1 inch.
Number of tamping feet per drum.	88 min., 112 max	120
Area of tamping-foot face, square inches.	5.0 min., 7.0 max.	6.0 min., 7.5 max,
Length of tamping feet, inches.	7 min.	7 min.
Ground pressure of tamping-foot face (based on 4 tamping feet per drum on the ground):		
- Drums empty, psi.	125 min.	300 min.
- Drums filled with water, psi	200 min.	500 min.
- Drums filled with sand and water, psi.	270 min.	700 min.

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:04Z
Check the source to verify that this is the currentversion before use.

3.2 First article (preproduction model). The contractor shall furnish one or more complete rollers, for examination and testing within the time frame specified (see 6.2), to prove prior to starting production that his production methods and choice of design detail will produce rollers that comply with the requirements of this specification. Examination and tests shall be as specified in Section 4, and unless otherwise specified herein, all examinations and tests shall be conducted by the contractor subject to surveillance and approval by the Government (see 6.2). When specified (see 6.2), the Government will conduct any or all of the preproduction examination and tests as specified (see 6.2).

3.3 Initial production. When specified (see 6.2), the contractor shall furnish the Government one or more rollers for inspection as specified in 4.4.

3.4 Material. Material shall be as specified herein. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 6.6).

3.5 Frame. Drum frames shall be made of structural steel or formed steel plate and shall be rigidly braced. The drum frames shall be connected so that each drum oscillates independently of the other drums through an angle of at least 30 degrees, and the horizontal plane through the axis of oscillation shall bisect this angle. A positive means shall be provided to limit oscillation of drums and shall prevent drums from interlocking.

3.6 Type II roller. When specified (see 6.2), the type II roller shall be furnished with a beam, stabilizing bar, and an independent frame for each drum. Each frame shall be equipped with two oscillating pins for independent oscillation: One pin shall be located at center of each front frame member and connected to the beam and the second pin shall be located at center of each rear frame member and connected to the stabilizing bar. Oscillation shall be not less than 15 degrees above and below the horizontal plane of axis. A positive means shall be provided to limit oscillation of drums and to prevent drums from interlocking. Drum frames, beam, and stabilizing bar shall be fabricated of boxed type steel construction, and shall be rigidly braced. The beam shall be perpendicularly connected to the drawbar to form a "T" shape and shall be reinforced and equipped with gusset plates.

3.7 Drawbar. The drawbar shall be removable and replaced without cutting or welding. The drawbar shall be designed and constructed to permit construction equipment to either pull or push the roller. The drawbar shall be equipped with an adjustable, universal-joint-type front clevis which shall permit coupling the roller to a standard SAE J749 drawbar for a 40,000 pound vehicle, except that the clevis shall contain a hole to accommodate a 2-inch diameter size pin. The drawbar shall be mounted to the frame in such a manner that the ground contact pressure of each drum shall be equal.

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:04Z
Check the source to verify that this is the currentversion before use.

3.8 Rear clevis. A clevis shall be attached to the rear main-frame member and shall contain a hole to accommodate a 2-inch diameter, SAE J749 pin to permit tandem operation (one roller behind another roller) of the rollers.

3.9 Drums. The shell and heads of each drum shall be constructed of not less than 1/2-inch-thick steel plates. The joints shall be welded and watertight. A hole with a 2-inch watertight pipe plug shall be provided to ballast the roller with liquid, and a ballast and cleanout hole of not less than 100 square inches in area shall be provided to ballast the roller with granular material. The holes shall be located on the outside end of the drum, where possible, and near the perimeter of the drum. The 100-square-inch-area hole shall be equipped with a watertight cover, and the cover mounting bolts shall be spot welded in place from the inside of the drum.

3.10 Tamping feet. The tamping feet shall have tapered shanks and shall have replaceable tamping tips. The tamping feet shanks shall be cast or forged from steel. The tamping feet shanks shall be welded to the drum. The tamping tips shall be steel, heat-treated to a Brinell hardness of not less than 250, and replaceable without cutting or welding.

3.11 Axles and bearings. Each drum shall be equipped with an independent axle extending entirely through the drum. The axle or the drum shall be mounted on anti-friction bearings having dusttight and watertight seals. Bearings shall be adjustable without removal of drums from axle or axle from frame.

3.12 Cleaners. Adjustable cleaners shall be provided and shall prevent accumulation of material on drums when the drums are operated in either the forward or reverse direction. Cleaners shall be replaceable.

3.13 Lubrication. All surfaces requiring lubrication shall be provided with a suitable means for lubricating.

3.13.1 Lubricants. The rollers shall operate as specified herein when lubricated with greases conforming to MIL-G-10924.

3.13.2 Lubrication fittings. Lubrication fittings shall conform to MIL-F-3541, Type I, II, or III. Fittings shall be located in a protected position. Fittings shall be accessible to a grease gun conforming to MIL-G-3859. Accessibility to fittings shall be obtained without the removal or adjustment or accessories or parts.

3.13.3 Pressure-release device. A suitable pressure-release device shall be provided where the use of 1,000 psi and higher pressure-lubricating equipment could damage grease seals or other parts.

3.13.4 Delivery lubrication service. When delivered, all components except those for which preservatives are specified in 5.1 shall be lubricated. Grease

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:04Z
Check the source to verify that this is the current version before use.

lubrication shall be with greases conforming to MIL-G-10924. Each lubricated component shall be tagged in a conspicuous place to indicate the temperature range and grades of greases used.

3.14 Lifting and tiedown attachments.

3.14.1 Lifting attachments. Permanently affixed attachments that enable the equipment to be lifted in its normal travel position shall be provided. The attachments shall meet the requirements specified in MIL-STD-209. Lifting attachments may also be used as tiedown attachments when such attachments meet the requirements specified in 3.15.

3.15 Tiedown attachments. Permanently affixed attachments that permit fastening the eqipment to the floor or deck of a transportation medium shall be provided. The attachments shall meet the requirements specified in MIL-STD-209.

3.16 Identification marking. The roller shall be identified in accordance with MIL-STD-130. The plates shall be in accordance with the Metal Name Plate Industry Standards and Practices publication as published by the National Association of Metal Name Plate Manufacturers, Inc. (NAME). Identification and shipping data plates shall conform to MIL-P-514, Composition C, of Type I, Grade A, Class 1 material. Plates shall be attached by screws, bolts, or rivets in a conspicuous protected location. When specified (see 6.2), identification plates will be furnished by the Government.

3.17 Shipping data plate. A shipping data plate, conforming to MIL-P-514, Type III, Composition C, of Type I, Grade A, Class 1 material, shall be permanently affixed to the roller frame in a conspicuous place, and shall indicate location and capacity of lifting and tiedown attachments.

3.18 Treatment and painting. The portions of the roller normally painted shall be cleaned, treated, primed and painted in accordance with MIL-T-704, Type F. The finishing coat shall be in accordance with MIL-C-46168, color forest green.

3.19 Marking. The unballasted shipping weight of each roller shall be marked on each side of the frame in such a manner as to be discernible. Marking shall conform to MIL-T-704.

3.20 Workmanship. All parts, components, and assemblies of the roller including castings, forgings, molded parts, stampings, bearings, seals, machined surfaces, and welded parts shall be clean and free from sand, dirt, fins, pits, sprues, scale, flux, and other harmful extraneous material. External surfaces shall be smooth, and all exposed edges shall be rounded or beveled.

3.20.1 Steel fabrication. Steel used in the fabrication of the roller shall be free from kinks and sharp bends. The straightening of material shall be done by methods that will not cause injury to the metal.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:04Z
Check the source to verify that this is the current version before use.

Shearing and clipping shall be done neatly and accurately. Corners shall be square and true, and all edges and burrs shall be removed. Flame cutting may be employed instead of shearing or sawing. Burned surfaces of flame-cut material shall be ground smooth. Precautions shall be taken to avoid overheating, and heated metals shall be allowed to cool slowly. All bends of a major character shall be made with metal dies or fixtures to insure uniformity of size and shape.

3.20.2 Bolted connections. Boltholes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with commercial practice, and all bolts, nuts, and screws shall be tight. Devices securing bolts or capscrews shall be of sufficient strength to withstand the tensile strength of the bolt.

3.20.3 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall completely fill the holes. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.21 Welders and welding.

3.21.1 Welders. Before assigning any welder to manual welding work covered by this specification, the contractor shall provide the contracting officer with certification that the welder has passed qualification tests as prescribed by any of the following listed codes for the type of welding operations to be performed and that such qualification is effective as defined by the particular code:

AWS D1.1, Structural Welding Code, Section 5, Qualification.
ASME Boiler and Pressure Vessel Code, Section IX, Welding Qualifications.
Equal welder qualification program, subject to Government approval.

3.21.2 Welding. Welding shall be in accordance with the AWS and ASME codes and the AWS's Welding Handbook. The surfaces of parts to be welded shall be free from rust, scale, paint, grease, and other foreign matter. Welds shall transmit stress without permanent deformation or failure when the parts connected by the welds are subjected to proof and service loading.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202640-16T13:04Z
Check the source to verify that this is the currentversion before use.

4.1.1 Component and material inspection. The contractor is responsible for insuring that component and materials used are manufactured, examined and tested in accordance with referenced specifications and standards.

4.2 Classification of inspections. Inspections shall be classified as follows:

(a) First article inspection (see 4.3).
(b) Initial production inspection (see 4.4).
(c) Quality conformance inspection (see 4.5).
(d) Inspection comparison (see 4.7).
(e) Inspection of packaging. (see 4.8).

4.3 First article inspection.

4.3.1 Examination. The preproduction roller shall be examined as specified in 4.6.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The preproduction roller shall be tested as specified in 4.6.2.1 through 4.6.2.4. Failure of any test shall be cause for rejection.

4.4 Initial production inspection. When specified (see 3.3), one or more initial production rollers will be selected at random by the Government from the rollers being produced from production tooling and will be examined as specified in 4.6.1 and tested as specified in 4.6.2.1 through 4.6.2.4 to determine conformance to the requirements of this specification. The inspection will be performed by the Government at a site or sites selected by the Government. Acceptance of an initial production roller shall not exclude the remaining rollers from the quality conformance inspection and acceptance provisions specified in Section 4. In addition to any test specified as part of the initial production tests, the Government reserves the right to conduct any and all other tests contained in this specification as part of the initial production test and failure of such additional tests shall have the same effect as failure of those tests specified as initial production tests.

4.4.1 Inspection failure. Failure of an initial production roller to meet any requirement specified herein during and as a result of the examination and tests specified in 4.4 shall be cause for rejection of the initial production roller and shall be cause for refusal by the Government to continue acceptance of production rollers until evidence has been provided by the contractor that corrective action has been taken to eliminate the deficiencies. Correction of such deficiencies shall be accomplished by the contractor at no cost to the Government on rollers previously accepted and produced under the contract. Any deficiencies found as a result of the initial production inspection will be considered prima facie evidence that all rollers accepted prior to the completion of initial production inspection are similarly deficient unless evidence to the contrary is furnished by the contractor and such evidence is acceptable to the contracting officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:04Z
Check the source to verify that this is the current version before use.

4.5 Quality conformance inspection.

4.5.1 Examination.

4.5.1.1 Individual. Each roller shall be examined for the defects specified in 4.6.1. Presence of any defect shall be cause for rejection.

4.6 Inspection procedure.

4.6.1 Examination. The rollers shall be examined for the following defects:

101. Dimensions and weights not as specified.
102. Parts or components missing or do not function.
103. Material not as specified.
104. Drum oscillation not as specified.
105. Drums not watertight.
106. Tamping feet not as specified.
107. Drawbar not as specified.
108. Axles not as specified.
109. Bearings not as specified.
110. Cleaners not as specified.
111. Lubrication and lube fittings not as specified.
112. Identification markings not as specified.
113. Shipping data plate not as specified.
114. Treatment and painting not as specified.
115. Marking not as specified.
116. Technical publications missing or not as specified (see 6.4).
117. Repair parts missing or not as specified (see 6.5).
118. Maintenance tools missing or not as specified (see 6.5).
119. Workmanship not as specified.

4.6.2 Tests.

4.6.2.1 Test conditions. The roller shall be lubricated with grease specified in 3.13. For the purpose of these tests, a test roller is defined as the roller being tested (the roller immediately behind the tractor prime mover) when more than one roller is used to accomplish the test.

4.6.2.2 Operational test. The test roller shall be filled with water and hitched to a tractor. A second roller filled with water and of the same size as the test roller shall be hooked in tandem behind the test roller. The tandem roller assembly shall be towed over earth and rock fill for a period of 8 hours. A speed of approximately 5 mph shall be maintained and all turns shall be made in the shortest possible turning radius. The tandem roller assembly shall then be towed for 4 hours over loose fill with a moisture and fine material content which will cause fill material to stick to the roller drums. Ten percent of the replaceable tamping tips on the test roller shall be removed upon completion of 8 hours towing and replaced with new tamping tips. The test roller shall be observed during this test. Any evidence of water leakage, inability of drums to oscillate as specified,

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:04Z
Check the source to verify that this is the current version before use.

inability of cleaners to prevent buildup of material on drums, inability to remove and replace tamping tips as specified, or any permanent deformation or breakage of components or parts shall constitute failure of this test.

4.6.2.3 Ground pressure of tamping-foot face. The roller shall be weighed with drums empty, with drums full of water, and with drums full of sand and water. Based on having four tamping feet per drum on the ground, the ground pressure of the tamping foot face shall be determined for the roller with empty drums, for the roller with drums filled with water, and for the roller with drums filled with sand and water by the following formula:

Formula: $P = \frac{W}{FNA}$

Where P = ground pressure of each tamping foot face in psi.
W = weight of roller in pounds.
F = number of tamping feet per drum in contact with a hard-ground-surface.
N = number of drums on the roller.
A = area of tamping foot face in square inches.

Computed ground pressure of tamping foot not as specified in 3.1.1 shall constitute failure of this test.

4.6.2.4 Test procedures of lifting provisions. Test procedures of lifting provisions shall be as follows:

(a) Lift the roller and hold in suspension in its normal travel position using slings that converge not more than 24 feet above the lowest extremity of the roller. Determine the forward angle of application for each provision. Measure the clearance between each sling and the roller. Measure eye openings and clearance dimensions of the provision. Measure the land carried by each provision.

(b) Restrain the roller by anchoring the main frame and subject each provision to a force equal to the load factor specified in MIL-STD-209 times the load it carried in (a) above. An alternate method of test is to lift the roller as in (a) above and add weights to the main frame until the required force is obtained. Hold the roller under either of the loading conditions for at least 90 seconds.

4.6.2.5 Failure criteria. Weld failure of permanent deformation caused by lifting or failure to meet the requirements of MIL-STD-209, shall constitute failure of this test.

4.5.2.6 Test procedures of tiedown provisions. With the roller anchored by means other than the provisions being tested, apply the proportion of the static loads as specified in MIL-STD-209 to each attachment. Measure dimensions of the tiedown.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:04Z
Check the source to verify that this is the current version before use.

4.6.2.7 Failure criteria. Failure to meet the requirements of MIL-STD-209 shall constitute failure of this test.

4.7 Inspection comparison. The Government may select rollers at any time during the contract production period and subject these rollers to the examination specified in 4.6.1 and the tests specified in 4.4 to determine conformance to the requirements of this specification. The inspection will be performed by the Government at a site selected by the Government, on units selected at random from those which have been accepted by the Government and will not include the previously inspected preproduction model and initial production rollers. In addition to any tests specified as part of the inspection comparison, the Government reserves the right to conduct any and all other tests contained in this specification as part of the inspection comparison and failure of such additional tests shall have the same effect as failure of those tests specified as inspection comparison.

4.7.1 Inspection failure. Failure of any roller to meet any requirement specified herein during and as a result of the examination and tests specified in 4.7 shall be cause for rejection of the roller and shall be cause for refusal by the Government to continue acceptance of production rollers until evidence has been provided by the contractor that corrective action has been taken to eliminate the deficiencies. Correction of such deficiencies shall be accomplished by the contractor at no cost to the Government on rollers produced and accepted under the contract since approval of the initial production roller. Any deficiencies found as a result of inspection comparison inspection will be considered prima facie evidence that all rollers accepted after approval of the initial production rollers are similarly deficient unless evidence to the contrary is furnished by the contractor and such evidence is acceptable to the contracting officer.

4.8 Inspection of packaging.

4.8.1 Quality conformance inspection of pack.

4.8.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.8.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.8.1.3 Examination. Samples selected in accordance with 4.8.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

120.	Materials, methods and containers not as specified for level A. Each incorrect material, method, or container shall be considered one defect.
121.	Removed bolts, nuts, pins, and washers not placed and secured as specified for level A.
122.	Unprotected exterior metal surfaces not coated with preservative as specified for level A.

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:04Z
Check the source to verify that this is the currentversion before use.

123. Maintenance tools not preserved and packaged in accordance with the referenced document for level A.
124. Consolidation not as specified for level A.
125. Securing of components to the roller frame not as specified for level A.
126. Marking missing, illegible, incorrect, or incomplete, for level A or commercial.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or commercial as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Disassembly. Disassembly shall be to the extent that economy in packing and shipping can be obtained, provided no special tools or skills are required for reassembly or the cost of assembly would be in excess compared to the economy of packing and shipping. Removed bolts, nuts, pins, and washers shall be placed in mating parts and secured to prevent their loss.

5.1.1.2 Unprotected surfaces. Unprotected exterior metal surfaces exposed by disassembly shall be coated with type P1 preservative. The preservative shall conform to the applicable specification listed in and shall be applied in accordance with MIL-P-116.

5.1.1.3 Repair parts. The preservative application criteria and applicable method(s) of preservation of MIL-P-116 shall be used to preserve repair parts.

5.1.1.4 Maintenance tools. Maintenance tools shall be preserved in accordance with the level A requirements of PPP-P-40.

5.1.1.5 Technical publications. Technical publications shall be preserved in accordance with MIL-P-116, method IC-1 or IC-3, and secured to the roller frame in a protected location with tape, conforming to MIL-T-22085, type II, or consolidated with the components specified in 5.1.1.6.

5.1.1.6 Consolidation. The repair parts, maintenance tools and small parts removed for disassembly shall be consolidated together in a close fitting box conforming to PPP-B-601, domestic type, style optional. Strapping shall not be required.

5.1.2 Commercial. Each complete roller shall be preserved in accordance with MIL-STD-1188, except unit packing shall not be required.

5.2 Packing. Packing shall be level A or commercial as specified (see 6.2).

5.2.1 Level A. Each roller shall be shipped unboxed. The consolidation box and the drawbar, when an overall reduction in cubage can be accomplished (see 5.1.1.1), shall be secured to the roller frame in a manner that will not

Source: https://assist.dla.mil -- Downloaded: 202610-16T13:04Z
Check the source to verify that this is the current version before use.

interfere with lifting or towing. Securing shall be accomplished with strapping conforming to QQ-S-781, type I or IV, class 1, finish B, size as applicable.

5.2.2 Commercial. Each complete roller shall be prepared for shipment in a manner to assure carrier acceptance and safe delivery to destination at lowest ratings. Containers and packing shall comply with Uniform Freight Classification Rules or with National Motor Freight Classification Rules.

5.3 Marking.

5.3.1 Military. Marking for level A shall be in accordance with MIL-STD-129.

5.3.2 Commercial. Marking for commercial packaging shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended use. The sheepsfoot roller is capable of tandem compaction operation and is intended for use in compacting earth and rocky embankments and for localized breakup of existing earth or graveled roads and subgrade soil to increase the loadbearing capacity. The roller permits positive, solid compaction with a minimum of passes over surface areas, such as built-up solid fills for highways, airports, dams, bridge approaches, levees, and straits.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type and class of roller required (see 1.2).
(c) Date of issue of DoDISS applicable to this contract and exceptions thereto (see 2.1.1).
(d) Time frame for submission of preproduction model and number of rollers to be furnished, (see 3.2).
(e) When the Government will conduct any or all of the preproduction model examination and tests. When the Government will conduct some but not all of the preproduction examination and tests, the contracting officer should specify which examination and tests will be conducted by the Government and which examination and tests shall be conducted by the contractor (see 3.2).
(f) When initial production testing is required and number of rollers to be furnished (see 3.3).
(g) When the type II roller shall be furnished with a beam, stabilizing bar, and an independent frame for each drum (see 3.6).
(h) When identification plates will be furnished by the Government (see 3.16).
(i) Color of finish coat if different from the forest green specified in 3.18.
(j) Degree of preservation and degree of packing required (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:04Z
Check the source to verify that this is the current version before use.

6.3 Preproduction model. Any changes or deviations of production rollers from the approved preproduction model during production will be subject to the approval of the contracting officer. Approval of the preproduction model will not relieve the contractor of his obligation to furnish rollers conforming to this specification.

6.4 Data requirements. The contracting officer should include requirements for such data as technical publications, instructional materials, illustrated parts lists, and contractor's maintenance and operation manual to be furnished with each roller.

6.5 Provisioning. The contracting officer should include provisioning requirements for repair parts and maintenance tools as necessary (including any special tools), and instructions on shipment of rollers.

6.6 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.4).

Custodian:
Army - ME

Preparing activity:
Army - ME

Review activity:
DLA-CS

Project 3895-0254

User activities:
Army - AT
Navy - MC

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:04Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Mobility Equipment Research and
Development Command
ATTN: DRDME-DS
Fort Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:04Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-R-1284E Rollers, Towed, Sheepsfoot, 2 or 3 Drums in Line

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T13:04Z
Check the source to verify that this is the current version before use.