00-L-360D
September 20, 1985
SUPERSEDING
00-L-360C
October 16, 1978

FEDERAL SPECIFICATION

LIFTS, MOTOR VEHICLE

This specification is approved by the Assistant Administrator, Office of Federal Supply and Services, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers single and double post hydraulic type lifts for motor vehicles.

1.2 Classification.

1.2.1 Types, classes, sizes, and styles. The motor vehicle lifts covered by this specification shall be of the following types, classes, sizes, and styles, as specified (see 6.2):

Type I - Two post, full hydraulic, free wheel.

Class A - Rail free, axle saddle yoke support (one post horizontally adjustable for vehicle wheelbase).

Size 1 - Passenger car and light truck.

Style a - Air-oil operation, 11,000 pound capacity.
Style b - Electric-oil operation, 16,000 pound capacity.

Size 2 - Truck and bus.

Style a - Air-oil operation, 24,000 pound capacity.
Style b - Electric-oil operation, 36,000 pound capacity.

Size 3 - Passenger car and medium truck.

Style a - Air-oil operation, 16,000 pound capacity (5,000 pound capacity front plunger and 11,000 pound capacity rear plunger).
Style b - Electrical-oil operation, 24,000 pound capacity (8,000 pound capacity front plunger and 16,000 pound capacity rear plunger).

Class B - Split rail superstructure arrangement, air-oil operation, 24,000 pound capacity.

FSC 4910

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:59Z
Check the source to verify that this is the current version before use.

Class C - Continuous two rail arrangement, air-oil operation, 24,000 pound capacity.

Type II - Single post, frame contact, swivel arm, full hydraulic, free wheel.

Style a - Air-oil operation, 8,000 pound capacity.
Style b - Electric-oil operation, 8,000 pound capacity.

2. APPLICABLE DOCUMENTS

2.1 Government publications. The issues of the following documents, in effect on date of invitation for bids or solicitation for offers, form a part of this specification to the extent specified herein.

Federal Specifications

CC-M-1807	-	Motors, Alternating Current, Fractional and Integral Horsepower (500 HP and Smaller)
PPP-B-601	-	Boxes, Wood, Cleated-Plywood
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-D-729	-	Drums, Shipping and Storage, Steel, 55-Gallon (208 Liters)
PPP-T-60	-	Tape, Packaging, Waterproof

Federal Standards

FED-STD-H28	-	Screw-Thread Standards for Federal Services
FED-STD-123	-	Marking for Shipment (Civil Agencies)

(Activities outside the Federal Government may obtain copies of Federal specifications, standards, and commercial item descriptions as outlined under General Information in the Index of Federal Specifications, Standards and Commercial Item Descriptions. The Index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402).

(Single copies of this specification, and other Federal Specifications and commercial item descriptions required by activities outside the Federal Government for bidding purposes, are available without charge from General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Houston, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.)

(Federal Government activities may obtain copies of Federal standardization documents and the Index of Federal Specifications, Standards and Commercial Item Descriptions from established distribution points in their agencies.)

Military Specifications

MIL-P-116	-	Preservation, Methods of
MIL-B-121	-	Barrier Material, Greaseproofed, Waterproofed, Flexible

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:59Z
Check the source to verify that this is the current version before use.

MIL-T-152 - Treatment, Moisture and Fungus-Resistant, of Communications, Electronic, and Associated Electrical Equipment
MIL-V-173 - Varnish, Moisture-and-Fungus-Resistant (For Treatment of Communications, Electronic, and Associated Equipment)
MIL-C-3774 - Crates, Wood; Open 12,000-and 16,000-Pound Capacity
MIL-C-5501 - Caps and Plugs, Protective, Dust and Moisture Seal, General Specification for
MIL-E-16298 - Electric Machines Having Rotating Parts and Associated Repair Parts: Packaging of
MIL-E-17555 - Electronic and Electrical Equipment, Accessories, and Repair Parts: Packaging and Packing of
MIL-C-52950 - Crates, Wood, Open and Covered

Military Standards

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-130 - Identification Marking of US Military Property
MIL-STD-889 - Dissimilar Metals
MIL-STD-1186 - Cushioning, Anchoring, Bracing, Blocking and Waterproofing; With Appropriate Test Methods

(Copies of military specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Federal Regulation:

Occupational Health and Safety Administration (OSHA) 29 CFR 1910.176-190 General Industrial Safety and Health Standards

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

American National Standards Institute (ANSI)

ANSI B153.1 - Safety Requirements for the Construction, Care, and Use of Automotive Lifts

(Application for copies should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

American Society for Testing and Materials (ASTM)

ASTM D3951-82 - Standard Practice for Commercial Packaging
ASTM E380-84 - Standard for Metric Practice

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

National Electrical Manufacturers' Association (NEMA)

NEMA ICS 1 - General Standards for Industrial Control and Systems

(Application for copies should be addressed to the National Electrical Manufacturers' Association, 2101 L Street, NW, Washington, DC 20037.)

National Fire Protection Association (NFPA)

NFPA 70 - National Electrical Code

(Application for copies should be addressed to the National Fire Protection Association, Batterymarch Park, Quincy, MA 02269.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), the contractor shall furnish one or more complete lifts for first article inspection (see 4.3 and 6.2). The first article may be either a preproduction model, or an initial production item which conforms to the requirements of this specification. In either case, the approved first article and the production items shall be in accordance with the terms of the contract. Approval of the first article shall not relieve the contractor of the responsibility to furnish equipment in accordance with the requirements of this specification.

3.2 Design. The lifts shall be designed to meet the applicable requirements of ANSI B153.1 and the requirements specified herein. The design shall be such that parts subject to wear, breakage, or distortion shall be accessible for adjustment, replacement or repair without modification, distortion, or damage to the lifts or any part or component of the lifts.

3.2.1 Measurement system. The US Customary System of Units (US) or the International System of Units (SI) may be used in the design and construction of the lifts. In this specification, all measurements, dimensions, sizes, and capacities are given in the US system. These measurements may be converted to the SI system by using the conversion factors and methods specified in ASTM E380-84.

3.2.2 Threads. Threads shall conform to FED-STD-H28 and the applicable Detailed Standard section referenced therein.

3.2.3 Interchangeability. All parts shall be manufactured to definite standards, clearances, and tolerances in order that any such parts of a

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

particular type or model may be replaced, interchanged, and adjusted without modification of the replacement parts or any other parts of the unit. When practical, all parts shall be permanently and legibly marked in accordance with MIL-STD-130.

3.3 Material. Materials not specifically designated herein or in the contract shall be of a quality commensurate with commercial practice within the producing industry, shall be suitable for the intended purpose in the design of the end item, and shall meet all requirements specified herein. Materials shall be free from defects which would adversely affect the performance or maintainability of the individual components or the overall assembly. It shall not be permissible to use reclaimed parts as is, or rebuilt from scrap or other used equipment. When dissimilar metals are used in contact with each other, suitable protection against galvanic corrosion shall be applied in accordance with MIL-STD-889.

3.4 Construction. The lifts shall be furnished complete so that, when installed and connected to the proper power source, they shall meet or exceed the requirements specified herein. Parts used in fabrication of the lifts shall be new and free of defects. Part surfaces shall be clean and free of extraneous materials. External surfaces shall be smooth and free of sharp edges.

3.4.1 Castings and forgings. Castings shall be free from blowholes, porosity, hard spots, shrinkage defects, cracks, or other defects. Forgings shall be free from scale, inclusions, cold shuts, mismatching, sharp edges, or other defects. Castings and forgings shall be free from any properties adversely affecting their strength, durability, or suitability. Reclaiming or repair of major castings and forgings shall be permitted if the repair is not on a critical surface.

3.4.2 Welding, brazing, and soldering. Welding, brazing, and soldering shall be of a quality which shall sustain all requirements of the welded, brazed, or soldered parts. These operations shall not be employed as repair measures for defective parts.

3.4.3 Fastening devices. Screws, pins, bolts, and similar parts shall be installed with means for preventing loss of tightness or adjustment. All such parts, when subject to removal or adjustment, shall not be swaged, peened, staked, or otherwise deformed.

3.4.4 Lubrication. All bearings (except sealed-for-life type), mating gears, and sliding parts shall be provided with standard means for lubrication. Oil holes, grease fittings, and filler caps shall be accessible without requiring disassembly of functional parts. Lubrication reservoirs, if applicable, shall have means for checking levels. Means shall be provided to lubricate the plunger throughout its maximum travel, and to prevent water, dirt, and other foreign matter from entering the assembly.

3.4.5 Safety.

3.4.5.1 Safety devices. Each lift shall be equipped with safety devices conforming to the applicable requirements of ANSI B153.1. Each air-oil operated

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:59Z
Check the source to verify that this is the current version before use.

lift shall be equipped with a low oil supply control. Unless otherwise specified (see 6.2), an automatic mechanical device shall be provided to hold the lift in the extended position. Protection shall be provided against electrical shock for electric-oil lifts. When special safety devices are required, they shall be as specified (see 6.2).

3.4.5.2 Occupational safety standards. The product shall comply with OSHA standards set forth in 29 CFR 1910.176-190 that are applicable to this type of equipment.

3.5 Performance and product characteristics.

3.5.1 Type 1, class A, sizes 1, 2, and 3, style a. The lifts shall be of the adjustable, two post, full hydraulic type, air-oil operated (actuated by an air supply). The superstructure shall be rail free, provide axle saddle yoke free wheel support, and be capable of lifting vehicles of the dimensions and weight characteristics specified in Table I. Adapters shall be furnished to accommodate vehicles equipped with independent front wheel suspension. (For definition of terms used in Table I see 6.5.)

TABLE I. Lift characteristics.

Type, class, size, and style	Rated capacity (minimum) with center load	Height of rise (minimum)	Wheelbase 1/ capacity (min. to max.)	Minimum 1/ inside tread range
	Pounds	Inches	Inches	Inches
Type I, class A, size 1, style a	11,000	60	70 to 166	36 to 48
Type I, class A, size 1, style b	16,000	60	70 to 166	36 to 48
Type I, class A, size 2, style a	24,000	60	78 to 252	43 to 50
Type I, class A, size 2, style b	36,000	60	78 to 252	43 to 50
Type I, class A, size 3, style a	16,000	60	64 to 184	41 to 50
Type I, class A, size 3, style b	24,000	60	64 to 184	41 to 50
Type I, class B	24,000	60	80 to 249	41 to 50
Type I, class C	24,000	60	80 to 249	41 to 50
Type II, style a	8,000	66	Frame contact	36 to 50
Type II, style b	8,000	66	Frame contact	36 to 50

1/ Unless otherwise specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.5.2 Type I, class A, sizes 1, 2, and 3, style b. The lifts shall be of the adjustable, two post, full hydraulic type, electric-oil operated (actuated by electric, oil pump units). The superstructure shall be rail free, provide axle saddle yoke free wheel support, and be capable of lifting vehicles of the dimensions and weight characteristics specified in Table I. Adapters shall be furnished to accommodate vehicles equipped with independent front wheel suspension.

3.5.3 Type I, class B. The lifts shall be of the fixed, two post, full hydraulic type, air-oil operated. The superstructure shall be of the split rail, free wheel type, not exceeding five inches in height, with sufficient strength to handle the rated capacity. The lifts shall be capable of elevating and supporting a total load of at least 24,000 pounds as specified in Table I. The superstructures shall be provided with adjustable support assemblies for single and tandem axles, including offset differential housings. Adapters shall be furnished to accommodate vehicles equipped with independent front wheel suspension.

3.5.4 Type I, class C. The lifts shall be of the fixed two post, full hydraulic type, air-oil operated. The superstructure shall be of the continuous two rail, free wheel type not exceeding six inches in height. Two inner and two outer heads and four slide blocks shall be provided for pivot head action. The outer heads shall pivot on the plunger and shall remain parallel with the beams. Axle supports shall clear the heads in any position. Two adjustable supports suitable for handling tandem rear truck axles with offset differential housings shall be provided. Separate individual supports suitable for handling front axles shall be provided. The lift shall be capable of elevating and supporting a total load of at least 24,000 pounds as specified in Table I. Adapters shall be furnished to accommodate vehicles equipped with independent front wheel suspension.

3.5.5 Type II, styles a and b. The lifts shall be of the single post, full hydraulic type. The superstructure shall be arranged for frame contact with adjustable swivel arms equipped with sliding pads and free wheel operation, and shall be capable of handling four wheel vehicles of the dimension and weight characteristics specified in Table I.

3.5.6 Rate of travel.

3.5.6.1 Rate of ascent. Each lift shall be capable of raising a capacity load to the full extent of vertical travel in 100 seconds or less.

3.5.6.2 Rate of descent. The maximum lowering speed for each lift, when loaded to its rated capacity, shall not exceed 20 feet per minute.

3.5.7 Height of rise. The height of rise for each lift shall be as specified in Table I.

3.5.8 Working pressure. Lifts shall be capable of performance in accordance with the applicable requirements of 3.5.1 through 3.5.5 when supplied with compressed air in sufficient volume, at a maintained pressure of not less than 150 pounds per square inch gage (psig), for air-oil operation and with oil pressure not less than 200 psig for electric-oil operation.

3.5.9 Positive stop. Each lift shall be provided with a positive stop to prevent the lift from being raised beyond the safe limit of vertical travel.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.5.10 Plunger and cylinder assembly hydraulic pressure. The plunger and cylinder assembly shall be capable of withstanding a hydraulic pressure of not less than 350 psig, when the plunger assembly is extended to its maximum travel position, without damage or leakage of fluid.

3.5.11 Control mechanism. The control mechanism shall comply with ANSI B153.1. Type I, class A, B, and C lifts, shall be equipped with controls designed to enable the operator to raise and lower the two plungers simultaneously and individually, and to stop either or both plungers for any desired period at any height within the vertical travel range.

3.5.12 Adjustments. On all lifts, the design and assembly of components that must be moved to accommodate vehicles of various wheelbase and tread dimensions shall be such that any necessary adjustment can be accomplished with manual exertion of not more than 50 pounds force on any individual component or assembly.

3.5.13 Trench covers. When specified (see 6.2), lifts designed for installation requiring a trench or floor depression more than seven inches in depth shall be provided with steel trench covers with a nonskid surface. The strength of the trench covers shall be such that a vehicle of the maximum weight within the rated capacity of the lift can be driven across the trench (with trench cover in place) without causing dislocation or permanent deformation of the covers.

3.5.14 Plunger assembly operation. The plunger assembly shall operate freely, and at a constant rate of movement throughout its full extension and retraction, without binding or catching in the bearing and guide assembly.

3.5.15 Superstructure overload requirement. The superstructure shall be capable of supporting loads at least 135 percent of the rated load capacity.

3.6 Electrical equipment.

3.6.1 Electrical components. Electrical components of the lifts, including starters, relays, switches, wiring, and their enclosures, shall conform to, and shall be located in accordance with, NEMA ICS 1 and NFPA 70, as applicable.

3.6.2 Motors. Unless otherwise specified (see 6.2), motors shall be capable of operation on 220 volts, 60 hertz, three phase. Electric-oil operated lifts shall be equipped with squirrel-cage, induction type, totally enclosed motors conforming to CC-M-1807. Horsepower (hp) and duty rating shall be in accordance with the contractor's commercial practice.

3.6.3 Power unit. For Postal Service acquisitions, the power unit furnished shall be driven by a five hp motor for the Type I, Size 3, lift and a 7 1/2 hp motor for the Type I, Size 2, lift mounted on a steel reservoir of 150 gallon capacity.

3.6.4 Fungus control. Components of electrical circuitry that are hermetically sealed or inherently resistant to fungus growth and moisture need not be treated. Components of electrical circuitry that are not inherently resistant to fungus growth or moisture shall be treated in accordance with MIL-T-152 and MIL-V-173.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:59Z
Check the source to verify that this is the current version before use.

3.7 Painting. Unless otherwise specified (see 6.2), painting and finishing shall be in accordance with the best commercial practice in the industry. Before painting, all surfaces shall be clean and free of all foreign matter detrimental to painting. At least one coat of primer (or a phosphate or chromate base) and one coat of enamel, or equivalent (i.e., epoxy enamel), shall be applied.

3.8 Product identification.

3.8.1 Military agencies. Identification information shall be provided on a nameplate. The nameplate may be incorporated into one or more corrosion resistant metallic plates at the option of the manufacturer. Characters and numerals shall be permanently and legibly engraved, etched, embossed, or stamped in bold face on a contrasting background. The plate shall be secured to the lift with permanent fasteners such as screws, bolts, and rivets at each of the four corners. The plate shall include the following information:

a. Nomenclature
b. National Stock Number (NSN)
c. Manufacturer's name
d. Manufacturer's model number
e. Manufacturer's serial number (if applicable)
f. Contract number.

3.8.2 Civil agencies. The lifts shall be marked in a legible and permanent manner with the manufacturer's name or trademark of such known character that the source of manufacture can be readily identified.

3.9 Workmanship. Standards of workmanship shall assure that the lifts shall have the stability, strength, safety, and efficient operating characteristics found in the best commercial units and as specified in Section 3.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 First article inspection. First article inspection shall be applied to the preproduction model or initial production item (see 3.1). Unless otherwise specified (see 6.2), first article inspection shall consist of the examination in 4.5 and all tests under 4.6. Failure of the first article to pass the examination or any of the tests shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:59Z
Check the source to verify that this is the currentversion before use.

4.4 Quality conformance inspection. Unless otherwise specified (see 6.2.), quality conformance inspection shall be applied to production items offered for acceptance under the contract. Unless otherwise specified (see 6.2), quality conformance inspection shall consist of (a) through (d) below. Failure of any item to pass an examination or test shall be cause for rejection of the item.

(a) Product examination (see 4.5).
(b) Plunger assembly pressure test (see 4.6.2).
(c) Plunger assembly operation test (see 4.6.3).
(d) Packaging inspection (see 4.7).

4.4.1 Sampling. Unless otherwise specified (see 6.2), sampling for quality conformance inspection shall be in accordance with MIL-STD-105 using the following Inspection Levels and Acceptable Quality Levels (AQL):

Inspection or Test	Inspection Level	AQL (Percent Defective)
Product examination (4.5)	II	1.0
Plunger assembly pressure test (4.6.2)	II	1.0
Plunger assembly operation test (4.6.3)	II	1.0
Packaging (4.7)	S-4	1.0

4.5 Product examination. Visually and manually examine the lifts to determine conformance with the requirements of 3.2 through 3.4.5.2 and 3.6 through 3.9. Visual examination shall include verification of completeness of manufacture and assembly, confomance to specified standards, adequacy of markings, proper cleaning, and freedom from defects. Manual examination shall include the operation of movable parts by hand to assure proper functioning. The examination provisions may be applied at the earliest practical point in manufacture at which it is feasible to inspect for acceptance without risk of change in the characteristic by subsequent operations. Failure of the contractor to provide objective evidence that the lifts have passed the examinations prescribed for them by the contractor's inspection system shall be cause for rejection.

4.5.1 Evidence of compliance with OSHA standards. Evidence of compliance with applicable safety and health requirements shall be reviewed (see 3.4.5.2 and 6.4).

4.6 Tests.

4.6.1 Performance test. The lifts shall be prepared for operation, except that it shall not be necessary to set the components in concrete, and then operated in accordance with the manufacturer's instructions. For testing purposes, pressures shall be maintained at not less than 150 psig for air-oil operation, and not less than 200 psig for electric-oil operation (see 3.5.8). The lifts shall be capable of raising the heaviest vehicle, within the applicable rated weight and dimensional capacity, to the fullest extent of vertical travel in the time specified in 3.5.6.1 to the height specified in Table I. Descent shall conform to the rate specified in 3.5.6.2. Any evidence of leakage, malfunction, or failure to meet the requirements shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

4.6.2 Plunger assembly pressure test. The plunger assembly shall be operated through its full stroke and forced against its stop under a hydraulic pressure of at least 350 psig for 15 minutes. There shall be no evidence of damage or fluid leakage (see 3.5.10).

4.6.3 Plunger assembly operation test. The plunger assembly shall be operated to its full stroke and then retracted (normal ballast acceptable) at zero pressure. The assembly shall be observed for contact freedom in the bearing and guide assembly (see 3.5.14).

4.6.4 Superstructure overload test. One completed superstructure section shall be inverted across two fixed bars which contact the lifting members of the superstructure at points three inches from the extreme ends (the maximum vehicle pickup point). A force shall then be brought to bear against the center of the bolster plate. Pressure shall be exerted to 135 percent of rated load and held for five minutes, relaxed, then alternately applied and relaxed at two cycles per minute for six complete cycles. Upon completion of these cycles, there shall be no evidence of damage or permanent deformation of the superstructure members (see 3.5.15).

4.7 Packaging inspection. Packaging inspection shall be conducted before and after packaging to determine compliance with the requirements of Section 5.

5. PREPARATION FOR DELIVERY

5.1 Disassembly. The lifts may be disassembled to the extent necessary to assure that all surfaces requiring a preservative are accessible for processing, to assure minimum cube for packing, and to permit reassembly without special skills or tools. Disassembly, when applicable, shall be as specified in MIL-STD-1186.

5.2 Preservation and packaging. Preservation and packaging shall be Level A or commercial, as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Cleaning and drying. The lifts shall be cleaned in accordance with process C-1 and dried in accordance with applicable procedures of MIL-P-116.

5.2.1.2 Preservative application. The interior surfaces of the cylinder assembly, oil reservoir, and oil pump shall be flushed with a type of preservative oil that is compatible with the supplier's unit. After flushing, the system shall be thoroughly drained. Prior to draining the hydraulic oils, fully extend the piston and nonrotating device from the cylinder assembly and coat the periphery with type P-7 preservative oil. The piston shall then be retracted into the cylinder and secured to restrict movement. Bare ferrous metal surfaces of the superstructure, support assemblies, adapters, and trench covers shall be coated with type P-1 or type P-19 preservative. Air-oil valves, pipe fittings, hardware items, and all other small components with exposed, bare, ferrous metal surfaces shall be preserved with type P-7 preservative oil. Preservatives specified shall conform to MIL-P-116.

5.2.1.3 Unit protection. The method of unit protection for the basic lifts shall conform to method I of MIL-P-116. Small components which are coated with

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

oil shall be covered with barrier material conforming to MIL-B-121, grade A. Parts which are susceptible to damage shall be packed in a fiberboard box conforming to PPP-B-636, class weather-resistant. Air-oil inlets and outlets of the lift equipment shall be sealed with cap or plugs conforming to MIL-C-5501 or with tape conforming to PPP-T-60, type optional. When furnished, hydraulic oils shall be shipped in drums(s) conforming to PPP-D-729.

5.2.1.4 Motors. Motors shall be preserved in accordance with level A requirements of MIL-E-16298, using the applicable requirements for assembled machines.

5.2.1.5 Electrical equipment. Unattached electrical equipment shall be preserved in accordance with level A requirements of MIL-E-17555. When attached, the electric control switch and switch box shall be protected by sealing all openings with tape conforming to PPP-T-60, type optional.

5.2.1.6 Technical data. Publications issued with the lifts shall be preserved in accordance with method IC-1 of MIL-P-116.

5.2.1.7 Consolidated packaging. Small components and technical data shall be consolidated and packed in one or more snug-fitting boxes conforming to PPP-B-601, domestic type, or PPP-B-621, class 1. Blocking and cushioning shall be applied in a manner to restrict movement within the container as specified in MIL-STD-1186.

5.2.2 Commercial. Commercial preservation shall be as specified in ASTM D3951-82.

5.3 Packing. Packing shall be Level A or commercial, as specified (see 6.2).

5.3.1 Level A. Each lift shall be packed in an open crate conforming to MIL-C-3774, type I, style A, or MIL-C-52950, type V, style B. Arrangement of contents, anchoring, blocking, bracing and cushioning shall be as specified in MIL-STD-1186.

5.3.2 Commercial. Commercial packing shall be as specified in ASTM D3951-82.

5.4 Marking. Marking shall be military, commercial, or civil, as specified (see 6.2).

5.4.1 Military. Military marking shall be as specified in MIL-STD-129.

5.4.2 Commercial. Commercial marking shall be as specified in ASTM D3951-82.

5.4.3 Marking for civil agencies. When specified (see 6.2), marking for shipment for civil agencies shall be as specified in FED-STD-123.

6. NOTES

6.1 Intended use. Type I lifts are intended to be used primarily for providing support to the vehicle axle while lifting motor vehicles. Type II lifts

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:59Z
Check the source to verify that this is the current version before use.

are intended to be used primarily for providing support to the vehicle frame while lifting motor vehicles.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type, class, size, and style required (see 1.2.1).
(c) First article when required (see 3.1).
(d) Automatic mechanical holding device if different (see 3.4.5.1).
(e) Any special safety devices required (see 3.4.5.1).
(f) Wheelbase capacity if different (see Table I).
(g) Inside tread range if different (see Table I).
(h) Trench covers when required (see 3.5.13).
(i) Motors if different (see 3.6.2).
(j) Painting and finishing if different (see 3.7).
(k First article inspection if different (see 4.3).
(l) Quality conformance inspection if different (see 4.4).
(m) Sampling if different (see 4.4.1).
(n) Level of preservation, packing, and marking if different (see 5.2, 5.3, and 5.4).
(o) Civil agency shipment marking when required (see 5.4.3).

6.3 Contract data requirements. Required technical data such as operator's manuals, parts lists, and other instructions for operation and maintenance, as identified on a numbered DD Form 1664, should be specified on a DD Form 1423 incorporated in the contract.

6.3.1 Repair part manuals. Repair part identification, in repair part manuals, shall include the prime contractor's name, nomenclature, part number, and price. Repair part identification shall also include the name of the original equipment/part manufacturer (OEM - actual part manufacturer), Federal Supply Code for Manufacturers (FSCM), nomenclature, part number, and price of the part immediately after the prime contractor's part identification. High mortality rate items shall be so identified as shown in MIL-M-7298.

6.4 OSHA standards. Products which meet all requirements of this specification comply with the OSHA standards published prior to the date of this specification and identified in Section 3 (see 3.4.5.2).

6.5 Definitions. Terms used in this specification are defined as follows:

(a) Rated capacity - as defined in ANSI B153.1.
(b) Height of rise - the distance between floor level and the points of contract between lifting members and the vehicle with the plunger(s) fully extended.
(c) Wheelbase - the distance between the centerlines of the front and rear axles on two axle vehicles and the distance between the centerline of the front axle and the centerline of the rearmost axle on three axle vehicles.
(d) Inside tread - the distance between the inner sides of the tires of the vehicle.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:59Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians
Army - AL
Air Force - 99

Review Activity
Air Force - 82

CIVIL AGENCY COORDINATING ACTIVITY:
GSA-FSS

PREPARING ACTIVITY:
Army - AL

DoD Project 4910-0595

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:59Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Research
and Development Center
ATTN: SMCAR-ETS (R)
Rock Island, IL 61299-7300

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:59Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
00-L-360, Rev D	Lifts, Motor Vehicle

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:59Z
Check the source to verify that this is the current version before use.