00-M-280G
January 17, 1977
SUPERSEDING
Fed. Spec. 00-M-280F
November 6, 1972

FEDERAL SPECIFICATION

MEAT SLICER, HAND-OPERATED, AND MEAT SLICING MACHINES, ELECTRIC

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers hand-operated, and electric-motor-operated meat slicing machines.

1.2 Classification. Meat slicing machines shall be of the following types, classes, styles, feeds, and models, as specified (see 6.2).

Type I - Hand-operated.

Type II - Motor-operated.

Class 1 - Fully automatic.

Style 1 - General (gravity chute).

Feed 1 - Constant speed.
Feed 2 - Variable speed.

Style 2 - With grouping, shingling, discharge conveyor attachment, and stand.

Class 2 - Semiautomatic.

Style 1 - General use.

Style 3 - Shipboard use.

Size 1 - Small craft use.
Size 3 - Submarine use.

FSC 7320

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

Model 1 - Bench mounting.
Model 2 - Pedestal mounted.
Model 3 - Stand (with casters).

(NOTE: Models not applicable to type I and to type II, style 2).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

L-P-378	-	Plastic Sheet and Strip, Thin Gage, Polyolefin.
CC-M-1807	-	Motors, Alternating Current, Fractional and Integral Horsepower (500 HP and Smaller).
FF-C-77	-	Casters, Rigid and Swivel (Institutional Duty).
QQ-A-250/8	-	Aluminum Alloy, 5052, Plate and Sheet.
QQ-C-320	-	Chromium Plating (Electro Deposited).
UU-P-268	-	Paper, Kraft, Wrapping.
MMM-A-260	-	Adhesive, Water Resistant (For Sealing Waterproofed Paper).
PPP-B-601	-	Boxes, Wood, Cleated-Plywood.
PPP-B-621	-	Boxes, Wood, Nailed and Lock Corner.
PPP-B-636	-	Boxes, Shipping, Fiberboard.
PPP-B-1055	-	Barrier Material, Waterproofed, Flexible.
PPP-C-650	-	Crates, Wood, Open and Covered.
PPP-T-45	-	Tape, Gummed, Paper Reinforced and Plain, for Sealing and Securing.

Federal Standards:

FED-STD-123	-	Marking for Shipment (Civil Agencies).
FED-STD-151	-	Metals; Test Methods.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

(Single copies of this specification and other Federal specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications:

MIL-C-104	-	Crates, Wood; Lumber and Plywood Sheathed, Nailed and Bolted.
MIL-P-116	-	Preservation-Packaging, Methods Of.
MIL-B-121	-	Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-V-13811	-	Varnish, Waterproofing, Electrical Ignition.
MIL-T-22085	-	Tapes, Adhesive, Preservation and Sealing.

Military Standards:

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-461	-	Electromagnetic Interference Characteristics, Requirements for Equipment.
MIL-STD-462	-	Electromagnetic Interference Characteristics, Measurement Of.
MIL-STD-1474	-	Noise Limit for Army Material.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

Underwriters Laboratories Inc. (UL) Standards

UL 73 - Motor-Operated Appliances

(Application for copies should be addressed to the Underwriters Laboratories Inc., 207 East Ohio Street, Chicago, IL 60611; 333 Pfingsten Road, Northbrook, IL 60062; 1285 Walt Whitman Road, Melville, L.I., New York 11746; 1655 Scott Boulevard, Santa Clara, CA 95050, or 2602 Tampa East Blvd., Tampa, FL 33169.)

American Society for Testing and Materials (ASTM) Standard

A 167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet and Strip

B 26 - Aluminum-Alloy Sand Castings
B 85 - Aluminum-Alloy Die Castings
B 108 - Aluminum-Alloy Permanent Mold Castings

E 18 - Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

National Sanitation Foundation (NSF) Standards

Basic Criteria C-2 Special Equipment and Devices

Standard No. 8 - Commercial Powered Food Preparation Equipment

Listing of Food Service Equipment

(Application for copies should be addressed to the National Sanitation Foundation, NSF Building, Ann Arbor, MI 48105.)

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Standard product. The meat slicing machines shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product with any added features needed to comply with the requirements of this specification. Modifications to add features shall not incorporate different parts unless such parts are used on other current commercial models. Standard or modified commercial products furnished in accordance with this specification shall be identifiable by all regular manufacturer's or commercial service organizations servicing the brand involved. Service organizations shall be capable of providing complete parts and repair services on models furnished to the Government consistent with their normal commercial practices.

3.2 Codes and standards. All electric meat slicing machines shall comply to the applicable requirements of UL 73 and NSF Standard No. 8 and hand-operated meat slicers shall comply to the applicable requirements of NSF Basic Criteria C-2.

3.2.1 Compliance. Prior to commencing production the contractor shall submit to the contracting officer or his authorized representative satisfactory evidence that the meat slicers he proposes to furnish under this specification meet the applicable requirements of UL 73 and NSF Standard No. 8 or NSF Basic Criteria C-2, as applicable.

3.2.1.1 UL. Acceptable evidence of meeting the requirements of this standard shall be the UL label or the UL listing mark, or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the electric meat slicing machines have been tested and conform to UL 73.

3.2.1.2 NSF. Acceptable evidence of meeting the requirements of NSF shall be:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" or display of the NSF seal on the finished meat slicer, or

(2) A certification for the meat slicing machine issued by NSF under their special one-time contract evaluation/certification service, or

(3) A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which meat slicing machines are being procured indicating that the slicers have been tested and conform to NSF Standard No. 8 or NSF Basic Criteria C-2, as applicable.

3.3 Materials and components. Materials and components shall be as specified herein. Materials not definitely specified shall be of the quality normally used by the manufacturer in his standard commercial meat slicing machines provided the completed item complies with all provisions of this specification.

3.3.1 Stainless steel. Stainless steel, with the exception of the slicing knife, shall conform to type 302 or 304 of ASTM A 167 or nickel copper alloy having not less than 60 percent nickel and 23 percent copper when tested as specified in 4.2.1.1.

3.3.1.1 Slicing knife. The slicing knife shall be heat treated stainless steel of cutlery grade having not less than 0.40 percent carbon and 13.00

3.3.2 Aluminum alloy

3.3.2.1 Castings. Aluminum alloy castings shall be sand, permanent mold or die casting. Sand castings shall conform to alloy designation 208.0, 319.0 or 355.0 of ASTM B 26. Permanent mold casting shall conform to alloy designation 208.0, 319.0, 333.0, 355.0 or 356 of ASTM B 108. Die castings shall conform to 360.0 or 380.0 of ASTM B 85.

3.3.2.2 Sheet. Aluminum alloy sheet shall conform to 5052-H24 or 5052-H34 of QQ-A-250/8.

3.3.3 Motors. Motors shall be either alternating current (a.c.) or direct current (d.c.) as specified (see 6.2). Single phase a.c. motors shall be of the split phase, repulsion-start induction, capacitor-start, or capacitor type of CC-M-1807. Direct current motors shall be compound wound. The motor operating voltage and the type current supply (and if a.c., the phase and frequency) shall be as specified (see 6.2). The motor shall be specifically designed to operate on the specific voltage and current (and if a.c. the phase and frequency) specified. When specified (see 6.2), the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

machine shall be equipped with a motor protective device using a thermal, or overheating-protective cut-out of either the automatic or manual reset type. In addition to the above requirements, the motor shall have the following characteristics:

Ambient temperature rating	50 degrees Centigrade (C) for 1/8 and 1/4 horsepower (hp) and 40C for 1/3 hp.
Enclosure	Totally enclosed, drip-proof, or splashproof.
Horsepower (hp)	Not less than 1/3 for class 1 and class 2, style 3, size 1. Not less than 1/4 for class 2, style 1. Not less than 1/8 for class 2, style 3, size 3.
Speed	Constant.
Duty	Varying.
Bearings	Ball or sleeve.
Insulation	Class A or B.

3.4 General construction and design. The machines shall be constructed as specified herein and shall be complete with all accessories necessary for satisfactory operation, and shall operate as intended without vibration or objectionable noise when tested as specified in 4.4.1 and 4.4.7. The slicing knives on all machines shall conform to 3.4.1. All parts of the type II machines, with the exception of the slicing knife, that contact food shall be fabricated of the stainless steel specified in 3.3.1 or aluminum castings or sheet specified in 3.3.2.1 and 3.3.2.2, except that at the option of the manufacturer meat pushers, end weights, and spring feed plates may be of die cast zinc base alloy, nickel-chrominm plated as specified in 3.6. On type I machines in addition to the materials specified for the type II machines parts that contact food such as meat carriages, knife face plates, thickness adjusting face plates, receiving trays, meat supports, holders, clampers and pushing devices may be fabricated of carbon-steel, nickel-chromium plated as specified in 3.6.

3.4.1 Slicing knife. Each machine shall have a sharpened slicing knife fabricated of the material specified in 3.3.1.1. The hardness of the slicing

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

knife, measured one-fourth of an inch back of the cutting edge shall be not less than 56 nor more than 60 on the Rockwell C scale when tested as specified in 4.4.2.

3.4.2 Slicing knife drive. The slicing knife shall be driven by gears, a steel transmission chain, V-belt, poly V-belt, or timing belt. If driven by gears, the teeth shall be machine cut and deburred, and the gears shall be securely mounted on shafts. If fiber gears are used, they shall be fabricated of laminated phenolic material with uniformly woven fibers with tensile strength of 13000 pounds per square inch (psi) to 15000 psi with hardness of 74 to 75 inclusive as measured on the Rockwell Superficial Scale 15-T when tested as specified in 4.4.2.

3.4.3 Meat supports. The meat carriage and any devices for clamping or pushing the meat shall hold the meat securely in cutting position.

3.4.4 End-holding device. The type I machine shall have a device which secures the end of the meat and allows the meat to be uniformly sliced to within the last 1 inch. The type II, class 1 and 2 machines designed for gravity feed shall have an end weight or spring feed plate with teeth which permits slicing to within the last 1/4 inch.

3.4.5 Trays. A receiving tray or an area that is part of the base shall be furnished to provide a surface to accommodate slices of the largest cross sections of meat specified in the performance requirements of the type machine furnished. A tray or pan for catching the meat particles and meat juices shall be provided, unless the arrangement of the machine is such that none is necessary.

3.4.6 Housing and guards. Metal housings or metal guards shall be provided so as to enclose gears, belts, and both sides of the knife except where the cutting is done. The guards or housings shall protect the gears and belts against accumulation of meat particles and grease. At the point where cutting is done, a safety device shall prevent the operator's fingers from accidentally coming in contact with the slicing edge. Guards at the knife shall be removable or hinged for cleaning. All other guards and housing covers shall be designed so they can be dismantled for inspection and cleaning.

3.4.7 Bases and pedestals. The type I meat slicer shall be provided with four rubber feet for use on a table or counter. The type II, style 1 and 3 meat slicing machines shall be for bench mounting, or provided with a pedestal, as specified. If the machine is for bench mounting, the machine shall have a

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

base suitable for attachment to either a bench or stand. If the machine is furnished with a pedestal the pedestal shall be nonimal 34 inches high with provisions for securing to the floor.

3.4.7.1 Stand. When a model 3 machine is specified, the meat slicing machine shall be mounted on a corrosion-resisting steel stand, equipped with four legs and casters. The stand shall be of an open base, welded construction with a nominal overall height of 34 inches. The frame shall be constructed of not less than nominal 1-1/4 inch type 302 or 304 stainless steel tube having a minimum wall thickness of 0.083 inches. The tubular uprights forming the legs shall be welded at the top and bottom to horizontal tubular cross braces forming a one piece welded unit. The stand shall be provided with a stainless steel sheet top platform not thinner than 16 gage (0.0625 inch nominal). The top shall have an area for mounting the specified slicing machine and shall be provided with holes necessary for mounting the slicer. Reinforcing shall be provided under the top platform to rigidly support the machine. Edges of the top shall be flanged or rolled down over the top of the frame and shall be secured to allow ease of cleaning. Each leg shall be provided with a caster conforming to type II, class A, wheel diameter 5 inches, style A, B or C, mounting A or N of FF-C-77. Two of the casters shall be equipped with brakes. Casters shall be removable. The stand shall be capable of supporting a load of 175 pounds without deformation of the stand or casters when tested as specified in 4.4.8.

3.4.8 Bearings. Bearings for cutting knives, idler gears, and revolving drive shafts shall be of the ball, roller, or sleeve-type, either permanently lubricated or with a readily accessible means of lubrication. Sleeve type bearings shall be a high-grade bearing metal and shall be replaceable. All bearings shall be arranged so that the lubricant cannot come in contact with the product being cut. Meat carriage slide and other components requiring lubrication shall be accessible.

3.4.9 Scraper. A scraper or scrapers, fabricated of the material specified in 3.3.1 shall be provided, when necessary, to remove all waste particles adhering to the knife when the machine is in operation. This requirement shall not apply where the position or arrangement of the knife is such that no accumulation of meat particles will occur. Scrapers, if used, shall be readily accessible for cleaning.

3.4.10 Sharpener. The type I meat slicer shall be provided with a one or a two-stone sharpener. The type II meat slicers shall be provided with a two-stone sharpener. The sharpener shall be attached to the slicing knife frame, or supplied as a separate removable item fastened to the base of the machine with a removable nut or bolt. When the sharpener is a separate unit, a container or drawer within the machine structure shall be provided

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

for storing the sharpener when not in use. The design shall also eliminate the necessity of lifting or tilting the machine to remove the sharpener from storage. When not in use, the position of the nonremovable sharpener shall be such that no meat particles or juice shall accumulate. The sharpener shall be capable of sharpening the knife to produce slices of meat that are smooth and free from tears and bruises when tested as specified in 4.4.6.

3.4.11 Type I (hand-operated).

3.4.11.1 Design. The machine shall have a rotating slicing knife and a meat carriage arranged to move the meat reciprocally in relation to the knife. The slicing knife shall be operated by a manually driven wheel or handle. The meat shall be advanced manually to the slicing position, either by gravity feed or a meat pushing device, or a combination of both.

3.4.11.2 Performance. The machine shall be capable of evenly slicing firm cold meat, and hot and soft meat of rectangular cross sections as large as 7-1/4 inches wide by 4-1/4 inches high at a rate of not less than 35 slices per minute when tested as specified in 4.4.5. Each cut surface of each slice shall be smooth and free from tears or bruises.

3.4.11.3 Slice thickness. An adjustable mechanical device shall be provided so that the machine cuts slices from 1/48 to at least 3/8 inch thick.

3.4.11.4 Slicing knife. The slicing knife shall conform to 3.4.1 and shall be not less than 9 inches in diameter.

3.4.12 Type II (motor-operated), class 1 (fully automatic) style 1 (general use).

3.4.12.1 Feed 1 (constant).

3.4.12.1.1 Design. The machine shall have a rotating slicing knife and a constant feed gravity feed chute arranged to move the meat reciprocally in relation to the knife. The slicing knife and the gravity feed chute shall be simultaneously operated by an electric motor or motors conforming to 3.3.3. The machine shall be equipped with a gauge plate and either a gravity end weight or spring feed plate. The design of the machine shall permit manual operation of the gravity feed chute in the event the constant feed drive becomes inoperative or is not desired.

3.4.12.1.2 Performance. The machine shall be capable of slicing firm cold meat or hot and soft meat of any rectangular cross section up to 9 inches wide by 5-5/8 inches high at a rate of not less than 35 slices per minute when tested as specified in 4.4.5. Each cut surface of each slice shall be smooth and free from tear or bruises.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.4.12.1.3 Slice thickness. An adjustable mechanical device shall be provided so that the machine slices from 1/48 inch to not less than 5/16 inch thick. When specified (see 6.2), a machine shall be provided to cut slices that are from 1/48 inch thick to not less than 17/32 inch thick.

3.4.12.1.4 Slicing knife. The slicing knife shall conform to 3.4.1 and shall be not less than 11 inches in diameter.

3.4.12.1.5 Motors. The slicing knife motor shall be as specified in 3.3.3. The slicing knife motor shall operate the feed chute speed or a separate motor may be provided. When a separate motor is provided for the feed chute, the motor shall be of sufficient horsepower to meet the specified performance requirements and shall be provided with overload protection. When the chute is driven by the slicing knife motor the drive shall be accomplished by gearing.

3.4.12.1.6 Switch and wiring. The machine shall have an enclosed, quick-break switch which shall open all motor leads. The switch shall be an indicating type or be provided with a pilot light to indicate when the switch is in the "on" position. The indicating type switch shall be recessed into the body structure of the slicing machine or may be shielded to prevent inadvertant actuation. There shall be no electrical or mechanical failure, and no pitting or burning of contacts when the switch is tested as specified in 4.4.3. If the switch is a sealed type, the manufacturer may replace the tested switch with an identical model provided the tested switch satisfactorily passed the test. Unless otherwise specified (see 6.2), slicing machines shall be furnished with a flexible supply cord conforming to type ST, STO, SO, SJO, SJT, or SJTO of UL 73 not less than 8 feet in length. The supply cord shall be a 3-wire grounding type provided with a 3-prong grounding type plug. Cord and plug shall provide grounding for the machine. The motor, switch, and supply cord shall be wired ready for operation. All wires and terminals shall be fully enclosed.

3.4.12.2 Feed 2 (variable).

3.4.12.2.1 Design. The machine shall have a rotating slicing knife and a variable speed gravity feed chute. The feed chute shall be equipped with a variable speed selector to regulate the slicer speed from 0 to 55 strokes per minute minimum. The machine shall be equipped with a gauge plate and either a gravity end weight or spring feed plate. The design of the machine shall permit manual operation of the gravity feed chute in the event the variable speed drive becomes inoperative or is not desired.

3.4.12.2.2 Performance. The machine shall be capable of slicing firm cold meat or hot and soft meat of any rectangular cross section up to 10-3/4 inches wide by 3 inches high and round pieces up to 7 inches in diameter at

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

the rate specified in 3.4.12.2.1 when tested as specified in 4.4.5. Each cut surface of each slice shall be smooth and free from tears or bruises.

3.4.12.2.3 Slice thickness. An adjustable, mechanical device shall be provided to allow slicing of meats from 1/48 inch to at least 5/8 inch thick. Slice thickness shall be indicated on a graduated dial in a location readily visible to the operator.

3.4.12.2.4 Slicing knife. The slicing knife shall conform to 3.4.1 and shall be not less than 11 inches in diameter.

3.4.12.2.5 Motors. The slicing knife motor shall be as specified in 3.3.3. The slicing knife motor shall operate the feed chute speed or a separate motor may be provided. When a separate motor is provided for the feed chute, the motor shall be of sufficient horsepower to meet the specified performance requirements and shall be provided with overload protection. When the chute is driven by the slicing knife motor the drive shall be accomplished by gearing.

3.4.12.2.6 Switch and wiring. The switch and wiring shall be as specified in 3.4.12.1.6.

3.4.13 Type II (motor-operated), class 1 (fully automatic), style 2 (with grouping, shingling, and conveying attachment).

3.4.13.1 Design. The machine shall have a rotating slicing knife and a meat carriage arranged to move the meat reciprocally in relation to the knife. The meat carriage shall have a screw mechanism which shall automatically advance the carriage a predetermined amount, equal to the thickness of the slice being cut, for each slicing operation until the limit of advance of the meat carriage is reached. A synchronized discharge conveyor shall be incorporated in the design to automatically receive the slices. The conveyor shall have automatic controls for stopping and advancing the conveyor belt to permit stacking, grouping, and shingling of the sliced product. The slicing knife, meat carriage, and conveyor belt shall be simultaneously operated by an electric motor.

3.4.13.2 Performance. The machine shall be capable of evenly slicing firm cold meat with overall dimensions up to 24 inches in length, 9-1/2 inches wide and 5-5/8 inches high at a rate of not less 48 slices per minute when tested as specified in 4.4.5. The slices as received on the conveyor shall be neatly and uniformly stacked and grouped or shingled. The spacing between center of stacks shall be between 6-1/4 and 7 inches. Each cut surface of each slice shall be smooth and free from tears or bruises.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.4.13.3 Adjustment. Adjustable mechanical devices shall be provided so that the machine will cut slices up to 5/32 inch thick, stack at least 4 to 12 slices, and overlap, if shingling, 0 to 1-1/2 inches.

3.4.13.4 Slicing knife. The slicing knife shall conform to 3.4.1 and shall be not less than 14 inches in diameter.

3.4.13.5 Conveyor belt. The belt shall be of two-ply endless construction and of sufficient width to receive the largest slices of meat capable of being sliced on the machine. The overall length of the conveyor shall be not less than 55 inches and the effective working length of the belt shall be not less than 47 inches. The belt shall be of fabric with one side covered with white neoprene at least 1/32 inch thick, impregnated in the fabric. The total thickness of the belt shall be 1/8 inch, plus or minus 1/32 inch.

3.4.13.6 Motor. The motor shall be as specified in 3.3.3.1.

3.4.13.7 Switch and wiring. The switch and wiring shall be as specified in 3.4.12.1.6.

3.4.13.8 Stand, type II, style 2. A stand shall be provided with the type II, style 2 meat slicing machine. The stand shall have four legs with an open base and shall be of welded construction with a minimum height of 32 inches. The frame shall be constructed of 1-inch structural steel pipe having a minimum wall thickness of 0.104-inch and a top frame fabricated from 2 by 2 by 3/16 inch angle iron with the 90 degree angle assembled on the outside with one leg of the angle down. The legs shall be welded to the top frame and to horizontal steel pipe cross braces, 8 to 10 inches above the floor. Vertical pipe braces shall be provided between cross bracing and top. One of the legs at the end of the stand where the machine is mounted shall have a stainless steel adjustable foot. The top shall have an area for mounting the machine with provisions for securing the machine to the stand. Reinforcing shall be provided under the top frame to rigidly support the machine. The stand shall have diagonal braces on sides and ends. The diagonal braces shall be fabricated of 1-1/2 inches wide by 1/4 inch hot-rolled flat steel. The diagonal and vertical braces shall be welded at the ends. Diagonal and braces shall be welded in the center where the braces cross.

3.4.14 Type II (motor-operated), class 2 (semiautomatic), style 1 (general use).

3.4.14.1 Design. The machine shall have a rotating slicing knife and a meat carriage arranged to move the meat reciprocally in relation to the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

knife. The slicing knife shall be operated by an electric motor. The meat carriage shall be moved manually by means of a handgrip or handle. The meat shall be advanced to the slicing position, either by the combination of a spring operated meat pusher plate and thickness adjusting plate, or by an inclined meat carriage and gravity feed with end weight.

3.4.14.2 Performance. The machine shall be capable of evenly slicing firm cold meat or hot and soft meat of any rectangular cross section up to 9-5/8 inches wide by 3 inches high, or up to 6-1/2 inches in diameter. The meat carriage shall be capable of being reciprocated to produce not less than 40 slices per minute when tested as specified in 4.4.5. There shall be no excessive impact at the limit of either the forward or backward motion of the meat carriage. Each cut surface of each slice shall be smooth, and free from tears or bruises.

3.4.14.3 Adjustment of cut. An adjustable mechanical device shall be provided so that the machine cuts slices from 1/48 inch to not less than at least 3/8 inch thick.

3.4.14.4 Slicing knife. The slicing knife shall conform to 3.4.1 and shall be not less than 10 inches in diameter.

3.4.14.5 Motor. The motor shall be as specified in 3.3.3.

3.4.14.6 Switch and wiring. The switch and wiring shall be as specified in 3.4.12.1.6.

3.4.14.7 Weight. The total weight of the machine, with base for attachment to bench or table but without pedestal, shall not exceed 175 pounds when tested as specified in 4.4.9.

3.4.15 Type II (motor-operated), class 2 (semiautomatic), style 3, size 1 (small craft use).

3.4.15.1 Design. Machine design shall comply with the requirements specified in 3.4.14.1.

3.4.15.2 Performance. The performance shall comply with the requirements specified in 3.4.14.2.

3.4.15.3 Adjustment of cut. Adjustment of slice thickness shall comply with the requirements specified in 3.4.14.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.4.15.4 Slicing knife. The slicing knife shall comply with the requirements specified in 3.4.1 and 3.4.14.4. A sharpener conforming to the requirements of 3.4.10 shall be provided.

3.4.15.5 Motor. The motor shall be as specified in 3.3.3.

3.4.15.6 Switch and wiring. The switch and wiring shall comply with the requirements specified in 3.4.12.1.6.

3.4.16 Type II (motor-operated), class 2 (semiautomatic), style 3, size 3 (submarine use).

3.4.16.1 Design. Machine design shall comply with the requirements specified in 3.4.14.1 except that the meat carriage shall be horizontal and the machine shall not exceed 60 pounds in weight when tested as specified in 4.4.9. The overall dimensions shall not exceed 20-3/4 inches in length, 18 inches in width, and 14 inches in height.

3.4.16.2 Performance. The performance shall comply with the requirements specified in 3.4.14.2, except the machine shall be capable of slicing meat as large as 8-3/8 inches wide by 4 inches high, or up to 6 inches in diameter.

3.4.16.3 Adjustment of cut. Adjustment of slice thickness shall comply with the requirements specified in 3.4.14.3.

3.4.16.4 Slicing knife. The slicing knife shall comply with the requirements of 3.4.1 and 3.4.14.4.

3.4.16.5 Motor. The motor shall be as specified in 3.3.3.

3.4.16.6 Switch and wiring. The switch and wiring shall comply with the requirements specified in 3.4.12.1.6.

3.4.16.7 Sharpener. The machine shall be provided with a sharpener as specified in 3.4.10.

3.5 Electromagnetic compatibility. When specified (see 6.2), the meat slicers shall be designed and equipped for electromagnetic compatibility in accordance with class IIB of MIL-STD-461.

3.6 Noise limits. The meat slicing machine, except type I, shall not exceed 85 decibels A, weighted at the normal operator position when tested as specified in 4.4.10.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.7 Finish. Vitreous enamel shall not be used as a finish on any parts. Aluminum parts contacting food shall be anodized with the film sealed in water at a temperature between 120 and 212 degrees Fahrenheit (F). Molded nylon or plastic knobs and handles meeting NSF standards are acceptable. Finishes shall be uniform in appearance and free from powdery areas. Application of finishes shall be in accordance with the manufacturer's standard commercial practice. Components fabricated of carbon steel (including the knife) and die cast zinc base alloy parts shall be chrome-plated in accordance with class 1, type I of QQ-C-320.

3.8 Identification marking. Identification marking shall be permanently and legibly marked directly on the item or on an aluminum, brass, or stainless steel plate firmly affixed to the item. Marking shall be stamped, embossed, engraved, or applied by photosensitive means. The plate thickness shall be not less than 0.012 inches. The identification plate shall include the marking requirements of UL 73.

3.9 Repair and maintenance. Provisions shall be made to allow for ready adjustment, service, and replacement of the slicing knife, knife sharpener, electric motor, and conveyor belt (if applicable). In addition, there shall be free access to inspect, service, and adjust any component or equipment manufactured, without requiring disassembly of any other major component or equipment on the machine.

3.10 Fastening devices. All screws pins, and bolts shall be installed with means for preventing loss of tightness and adjustment. All such parts, when subject to removal or adjustment, shall not be peened, swaged, staked, or otherwise permanently deformed.

3.11 Lubrication. All moving parts requiring lubrication shall be provided with means of lubricating and shall be lubricated before delivery. Lubrication fittings shall be readily accessible.

3.11.1 Lubrication chart. A lubrication chart shall be furnished by the contractor and attached to each machine. The instructions on the chart shall indicate the grade of lubricant to be used and the parts to be serviced periodically.

3.12 Workmanship. Threaded fasteners shall be drawn tight. Burrs, rough edges, and slivers shall be removed. Welds and brazes shall be smooth, sound, and free from porosity, burn holes, cracks, fractures and incomplete fusion. All scale and flux deposits shall be removed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

4.1 QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. Except where otherwise indicated herein, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1 components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.2.1.1 Chemical analysis. Material specified in 3.3.1, 3.3.1.1 and nickel copper alloy, shall be tested for chemical analysis in accordance with method 111.2 of FED-STD-151. Failure to meet specified requirements shall be cause for rejection of the lot. The lot shall be the amount of material presented for inspection at one time.

4.2.2 In-process inspection.

4.2.2.1 Hardness testing. The slicing knife and fiber drive gear, if provided shall be tested for hardness in accordance with 4.4.2. The inspection level shall be S-3. The lot shall consist of all slicing knives and gears offered for inspection at one time. The sample unit shall be a slicing knife or gear. Whenever nonconformance is noted, correction shall be made to the affected items and the lot.

4.2.2.2 Anodizing. The anodizing process shall be examined to determine conformance with 3.6. Whenever nonconformance is noted, correction shall be made to the affected items and the lot in process.

4.2.3 End product inspection. The lot shall consist of all meat slicing machines of one type, class, style, feed, size and model offered for inspection at one time. The sample unit shall be a complete meat slicing machine.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

4.2.3.1 Visual examination. Examination shall be made of the meat slicing machine for the defects listed in table I. The inspection level shall be level II with an AQL of 2.5, expressed in terms of defects per hundred units.

TABLE I. Classification of defects

Examine	Defect
Standard product	Item not in accordance with manufacturer's standard product except for changes necessary to comply with specification requirements.
Finish	Not as specified in surfaces contacting food. Not as specified on other surfaces. Any rough or sharp edges or burrs. Surfaces blistered, peeled, chipped, or area of no film or thin film (metallic coatings).
Design and construction general (applicable to all components and assemblies)	Any wearing part not accessible for adjustment and replacement. Part missing or not specified type (unless otherwise classified herein). Any component fractured, dented, deteriorated, bowed, or malformed. Any component misplaced, loose, or not in proper alignment. Functioning component that is inoperative or will not operate as intended. Functioning component that requires abnormal force to operate. Not connected or joined as specified or poorly accomplished. Any adjustable assembly that cannot be adjusted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

Examine	Defect
Design and construction general (applicable to all components and assemblies) (cont'd)	Any adjustable assembly not properly adjusted to perform the function intended. Any component not readily accessible for servicing where required.
Welding (where required)	Missing, incomplete, burn holes, cracked, fractured, or otherwise not fused. Slag inclusion, slight undercut, not smooth and uniform, scale or flux deposits not removed.
Threaded fasteners	Missing, broken, stripped, or fractured. Loose.
Rivets (where applicable)	Missing or broken. Insufficiently peened or loose.
Electrical assembly	Wiring cut, abraded, not properly joined, loose at terminal, or not inclosed where required. Adequate slack not provided for wiring to relieve strain or excessive insulation stripped from wiring. Indicating type switch (as applicable) not recessed into body or not shielded.
Gages	Not properly calibrated, not specified capacity.
Lubrication (where applicable)	Not lubricated where required. Insufficiently lubricated. Lubrication fitting not readily accessible for servicing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

Examine	Defect
Assembly	Any component not properly assembled or secured. Unit perceptibly out of square or alignment.
Marking for identification	Missing, incomplete, not legible, not specified type, not in proper location, not affixed in the prescribed manner, not correct material.

4.2.3.2 Dimensional examination. An examination shall be made of the end item to determine compliance with dimensions specified. Any nonconformance shall constitute a defect. The inspection level shall be S-2 with an AQL of 4.0 defects, expressed in terms of defects per hundred units.

4.2.3.3 End item testing. Each machine shall be tested in accordance with 4.4.1. Failure to pass the test shall be cause for rejection of the individual machine. One representative production unit shall be tested as specified in 4.4.3, 4.4.5, 4.4.6, 4.4.7, 4.4.8 and 4.4.10 (except type I) and 4.4.4 and 4.4.9 when applicable. Failure of any test shall be cause for rejection of the lot.

4.2.4 Examination of packaging. An examination shall be made to determine that preservation-packaging, packing, and marking comply with the requirements of section 5. Defects shall be as indicated in table II. The sample unit shall be a shipping container fully prepared for delivery. The lot shall be the number of containers offered for inspection at one time. The inspection level shall be S-4 with an AQL of 6.5 defects, expressed in terms of defects per hundred units.

TABLE II. Examination of packaging

Examine	Defect
Markings, interior and exterior	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Preservation	Preservative improperly applied or missing

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

TABLE II. Examination of packaging (cont'd)

Examine	Defect
Materials	Component missing, damaged, or otherwise defective affecting serviceability.
Workmanship	Bolts missing or improperly affixed; blocking and cushioning inadequate or missing.
Content	Contents per container is more or less than required.

4.2.4.1 Examination of shipping containers. When shipping containers are required to be in accordance with PPP-B-601, PPP-B-621, PPP-B-636, PPP-C-650, or MIL-C-104, examination for defects in closure, waterproofing, anchoring and strapping shall be in accordance with appendix of the applicable container specification.

4.3 Certificate examination. Certificates of compliance, certified test reports, approval labels or listing marks for codes and standards, as applicable, that are submitted as proof of compliance with the specification requirements shall be examined and validated.

4.4 Test methods.

4.4.1 Operational test. Each machine shall be operated without load to determine that the machine complies with operational requirements of 3.4. Inability of the meat slicing machine to operate without vibration or objectional noise shall constitute failure of this test.

4.4.2 Rockwell hardness. The knife and fiber drive gears, if provided, shall be tested for hardness in accordance with ASTM E 18 (see 3.4.1 and 3.4.2).

4.4.3 Switch test. The machine shall be connected to a supply circuit of nominal rated voltage and rated frequency if a.c., with the rotor of the motor blocked in a stalled condition. In lieu of blocking, the motor may be removed from the machine and locked in a bench fixture. While in this condition, the motor switch shall be operated through 50 cycles of operation at 5 cycles per minute to determine conformance with 3.4.12.1.6. Each cycle shall consist of snapping the switch on and immediately snapping it off, then allowing an off period of not less than 10 seconds before the cycle is repeated. During the test, exposed noncurrent carrying metal

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

parts of the machine shall be grounded and the ungrounded conductors in the supply circuit provided with protective fuses or current-rupturing devices, suitable for carrying the stalled rotor current. Inability of the switch to operate through the specified number of times, as specified, shall constitute failure of this test.

4.4.4 Electromagnetic compatibility test. When electromagnetic compatibility is required, the first article or initial unit of production as specified shall be tested by the supplier in accordance with test method CE03, and RE02 of MIL-STD-462. The Government reserves the right to witness tests performed by the supplier or his private testing organization. The supplier shall furnish the contracting officer written certification that the Interference Control Plan, the EMI/EMC Test Plan, the Electromagnetic Test Report and the requirements meet MIL-STD-461.

4.4.5 Performance test. The machine shall be set to slice thickness not exceeding 1/16 inch and operated with load to determine that it is capable of slicing meat at the rate and with clean cuts as specified in 3.4.11.2, 3.4.12.1.2, 3.4.12.2.2, 3.4.13.2 (check stacking, grouping, and shingling), 3.4.14.2 and 3.4.15.2 and 3.4.16.2. The machine shall be tested by slicing firm cold meat and hot and soft meat as applicable for at least five minutes each. Inability of the meat slicing machine to meet the specified requirement shall constitute failure of this test.

4.4.6 Sharpener test. The slicing knife shall be dulled to a point where the slices of meat cut are rough or ragged. Then the sharpener shall be placed in operating position and run through a complete sharpening cycle. After sharpening, the meat shall be sliced and checked for conformance with the meat cutting performance requirements of 3.4.10. Inability of the machine to resharpen the knife and cut meat smoothly shall constitute failure of this test.

4.4.7 Rough handling test (transportation) for type II, class 2, slicing machines. The meat slicers packed as specified in 5.2.1.4 or 5.2.2.4, shall be subjected to the rough handling test specified in MIL-P-116. At the conclusion of the test, the meat slicing machine shall be connected to the specified power supply and operated for 10 minutes to determine compliance with the operational capability specified in 3.4. Inability of the machines to meet the specified requirements of this test shall constitute failure of this test.

4.4.8 Stand. The stand top shall be loaded with equally distributed weights totalling 175 pounds for 10 minutes. At the end of this period the load shall be removed and the stand examined to determine conformance

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

with deformation requirements of 3.4.7.1. Inability of the stand to withstand the specified load for 10 minutes shall constitute failure of this test.

4.4.9 Weight. The type II, class 2, style 1 and the type II, class 2, style 3, size 3 meat slicers shall be weighed on a scale, certified accurate for trade purposes, to determine compliance with the weight requirements of 3.4.14.7 or 3.4.16.1, as applicable. Any nonconformance with specified requirements shall constitute failure of this test.

4.4.10 Noise test. The meat slicing machine shall be tested in accordance with MIL-STD-1474 to determine conformance with 3.6. Any nonconformance to be within the noise limit shall constitute failure of this test.

5. PREPARATION FOR DELIVERY

5.1 Preservation-packaging. Preservation-packaging shall be in accordance with MIL-P-116 as specified herein.

5.1.1 Level A. Preservation-packaging shall be in accordance with MIL-P-116 as specified herein.

5.1.1.1 Preservation.

5.1.1.1.1 Disassembly. All detachable protruding parts of each machine that might be damaged during shipment shall be removed.

5.1.1.1.2 Cleaning and drying. All exposed ferrous metal surfaces and the slicing knife shall be cleaned process C-1 and thoroughly dried.

5.1.1.1.3 Application of preservative. Surfaces cleaned and dried as specified shall be coated with type P-14 preservative.

5.1.1.1.4 Lubrication. All bearings and parts requiring lubrication shall be lubricated to capacity with the manufacturer's recommended lubricant containing a rust inhibitor.

5.1.1.1.5 Protection of preservative. Surfaces from which preservative compound might be removed by contact with packaging and packing materials shall be covered or wrapped with greaseproof barrier material conforming to type I or II, grade A, class 1 or 2 of MIL-B-121. Barrier material shall be secured with tape conforming to type III, grade B of PPP-T-45, cotton tape or twine, or heat sealed when heat sealable barrier material is used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

5.1.1.1.6 Sealing. Switches, terminals, control boxes, and all openings into the motor shall be sealed with tape conforming to MIL-T-22085 and the tape overcoated with varnish conforming to MIL-V-13811. A caution tag shall be attached to the switch or electric cord with the following inscription:

CAUTION: Remove protective tape from the exterior of the motor before operation of the machine.

5.1.1.2 Packaging.

5.1.1.2.1 Type I machines. Parts of each type I machine that are free to move shall be secured in place to prevent movement while in transit. Exposed edges of the slicing knife shall be protected with fiberboard or other cushioning material. Each machine shall be packaged in a fiberboard box conforming to style RSC, type CF, variety SW, class domestic of PPP-B-636. Corrugated fiberboard inserts made from the same material as the box shall be used to provide a minimum of one half inch clearance between the inner surfaces of the box and projecting parts of the machine, and to immobilize the machine in the box. Accessories, if any, shall be packaged in accordance with method III of MIL-P-116. The packaged accessories shall be placed and secured in the same box as the machine. Box closure shall be in accordance with the appendix of PPP-B-636.

5.1.1.2.2 Type II machines. Parts of each type II machine that are free to move shall be securely fastened in a fixed position to prevent movement while in transit. Exposed edges of the slicing knife shall be protected with fiberboard or other cushioning material. The electric cord shall be coiled and secured to the machine. Detached components, shall be packaged in accordance with method III of MIL-P-116. The tools and repair parts for class 2, style 3 machines, preserved as specified in 5.1, shall be packaged in accordance with method III of MIL-P-116. Each box shall be closed in accordance with the appendix of PPP-B-636.

5.1.2 Level C. The machine shall be preserved-packaged to afford adequate protection against corrosion deterioration and physical damage during shipment from supply source to the first receiving activity. The supplier may use his standard practice when it meets these requirements.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

5.2.1.1 Type I machines. Two type I machines, preserved-packaged as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to style RSC, grade V2s of PPP-B-636. Each fiberboard container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of PPP-B-636.

5.2.1.2 Type II, class 1, style 1 machines. Each type II, class 1, style 1 machine, preserved and packaged as specified in 5.1, shall be packed in a shipping container conforming to overseas type, style A or J, grade A or B, type 3 load of PPP-B-621. Shipping containers shall be provided with skids in accordance with the applicable container specification. The machine shall be securely bolted to the base and skids of the shipping container with not less than four bolts. Detached components shall be secured in an unused portion of the shipping container. The machine shall be covered with a full-length shroud made of waterproof barrier material conforming to class E-2, H-5, or M-1 of PPP-B-1055. All seams of the shroud shall be sealed with a minimum three-fourths of an inch wide continuous seam of water-resistant adhesive conforming to MMM-A-260. Alternatively, the shroud may be fabricated from polyethylene with all seams heat sealed. The polyethylene flexible film shall be 0.003-inch thick conforming to type I of L-P-378. Closure and strapping shall be in accordance with the appendix of the applicable container specification. Stands for model 3 machines shall be packed as specified in 5.2.1.5.

5.2.1.3 Type II, class 1, style 2 machines. Each type II, class 1, style 2 machine, preserved-packaged as specified in 5.1, shall be packed in a shipping container conforming to type I of MIL-C-104. The machine shall be secured within the container in accordance with the appendix of the container specification. Detached components shall be secured in an unused portion of the shipping container. Closure and strapping shall be in accordance with the appendix of the container specification.

5.2.1.4 Type II, class 2 machines. Each type II, class 2 machine, preserved-packaged as specified in 5.1, shall be packed in a shipping container, in a manner so as to have no visible evidence of damage after being tested as specified in 4.4.7. Each shipping container shall conform to overseas type, style A or J, grade A or B, type 3 load of PPP-B-601 or class 2, style 2 or 4, grade A or B, type 3 load of PPP-B-621. Shipping containers shall be provided with skids in accordance with the applicable container specification. Each machine shall be covered with a full-length shroud as specified in 5.2.1.2. Closure and strapping shall be in accordance with the appendix of the applicable container specification. Stands for model 3 machines shall be packed as specified in 5.2.1.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

5.2.1.5 Stands. Each stand for model 3 and type II, style 2 machines shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, grade V2s of PPP-B-636. Fiberboard inserts shall be used, as necessary, to prevent projecting parts of the stand from contacting interior surfaces of the shipping container. Each fiberboard container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of PPP-B-636.

5.2.2 Level B.

5.2.2.1 Type I machines. Two type I machines, preserved-packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF (variety SW) or SF, class domestic of PPP-B-636. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.2 Type II, class 1, style 1 machines. Each type II, class 1, style 1 machine, preserved-packaged as specified in 5.1, shall be packed as specified in 5.2.1.2, except that shipping containers shall conform to class 1, style 2 or 4, grade B, type 3 load of PPP-B-621, or domestic type, style A or J, grade B, type 3 load of PPP-B-601; the shroud shall be fabricated from 40-pound kraft wrapping paper conforming to UU-P-268 or polyethylene as specified in 5.2.1.2. Stands for model 3 machines shall be packed as specified in 5.2.2.5. Each shipping container shall be provided with skids as specified in 5.2.1.2.

5.2.2.3 Type II, class 1, style 2, machines. Each type II, class 1, style 2 machine, preserved-packaged as specified in 5.1, shall be packed as specified in 5.2.1.3, except that the crate shall conform to type IV of PPP-C-650 and shall be provided with a shroud as specified in 5.2.2.2.

5.2.2.4 Type II, class 2 machines. Each type II, class 2 machine, preserved-packaged as specified in 5.1, shall be packed and tested as specified in 5.2.1.4, except that shipping containers shall conform to class 1, style 2 or 4, grade B, type 3 load of PPP-B-621, or domestic type, style A or J, grade B, type 3 load of PPP-B-601; shroud shall be as specified in 5.2.2.2. Stands for model 3 machines shall be packed as specified in 5.2.2.5.

5.2.2.5 Stand. Each stand for model 3 and type II, style 2 machine shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF (variety SW) or SF, class domestic of PPP-B-636. Fiberboard inserts shall be used, as necessary to prevent projecting parts of the stand

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

from contacting interior surfaces of the shipping container. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.6 Weather-resistant fiberboard containers. When specified (see 6.2), the fiberboard shipping containers specified in 5.2.2.1 and 5.2.2.5 shall be a grade V3c, V3s or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of the container specification.

5.2.3 Level C. Machines, preserved-packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.3 Marking. Marking shall be in accordance with 5.3.1 or 5.3.2 as specified (see 6.2).

5.3.1 Civil agencies. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with FED-STD-123.

5.3.2 Military requirements. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129. Set marking requirements shall apply to shipping containers for model 3 machines.

6. NOTES

6.1 Intended use. The meat slicers covered by this specification are intended for use in kitchens, galleys, central meat cutting plants, and commissary store meat markets.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type, class, style, feed, model and size required (see 1.2).
(c) Voltage and type of current (and if a.c. the phase and frequency required (see 3.3.3).
(d) When a motor protective device is required (see 3.3.3).
(e) When slice thickness of 17/32 is required (see 3.4.12.1.3).
(f) Length of extension cord, if other than specified (see 3.4.12.1.6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

(g) When electromagnetic compatibility is required (see 3.5).
(h) Selection of the applicable levels of preservation-packaging, and packing (see 5.1 and 5.2).
(i) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.6).
(j) Marking required (see 5.3).

6.2.1 Contract data requirements. Any data items to be delivered under any contract for items covered by this specification should be specifically called for in the contract in accordance with the applicable regulations of the procuring activity.

Custodians:

Army - GL
Navy - YD
Air Force - 99

Review activities:

Army - MD
Navy - MS, SA

User activity:

Navy - MC

Preparing activity:

Army - GL

Civil Agency Coordinating Activities:

GSA - FSS
HEW - FDA
VA - DMS

Project No. 7320-0565

Orders for this publication are to be placed with the General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of the specification to obtain extra copies and other documents referenced herein. Price 65 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.