00-V-205H
February 1, 1977
SUPERSEDING
Int. Fed. Spec. 00-V-00205G(Army-GL)
December 9, 1975 and
Fed. Spec. 00-V-205F
May 29, 1969

FEDERAL SPECIFICATION

VEGETABLE CUTTING AND SLICING MACHINES, (ELECTRIC); AND TABLE, (FOOD PREPARATION)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers electric motor driven vegetable cutting and slicing machines and an optional mobile table with drain to hold a cutting and slicing machine.

1.2 Classification.

1.2.1 Types, styles, and classes. The vegetable cutting and slicing machines shall be of the following types, styles, and classes (see 6.2).

Type I - Multipurpose (bias, horizontal, and strip cutting).
  Style A - With attachments for each type cut.
  Style B - Self contained (no attachments necessary).

Type II - Single purpose (high speed cutting of cabbage for slaw).
Class 1 - With table.
Class 2 - Without table.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

CC-M-1807	-	Motor, Alternating Current, Fractional and Integral Horsepower (500 HP and Smaller).
FF-C-77	-	Casters, Rigid and Swivel (Institutional Duty).
MMM-A-260	-	Adhesive, Water-Resistant, (For Sealing Waterproofed Paper).

FSC 7320

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

PPP-B-601	-	Boxes, Wood, Cleated-Plywood.
PPP-B-621	-	Boxes, Wood, Nailed and Lock Corner.
PPP-B-636	-	Boxes, Shipping, Fiberboard.
PPP-B-1055	-	Barrier Material, Waterproofed, Flexible.
PPP-T-45	-	Tape, Gummed, Paper, Reinforced and Plain, For Sealing and Securing.
PPP-T-60	-	Tape: Packaging, Waterproof.

Federal Standards:

FED-STD-66	-	Steel: Chemical Composition and Hardenability.
FED-STD-123	-	Marking for Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications:

MIL-P-116	-	Preservation-Packaging, Methods Of.
MIL-B-121	-	Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-V-173	-	Varnish, Moisture-and Fungus-Resistant (For Treatment of Communications, Electronic, and Associated Equipment).

Military Standards:

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:58Z
Check the source to verify that this is the current version before use.

MIL-STD-461 - Electromagnetic Interference Characteristics Requirement for Equipment.
MIL-STD-462 - Electromagnetic Interference Characteristics, Measurements of.
MIL-STD-1474 - Noise Limits for Army Materiel.

DRAWING

US ARMY NATICK RESEARCH AND DEVELOPMENT COMMAND

5-11-962 - Table, for Vegetable Cutting and Slicing Machines (Electric)

(Copies of Military Specifications, Standards, and Drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

American Society for Testing and Materials (ASTM) Standard:

E 18 - Rockwell Hardness and Rockwell Superficial Hardness of Metallic Material

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

National Sanitation Foundation (NSF) Standards:

No. 2 - Food Service Equipment

No. 8 - Commercial Powered Food Preparation Equipment

Listing of Food Service Equipment

(Applications for copies should be addressed to the National Sanitation Foundation, NSF Building, Ann Arbor, MI 48105.)

Underwriters' Laboratories, Inc. (UL) Standards:

(Application for copies of UL Standards should be addressed to the Underwriters' Laboratories, Inc., 207 East Ohio St., Chicago, IL 60611; 333 Pfingsten Rd., Northbrook, IL 60062; 1285 Walt Whitman Rd., Melville, L.I., NY 11746; 1655 Scott Blvd., Santa Clara, CA 95050, or 2602 Tampa East Blvd., Tampa, FL 33619.)

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:58Z
Check the source to verify that this is the current version before use.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Standard product. The vegetable cutting and slicing machine shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product with any added features needed to comply with the requirements of this specification. Modifications to add features shall not incorporate different parts unless such parts are used on other current commercial models. Standard or modified commercial products furnished in accordance with this specification shall be identifiable by all regular manufacturer's or commercial service organizations servicing the brand involved. Service organizations shall be capable of providing complete parts and repair services on models furnished to the Government consistent with their normal commercial practices.

3.2 Standards. The vegetable cutting and slicing machine and table shall comply with the applicable requirements of NSF Standards No. 8 and 2, respectively. The electrical components shall comply with the requirements of UL Standards, as applicable.

3.2.1 Compliance. Prior to approval of the first shipment, the supplier shall submit satisfactory evidence to the contracting officer or his authorized representative that the vegetable cutting and slicing machine conforms to the requirements of UL and NSF standards, as applicable.

3.2.1.1 NSF. Acceptable evidence of meeting the requirements of NSF shall be:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" or display of the NSF seal on the finished vegetable cutting and slicing machine or table, or

(2) A certification for the vegetable cutting and slicing machine and tables issued by NSF under their special one-time contract evaluation-certification service shall be submitted, or

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

(3) A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the machines and tables are being procured indicating that the vegetable cutting and slicing machines and tables have been tested and conform to NSF Standards No. 8 and 2, respectively.

3.2.1.2 UL. Acceptable evidence of meeting the requirements of UL standards, as applicable, shall be the UL label, UL listing mark, or a certified test report from a recognized independent testing laboratory acceptable to the Government indicating compliance with requirements of UL standards, as applicable.

3.3 Materials and components. Materials and components shall be as specified herein. Materials not definitely specified shall be of the quality normally used by the manufacturer in his standard commercial vegetable cutting and slicing machine provided the completed item complies with all provisions of this specification.

3.4 Design and construction. The type I vegetable cutting and slicing machine shall be designed for multipurpose cutting (bias, horizontal, and strip cutting). The type II vegetable cutting and slicing machine shall be designed to make only the bias cut. The vegetable cutting and slicing machines shall be electric motor driven and shall have provisions for mounting on a flat surface. All vegetable cutting and slicing machines shall consist essentially of a cutting head, hinged food plunger, cutting knives, and an electric motor.

3.4.1 Type I. Type I vegetable cutting and slicing machines shall be provided with means to allow the following adjustment for cuts, as applicable, without the use of tools, when tested as specified in 4.4.1.

Bias cut. For American fries, cabbage slaws and other types of vegetables at desired thickness from 1/64 inch to 3/8 inch.

Horizontal or straight cut. At desired thickness from 1/64 inch to 3/8 inch.

Strip cut. 7/16 inch square, for French fries and rough chopping. Strip cut 3/16 inch square, for juliennes, carrot sticks, and fine chopping.

3.4.1.1 Style A. The style A vegetable cutting and slicing machine shall perform all of the cuts specified in 3.4.1 with the use of a different attachment for each type of cut. Foodstuffs shall be cut and sliced and not forced through grids.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:58Z
Check the source to verify that this is the current version before use.

3.4.1.2 Style B. The style B vegetable cutting and slicing machine shall perform any combination of the cuts specified in 3.4.1 in sequence without stopping the machine or adding any external attachments. Foodstuffs shall be cut and sliced and not forced through grids.

3.4.1.3 Capacity. The type I machine shall have the capacity to cut or slice the minimum quantities of vegetables per hour as listed below when tested as specified in 4.4.1.

720 pounds of french fried potatoes.
240 pounds of shoe string potatoes.
1200 pounds of American fries.
600 pounds of cabbage slaw.
240 pounds of fine chop.
720 pounds of rough chop.

3.4.2 Type II. Type II vegetable cutting and slicing machine shall have the capacity to cut 600 pounds of cabbage slaw per hour when tested as specified in 4.4.1. Means shall be provided for adjusting the thickness range of the cabbage slaw from 1/64 to 3/8 inch.

3.4.3 Cutting head. The cutting head for all machines shall consist of a disc, plate or reciprocating head with one or more cutting knives, and shall be removable for cleaning and servicing without using tools when tested as specified in 4.4.1.

3.4.4 Plungers. All machines shall be provided with plungers or tampers for pushing foodstuffs to the knives. The plungers or tampers shall fit their respective openings and have a shoulder or stop to prevent contact with the cutting knives. The plungers or tampers shall be hinged directly to the entry chute.

3.4.5 Cutting knives. The cutting knives for all machines shall conform to the chemical composition of one of the AISI steel numbers 420 or 440 as specified in FED-STD-66. The knives shall have a hardness of 50 to 55 on Rockwell "C" scale when tested as specified in 4.4.2. Knives shall be accessible for replacement when tested as specified in 4.4.1.

3.4.6 Table, food preparation. Class 1 of either type machine shall be provided with a table conforming to Drawing 5-11-962. The table shall be provided with four casters, one in each corner conforming to type II, class B, 5 inch wheel diameter, style b or c mounting optional of FF-C-77. Two casters on the same end of the table shall be provided with foot brakes.

3.4.7 Bearings. Machine bearings shall be ball, roller, sleeve, or oil impregnated, (see 3.4.8 for spiral gear bearings) and shall be housed or sealed so that moisture and dirt cannot enter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

3.4.8 Gears. Gears shall be enclosed in an oiltight housing, and operate in a bath of oil or grease lubricant. Cast-iron gears shall not mesh with other cast-iron gears. Phenolic composition gears, if used, shall be of the laminated fabric case type. Spiral bevel gears shall be mounted on shafts in either ball bearings or taper roller bearings to provide for both thrust and radial loads. Gears shall be integral or keyed to shafts. Keyed gears shall have means provided to prevent axial movement along the shaft. The use of setscrews for holding gears on shafts is not acceptable. Nuts, used for securing gears, shall be threaded to tighten when gears are rotating, or shall have locknuts. The use of lockwashers without the use of locknuts is not acceptable.

3.5 Electric motor. Unless otherwise specified (see 6.2), the electric motor for each type machine shall be a capacitor type for use on a nominal 120-volt, 60-hertz, 1-phase system. The motor shall be totally enclosed or drip proof and conform to CC-M-1807 and shall have a minimum of 1/3 horsepower rating for continuous operation to satisfy capacity specified in 3.4.1.3 or 3.4.2, as applicable. Starting shall be by an "ON-OFF" switch. The switch shall be recessed into the body structure of the machine or may be shielded to prevent inadvertant accidental operation. A red light with a reflector-type lens shall be provided near the operating switch to indicate when the current is on. A safety switch shall be attached to the machine cover to instantly cut off the current to the motor if the machine cover is opened with the operating switch in the "ON" position. If a cover retaining chain is used, a secondary chain shall also be provided as a backup to prevent machine cover and housing damage. Each machine shall be provided with a 3-conductor power cord, UL type SJ, SV, or SJT. One conductor shall provide grounding for the machine. A three prong male plug shall be provided in a recessed receptacle at the rear of the class 1 machines. A mating female plug shall be provided at one end of the power cord for the class 1 machine and the other end shall be provided with a parallel blade, grounding-type, attachment plug cap. For class 2 machines one end of the cord shall be connected directly to the machine and the other end to a parallel blade, ground-type, attachment plug cap. The cords shall be a minimum of 7 feet in length.

3.5.1 Electromagnetic compatibility. When specified (see 6.2), the vegetable cutting and slicing machine shall be designed and equipped for electromagnetic compatibility in accordance with class IIB of MIL-STD-461.

3.5.2 Drive. The electric motor shall be mounted in the base of the machine and shall drive the cutting knives through direct connection and reduction gears.

3.6 Fungus and moisture resistance. When specified (see 6.2), the machine shall be treated to resist fungus and moisture as follows:

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:58Z
Check the source to verify that this is the current version before use.

a. Circuit elements with temperature rise not more than 75 Fahrenheit (F.) when operating at full load, shall be coated with fungus-resistant varnish conforming to requirements of MIL-V-173. Circuit elements include, but are not limited to, cables, wire, terminal blocks, capacitors, and coils.

b. Electrical components not requiring fungus moisture resistance. Electrical components such as switches, fuses and contacts shall not be treated. Other materials and components which are inherently fungus resistant or are hermetically sealed need not be treated.

3.7 Noise limits. The vegetable cutting and slicing machine shall not exceed 85 decibels A, weighted at the normal operator position when tested as specified in 4.4.4.

3.8 Lubrication. All bearings, revolving shafts and other rotating or sliding parts shall be provided with means for lubrication and shall be lubricated prior to shipment. All grease-fittings shall be accessible.

3.9 Marking. Identification and instruction plates shall be permently and legibly marked directly on the item or on an aluminum, brass or stainless steel plate firmly affixed to the item. Marking shall be stamped, embossed, engraved or photosensitive. The plate thickness shall be not less than 0.012 inch.

3.9.1 Identification. Each vegetable cutting and slicing machine identification plate shall include the item name, contract number, national stock number, manufacturers' model or serial number, name, tradename or trademark of such known character as to be readily identifiable to the manufacturer. In addition, such information as required by UL for the electrical cutting and slicing machine shall be included on the plate.

3.9.2 Instruction plate. The vegetable cutting and slicing machine shall be provided with the manufacturers standard instruction plate in a location visible to the operator. Lettering shall be not less than 1/16 inch high. The instruction plate(s) shall contain cleaning and lubricating instructions, diagrams (if necessary) and freguency of cleaning and lubricating. Also, a caution note that the machine shall be used for cutting and slicing vegetables only.

3.10 Attachments. When specified (see 6.2), the type I, style B vegetable cutting and slicing machine shall be provided with the following additional attachments:

(a) Shredder - Cutting head (1/4 inch, for preparing salads).
(b) Grater - Cutting head (for grating cheese, et cetera).

3.11 Finish. Finish of vegetable cutting and slicing machines and tables shall be in accordance with applicable requirements of NSF Standards No. 8 and No. 2 respectively.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

3.12 Workmanship. All components and assemblies of the vegetable cutting and slicing machines and table shall be free from dirt and other extraneous material, burrs, slivers, rough die, tool and grind marks, dents, and cracks. Castings, molded parts and stampings, if used, shall be free of sand, fins, pits, blow holes and sprues.

3.12.1 Metal fabrication. Metal used in the fabrication of the tables shall be free from kinks and unspecified bends. Forming and shearing shall not cause damage to the metal and shall be done neatly and accurately.

3.12.2 Welding. The surfaces of parts to be welded shall be free from rust, scale, paint, grease, and other foreign matter, welds shall be smooth and free of cracks, burn holes, undercuts or incomplete fusion. All scale and flux shall be removed from the finished weld area.

3.12.3 Fastening devices. Threaded fasteners and rivet holes shall be accurately punched or drilled and shall have burrs removed. Threaded fasteners shall not be broken, cracked or stripped and shall be securely torqued. Rivets shall fill the hole completely and the heads shall be in full contact with the surface of the member and concentric with the hole.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.2.1.1 Corrosion-resisting steel analysis. Corrosion-resisting steel shall be analyzed in accordance with the check analysis procedures of FED-STD-66. Two samples shall be taken from each lot of material of the same form and thickness, unless the lot consists of only one piece, in which case only one sample shall be taken. Failure of any sample to comply shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

4.2.2 In-process inspection.

4.2.2.1 Visual examination of operations. Examination shall be made to establish that no deviations are made from requirements as listed:

(a) Bearing requirements as specified in 3.4.7.
(b) Gear requirements as specified in 3.4.8.
(c) Fungus and moisture resistance treatment as required in 3.6.

Whenever nonconformance is noted, correction shall be made to affected items and the lot in process.

4.2.2.2 Hardness testing. The cutting knives shall be tested for hardness in accordance with 4.4.2. The inspection level shall be S-2 with an acceptable quality level (AQL) of 4.0 defects, expressed in terms of defects per hundred units. The sample unit shall be one cutting knife. The lot shall consist of all cutting knives of one type offered for acceptance at one time.

4.2.3 End product inspection. The lot shall consist of all machines of one type, style, and class offered for acceptance at one time. The sample unit shall be one completely fabricated machine (with table, if applicable).

4.2.3.1 Visual examination. Examination of the machine and table shall be in accordance with the classification of defects listed in table I. The inspection level shall be II with an AQL of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE I. Classification of visual defects

Examine	Defect	Classification Major	Minor
Standard product	Item not in accordance with manufacturer's standard product except for changes necessary to comply with specification requirements	X	
Finish	Not as specified	X	
Design and construction, general	Component or accessory missing	X	
	Not constructed as specified	X	
	Not fabricated of material specified	X	
	Component split, cracked, or showing delamination	X	
	Any component misplaced or not in alignment	X	
	Adjustable assembly not adjustable	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Fastening devices	Missing, cracked or stripped	X	
	One bolt, nut, screw or washer missing		X
	Two or more bolts, nuts, screws or washer missing	X	
	Fastener loose		X
	Fastener improperly torqued	X	
	Rivet holes not accurately punched	X	
	Rivet not peened properly	X	
Welding	Missing	X	
	Not free from rust, scale, paint, grease and other foreign matter	X	
	Scale and flux deposits not removed		X
	Weld not smooth and free of cracks, burnholes, undercuts or incomplete fusion	X	
Castings, molded parts and stampings	Miscast or incomplete, not free of sand, fins, pits, sprues and blow-holes	X	
Workmanship	Any burr, sliver, sharp edge, rough die, tool, gouge, or grind marks	X	
	Any component fractured, buckled, punctured, dented, malformed, or damaged	X	
Machine	Not capable of being mounted on flat surface	X	
Switch "ON-OFF"	Not recessed into body or not shielded	X	
Plungers	Do not have stop shoulders to prevent contact with cutting blade	X	
	Food plunger not hinged to entry chute	X	
Lubrication	Missing	X	
Casters	Two casters not provided with foot brakes as specified	X	
Identification markings	Missing, incomplete, illegible		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

4.2.3.2 Dimensional examination. Examination shall be made of the table to determine compliance with the dimensional requirements of this specification. Any dimension that is not within the specified requirements shall be classified a defect. The inspection level shall be S-2 with an AQL of 6.5 defects, expressed in terms of defects per hundred units.

4.2.3.3 End item testing. One representative unit shall be tested in accordance with 4.4.1, 4.4.3 (when applicable), and 4.4.4. Any nonconformance shall be cause for rejection of the unit.

4.2.4 Examination of preparation for delivery. An examination shall be made to determine that preservation-packaging, packing and marking comply with the requirements of section 5. Defects shall be as specified in table II. The sample unit shall be one shipping container fully prepared for delivery except containers need not be closed. The lot shall be the number of containers offered for inspection at one time. The inspection level shall be S-4 with an AQL of 6.5 defects, expressed in terms of defects per hundred units.

TABLE II. Examination of preparation for delivery

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Component missing, damaged, or otherwise defective.
Workmanship	Item not covered with shroud or shroud not sealed as specified. Bulged or distorted container.

4.2.4.1 Examination of shipping containers. When shipping containers are required to be in accordance with PPP-B-601 or PPP-B-621, examination for defects in closure and strapping shall be in accordance with the appendix of the applicable container specification.

4.2.4.2 Examination of fiberboard box. Examination of the closure of the fiberboard box shall be in accordance with the appendix of PPP-B-636.

4.3 Certificate examination. Certificates of compliance, certified test reports, approval labels or listing marks for codes and standards, as applicable, that are submitted as proof of compliance with the specification requirements shall be examined and validated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

4.4 Test methods.

4.4.1 Performance test. Type I and type II vegetable cutting and slicing machine(s) shall be operated for a minimum of 5 minutes using potatoes, cabbage and carrots, as applicable, to determine the following:

(a) Sizes and forms of cuts as specified in 3.4.1 through 3.4.2, as applicable.

(b) On the basis of the 5 minute test the capacity per hour of foodstuffs shall be caluclated to determine compliance with 3.4.1.3 for the type I machines and 3.4.2 for the type II machines. The machine shall then be stopped and the cutting head and knives shall be removed without using tools, to determine accessibility for cleaning and replacement in compliance with 3.4.3 and 3.4.5. Inability to meet the cutting capacity requirements specified shall constitute failure of the test.

4.4.2 Hardness test. Cutting knives shall be tested for hardness in accordance with ASTM E 18 to determine compliance with 3.4.5. Any nonconformance to meet the hardness requirements specified shall consititute failure of the test.

4.4.3 Electromagnetic compatibility test. When electromagnetic compatibility is required, the initial unit of production shall be tested by the supplier in accordance with test method CE03, and RE02 of MIL-STD-462. The Government reserves the right to witness tests performed by the supplier or his private testing organization. The supplier shall furnish to the contracting officer written certification that the Interference Control Plan, the EMI/EMC Test Plan, the Electromagnetic Compatibility Test Report and requirements meet MIL-STD-461.

4.4.4 Noise test. The vegetable cutting and slicing machine shall be tested in accordance with MIL-STD-1474 to determine conformance with 3.7. Any nonconformance to be within the noise limit shall constitute failure of this test.

5. PREPARATION FOR DELIVERY

5.1 Preservation-packaging. Preservation-packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Disassembly. Each machine and table shall have all projecting detachable components that might cause damage to the machine or be damaged during shipment, detached.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:58Z
Check the source to verify that this is the current version before use.

5.1.1.2 Preservation. All exposed, uncoated, ferrous metal surfaces of the machines, detached parts, attachments and tables except for corrosion-resisting steel, shall be cleaned by process C-1, thoroughly dried, and then coated with type P-14 preservative of MIL-P-116. Surfaces from which preservatives might be removed by contact with packaging and packing materials shall be wrapped with greaseproof barrier material conforming to type I or II, grade A, class 1 or 2 of MIL-B-121. The greaseproof wrap shall be secured with jute, sisal, manila, cotton twine, or tape conforming to PPP-T-60 or PPP-T-45 or shall be heat sealed when heat sealable barrier material is used.

5.1.1.3 Packaging.

5.1.1.3.1 Machine. All parts of each machine, such as levers, switches, and rotating and moving components not disassembled or removed that may be damaged or cause damage while in transit shall be secured in place. The electric cable shall be coiled and secured to the machine with twine or tape as specified in 5.1.1.2.

5.1.1.3.2 Detached components and plungers. The detached components, attachments and plungers or tampers shall be packaged in a snug-fitting fiberboard box conforming to style optional, grade W5c or W5s of PPP-B-636. The contents of each box shall be cushioned, as necessary, to prevent damage while in transit. Each fiberboard box shall be securely closed in accordance with method IV as specified in the appendix of PPP-B-636.

5.1.2 Level C. Machines and tables shall be preserved-packaged to afford adequate protection against corrosion, deterioration, and physical damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets these requirements.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Each machine, preserved-packaged as specified in 5.1 shall be packed in a nailed wood or cleated plywood shipping container conforming to class 2, style 2 or 4, grade A or B, type 3 load of PPP-B-621 or overseas type, style A or J, grade A or B, type 3 load of PPP-B-601, respectively. Each shipping container, regardless of weight, shall be provided with skids in accordance with the applicable container specification and the contents waterproofed as specified in 5.2.1.1. The fiberboard box containing detached components shall be placed in an unused portion of the shipping container. The contents shall be secured by bolting to the base of the container or by lumber blocking or bracing. Bolting shall be by means of carriage bolts with bolts engaging skids. Cushioning material shall be used between lumber blocking and bracing and surfaces of the machine. Each shipping container shall be closed and strapped in accordance with the appendix of the applicable container specification.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:58Z
Check the source to verify that this is the currenversion before use.

5.2.1.1 Waterproofing. The machine shall be covered with a full height shroud made of waterproof barrier material conforming to class E-2, H-5, or M-1 of PPP-B-1055. All seams of the shroud shall be sealed with a 3/4 inch minimum width continuous seam of water resistant adhesive conforming to MMM-A-260. Alternatively, the shroud may be fabricated from minimum 0.004 inch thick polyethylene and the polyethylene shroud heat sealed or secured with tape conforming to type IV of PPP-T-60.

5.2.1.2 Tables. Each table, preserved-packaged as specified in 5.1, shall be packed in an inverted position in a nailed wood or cleated plywood shipping container as specified in 5.2.1, except that skids shall not be required. Cushioning material shall be placed between the table top and bottom of the shipping container.

5.2.2 Level B. Each machine, preserved-packaged as specified in 5.1, shall be packed as specified in 5.2.1, except the shipping container shall conform to class 1 or domestic type, as applicable.

5.2.2.1 Tables. Each table, preserved-packaged as specified in 5.1, shall be packed in an inverted position in a nailed wood or cleated plywood shipping container as specified in 5.2.2, except that skids shall not be required. Cushioning material shall be placed between the table top and bottom of the shipping container.

5.2.3 Level C. Machines and tables, preserved-packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers and packing shall comply with Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.3 Marking. Marking shall be in accordance with 5.3.1 or 5.3.2, as specified (see 6.2).

5.3.1 Civil agencies. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with FED-STD-123.

5.3.2 Military requirements. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The vegetable cutting and slicing machines covered by this specification are intended for dining halls, galleys, and kitchens for cutting and slicing foodstuffs. The mobile table is intended to hold the machine and provide a place to wash fruits and vegetables.

6.2 Ordering data. Purchasers should select the preferred option permitted herein and include the following information in procurement documents:

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:58Z
Check the source to verify that this is the current version before use.

(a) Title, number and date of this specification.
(b) Type, style and class of machine required (see 1.2).
(c) Electrical characteristics, if other than specified (see 3.5).
(d) When electromagnetic compatibility is required (see 3.5.1).
(e) When fungus and moisture resistance treatment is required (see 3.6).
(f) Attachments required (see 3.10).
(g) Selection of applicable levels of preservation-packaging and packing (see 5.1 and 5.2).
(h) Marking required (see 5.3).

6.2.1 Contract data requirements. Any data items to be delivered under any contract for items covered by this specification should be specifically called for in the contract in accordance with the applicable regulations of the procuring activity.

Custodians:

Army - GL
Navy - YD
Air Force - 99

Review activities:

Navy - MS, SA

User activity:

Navy - MC

Preparing activity:

Army - GL

Civil Agency Coordinating Activities:

GSA - FSS

Project No. 7320-0631

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies of documents referenced herein. Price 35 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.