PP-C-1802A
August 15, 1980
SUPERSEDING
Fed. Spec. PP-C-1802
August 20, 1973

FEDERAL SPECIFICATION

CHICKEN OR TURKEY, CANNED, BONED

This specification was approved by the Secretary, US Department of Agriculture, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers canned, boned, chicken or turkey and diced canned, boned chicken or turkey both in broth as a regular pack or in broth as a dietetic pack.

1.2 Classification. The product shall be of the following types, classes and styles, as specified (see 6.1):

Type I	-	Chicken boned
Class 1	-	Pieces, with 30 percent broth
Class 2	-	Diced, with 20 percent broth
Style (a)	-	Regular
Style (b)	-	Dietetic
Type II	-	Turkey, boned
Class 1	-	Pieces, with 30 percent broth
Class 2	-	Diced, with 20 percent broth
Style (a)	-	Regular
Style (b)	-	Dietetic

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-C-29	-	Canned Subsistence Items, Packaging and Packing Of

Federal Standard:

FED-STD-123	-	Marking for Shipment (Civil Agencies)

FSC 8905/8940

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

(Activities outside the Federal Government may obtain copies of Federal specifications, standards and commercial item descriptions as outlined under General Information in the Index of Federal Specifications, Standards and Commercial Item Descriptions. The Index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.

(Single copies of this specification, other Federal specifications, standards and commercial items descriptions required by activities outside the Federal Government for bidding purposes are available without charge from General Services Administration Business Service Centers in Boston; New York; Philadelphia; Washington, DC; Atlanta; Chicago; Kansas City, MO; Fort Worth; Houston; Denver; San Francisco; Los Angeles; and Seattle, WA.

(Federal Government activities may obtain copies of Federal specifications, standards and the Index of Federal Specifications, Standards and Commercial Item Descriptions from established distribution points in their agencies.)

Military Specifications:

MIL-F-3764 - Food Packet, In-Flight, Individual
MIL-L-1497 - Labeling of Metal Cans for Subsistence Items

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-668 - Sanitary Standards for Food Plants

(Copies of Military specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

LAWS AND REGULATIONS

US Department of Agriculture

Regulations Governing the Voluntary Grading of Poultry Products and Rabbit Products and United States Classes, Standards, and Grades with Respect Thereto (7CFR Part 2870).

(Single copies may be obtained without charge from the US Department of Agriculture, Food Safety and Quality Service, Washington, DC 20250.)

Poultry Products Inspection Regulations (9 CFR Part 381)

(Single copies may be obtained without charge from the US Department of Agriculture, Food Safety and Quality Service, Meat and Poultry Inspection, Washington, DC 20250.)

Source: https://assist.dla.mil Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

US Standards for Condition of Food Containers

(Application for copies should be addressed to the Mathematics and Statistics Division, Food Safety and Quality Service, U.S. Department of Agriculture, Washington, DC 20250.)

US Department of Health, Education and Welfare

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder

(The Code of Federal Regulations (CFR) and the Federal Register (FR), are for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

American Public Health Association

Standard Methods for the Examination of Dairy Products

(Application for copies should be addressed to the American Public Health Association, 1790 Boradway, New York, NY 10019.)

Association of Official Analytical Chemists

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

3. REQUIREMENTS

3.1 Material.

3.1.1 Chickens. Chickens shall be roasters 4 lbs. or over (1.8 kg or over) or fowl, or a combination of roasters and fowl.

3.1.2 Turkeys. Turkeys shall be young tom turkeys, yearling hen turkeys or yearling or mature turkeys.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

3.1.3 Chickens and turkeys for Civil agencies. Chickens and turkeys shall conform to the quality requirements for U.S. Procurement Grade II or better as specified in the Regulations Governing the Voluntary Grading of Poultry Products and Rabbit Products and United States Classes, Standards, and Grades with Respect Thereto (7CFR Part 2870).

3.1.4 Mechanically deboned poultry meat. Mechanically deboned poultry meat shall be produced using USDA approved deboning equipment. Mechanically deboned poultry shall conform to the time and temperature requirements of 3.3. Frozen mechanically deboned poultry shall not be used. Mechanically deboned poultry meat shall not be used in class 2 products.

3.1.5 Chicken or turkey fat. The chicken or turkey fat if used to standardize the fat content of the finished product to meet the requirements of 3.4.2 shall be in excellent condition (this shall exclude but not be restricted to fat which is moldy, discolored, e.g., green, black, dark brown, blue, purple; or has a foreign flavor or odor, e.g., kerosene, fuel oil, putrid, stale, rancid, or turpentine).

3.1.6 Freezing of raw chicken or turkey. Chicken or turkey may be frozen. If frozen poultry is used, it shall have been frozen to an internal temperature of 0°F (-18°C) or lower within 72 hours after placing in the freezer. Raw poultry shall not have been held in the frozen state for long than 180 days. Raw poultry shall not be frozen more than once prior to use in the product.

3.1.7 Salt. The salt (sodium chloride) shall be white, refined, with or without anti-caking agents. Iodized salt shall not be used.

3.2 Processing.

3.2.1 The product shall be processed in accordance with the requirements of table I to produce a product complying with 3.4.

TABLE I. Processing

Item No.	Requirement
1.	The product shall be formulated from raw or cooked, skinned, trimmed, boned, chicken or turkey meat in natural proportions from the whole bird except that back, legs, necks and wings may be used in less than natural proportions for class 1 products. (See item 4 below). Skin and giblets (gizzard, heart and liver) shall not be used. For class 1 (both types 1 and II), salt and if necessary, broth and rendered chicken or turkey fat to produce a product complying with 3.4 shall be used. 1/ Mechanically deboned poultry meat shall not be used in excess of six percent of the total batch weight. Class 2 products shall contain not more than 20 percent broth, chicken or turkey, as applicable. 2/

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

TABLE I. Processing (cont'd)

Item No.	Requirement
2.	Sodium chloride shall not be used in the preparation of dietetic packs (style (b) products).
3.	The poultry shall be cooked by any suitable means until tender.
4.	Class 2 products shall be formed or fabricated in rolls and chilled and mechanically diced with dicer settings set at 5/8 by 5/8 by 5/8 inches (± 1/8 inch) (16 x 16 x 16 mm) (± 3 mm). (Note: The meat from the back, legs, necks and wings shall be excluded in order to meet this requirement). Cooked diced chicken or turkey may be frozen (see 3.3).
5.	The product including broth, as applicable, shall be filled into cans, which shall then be vacuumized, sealed and heat treated in a manner which will stabilize the product for conformance to requirements of Food Safety and Quality Service, US Department of Agriculture (USDA).

1/ A good quality chicken or turkey fat meeting requirements of 3.1.5 may be substituted for each other providing the finished product meets the requirements of table III. Correctness of ingredient statement when fats are substituted is the responsiblity of the contractor.

2/ Chicken or turkey broth shall represent the first extraction when the meat is cooked in accordance with recognized good commercial practice. When precooked meat is used, the broth shall be prepared from chickens and turkeys meeting the requirements of 3.1.3. The broth may be frozen provided it is handled in accordance with 3.3.

3.3 Time and temperature limitations. The chicken or turkey meat shall be handled so as to comply with the following limitations:

(1) The following time and temperature limitations apply to raw or cooked chicken or turkey meat and broth during holding and processing operations up to time of final retorting.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

Temperature	Time
0°F (-18°C)	20 days
33°F (1°C)	72 hours
40°F (4°C)	48 hours
50°F (10°C)	4 hours

(2) Maximum time after cooking to reduce temperature to 50°F (10°C) — 2 hours

(3) Maximum temperature of poultry to be used for mechanical deboning. — 40°F (4°C)

(4) Maximum time to reduce mechanically deboned poultry meat to 40°F (4°C) — 60 minutes

(5) Maximum time from start of mechanically deboning to final use in the product. — 24 hours

(6) Maximum time from start of formulation until product is filled into cans. — 2 hours

3.4 Finished product.

3.4.1 Physical requirements. The finished product shall comply, on a unit container basis, with the requirements of table II, as determined in accordance with 4.3.3.

TABLE II. Physical requirements

Item No.	Requirement
	All types, classes and styles
1.	There shall be no burnt, scorched, musty, moldy, rancid, sour, stale, kerosene, fuel oil, turpentine, or any other odor or flavor foreign to the product.
2.	There shall be no foreign color (such as, but not restricted to red, green, black, dark brown, blue or purple) in the product.
3.	There shall be no foreign material (such as, but not restricted to hair, dirt, insects, insect parts, paper, wood, glass, or metal particles) in the product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

TABLE II. Physical requirements (cont'd)

Item No.	Requirement
	All types, classes and styles
4.	There shall be no giblets, or fragments of giblets whose greatest dimension is more than 1/4 inch (6 mm).
5.	The product shall not have the appearance of ground meat.
6.	There shall be no more than 2 pieces of skin whose greatest dimension is more than 1/4 inch (6 mm) and no skin whose greatest dimension is more than 1/2 inch (13 mm).
	Types I and II, class 1 products
7.	The total weight of the product retained on the three sieves shall be not less than the following amounts in the specified container size (see 4.4.1.1):
	401 by 411 (or 404 by 404): 20 ounces (567 g) — 300 by 200: 4 ounces (113 g)
8.	The product shall be in such form as to be easily broken apart into distinct pieces using a fork or similar instrument.
9.	The weight of the meat pieces retained on the designated sieve sizes shall be as follows:
	401 by 411 (or 404 by 404): US Standard 1-inch: Not less than 5 ounces (142 g); US Standard No. 1-inch and US Standard 1/2 inch: Not less than 19 ounces (539 g) — 300 by 200: US Standard No. 1-inch and US Standard 1/2 inch: Not less than 3-3/4 ounces (106 g)
10.	There shall be no piece of bone in excess of 1 inch (25 mm) in any dimension and no more than the following number of bones having a dimension greater than 1/4 inch (6 mm) in the container sizes indicated:
	401 by 411 (or 404 by 404): 2 — 300 by 200: 1

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:02Z
Check the source to verify that this is the current version before use.

TABLE II. Physical requirements (cont'd)

Item No.	Requirement
	Types I and II, class 1 products
11.	The product shall contain not more than the following number of pieces of material (for the container size indicated) whose greatest dimensions is more than 1/4 inch (6 mm) and which does not break up or disintegrate when subjected to pressure from a spatula, flat side of a knife blade, or fork. 1/ 2/
	401 by 411 (or 404 by 404): 5 — 300 by 200: 1
12.	The product shall contain not more than the following number of pieces of blood vessels (for the container size indicated) whose greatest dimension is more than 1/4 inch (6 mm):
	401 by 411 (or 404 by 404): 10 — 300 by 200: 2
	Types I and II, class 2 products
13.	The total weight of the product retained on the three sieves shall be not less than 40 ounces (1134 g) (see 4.4.1.2). The product shall be in such form as to be easily broken apart into distinct dices using a fork or similar instrument.
14.	Not more than 25 percent of the diced meat shall pass through the US Standard 3/8 inch (10 mm) sieve (see 4.4.1.2).
15.	There shall be no more than two bones having any dimension greater than 1/4 inch (6 mm) and no piece of bone in excess of 1 inch (25 mm) in any dimension.
16.	The product shall contain not more than 8 pieces of material whose greatest dimension is more than 1/4 inch (6 mm) and which does not break up or disintegrate when subjected to pressure from a spatula, flat side of a knife blade, or fork. 1/ 2/
17.	The product shall contain not more than 10 pieces of blood vessel whose greatest dimension is more than 1/4 inch (6 mm).

1/ A mechanical aid other than that specified above, shall not be used in determining compliance with this requirement. The material for which this requirement is designed shall include but not be restricted to cartilage, ligament, tendon, or connective tissues.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

2/ Further fragmentation of chicken or turkey is not permitted in order to measure the size of the cartilage, ligament, or tendon fragment. Separation of pieces which adhere to each other is permissible.

3.4.2 Chemical requirements. The finished product shall comply with the requirements of table III on a unit basis.

TABLE III. Chemical requirements

Item No.		Requirement		
		Types I and II, class 1	Types I and II, class 2	
			Style (a)	Style (b)
1	Fat content (percent)			
	Not more than	16	10	10
	Not less than	-	4	4
2	Salt content (percent)	0.8 to 1.5	0.8 to 1.5	-
3	Sodium content (milligrams per 100 grams of drained weight product) Not more than	-	-	70

3.5 All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

3.6 Plant qualification. The product shall originate, be processed, marked and handled in plants which are operated under the Poultry Products Inspection Regulations of the US Department of Agriculture. Finished product refrigeration facilities (freezer, storage and shipping) not operating under these regulations shall meet the requirements of MIL-STD-668.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to the prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

4.2 Plant qualification. The product furnished under this document shall be unacceptable if not produced and stored in plants which currently meet the qualification conditions of 3.6.

4.3 Quality conformance inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.3.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.3.1.1 Examination of chicken or turkey. Examination shall be made of the poultry carcasses for conformance to the requirements of 3.1.1, 3.1.2, and 3.1.3 (for Civil Agencies) and of mechanically deboned poultry meat for conformance to the requirements of 3.1.4. In addition, when frozen poultry is used, the supplier shall furnish a USDA certification to the effect that product has been examined subsequent to freezing and is in compliance with the freezing requirements of the Poultry Products Inspection Regulations. Any noncompliance shall be cause for rejection of the involved component lot, or the finished product of which it is a part.

4.3.1.2 Examination of chicken or turkey fat. Examination of chicken or turkey fat shall be made to determine compliance with 3.1.5. Examination shall be made in accordance with table IV. The sample unit shall be an approximate 1-pound (.45 kg) composite of product drawn from five primary containers or all the containers if the lot consists of less than five primary containers. The finding of one or more defects shall be cause for rejection of the involved lot of chicken or turkey fat or the finished product made therefrom.

TABLE IV. Examination of chicken or turkey fat

Category	Defect
Major A	
101	Presence of foreign flavor or odor, e.g., putrid, stale, rancid, kerosene, fuel oil or turpentine.
102	Discolored, e.g., green, black, dark brown, blue, or purple.
103	Presence of foreign material, e.g., dirt, wood, metal filings, glass or other extraneous material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

4.3.1.3 Examination of salt. Examination of salt shall be made to determine compliance with the requirements of 3.1.7 as concerns identity. The determination shall be made by examination of labels, invoices or other valid documents. Noncompliance with one or more identity requirements shall be cause for rejection of the lot or the finished product made therefrom, as applicable.

4.3.2 In-process inspection. Unless otherwise specified (see 6.1), examination shall be made during processing to determine compliance with the requirements of table I and 3.3. Nonconformance to one or more of the above referenced requirements shall be cause for rejection of the lot.

4.3.3 End item inspection. The lot size shall be expressed in units of filled and sealed cans.

4.3.3.1 Net weight examination. The canned product shall be examined for the net weight defects listed on table V. The sample unit shall be one filled and sealed can. The inspection level shall be S-3 and the acceptable quality level (AQL) shall be 10.0 percent defective.

TABLE V. Examination for net weight 1/

Category	Defect
Minor	
201	Net weight less than 5-1/2 ounces (156 g) (applicable to 300 by 200 cans). (class 1)
202	Net weight less than 28-1/2 ounces (808 g) (applicable to 401 by 411 or 404 by 404 cans). (class 1)
203	Net weight less than 48 ounces (1361 g) (applicable to 404 by 700 cans). (class 2)

1/ Lot shall be rejected if the average net weight of the samples is less than the net weight specified in 5.1.

4.3.3.2 Product characteristic examination. The canned product shall be examined for defects in accordance with table VI. The sample unit shall be the contents of one can. The inspection level shall be S-3 and the AQL shall be 2.5 major B and 10.0 total defects per hundred units. The occurrence of any major A defect shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

TABLE VI. Examination for product characteristics

Category			Defect
Major A	Major B	Minor	Applicable to all types, classes and styles
101			Presence of burnt, scorched, musty, moldy, rancid, sour, stale, kerosene, fuel, oil, turpentine or any other odor or flavor foreign to the product.
102			Presence of foreign color, e.g., red, green, black, dark brown, blue or purple.
103			Presence of foreign material, e.g., hair, dirt, insects, insect parts, paper, wood, glass or metal particles.
		201	Presence of giblets or fragments of giblets whose greatest dimension exceeds 1/4 inch (6 mm). 1/
	151		The product does not easily break apart into distinct pieces using a fork or similar instrument.
	152		Presence of bone with a dimension that is in excess of 1 inch (25 mm). (Applicable to 300 by 200, 401 by 411 or 404 by 404 cans). 1/
	153		More than two bones with a dimension greater than 1/4 inch (6 mm). (Applicable to 401 by 411 or 404 by 404 cans). 1/
	154		More than one piece of bone with a dimension greater than 1/4 inch (6 mm). (Applicable to 300 by 200 can). 1/
		202	More than two pieces of skin whose dimension exceeds 1/4 inch (6 mm). 1/
	155		Presence of a piece of skin with a dimension greater than 1/2 inch (13 mm). 1/
		203	More than five pieces of material with dimension greater than 1/4 inch (6 mm) which do not break up or disintegrate when subjected to pressure from a spatula, flat side of a knife, or fork. (Applicable to 401 by 411 or 404 by 404 cans). 1/ 4/

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

TABLE VI. Examination for product characteristics (cont'd)

Category			Defect
Major A	Major B	Minor	Applicable to all types, classes and styles
		204	Presence of more than one piece of material whose greater dimension is more than 1/4 inch (6 mm) and which does not break up or disintegrate when subjected to pressure from a spatula, flat side of knife, or fork. (Applicable to 300 by 200 cans). 1/ 4/
		205	More than ten pieces of blood vessels whose greatest dimension exceeds 1/4 inch (6 mm). (Applicable to 401 by 411 or 404 by 404 cans). 1/
		206	More than two pieces of blood vessel whose greatest dimension exceeds 1/4 inch (6 mm) each. (Applicable to 300 by 200 cans). 1/
		207	Product has the appearance of ground meat.
			Applicable to types I and II, class 2 product
	156		Total weight of the product retained on three sieves less than 40 ounces (1134 g) (see 4.4.1.2). 2/
	157		More than 25 percent of the diced meat passes through a US Standard 3/8 inch (10 mm) sieve (see 4.4.1.2). 5/
		208	More than eight pieces of material whose greatest dimension exceeds 1/4 inch (6 mm) which does not break up or disintegrate when subjected to pressure from a spatula, flat side of a knife blade, or a fork. 1/ 4/
			Applicable to types I and II, class 1
	158		Total weight of the product retained on the three sieves (see item 7, table II) less than 20 ounces (567 g) (applicable to 401 by 411 or 404 by 404 cans) (see 4.4.1.1). 2/
	159		Total weight of product retained on the three sieves (see item 7, table II) less than 4 ounces (113 g) (applicable to 300 by 200 cans) (see 4.4.1.1). 3/

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

TABLE VI. Examination for product characteristics (cont'd)

Category			Defect
Major A	Major B	Minor	Applicable to types I and II, class 1
	160		Total weight of meat retained on a US Standard 1 inch (25 mm) sieve less than 5 ounces (142 g) (applicable to 401 by 411 or 404 by 404 cans) (see 4.4.1.1). 6/
	161		Total weight of meat retained on two sieves (US Standard 1-inch (25.4 mm) and US Standard 1/2-inch (12.7 mm) less than 19 ounces (539 g) (applicable to 401 by 411 or 404 by 404 cans) 2/ or less than 3-3/4 ounces (106 g) (applicable to 300 by 200 cans) (see 4.4.1). 3/

1/ Measure to the nearest 1/8 inch (3 mm).

2/ Weigh to the nearest 1/2 ounce (14 g).

3/ Weigh to the nearest 1/8 ounce (1 g).

4/ No mechanical aid other than that specified shall be used. The chicken or turkey shall not be further fragmented in order to measure the size of cartilage, ligament, or tendon fragment. Separation of pieces which adhere to each other is permissible.

5/ Calculate to the nearest 1 percent.

6/ Weigh to the nearest 1/4 ounce (7 g).

4.3.4 End item testing. The finished product shall be tested in accordance with the analytical requirements of 3.4.2. Procedures for testing shall be as specified in 4.4.2. The sample unit for the 5-3/4 ounce (163 g) can (300 by 200) shall be one primary container. The lot size shall be expressed in terms of primary containers. Sample size shall be the number of sample units indicated by inspection level S-2. The AQL, expressed as percent defective for each characteristic, shall be 6.5. A nonconformance to a test requirement shall be considered a major defective unit. Results shall be reported to the nearest decimal or whole number as specified for the pertinent requirement. The sample for testing for the 29 ounce (822 g) can (401 by 411 or 404 by 404) and the 50 ounce (1417 g) can (404 by 700) shall be a 1-pound (454 g) composite from the number of primary containers indicated by inspection level S-1. Nonconformance to one or both test requirements shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

4.3.5 Packaging inspection. Inspection for can and shipping container requirements shall be in accordance with PPP-C-29.

4.3.5.1 Examination of cans. Examination for external condition, leakage, vacuum, interior and exterior coating and can labeling shall be made in accordance with the applicable examination criteria of PPP-C-29.

4.3.5.2 Examination for packing and shipping container. Examination for packing and shipping container shall be made in accordance with the applicable examination criteria of PPP-C-29.

4.4 Methods of inspection.

4.4.1 Sieving procedures.

4.4.1.1 Physical analysis (types I and II, class 1 products). Net contents shall be determined by weighing a filled, unopened can (cans tested for vacuum may be used) and subtracting a tare weight determined by averaging the weight of several empty cans and lids. The contents of the can shall be emptied into a container and gently mixed with approximately three times the can's volume of hot water 180° - 212°F (82° -100°C). The container shall be a saucepan or small stock pot of such size that it will be filled 1/2 to 3/4 full. Mixing time shall be long enough to insure that the rendered fat is in liquid condition. Product and water shall be poured slowly over the end and onto the top sieve in a set of three nested woven wire circular screens (8- or 12-inch (203 or 304 mm) diameter as applicable to quantity of product) the top one being US Standard 1.06 inch or 1 inch, the middle one US Standard 0.530 inch or 1/2 inch, and the bottom one a US Standard No. 8 (2.38 mm). The sieves shall be tilted slightly and allowed to drain for 2 minutes. The weights of product retained on the sieves are the weights to be used for items 7 and 9 of table II.

4.4.1.2 Physical analysis (types I and II, class 2 products). The procedure shall be as described in 4.4.1.1 except that the can contents shall first be drained of the free flowing broth over the set of three nested screens before proceeding with the addition of hot water. The additional exception to 4.4.1.1 calls for the use of the following nested size sieves:

Top:	US Standard 0.530 or 1/2 inch (13.5 or 12.7 mm)
Middle:	US Standard 3/8 inch (9.51 mm)
Bottom:	US Standard No. 8 (2.38 mm)

The weight of product retained on the sieves are the weights to be used to determine compliance with requirements of items 13 and 14 of table II.

4.4.2 Chemical analysis. Chemical analysis shall be made in accordance with the following methods from Official Methods of Analysis of the Association of Official Analytical Chemists:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

Test	Chapter and Section	Method
Fat	Meat and Meat Products, section: Meat	Crude fat or Ether Extract (using petroleum ether)
Salt (sodium chloride)		Salt
Sodium	Fish and other Marine Products Section: Sodium and Potassium	Dry Ashing

5. PREPARATION FOR DELIVERY

5.1 Packaging level A and C. The product, in weights and can sizes listed in table VII, shall be packaged in accordance with the level A or C requirements of PPP-C-29 as specified (see 6.1). The filled and sealed can shall have a minimum vacuum of 5 inches (84 kPa) of mercury when tested in accordance with PPP-C-29.

TABLE VII. Can size and net contents (lot average) 1/

Can size	Net contents (ounces)		Allowable unit variation
	Class 1	Class 2	
300 by 200	5-3/4 (163 g)	-	1/4 ounce (7 g)
401 by 411 or 404 by 404	29 (822 g)	-	1/2 ounce (14 g)
404 by 700	-	50 (1417 g)	2 ounces (57 g)

1/ A minus tolerance as shown above will be allowed in any one container provided the average net weight of the containers is not less than the net weight specified above.

5.2 Packing, levels A, B and C. The cans of the product shall be packed in accordance with the level A, B or C requirements of PPP-C-29 as specified (see 6.1).

5.3 Labeling and marking.

5.3.1 Military agencies (cans). Cans shall be labeled in accordance with MIL-L-1497. In addition, the 300 by 200 cans shall contain the following information:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

CHICKEN OR TURKEY (as applicable), BONED WITH BROTH

TO HEAT

Submerge closed can in boiling water, or
Place can in food warmer or
Place OPEN can over flame (avoid burning or overheating). 1/

1/ Do not use this line when can is to be used as a component of Food Packet, In-Flight, Individual, MIL-F-3764.

5.3.2 Shipping containers. Shipping containers shall be marked in accordance with MIL-STD-129.

5.3.3 Civil agencies.

5.3.3.1 Cans. Labeling that complies with the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder is acceptable.

5.3.3.2 Shipping containers. Shipping containers shall be marked in accordance with FED-STD-123.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type of product required (see 1.2).
(c) When final inspection is to be made after delivery to the point of destination (see 4.3.1.2).
(d) When in-process inspection is not required (see 4.3.2).
(e) Size of packaging required (see 5.1).
(f) Levels of packaging and packing required (see 5.1 and 5.2).

6.2 Award of contract for the product specified in this document will be limited to plants known to maintain the required sanitation conditions of 3.6 and 4.2.

6.3 Metric equivalents. Metric equivalents, indicated in parentheses throughout this document, are based on practices, conversion factors, and symbols specified in ASTM E 380 Standard for Metric Practice, and are for information only. In each instance, the value stated in US customary units shall be controlling. Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

PP-C-1802A

Custodians:

Army - GS
Navy - SA
Air Force - 50

Review activities:

Army - MD
Navy - MC, MS
DP - SS

Preparing activity:

Army - GL

Civil Agency Coordinating Activities:

GSA-FSS
HEW-FDA, NIH
USDA-FSQS, FQAD
VA-DMS

Project No. 8905-0941

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.