PP-P-002177A(Army-GL)

March 28, 1986
SUPERSEDING
PP-P-002177(Army-GL)
June 28, 1983

INTERIM FEDERAL SPECIFICATION

PORK SAUSAGE LINKS IN BRINE, THERMOSTABILIZED, TRAY PACK

This interim Federal specification was developed by the U.S. Army Natick Research, Development and Engineering Center, Natick, MA 01760-5014, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE

1.1 Scope. This specification covers pork sausage links in brine, thermostabilized in tray pack cans for use by the Department of Defense as a component of operational rations.

2. APPLICABLE DOCUMENTS

2.1 Government publications. The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

TT-C-495	-	Coatings, Exterior, for Tinned Food Cans
PPP-B-636	-	Boxes, Shipping, Fiberboard

(Activities outside the Federal Government may obtain copies of Federal specifications, standards, and commercial item descriptions as outlined under General Information in the Index of Federal Specifications, Standards and Commercial Item Descriptions. The Index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription bases by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

AMSC N/A FSC 8940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

(Single copies of this specification, other Federal specifications, and commercial item descriptions required by activities outside the Federal Government for bidding purposes are available without charge from General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.

(Federal Government activitis may obtain copies of Federal standardization documents, and the Index of Federal Specifications, Standards and Commercial Item Descriptions from established distribution points in their agencies.)

Military Specifications:

MIL-L-1497 - Labeling of Metal Cans for Subsistence items
MIL-L-35078 - Loads, Unit: Preparation of Nonperishable Subsistence Items; General Specification For

Military Standards:

MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-900 - Bacterial Standards for Starches, Flours, Cereals, Alimentary Pastes, Dry Milks and Sugars Used in the Preparation of Thermostabilized Foods for the Armed Forces

(Copies of Military specifications and standards required by contractors in connection with specific acquisition functions should be obtained from the procuring activity or as directed by the contracting officer.)

Federal Regulations

U.S. Department of Health and Human Services

Federal Food, Drug and Cosmetic Act and regulations promulgated thereunder (21 CFR Parts 1-199)

(Applications for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

U.S. Department of Agriculture (USDA)

Institutional Meat Purchase Specifications for Sausage Products, Series 800

Meat and Poultry Inspection Regulations

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T12:02Z
Check the source to verify that this is the current version before use.

U.S. Standards for Condition of Food Containers

(Application for copies should be addressed to the Director, Market Research and Development Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

Environmental Protection Agency (EPA)

National Interim Primary Drinking Water Regulations

(Application for copies should be addressed to the Office of Drinking Water WH550, Environmental Protection Agency, Washington, DC 20460.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

Association of Official Analytical Chemists (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

National Acadamy of Science

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.1, and 6.4).

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:02Z
Check the source to verify that this is the current version before use.

3.2.1 Pork sausage links. The pork sausage links shall conform to item No. 802, style D, the Institutional Meat Purchase Specifications (IMPS) for Sausage Products, Series 800. The links shall be formulated and prepared as specified in 3.3.

3.2.2 Dextrose. Dextrose shall comply with the Food Chemicals Codex.

3.2.3 Ginger, ground. Ground ginger shall be derived from the root or rhizome of Zingiber officinale Roscoe and shall possess an aromatic odor and flavor with a tan to pale brown color. The ground ginger shall contain not less than 1.5 mL of volatile oil per 100 grams and be of such size that not less than 95 percent shall pass through a U.S. Standard No. 30 sieve.

3.2.4 Pepper, black, ground. The ground black pepper shall have been ground from deep brown to black, deep-set, wrinkled immature berries of Piper nigrum L. The ground pepper shall have a characteristic, penetrating odor, a hot biting pungent flavor, and a light gray to speckled black-gray color. The black pepper shall contain not less than 2.0 mL of volatile oil per 100 grams and be of such size that not less than 95 percent shall pass through a U.S. Standard No. 16 sieve.

3.2.5 Pepper, white, ground. Ground white pepper shall be derived from the dried mature berries of Piper nigrum L. from which the outer covering or the outer and inner coverings have been removed. The ground pepper shall have a characteristic, penetrating odor, a hot biting pungent flavor, and a light color. The ground white pepper shall contain not less than 1.0 mL of volatile oil per 100 grams and be of such size that not less than 95 percent shall pass through a U.S. Standard No. 40 sieve.

3.2.6 Sage, ground. Ground sage shall be derived form the dried leaves of Salvia officinalis L. and shall be a green to grayish-green color, with a fragrant, aromatic odor and a slightly bitter taste. The volatile oil content shall be not less than 1.5 mL/100g and the sage shall be of such size that not less than 95 percent shall pass through a U.S. Standard No. 20 sieve.

3.2.7 Salt. Salt shall be noniodized, white, refined, sodium chloride with or without anticaking agents.

3.2.8 Sausage casing. Sausage casing shall be made of reconstituted collagen (edible) designed for processing (see 6.3) and shall have been fabricated to maintain integrity during processing.

3.2.9 Sugar. Sugar shall be clean, refined, sucrose, granulated cane or beet, or a combination of both. The sugar shall comply with MIL-STD-900.

3.2.10 Water. Water used for ice making, formulation, and washing shall conform to the National Interim Primary Drinking Water Regulations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

3.2.11 Preblended spice and seasoning mixture. Preblended spices and seasonings may be used. The spices and seasonings in the mixture shall comply with the requirements of this specification. The containers used for the spice and seasoning blend shall be labeled with each ingredient and the percentage of each ingredient in the blend. The ingredients shall be in the same proportions as specified in the ingredient formula.

3.3 Preparation and processing.

3.3.1 Pork sausage link preparation. The pork sausage links shall be formulated and prepared as follows:

Ingredients	Weight
Pork	100 pounds
Ice	3 pounds
Salt	28 ounces
Dextrose	14 ounces
Sugar	14 ounces
Pepper, white, ground	4 ounces
Sage, ground	3 ounces
Pepper, black, ground	1 ounces
Ginger, ground	0.5 ounces

a. The mixture shall be stuffed into the casings.

b. The sausage links shall be oven-cooked until no pink or red color remains in the links. In addition, the cooking procedure shall be sufficient to produce a light brown to dark brown surface color.

c. Unless filling of trays occurs immediately after cooking, the cooked sausage shall be cooled to a temperature of 28° to 40°F and held in this temperature range for not more than 48 hours prior to filling.

3.3.2 Brine preparation. Salt and water shall be combined to provide a 1.5 to 2.0 percent brine (salt) solution.

3.4 Tray pack filling and sealing. Each tray pack can (see 5.1.1) shall be filled with cooked pork sausage links and brine such as to conform to the finished product requirements and to the following requirements. Brine may be filled hot or cold. Brine shall be made fresh daily and brine remaining at the end of a production shall be discarded.

a. Not less than ninety uniformly sized sausage links shall be packed packed in the tray pack can in three rows across the width of the can. Each row shall consist of two layers of links. Extra links shall be filled into the spaces remaining at the ends of the tray pack cans.

b. The temperature of the sausage links at time of filling shall not exceed 40°F unless filling of the cans occurs immediately after cooking.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

c. Each can shall be hermetically sealed (under a vacuum of not less than 10 inches of mercury) immediately after filling.

d. The filled and sealed tray pack cans shall be in the retort process within 1 hour after sealing.

3.5 Tray pack thermoprocessing. The filled and sealed tray pack cans shall be thermostabilized by retorting until a sterilization value (F_o) of not less than 6 has been achieved.

3.6 Finished product requirements. The finished product shall comply with following requirements:

a. There shall be no foreign material, such as but not limited to dirt, insects, insect parts, hair, wood, paper, paint, glass, or metal.

b. There shall be no foreign odor or flavor, such as but not limited to stale, sour, rancid, musty, or moldy.

c. There shall be no color foreign to the product.

d. Links shall fit into the tray without breaking.

e. There shall be not more than 3 broken sausage links in a tray pack can.

f. Links shall not be soft or mushy.

g. Sausage link casings shall maintain their integrity (shall not show evidence of sloughing).

h. Links shall have a surface color ranging from light brown to dark brown.

i. The links shall not have an uncooked or raw internal color.

j. No individual can shall contain less than 54.0 ounces drained weight of sausage links.

k. The average net weight shall be not less than 104 ounces.

l. No individual can shall contain less than 102 ounces of product.

m. The average fat content shall be not greater than 23.0 percent.

n. The fat content of any individual tray pack shall be not greater than 25.0 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

o. The salt content of any individual tray pack shall be not less than 1.5 percent nor greater than 2.5 percent.

p. The product shall show no evidence of excessive heating (materially darkened or scorched).

3.6.1 Palatability. The finished product shall be equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance.

3.7 Plant qualification. The pork component and the finished product shall originate and be produced, processed, and stored in plants regularly operating under Meat and Poultry Inspection Regulations of the U.S. Department of Agriculture.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this specification. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of supervision necessary to assure compliance with the requirements of this specification.

4.3 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this specification and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this specification or any appearance or palatability failure shall be cause for rejection of the first article.

4.4 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2, shall be certified by the ingredient supplier or ingredient manufacturer, or compliance be evident by examination of pertinent labels, markings, U.S. Grade certificates, certificates of analyses, or other such valid documents valid

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

acceptqable to the inspection agency. In addition, prior to use, each ingredient shall be examined organoleptically, as necessary, to determine conformance to the condition requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.4.2 Pork sausage examination. Examination of pork sausage links shall be made to determine compliance with the requirements of 3.2.1. In addition, records of formulation, temperatures, and holding times shall be maintained. When sausage links are obtained from a contractor other than the prime contractor, they shall receive a source inspection to determine compliance with 3.2.1 and shall be so certified by the USDA. Failure to comply with requirements shall be basis for rejection of the lot.

4.5 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, can interior coating, filling, sealing and packing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation, or other valid documents shall be cause for rejection of the involved product.

4.6 Tray pack inspection. The inspection lot shall include only tray packs produced in one workshift. The USDA reserves the right to separate the inspection lot into smaller inspection lots.

4.6.1 Net weight inspection. Randomly select 30 filled and sealed tray pack cans from the inspection lot and weigh separately. Subtract the average tare weight (determined by randomly selecting and weighing 30 of the empty tray pack cans and lids used in preparing the product and dividing the total weight by 30) from the weight of each tray pack in the sample. The results shall be reported to the nearest 1 ounce. If the average net weight is less than 104 ounces or if the net weight of any individual can is less than 102 ounces, the lot shall be rejected.

4.6.2 Product inspection. The sample size shall be as indicated by the double sampling plan specified in table I. The tray pack cans shall be selected at random from the lot. The tray pack cans shall be heated for 35 minutes in 180° to 190°F water, opened, and inspected for the defects listed in table II.

TABLE I. Double sampling plan for product inspection 1/

Lot size (cans)	Sample size (No. of cans)	Cumulative sample	Acceptance number	Rejection number
0-3200	8	---	0	2
	8	16	1	2
3201-35000	13	---	0	3
	13	26	3	4

1/ a. If no defects are found in the first sample, the lot shall be accepted.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:02Z
Check the source to verify that this is the currenversion before use.

b. If the number of defects found in the first sample equals or exceeds the rejection number, the lot shall be rejected.

c. If the number of defects found in the first sample exceeds the acceptance number but is less than the rejection number, the second sample shall be inspected. Defects found in the first and second samples shall be combined and if the number of defects in the cumulative sample equals or exceeds the rejection number, the lot shall be rejected.

TABLE II. Product defects 1/ 2/

Category	Defect
Major	
101	Links do not have a surface color ranging from light brown to dark brown.
102	Less than 90 links per tray pack can.
103	Links not packed in three rows across the width of the tray pack can.
104	Links not layer packed.
105	Four or more broken sausage links per tray pack can.
106	Presence of soft or mushy links.
107	Links possessing an uncooked or raw internal color.
108	Drained weight of sausage links in a can is less than than 54.0 ounces. 3/
109	Sausage casing material shows evidence of sloughing
110	Product shows evidence of excessive heating (materially darkened or scorched).

1/ The presence of foreign material (e.g., glass, dirt, insect parts, hair wood, metal), foreign odor or flavor (e.g., moldy, rancid, sour, stale), or foreign color shall be cause for rejection of the lot. Acceptability of product shall be determined by a Meat and Poultry Inspection Operations employee.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

2/ Product not equal to or better than the approved preproduction sample (see 6.1) in palatability or overall appearance shall be cause for rejection of the lot. (This comparison shall be performed only when deemed necessary by an AMS agent.)

3/ To determine drained weight, the free liquid in the can shall be poured off and the remaining contents shall be poured into a flat bottom container. A minimum of three times the tray pack can's volume of 190° to 212°F water shall be added to the container so as to cover the contents. The contents and water shall be agitated so as to liquify rendered fat without breaking the links. The contents shall then be poured into a U.S. Standard 1/2 inch sieve in a manner that will distribute the product over the sieve without breaking the links. Sieve area shall be such that the distributed product does not completely cover all the openings of the sieve. The sieve shall be tilted at approximately a 45° angle and allowed to drain for 2 minutes before determining the drained weight by subtracting the sieve tare weight from the gross weight. The drained weight shall be reported to the nearest 0.1 ounce.

4.6.3 Fat and salt content testing. Nine tray pack cans shall be selected at random from the lot and distributed as follows:

- Three for laboratory analysis.
- Three for submission to the contractor.
- Three for retention by the AMS agent as a reserve sample.

The three tray packs for laboratory analyses shall be individually tested for fat and salt content in accordance with the Meat and Meat Products chapter of the Official Methods of Analysis of the Association of official Analytical Chemists, except that preparation of the samples shall be as follows: The three unopened tray packs shall be gently warmed in water bath to melt fat adhering to the inside of the cans. The cans shall be opened and the entire contents of each can shall be separately blended in a Waring blender or equivalent. The lot shall be rejected if:

a. The average fat content of the three tray packs is greater than 23.0 percent.

b. The fat content of any individual tray pack is greater than 25.0 percent.

c. The salt content of any individual tray pack is less than 1.5 or greater than 2.5 percent.

Analysis of reserve samples at the request of the contractor shall not be permitted unless the original laboratory analysis indicated that the involved lot will be rejected because of noncompliance with the fat or salt content requirement. When the reserve samples are analyzed, the analyses for both fat and salt shall be made and will be considered final. Unused reserve samples shall be returned to the contractor for inclusion in subsequent lots.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

4.7 Can condition examination. Examination of filled and sealed tray pack cans shall be in accordance with the United States Standards for Condition of Food Containers, except that the labeling shall be inspected in accordance with MIL-L-1497 (see 5.4).

4.8 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable) in accordance with the appendix of PPP-B-636. In addition, the following defects shall be classified as follows: Major: (1) National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible. (2) Reinforcement with other than nonmetallic strapping or tape. Minor: (1) Other required markings missing, incorrect, or illegible. (2) Interior packing with fiberboard liner or pads not as specified; (3) Height of box liner less than inside depth dimension of box by more than 1/8 inch or extends above top edge of box; (4) length or width of pads less than box dimensions by more than 1/8 inch; (5) Arrangement or number of cans not as specified.

4.9 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

5. PREPARATION FOR DELIVERY

5.1 Packaging. The product shall be packaged in accordance with level A or C as specified (see 6.1).

5.1.1 Level A. A size 1001 by 1206 by 200 tray pack can shall be filled with 104 ounces of the food product, sealed, and thermoprocessed as specified in 3.4 and 3.5. The base plate of the can shall be electrolytic chromium-coated steel and shall be of sufficient temper to protect the product during shipment and storage. The base plate weight of the body and end of each can shall be 90 pounds per base box. The entire inside area of the can shall be coated. Scratches or fractures shall not penetrate through the interior can coating. The interior can coating shall not peel or blister when in contact with the product. The interior can coating shall neither affect nor be affected by the packaged product. A certificate of conformance shall be furnished to certify compliance with the interior can coating requirements. The can shall be coated overall on the outside with a coating conforming to type I of TT-C-495.

5.1.2 Level C. The product shall be packaged as specified in 5.1.1, except that cans with commercial exterior coating will be acceptable.

5.2 Packing. The product shall be packed in accordance with level A, B or C as specified (see 6.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

5.2.1 Level A packing. Four cans of product, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, grade V2s of PPP-B-636. The cans shall be packed flat, four in depth within the box. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). The pads shall be not less than 1/8 inch of the full length and width dimensions of the box and shall be fabricated of grade V3c fiberboard. The pads shall be placed between the cans and on the top and bottom of the stacked cans. Each fiber-board box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Four cans of product, packaged as specified in 5.1, shall be packed as specified in 5.2.1, except the box shall be constructed of grade V3c, V3s, or V4s fiberboard.

5.2.3 Level C packing. Four cans of product, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, class domestic, grade 275 of PPP-B-636. The cans shall be packed flat, four in depth within the box. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). The pads shall be placed between the cans and on the top and bottom of the stacked cans. Each pad shall be not less than 1/8 inch of the full length and width dimension of the box and shall be fabricated of the same material as the box.

5.3 Unit loads. When specified (see 6.1), the product, packed as specified in 5.2.2 and 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping.

5.4 Labeling. Each tray pack can shall be labeled in accordance with MIL-L-1497. In addition, the name of the product shall be marked, stamping is permitted, on one 1001 by 200 side of the can. The labeling shall be legible when examined in accordance with 4.7 after submerging the can in boiling water for 30 minutes. Paper labels are not permitted. Cans shall show the following statements:

a. To heat in water: Submerge sealed cans in boiling water. Bring to a boil, continue boiling for 40 to 45 minutes. Avoid overheating to the point where internal pressure is evident (can shows evidence of bulging). Remove from water and open lid for serving. CAUTION: Use care when opening as pressure may have been generated within the can.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

b. To heat in oven: Either punch several holes in lid of can or open can in usual manner leaving the loose lid in place to prevent moisture loss. Place in a 350°F oven for approximately 35 to 40 minutes until contents reach an internal temperature of 165°F. WARNING: Do not place closed can in oven as heating will increase internal pressure which may cause the can to burst.

YIELD

Approximately 30 servings of 3 links each.

5.5 Marking.

5.5.1 Shipping containers. In addition to any special marking required by the contract, shipping containers shall be marked in accordance with MIL-STD-129.

5.5.2 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078. In addition, the following precautionary markings in capital letters larger than other marking shall be included:

CAUTION: DO NOT STACK PALLETS IN TRANSIT OR MORE THAN TWO HIGH IN STORAGE.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. When a first article is required (see 3.1, 4.3, and 6.4).
c. Provisions for approved preproduction samples (see 3.6.1 and 6.4).
d. Level of packaging and packing required (see 5.1 and 5.2).
e. Type and class of unit load when required (see 5.2.1 and 5.3).

6.2 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.3 Sausage casing. During development of this product casings meeting the requirements of 3.2.8 were obtained from Devro Inc. #210-613. Equivalent casings from other suppliers may be used.

6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:02Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
PP–P–002177A(Army–GL)	PORK SAUSAGE LINKS IN BRINE, THERMOSTABILIZED, TRAY PAC

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK/OP1, Feb 86

Source: https://assist.dla.mil -- Downloaded: 2026-40-26T12:02Z
Check the source to verify that this is the current version before use.