MIL-A-60257A(MU)
AMENDMENT 2
15 April 1973
SUPERSEDING
AMENDMENT 1
15 January 1973

MILITARY SPECIFICATION
ADAPTER, MOUNT ASSEMBLY: 10541111

This amendment forms a part of Military Specification MIL-A-60257A(MU) dated 18 June 1970.

Paragraph 3.5.5, Azimuth Excursion: Delete "5675 Mils" and substitute "5450 Mils".

Paragraph 3.5.7, Circular Level: Delete "5675 Mils" and substitute "5450 Mils".

* Paragraph 4.6.1.2, Shock: In second sentence delete "Procedure II" and substitute "Procedure I".

* Paragraph 4.6.1.3, Vibration: Delete fourth sentence and substitute "The vibration test shall be performed in accordance with Figure 514-1, Curve C of MIL-STD-810 except double amplitude shall not exceed .036 inch".

* "The margin of this specification is marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project No. 1240-A496

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:23Z
Check the source to verify that this is the current version before use.