MILITARY SPECIFICATION

INDICATORS, BUILT-IN-TEST (BIT), GENERAL SPECIFICATION FOR

This specification is approved for use by all Departments and Agencies of the Department of Defense

1. SCOPE

1.1 Scope - This specification covers the general requirements for Built-In-Test indicators hereinafter referred to as BIT indicators. The indicators are designed to display the operational status of electrical and electronic equipment.

1.2 Classification - The BIT indicators are sealed, electrically (pulse) operated, magnetically latched, and either manually or electrically resettable. Detail requirements for individual BIT indicators, including mounting and display presentation, shall be in accordance with the applicable Military Specification Sheets.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-T-18303	Test Procedures, Preproduction and Inspection, for Aircraft Electronic Equipment, Format for

FSC 5945

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:36Z
Check the source to verify that this is the current version before use.

STANDARDS

Federal

FED-STD-595	Colors

Military

MIL-STD-100	Engineering Drawing Practices
MIL-STD-143	Specification and Standards, Order of Precedence for the Selection of
MIL-STD-202	Test Methods for Electronic and Electrical Component Parts
MIL-STD-454	Standard General Requirements for Electronic Equipment
MIL-STD-461	Electromagnetic Interference Characteristics Requirements for Equipment
MIL-STD-462	Electromagnetic Interference Characteristics, Measurement of
MIL-STD-781	Reliability Tests Expotential Distribution
MIL-STD-794	Parts and Equipment, Procedures for Packaging and Packing of
MIL-STD-1285	Marking of Electrical and Electronic Parts

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Specification sheets - Individual BIT indicator requirements shall be in accordance with the applicable specification sheets and as specified herein (see 6.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:36Z
Check the source to verify that this is the current version before use.

3.2 Qualification - The indicators furnished under this specification shall be products which are qualified for listing on the applicable qualified products list at the time for opening of bids (see 4.3 and 6.5).

3.3 Materials - All materials shall be of a uniform quality and free of defects which might impair the functioning and accuracy of the indicator. Specifications and standards for necessary commodities and services not specified herein shall be selected in accordance with MIL-STD-143.

3.3.1 Fungus proof materials - Selection and use of fungus proof materials shall be as specified in MIL-STD-454, Requirement No. 4.

3.3.2 Metals - Metals shall be of the corrosion resistant type or suitably treated to resist corrosion from fuels, salt spray, humidity, and other conditions likely to be met in storage or normal service use of the indicator.

3.3.2.1 Dissimilar metals - The selection and use of dissimilar metals shall be as specified in MIL-STD-454, Requirement No. 16, Class 3.

3.3.3 Protective treatment - When materials are used that are subject to atmospheric or environmental conditions likely to degrade during normal service life, they shall be protected in a manner that will in no way prevent compliance with the performance requirements of this specification. Any protective coating which will crack, chip, or scale during normal service life, or which will be affected by extremes of atmospheric or environmental conditions, shall not be used.

3.3.4 Interchangeability of parts - All parts having the same manufacturer's part number shall be directly and completely interchangeable with each other with respect to installation and performance. Changes in manufacturer's part numbers shall be governed by the drawing requirements of MIL-STD-100.

3.4 Design and construction - The indicator shall be designed and constructed such that no part will become loose during the service life specified herein. It shall be built to operate as required when subjected to the strains, shocks, vibrations, and other conditions incident to shipping, storage, installation, and service use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:36Z
Check the source to verify that this is the current version before use.

3.4.1 Operation - The indicator shall operate in accordance with the applicable specification sheet. The indicator shall be either electrically or manually operated as required by the applicable specification sheet. This requirement applies with the indicator mounted in any position and when operated either continuously or intermittently.

3.4.2 Data display presentation - The number of data display positions shall be two. One position shall indicate an operative condition for the equipment on which the indicator is used; the other position shall indicate a non-operative condition. The color of the data display for operative and non-operative indications shall be in accordance with the applicable sheet.

3.4.3 Operating voltage - The operating voltage shall be as specified in the applicable specification sheet.

3.4.4 Power consumption - Power consumption shall be in accordance with the applicable specification sheet.

3.4.5 Data display window - The data display window shall be made of clear glass. The glass shall be impervious to any environmental condition and combination thereof specified herein.

3.4.6 Coil - The coil and all other internal electrical circuitry shall be insulated from the case and other grounded parts.

3.4.7 Case - The case shall provide a sealed enclosure for the internal mechanism of the indicator. The seal shall not be dependent upon materials which will be affected by the action of either any one environment or combination of environments to which the indicator may be subjected.

3.4.7.1 Color - The color of the case shall be black. The luster and degree of blackness shall closely approximate Color No. 37038 of FED-STD-595.

3.4.8 Terminations - The indicator shall be provided with either solder terminals or insulated wire leads in accordance with the applicable specification sheet. Terminations shall be identified in accordance with the applicable specification sheet.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:36Z
Check the source to verify that this is the currentversion before use.

3.4.8.1 Solder Terminals - All terminals used for soldered connections shall be hot-tin dipped or solder coated to facilitate soldering, and shall accommodate a minimum of one size 22 stranded wire.

3.4.8.2 Stress - Each termination shall withstand a 4.5 pound pull without loosening or being damaged.

3.4.9 Soldering - All soldering shall be in accordance with MIL-STD-454, Requirement No. 5.

3.4.10 Size - Outline and mounting dimensions of the indicator shall be in accordance with the applicable specification sheet.

3.4.11 Weight - The total weight of the indicator shall not exceed the weight specified in the applicable specification sheet.

3.4.12 Identification of product - The indicator shall be marked for identification in accordance with the applicable specification sheet and MIL-STD-1285 Method I, including the appropriate military part number, manufacturer's code, and date code of manufacture.

3.4.13 Workmanship - Workmanship shall be in accordance with MIL-STD-454, Requirement 9.

3.5 Operational environments - The indicator shall operate in accordance with paragraph 3.4.1 under the environmental conditions specified herein.

3.5.1 Temperature - Unless otherwise specified in the applicable specification sheet, the indicator shall operate satisfactorily at any temperature between -65°C and +125°C.

3.5.1.1 Storage - The indicator shall not be damaged and shall operate satisfactorily after storage at any temperature ranging from -65°C to +125°C.

3.5.2 Fogging - There shall be no fogging inside the display window of the indicator under any environmental condition and combination thereof specified herein.

3.5.3 Altitude - The indicator shall operate at any pressure from 30 inches of mercury (sea level) to 0.32 inch

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:36Z
Check the source to verify that this is the current version before use.

of mercury (100,000 feet), and shall operate with pressure varying at a maximum rate of 0.5 inch of mercury per second.

3.5.4 Dielectric stress - The indicator shall withstand the application of 100 VDC between all terminals that are designed to be electrically isolated from each other, and 500 VDC between terminals and case for a period of one minute at an external barometric pressure of 0.32 inch of mercury (100,000 feet) without damage or breakdown of insulation.

3.5.5 Vibration - The indicator shall operate during and after being subjected to a vibration of 0.06 inch double amplitude or 10G, whichever is less, over a frequency range of 10 to 2000 Hz.

3.5.6 Shock - The indicator shall not be damaged and shall retain the appropriate data indication when subjected to shocks of 11 ± 1 millisecond at 50G's.

3.5.7 Acceleration - The indicator shall not be damaged and shall retain the appropriate data indication when subjected to accelerations of up to and including 50G's maximum.

3.5.8 Magnetic effect - Indicator operation shall not be affected by a magnetic field intensity of 0.19 Oersted maximum. (See 6.2)

3.5.9 Insulation resistance - The indicator's insulation resistance shall not be less than 500 megohms at 100 VDC between all terminals designed to be electrically isolated from each other, and shall not be less than 1000 megohms at 500 VDC between all terminals and case.

3.5.10 Salt spray - The indicator shall not corrode or show signs of moisture inside the display window and case when subjected to a salt spray atmosphere.

3.5.11 Moisture resistance - The indicator shall not corrode or show signs of moisture inside the display window and case when subjected to a relative humidity up to and including 98 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:36Z
Check the source to verify that this is the current version before use.

3.5.12 Radio noise suppression - The indicator shall comply with the radio noise suppression requirements for Class ID equipment of MIL-STD-461.

3.5.13 Reliability - The indicator shall have a Mean-Time-Between-Failure (MTBF) of 500 hours.

3.5.14 Life - The indicator shall have a satisfactory performance life of 500 hours.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection - Unless otherwise specified, in the contract or purchase order, the manufacturer is responsible for the performance of all inspection requirements as specified herein. The manufacturer may use either his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform and participate in any of the inspections set forth by this specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Test procedures - Test procedures and methods for performing all tests specified herein shall be prepared by the manufacturer and submitted for approval to the activity responsible for qualification testing. The manufacturer must obtain test procedure approval prior to submitting the product for tests. The right is reserved by the Government to require additional tests, than those tests contained in the approved test procedure, to determine compliance with the applicable specification requirements when it is deemed necessary. Test procedures shall be prepared in accordance with the requirements for format and content of MIL-T-18303.

4.1.2 Test reports - The manufacturer shall prepare test reports showing detailed quantitative results and data for all tests required by this specification and shall furnish these test reports to the Government and procuring activity upon request. Each report shall be signed by a responsible representative of either the manufacturer or laboratory as applicable and shall contain the following statement, "As the authorized representative of the manufacturer the undersigned warrants and represents that all information supplied herewith is true and accurate."

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:36Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection - Indicators covered by this specification shall be subjected to the following inspections.

(1) Qualification inspection

(2) Quality conformance inspection

4.3 Qualification inspection - The qualification inspection shall consist of the performance tests of 4.6 and the reliability tests of 4.7. Test sample quantity shall be in accordance with 4.3.1. Failure of any indicator to pass any test shall constitute rejection of all indicators in the test sample. Rejected indicators shall be returned to the manufacturer for failure analysis and prior to re-submittal of a new test sample the manufacturer shall satisfactorily establish that the appropriate corrective action has been implemented. If any of the products are modified in any way after satisfactory completion of the qualification inspection, the modified form shall be subjected to a new qualification inspection.

4.3.1 Test sample quantity - The qualification inspection test sample shall consist of 10 indicators; 3 indicators to satisfy the requirements of paragraph 4.6 and 7 indicators to satisfy the requirements of paragraph 4.7. The test sample shall have been previously subjected only to the individual tests of paragraph 4.4.1.

4.3.2 Test sample submission - The test sample shall be forwarded at the manufacturer's expense to the laboratory designated in the letter of authorization (see 6.5).

4.3.2.1 Presubmission testing - No indicator shall be submitted for qualification testing until like indicators have been tested and inspected by the manufacturer and found to comply to the best of his knowledge and belief with all specification requirements. The manufacturer must furnish proof of presubmission testing to the Government upon request.

4.3.3 Test sample identification - Each indicator of the test sample shall be plainly identified by a durable tag,

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:36Z
Check the source to verify that this is the current version before use.

securely attached, and marked with the following information:

Sample for Qualification Test

Indicator, Electromagnetic, Built-In-Test

Submitted by (Manufacturer's name, date and part number) for Qualification test in accordance with Specification MIL-I-81663 under authorization (reference letter authorizing tests).

4.4 Quality conformance inspection - The manufacturer shall furnish all samples and shall be responsible for accomplishing the quality conformance inspection. The quality conformance inspection shall be under the supervision of the Government quality control representative. Acceptance or approval of material during the course of manufacture shall in no case be construed as a guarantee of the acceptance of the finished product. The quality conformance inspection shall consist of the following tests:

(a) Individual tests

(b) Sampling Plan A tests

(c) Sampling Plan B tests

4.4.1 Individual tests - Each indicator submitted for acceptance shall be subjected to the individual tests. These tests shall determine compliance with the requirements of material, workmanship and operational adequacy. As a minimum, each indicator accepted shall have passed the following tests:

Examination of product	4.6.1
Operational test	4.6.2
Burn-In test	4.6.3

4.4.2 Sampling plans - The Sampling plans shall consist of Sampling Plan A and Sampling Plan B tests. The indicators selected for sampling tests shall first have passed the individual tests. Indicators which have been subjected to Sampling Plan B tests shall not be delivered on contract.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:36Z
Check the source to verify that this is the current version before use.

4.4.2.1 Rejection and retest - When an indicator selected for sampling tests from a production run fails to comply with specification requirements, no indicator still on hand or later produced shall be accepted until the extent and cause of failure are determined. After corrections have been made, sufficient tests shall be conducted to assure that the indicator complies with all requirements of the specification.

4.4.2.1.1 Continued testing - Individual tests may continue for operation and production reasons, pending the results of the investigation of a sampling test failure. However, final acceptance of all indicators on hand or later produced shall not be made until it is determined that they comply with all requirements of the specification.

4.4.2.2 Sampling plan approval - Approval of Sampling Plan indicators shall be made by the Government quality control representative upon satisfactory completion of the designated tests. Any design, material, or performance defect made evident during this test shall be corrected by the manufacturer to the satisfaction of the procuring activity. Failure of the sample units to pass any of the tests shall be cause for deliveries of indicators under contract to cease and may be cause for removal from the Qualified Products List (QPL) until the proposed corrective action is accomplished and approved.

4.4.2.3 Sampling Plan A schedule - During each production run, indicators shall be selected at random and tested in accordance with 4.4.2.3.1 and the following schedule:

Quantity Offered for Acceptance	Quantity to be Selected for Sampling Plan A Tests
First 15	1
Next 50	1
Next 75	1
Next 100	1
Each additional 200 or fraction thereof	1

After a failure occurs, and the cause of failure is determined and appropriately corrected, shift to one sample out of the next fifteen and proceed as indicated. (one from next 50, etc.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:36Z
Check the source to verify that this is the current version before use.

4.4.2.3.1 Scope of Sampling Plan A test - Each sample selected for the Sampling Plan A test shall be subjected to the following tests in the order listed:

Examination of product	4.6.1
Operational test	4.6.2
Burn-In test	4.6.3
Temperature cycling	4.6.6
Dielectric stress	4.6.4
Seal	4.6.8

4.4.2.4 Sampling Plan B schedule - Sampling Plan B tests shall be conducted each and every two years thereafter from the latest date of product qualification and shall be at the manufacturer's expense under supervision of the Government quality control representative.

4.4.2.4.1 Test sample quantities - The test sample shall be selected at random from current production quantities in accordance with the qualification test sample quantity requirement of paragraph 4.3.1.

4.4.2.4.2 Scope of Sampling Plan B Test - Sampling Plan B Tests shall consist of the performance tests of 4.6 and the reliability tests of 4.7.

4.4.3 Production indicators - Indicators supplied under contract shall comply with all specification requirements for design, construction, workmanship, performance and quality. Each indicator may be required to pass the same tests as imposed on the qualification sample as deemed necessary by the Government. Evidence of non-compliance with the above shall constitute cause for removal from the Qualified Products List and for indicators already accepted by the Government, it shall be the obligation of the contractor to make necessary corrections as approved by the procuring activity.

4.4.3.1 Certification - Certification when required by the procuring activity shall certify that the indicator has been determined to be in full compliance with specification requirements for performance, workmanship, materials and quality. The certification shall reference either the contract or purchase order and shall be signed by a responsible officer of the manufacturer. The certificate shall contain the following statement, "As the authorized representative of the manufacturer, the undersigned warrants and represents that all the information supplied herewith is true and accurate.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:36Z
Check the source to verify that this is the current version before use.

4.5 Standard conditions - Unless otherwise specified, all inspections required by this specification shall be made under the following conditions:

Temperature	Room ambient 25° ± 5°C
Pressure	Normal atmospheric (approximately 29.92 inches Hg)
Humidity	Room ambient up to 95 percent relative humidity
Input power	In accordance with detail specification sheet

4.5.1 Shielding - Caution shall be taken to shield the indicator from magnetic fields of test equipment. (See 3.5.8)

4.6 Performance tests - Prior to and after conducting each environmental test, the indicator shall be instrumented and checked for satisfactory performance under standard conditions. A record shall be made of all data deemed necessary to determine that the indicator conforms with all operational and performance requirements herein. This check shall include operation at both highest and lowest specified input voltages and activating the indicator at least six times.

4.6.1 Examination of product - The indicator shall be examined to determine conformance with specification requirements for workmanship, dimensions, marking, and color.

4.6.2 Operational test - The indicator shall be checked for satisfactory operation in accordance with the applicable detail specification sheet and 3.4.1.

4.6.3 Burn-In - The indicator shall be operated continuously for 25 operational cycles under standard conditions in accordance with the operational cycle of paragraph 4.8, except that the time intervals of 4.8 shall not apply. During this period the indicator shall be monitored continuously for satisfactory operation.

4.6.4 Dielectric stress - The indicator shall be subjected to Test Method 301 of MIL-STD-202 except that the potentials and barometric pressure shall be in accordance with the requirements of paragraph 3.5.4. This test shall be repeated with the polarity of the test voltage reversed. The indicator shall be non-operating during the test but shall be checked for satisfactory operation afterwards. This test shall be conducted at room atmospheric pressure for Sampling Plan A indicators only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:36Z
Check the source to verify that this is the current version before use.

4.6.5 Magnetic effect - The indicator in the unactivated condition shall be placed 5.5 inches from a bar-magnet having an intensity between 0.17 and 0.19 Oersted. The indicator shall be rotated in each of the three mutually perpendicular axes and the effect of the magnetic field shall not cause the data indication to change. The test shall be conducted with the indicator's axis parallel and then perpendicular to the bar-magnet's longitudinal axis. The test shall be repeated with the indicator in the continuous electrically activated condition (100% duty cycle) and for each one of the two data indications.

4.6.6 Temperature cycling - The indicator shall be tested in accordance with Method 102, Test Condition C of MIL-STD-202 unless otherwise specified in the applicable specification sheet. The indicator shall be operated during step 3 of this test at both the highest and lowest specified voltages and checked for satisfactory operation. There shall be no internal fogging during and after this test.

4.6.7 Altitude - The indicator shall be tested in accordance with method 105, Test Condition D of MIL-STD-202. The units shall be operated for 10 minutes under these conditions at the highest specified voltage and checked for satisfactory operation. There shall be no internal fogging during and after this test.

4.6.8 Pressure Seal - The indicator shall be tested in accordance with Method 104, Test Condition B of MIL-STD-202. The indicator shall be checked for insulation resistance following the test. There shall be no internal fogging after this test. Test Condition A shall apply for Sampling Plan A indicators only.

4.6.9 Vibration - The indicator shall not be damaged and must operate during and after being tested in accordance with Method 204, Test Condition D of MIL-STD-202. The vibration level shall be 10 G's.

4.6.10 Salt spray - The indicator shall be tested in accordance with Method 101, Test Condition B of MIL-STD-202. The indicator shall be checked for satisfactory operation after the test. There shall be no corrosion or internal fogging after this test.

4.6.11 Insulation resistance - The indicator shall be subjected to Method 302 of MIL-STD-202 except that the potentials shall be in accordance with the requirements of paragraph 3.5.9. This test shall be repeated with the polarity of the test voltage reversed.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:36Z
Check the source to verify that this is the current version before use.

4.6.12 Moisture resistance - The indicator shall be subjected to Method 106, of MIL-STD-202. The polarization voltage shall be 200 VDC and shall be applied only between terminals and case. There shall be no corrosion or internal fogging after this test.

4.6.13 Radio noise - The indicator shall be tested for conducted and radiated susceptibility and interference in accordance with the requirements of paragraph 3.5.12 using the methods of MIL-STD-462. The indicator case shall be grounded to the low side of the power source as required.

4.6.14 Acceleration - The indicator shall not be damaged and must operate during and after being subjected to Method 212, Test Condition A of MIL-STD-202. The acceleration level shall be 50 G's.

4.6.15 Shock - The indicator shall not be damaged and must operate satisfactorily after being subjected to Method 213, Test Condition A of MIL-STD-202. The data indication shall not change during the test.

4.6.16 Storage - The indicators shall be stored for 48 hours at each temperature condition of -65°C and +125°C. After storage the indicators' temperature shall be allowed to stabilize at room ambient conditions. After stabilization, the indicators shall be visually inspected for defects and tested for sealing and satisfactory operation. There shall be no internal fogging during or after this test.

4.6.17 Stress - The indicator terminals shall be subjected to a 4.5 pound pull in accordance with the procedures of MIL-STD-202, Method 211, Test Condition A. The terminals shall not be loosened or damaged.

4.6.18 Life - The indicator shall be subjected to a life test of 500 hours under the standard conditions of 4.5. Operation shall be in accordance with the operational cycle requirement of paragraph 4.8. Two consecutive operational cycles shall be performed four times per hour equally spaced. Failure to meet the life test shall be cause for removal of the indicator from the qualified products list.

4.7 Reliability qualification tests - Reliability qualification tests shall be conducted in accordance with MIL-STD-781 except as modified herein. Indicators selected for reliability qualification testing shall first have passed the individual tests of 4.4.1. Indicators that have been subjected to reliability qualification testing shall not be delivered on contract.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:36Z
Check the source to verify that this is the current version before use.

4.7.1 Test level - Test level J shall be used except that temperature cycling shall be from -65°C to +125°C unless otherwise specified by the applicable specification sheet.

4.7.2 Accept - reject criteria - The accept - reject criteria of Test Plan II shall apply.

4.7.3 Operation and operational check - The indicator shall be operated in accordance with the operational cycle of 4.8. Two consecutive operational cycles shall be performed four times per hour equally spaced and the indicator checked for satisfactory operation in accordance with 3.4.1 during each heating cycle.

4.8 Operational cycle - The operational cycle shall consist of a 1 second energizing pulse, followed by a 4 second reset, and then a 10 second hold in the de-energized position.

4.9 Defects in indicators already accepted - The investigation of a test failure could indicate that defects may exist in indicators already accepted. If so, the contractor shall fully advise the procuring activity of these defects and methods for correcting them.

5. PREPARATION FOR DELIVERY

5.1 General - All indicators shall be preserved, packaged, packed, and marked for the level of shipment specified in the contract or order in accordance with MIL-STD-794.

6. NOTES

6.1 Intended use - The electromagnetic indicators specified herein will be used as a circuit condition indicator in aircraft electrical systems and electronic equipment.

6.2 Extraneous magnetic fields - Users are advised that the indicator may malfunction and operate erratically in certain applications, including testing, when subjected to magnetic field intensities in excess of 0.19 Oersted and should be appropriately shielded. (See 3.5.8)

6.3 Ordering data - Procurement documents should specify the following:

(a) Title, number, and date of this specification

(b) The quantity, applicable detail specification sheet number, and part number of the indicator

Source: https://assist.dla.mil -- Downloaded: 20261O-26T04:36Z
Check the source to verify that this is the current version before use.

(c) Levels of packaging and packing
(d) Test reports (See 4.1.2)

6.4 Precedence of documents - When the requirements of the applicable detail specification sheet, this specification, or applicable subsidiary specifications are in conflict, the following precedence applies.

(a) The applicable detail specification sheet

(b) This specification

(c) Referenced specifications

6.5 Qualification - With respect to products requiring qualification, awards will be made only for products which are, at the time set for opening of bids, qualified for inclusion in the applicable Qualified Products List (QPL), whether or not such products have actually been so listed by that date. The attention of the suppliers is called to the requirement of 3.2, and manufacturers are urged to arrange to have the products that they propose to offer to the Government tested for qualification at the earliest possible date in order that they may be eligible to be awarded contracts or orders for the products covered by this specification.

6.5.1 Application for qualification - The activity responsible for the QPL for MIL-I-81663 is the Naval Air Systems Command. The Naval Ammunition Depot, Crane, Indiana, has been designated by the Naval Air Systems Command as agent for the establishment of the QPL. Requests for information pertaining to and applications for qualifications should be addressed to: Commanding Officer, Code 3072, Naval Ammunition Depot, Crane, Indiana 47522.

Custodian:

Navy - AS

Preparing Activity:

Navy - AS

Project No. 5945-N142

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:36Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-I-81063(AS) INDICATORS, BUILT-IN-TEST (BIT), GENERAL SPECIFICATION FOR

ORGANIZATION

CITY AND STATE	CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity — optional)*	DATE

DD FORM [illegible] PREVIOUS EDITION IN USE MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:36Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

Naval Air Systems Command
Washington, D.C. 20361

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE NAVY



NAVAL AIR SYSTEMS COMMAND (AIR-52021)
DEPARTMENT OF THE NAVY
WASHINGTON, D.C. 20361

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:36Z
Check the source to verify that this is the current version before use.