INCH-POUND

MIL-DTL-55302/70D
12 November 2004
SUPERSEDING
MIL-C-55302/70C (USAF)
17 October 1986


DETAIL SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES, PIN, RIGHT ANGLE PLUG, ELECTRICAL, POLARIZED FOR PRINTED WIRING BOARDS (.100 SPACING)

MIL-DTL-55302/70D is inactive for new design after 1 October 1986.

This specification is approved for used by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-55302.




Inches	mm
.001	0.03
.004	0.10
.005	0.13
.008	0.20
.010	0.25
.020	0.51
.025	0.64
.030	0.76
.050	1.27
.087	2.21
.112	2.84
.114	2.90
.124	3.15
.125	3.18
.200	5.08
.227	5.77
.322	8.81
.422	10.72
.465	11.81
.594	15.09
1.250	31.75
2.151	54.64
2.500	63.50
2.822	71.68

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Nominal spacing between any two adjacent pin contacts shall be.090 ± .003 (2.29 ± .08 mm).
4. Unless otherwise specified, tolerances are ± .010 (0.25 mm).
5. For dimension A see table I.

FIGURE 1. Connectors, plug, .100 (2.54 mm) contact spacing pin terminal.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:48Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm
.050	1.27	.550	13.97
.087	2.21	.600	15.24
.100	2.54	.650	16.51
.150	3.81	.700	17.78
.200	5.08	.750	19.05
.250	6.35	.800	20.32
.300	7.62	.850	21.59
.350	8.89	.900	22.86
.400	10.16	.950	24.13
.450	11.43	1.000	25.40
.500	12.70		

NOTE: Contacts 1, 20 and 61 are identified on the front face of the connector per the insert arrangement.

FIGURE 2. Insert arrangement for .100 (2.54 mm) contact spacing connector (male engaging face).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:48Z
Check the source to verify that this is the current version before use.

Requirements:

Dimensions and configuration: See figure 1 and table I.

Material: In accordance with MIL-DTL-55302, except:

Body: reinforced epoxy resin or equivalent.

Bushing: SAE-AMS-5640 stainless steel or SAE-AMS-S-7720, composition 303, condition A.

Plating: The contact plating shall be gold in accordance with ASTM B488, type II, code C, class 1.27 over 100 microinches of copper in accordance with SAE-AMS-2418.

Contact identification: Contact locations are identified numerically as shown on figure 2.

Mating and unmating: The maximum mating force, in pounds, shall be 0.5 times the number of contacts, and the withdrawal force, in pounds, shall be a minimum of 0.08 times the number of contacts and shall not exceed the measured insertion force.

Contact resistance: With a test current of 3 A dc, the average resistance of all contact pairs measured shall not exceed 0.010 ohm, and no individual contact pair shall have a resistance exceeding 0.020 ohm.

Dielectric withstanding voltage:

Sea level: 1,300 volts rms, 60 Hz, ac.
High altitude: 325 volts rms, 60 Hz, ac.

Current rating: 3.0 amperes.

Insert arrangement: See figure 2.

Mating connectors: See MIL-DTL-55302/71.

Part or Identifying Number (PIN): M55302/70-(dash number from table I).

TABLE I. Dash number and dimensions.

Dash number	Dimension 1/ A
01	.114 (2.90)
02	.180 +.015 -.000 (4.57 +.38)

1/ Metric equivalents are given for information only. Millimeters are in parentheses.

Referenced documents. In addition to MIL-DTL-55302, this document references the following:

MIL-DTL-55302/71
ASTM B488
SAE-AMS-2418
SAE-AMS-5640
SAE-AMS-S-7720

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:48Z
Check the source to verify that this is the current version before use.

Previous changes. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

CONCLUDING MATERIAL

Custodians:
Air Force - 11
DLA - CC

Review activity:
Air Force - 19

Preparing activity:
DLA -CC

(Project 5935-4425-004)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:48Z
Check the source to verify that this is the current version before use.