INCH POUND
MIL-DTL-60567C
3 March 2005
SUPERSEDING
MIL-D-60567B
16 April 1990

DETAIL SPECIFICATION
DELAY ELEMENT, CARTRIDGE, M14 ASSEMBLY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for the M14 Cartridge Delay Element (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3, 4 or 5 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, 4 or 5 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-A-2550	Ammunition, General Specification for
MIL-A-8625	Anodic Coating for Aluminum and aluminum Alloys
MIL-B-51092	Boron, Amorphous, Powder
MIL-B-550	Barium Chromate

DEPARTMENT OF DEFENSE STANDARD

MIL-STD-810	Environmental Test Methods and Engineering Guidelines

Comments, suggestions, or questions on this document should be addressed to Commander, Indian Head Division, Naval Surface Warfare Center, Technical Information Branch (Code 4230), 101 Strauss Avenue, Indian Head, Maryland 20640-5035, or emailed to amanda.penn@navy.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil/

AMSC N/A FSC 1377

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:44Z
Check the source to verify that this is the current version before use.

(Copies of these documents are available online at http://assist.daps.dla.mil/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

Drawings	
DL8596122	Delay Element, Cartridge, M14, Assembly
8826728	Ammunition, Container, Metal, M21 for Delay Element, M5 or M8
8826729	Box, Packing, Ammunition, for Delay Element, M5 or M8 in Metal Container M21
851AS110	Ignition Device PVU-1/A
Weapon Specification	
WS 21535	Ignition Devices, (Percussion), PVU-1/A

(Application for copies should be addressed to: Commander, Indian Head Division, Naval Surface Warfare Center, Attn: Technical Information Branch (Code 4230), Indian Head, MD 20640-5035.)

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM E1742	Standard Practice for Radiographic Examination

(Copies of this document are available online at http://www.astm.org/ or from the American Society for Testing and Materials Customer Service, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.)

AMERICAN NATIONAL STANDARD INSTITUTE/AMERICAN SOCIETY FOR QUALITY

ANSI/ASQ Z1.4	Sampling Procedures and Tables for Inspection by Attributes
ANSI/ASQ A8402	Quality Management and Quality Assurance - Vocabulary

(Copies of these documents are available online at http://webstore.ansi.org/ansidocstore/default.asp, or from the American Society for Quality, PO Box 3005, 611 E. Wisconsin Ave., Milwaukee, WI 53201-4606.)

2.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related specification sheets), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:44Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a first article sample shall be subjected to first article inspection (see 4.4, 6.2, and 6.3).

3.2 Conformance to documents. The M14 delay element covered by this specification shall be manufactured in accordance with DL8596122 and all documents listed thereon.

3.3 Materials. All materials used in the manufacture of the cartridges shall conform strictly to the specifications referred to on the respective drawings unless specific approval in writing covering a departure therefrom has been obtained from the cognizant Navy design activity prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

3.4 Components.

3.4.1 Primary components. For the purpose of this specification, the PVU-1/A Ignition Device, Delay Charge and the output material charge are considered primary components. Only primary components from a single lot shall be used in a production lot of cartridges; however, one primary component production lot may be used in more than one cartridge production lot (see 6.7).

3.4.1.1 Ignition device. The ignition device shall be furnished from lots manufactured within the preceding 24 months or recertified within the preceding 12 months. The ignition device shall be manufactured per Drawing 851AS110 and accepted per WS 21535. Prior to assembly into a delay element, the ignition device shall be visually examined in accordance with 4.6.5 and radiographically examined for defects as specified in 4.7.1.

3.4.2 Protective finish. The finish of each component part shall be in accordance with MIL-A-8625 and the applicable drawing (see 4.7.2).

3.5 Assembly.

3.5.1 Radiographic examination. Each delay element assembly shall be radiographically examined for defects (see 4.7.3).

3.5.2 Vibration. The assembled delay element shall withstand vibration as prescribed in MIL-STD-810, Method 514.3, Test Procedure I, Test Condition 1-3.2.5 without evidence of any disintegration of the ignition device, propellant, or igniter, or derangement of any component (see 4.7.4 and 6.2).

3.6 Functional requirements.

3.6.1 Delay element performance.

3.6.1.1 Misfires. The ignition delay element shall not fail to fire.

3.6.1.2 Ballistics. The ignition delay charge shall consist of barium chromate, as specified in MIL-B-550, and boron, as specified in MIL-B-51092, in the proportion and quantity fixed by the contractor to produce the ignition delay times required in table I (see 6.6.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:44Z
Check the source to verify that this is the current version before use.

TABLE I. *Ballistic requirements.*

Temperature (°F)	Ignition delay time (sec)
–60 to –70 65 to 75 195 to 205	0.350 ± 100 0.300 ± 0.50 0.250 ± 100

3.7 Workmanship. Delay elements shall be free of cracks, splits, or other defects which might prevent proper mating with connecting parts or proper functioning of the device.

3.7.1 Metal defects. All components shall be free from cracks, splits, cold shuts, inclusions, porosity, or any similar defect.

3.7.2 Burr. No part shall have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.7.3 Foreign matter. No part or assembly shall contain chips, dirt, grease, rust, corrosion, or other foreign matter.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4)
b. Quality conformance inspection (see 4.5)

4.2 Quality assurance terms and definitions. Reference shall be made to ANSI/ASQ A8402 to define the quality assurance terms used.

4.3 Inspections. Inspections shall be in accordance with MIL-A-2550 and ASTM E 1742.

4.3.1 Inspection conditions. Unless otherwise specified in the contract or purchase order (see 6.2), inspection conditions shall be as follows:

a. Temperature: Room ambient 20 to 25 °C (68 to 77 °F)
b. Altitude: Sea level
c. Humidity: 50 percent relative, maximum
d. Atmospheric: 14.7 psia

4.4 First article inspection. At the beginning of regular production, the supplier shall submit a first article sample to a Government approved facility for evaluation. The sample shall consist of 23 delay bodies, 23 ignition device retainers to be tested as indicated in table II, and 10 sets of unassembled components (including explosive components) for visual and dimensional examination. The first article sample shall be manufactured using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be the same as used for regular production and shall be obtained from the same source of supply. When it becomes necessary

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:44Z
Check the source to verify that this is the current version before use.

to make a change in either the ignition device, propellant, or igniter lot after initial production, 12 assembled delay elements from the first production lot thereafter shall be tested in accordance with 4.7.5. The Government reserves the right to require new first article samples until such time as an acceptable sample is submitted (see 6.3).

TABLE II. *First article inspection.*

Paragraph		Test	Sample Size	Type of test	
Requirement	Test			Destructive	Nondestructive
3.4.2	4.7.2	Protective finish	23 Delay bodies	X	—
			23 Ignition device retainers	X	—
3.5.2	4.7.4	Vibration	12 Fr. Ballistics sample	—	X
3.6	4.7.5	Function tests	30	X	—

4.4.1 Examination, tests, and facility. After provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a Government laboratory or other such facility specified in the contract (see 6.2).

4.4.2 Temperature conditioning for ballistic test. The sample shall be temperature conditioned and tested to determine compliance with 3.6.1.2. The sample for firing shall be conditioned to table III.

TABLE III. *Temperature conditioning.*

Temperature (°F)	Not vibrated	Vibrated
–60 to –70	6	4
65 to 75	6	4
195 to 205	6	4

4.4.3 First article failure. Failure of the sample to comply with the requirements of the drawings and specifications shall result in first article sample disapproval.

4.5 Quality conformance inspection.

4.5.1 Lot.

4.5.1.1 Submission of product. The product shall be submitted in accordance with ANSI/ASQ Z1.4.

4.5.1.2 Lot size. Unless otherwise specified (see 6.2), the production lot size shall be not more than 600.

4.5.2 Examination and tests. The quality conformance sample shall be subjected to the examinations of 4.6 and all the test procedures of 4.7 except for 4.7.4.

4.6 Examination. All delay elements and components shall be examined visually and radiographically and characteristics defined in accordance with the applicable drawings. One hundred percent examination shall be performed for all critical defects. Examination for major or minor defects shall be performed on a

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:44Z
Check the source to verify that this is the current version before use.

defect basis in accordance with the classification of defects. Four power (4×) magnification may be used in performing visual examination for such defects as burrs and foreign matter. When compliance is in doubt as a result of visual inspection, the characteristic shall be measured or gaged to determine acceptability. All nonconforming items shall be rejected.

4.6.1 Delay Element, M14, Assembly Drawing 8596122.

Characteristic	Defect	Method of Inspection
Critical		
1	Any part missing	X-ray/Visual
2	Improper assembly	X-ray/Visual
3	Ignition device not properly seated	X-ray/Visual
4	Mixed ammunition	Visual
5	Flash hole missing	Visual
6	Ignition device uncrimped or seal missing	Visual
7	Marking missing incorrect or illegible	Visual
8	Delay charge not visible through flash hole	Visual
Major		
101	Concentricity of head with body	Gage
102	Diameter of body, max	Gage
103	Metal defective	Visual
104	Protective finish inadequate or defective	Visual
105	Burr	Visual
106	Foreign matter present	Visual
Minor		
201	Total length, max	Gage
202	Laquer missing or inadequate	Visual

4.6.2 Body Delay, Drawing 8594081, covering a detail of Drawing 8596122.

Characteristic	Defect	Method of Inspection
Critical		
1	Flash hole missing or obstructed	Visual
2	Metal defective	Visual
Major		
101	Pitch diameter, external thread, min	Gage
102	Major diameter, external thread, min	Gage
103	Concentricity of body with pitch diameter of thread	Gage
104	Diameter of cavity, max	Gage
105	Diameter of head, min	Gage
106	Diameter of flash hole	Gage
107	Diameter of thread relief	Gage
108	Length from cavity face to shoulder of head diameter	Gage
109	Protective finish inadequate or defective	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:44Z
Check the source to verify that this is the current version before use.

110	Thread damaged or not full	Visual
111	Burr	Visual
112	Foreign matter present	Visual
Minor		
201	Pitch diameter of external thread, max	Gage
202	Diameter of wrench hole	Gage
203	Diameter of thread pilot	Gage
204	Diameter of cavity, min	Gage
205	Diameter of head, max	Gage
206	Diameter of step rear of head	Gage
207	Depth of wrench hole	Gage
208	Depth to base of cavity	Gage
209	Total length	Gage
210	Length of step rear of head	Gage
211	Length of thread pilot	Gage
212	Width of thread relief	Gage
213	Location of wrench hole	Gage
214	Radius or chamfer missing or incorrect	Visual
215	Surface finish improper	Visual

4.6.3 Gasket, Aluminum, Drawing 8594082, covering a detail of Drawing 8596122.

Characteristic	Defect	Method of Inspection
Critical		
None defined		
Major		
101	Diameter, outside, min	Gage
102	Diameter, inside, max	Gage
103	Metal defective	Visual
104	Burr	Visual
105	Foreign matter present	Visual
Minor		
201	Diameter, outside, max	Gage
202	Diameter, inside, min	Gage
203	Thickness	Gage
204	Surface finish improper	Visual

4.6.4 Ignition device, Retainer, Drawing 8594083, covering a detail of Drawing 8596122.

Characteristic	Defect	Method of Inspection
Critical		
1	Flash hole missing or obstructed	Visual
2	Depth of ignition device pocket	Gage
3	Metal defective	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:44Z
Check the source to verify that this is the current version before use.

Major		
101	Pitch diameter of internal thread, max	Gage
102	Minor diameter of internal thread, max	Gage
103	Concentricity of head with body	Gage
104	Concentricity of pitch diameter of thread with body	Gage
105	Concentricity of ignition device pocket with body	Gage
106	Concentricity of recess around ignition device pocket with ignition device pocket	Gage
107	Diameter of body, min	Gage
108	Diameter of head	Gage
109	Diameter of ignition device pocket	Gage
110	Diameter at base of angled recess	Gage
111	Diameter of recess around ignition device pocket	Gage
112	Depth of cavity	Gage
113	Depth of recess around ignition device pocket	Gage
114	Depth of chamfer at ignition device pocket	Gage
115	Length of effective thread, min	Gage
116	Location of datum diameter	Gage
117	Thread damaged or not full	Visual
118	Diameter of flash hole	Gage
119	Symmetry of flat with body	Gage
120	Protective finish inadequate or defective	Visual
121	Surface finish of ignition device pocket improper	Visual
122	Burr	Visual
123	Foreign matter present	Visual
Minor		
201	Pitch diameter of internal thread, min	Gage
202	Diameter of body, max	Gage
203	Total length	Gage
204	Length of wrench flats	Gage
205	Width across wrench flats	Gage
206	Location of wrench flats	Gage
207	Radius or chamfer missing or incorrect	Visual
208	Surface finish improper, except as otherwise classified	Visual

4.6.5 Ignition Device (Percussion), PVU-1/A, Drawing 851AS110, covering a detail of Drawing 8596122.

Characteristic	Defect	Method of Inspection
Critical		
1	Mixed ignition device	Visual
2	Styphnate composition broken, cracked, or dislodged	Visual
3	Ignition device foil discolored	Visual
4	Metal defective	Visual
Major		

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:44Z
Check the source to verify that this is the current version before use.

101	Burr	Visual
102	Foreign matter present	Visual

Minor
None defined

4.6.6 Ammunition Container, Metal M21 for Delay Element M5 or M8, Drawing 8826728

Characteristic	Defect	Method of Inspection
Critical		
None defined		
Major		
None defined		
Minor		
201	Contents loose	Manual/Visual
202	Separator or filler missing	Visual
203	Sealing inadequate, incompetent, or incorrect	Visual
204	Container cut or damaged	Visual
205	Marking missing, incorrect, or illegible	Visual

4.6.7 Box, Packing Ammunition for Delay Element M5 or M8 in Metal Container, M21, Drawing 8826729.

Characteristic	Defect	Method of Inspection
Critical		
None defined		
Major		
None defined		
Minor		
201	Contents loose	Manual/Visual
202	Hardware missing, loose, broken, or improperly engaged	Visual
203	Strapping missing, loose, broken, or improperly assembled	Visual
204	Contents of box exposed	Visual
205	Box damaged	Visual
206	Marking missing, incorrect, or illegible	Visual
207	Number of cartons incorrect	Visual

4.7 Test methods and procedures.

4.7.1 Ignition device x-ray. Prior to assembly into the cartridge, the ignition device shall be radiographically examined in accordance with ASTM E1792. Each ignition device shall be x-rayed on boards or trays with the cup side perpendicular to the rays. The x-ray negatives shall be identified by item nomenclature and by lot number. Ignition devices are to be left mounted to the boards or trays until after

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:44Z
Check the source to verify that this is the current version before use.

the x-rays have been reviewed and defects identified to facilitate removal of defective units. After screening, the x-ray negatives with defectives identified, shall be forwarded to the engineering activity designated by the acquiring activity (see 6.2). Interpretation of the radiographic films shall verify the following: missing or abnormally thin charge; charge broken, cracked or porous; cracked or off-center anvil or other misplaced or deformed inert parts; anvil abnormally close to the ignition device cup dome; and all other observable defects in assembly.

4.7.2 Protective finish. Unless otherwise specified (see 6.2), sampling plans and procedures in the determination of acceptability of coated parts submitted by the contractor shall be in accordance with the contract and MIL-A-8625. The anodized part shall be sectioned longitudinally to better expose the critical surfaces to salt spray test.

4.7.3 Delay element x-ray. Prior to assembly into a cartridge, the delay element shall be radiographically examined in accordance with ASTM E1742. Each delay element shall be x-rayed with the sides of the delay element perpendicular to the rays. The x-ray negatives shall be identified by item nomenclature and by lot number. Delay elements are to be left mounted to the boards or trays until after the x-rays have been reviewed and defects identified to facilitate removal of defective units. After screening, the x-ray negatives with defectives identified, shall be forwarded to the engineering activity designated by the acquiring activity.

4.7.4 Vibration test. Twelve of the 30 assembled delay elements of the first article sample, x-rayed as directed in 4.7.4, properly identified, shall be subjected to vibration. The method and procedures for performing the vibration test shall be in accordance with MIL-STD-810 Method 514.3, Test Procedure I, Test Condition 1-3.2.5 (see 6.2). Then the 12 vibrated delay elements shall be x-rayed again. Evidence of any disintegration of the ignition device, propellant, or derangement of any component shall be cause for rejection of the sample. When there is a change in the method of charging the delay element or in the lot of ignition devices, twelve additional delay elements shall be selected and tested as indicated herein.

4.7.5 Functional. The following tests shall be performed by the Government.

4.7.5.1 Ballistics

4.7.5.1.1 First article. Thirty assembled delay elements of the first article sample shall be grouped and temperature conditioned as described in table III and 4.8. Following removal from the conditioning chamber, the delay element shall be tested as required by 3.6.1.2. Failure of delay element to comply with 3.6.1.2 shall be cause for sample rejection.

4.7.5.1.2 Production lot acceptance. Thirty assembled delay elements from each production lot shall be grouped and temperature conditioned in accordance with 3.6.1.2. Failure of a delay element to comply with 3.6.1.2 shall be cause for rejection of the lot. In addition to the sample of delay elements for the above test, 10 additional delay elements shall be furnished from each production lot for investigative purposes.

4.7.5.2 Retest. There shall be no retests.

4.7.5.2.1 Test failure. If a test failure is attributable to an assignable cause, excluding the test cartridge, the original test results shall be discarded and that test reconducted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:44Z
Check the source to verify that this is the current version before use.

4.8 Temperature conditioning. The conditioning chamber shall be preconditioned to the specified temperature. Once the temperature inside the chamber has stabilized, the samples shall be placed inside and maintained at the specified temperature for 4 hours minimum, 24 hours maximum.

4.8.1 Reconditioning. The sample must be tested within five minutes after removal from the conditioning chamber. If this time is exceeded, the cartridge shall be reconditioned in accordance with 4.8.

4.9 Inspection of packaging. The sampling and inspection of the preservation, packing, and container marking shall be in accordance with the requirements of section 5.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Intended use. The assembly is used in cartridge actuated devices for Aircrew Emergency Escape Systems. Since the delay element was developed specifically for use in military aircraft, there is no commercial application.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and revision letter of this specification
b. Issue of DODISS to be cited in the solicitation and, if required, the specific issue of individual documents referenced and that MIL-STD-810D shall be used (see 2.1, 3.5.2, and 4.7.4)
c. Whether a first article sample is required (see 3.1, 4.4, and 6.3)
d. Test facility for first article tests (see 4.4.1)
e. Production test activity and lot size (see 4.1 and 4.5.1.2)
f. Any special test conditions (see 4.3)
g. Directions for shipping radiographs of ignition devices and of entire lot of delay element assemblies (see 4.7.1 and 4.7.3)
h. Directions for sampling for protective finish tests (see 4.7.2)
i. Level of preservation and packing (see 5.1 and 6.4)
j. That the safety precaution requirements of the "Contractor's Safety Manual for Ammunition, Explosives, and Related Dangerous Material," DOD 4145.26M are applicable. NOTE: When this specification is used as part of the description of work to be accomplished by a Government activity, the safety precaution requirements of "Ammunition and Explosives

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:44Z
Check the source to verify that this is the current version before use.

Ashore," OP 5 are applicable.

6.3 First article. When a first article inspection is required, the contracting officer should provide specific guidance to offerors whether the items should be a first article sample or a sample selected from the first production items (see 3.1), and the number of items to be tested as specified in 4.4. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for examination, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product *which* has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 Packing and Marking. Packing and marking should be in accordance with Drawings 8826728 and 8826729, except that the marking should refer to Delay Element, cartridge, M14 Assembly.

6.5 Hazard notice. The cartridge described herein and certain of its components are flammable or explosive and present hazards in manufacture, handling, storage, and shipment. The contractor should recognize these properties and take appropriate measures to guard and protect against fire, explosion, adverse environment, corrosive atmosphere, rough handling, and electrically induced incidents.

6.6 Definition.

6.6.1 Ignition delay time. Ignition delay time is defined as the time from ignition device impact to the start of pressure rise.

6.7 Manufacture as a component. When the delay element is being manufactured in conjunction with a delay cartridge as a component thereof, the first article requirements for ballistic, vibration, x-ray, and packaging requirements are waived, and the requirements of the cartridge specification shall apply.

6.8 Subject term (keyword) listing.

Ejection systems, aircrew
Emergency escape systems, aircrew
Escape systems, aircrew
Life-saving systems, aircrew

6.9 Changes from previous issue. Marginal notations are not used to identify changes with respect to the previous issue because of the extensiveness of the changes. This revision was authorized by ECP number 045220I037.

Custodian:
Navy-OS
Air Force-99

Preparing activity
Navy-OS
(Project 1377-2005-012)

Review activity:
Air-Force 70

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:44Z
Check the source to verify that this is the current version before use.

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:44Z
Check the source to verify that this is the current version before use.