INCH-POUNDS

MIL-F-70435(AR)
AMENDMENT 6
18 SEPTEMBER 1989
SUPERSEDING
AMENDMENT 5
28 February 1989

MILITARY SPECIFICATION

FUZE, POINT DETONATING, M759

This Amendment forms a part of Military Specification MIL-F-70435(AR), dated 15 July 1983, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

3.2.2.4 Delete in its entirety and substitute the following:

"3.2.2.4 Transportation vibration/temperature. After undergoing vibration at temperatures from -540 to 71°F, in accordance with MIL-STD-331, Test 119, the fuze shall be safe to handle and meet the arming, non-arming and target reliability requirements (see 4.5.2.4).

PAGE 5

Table I, Jumble, Delete: "4.2.2" and substitute "4.5.2.2".

PAGE 8

Table I, Delete: "3.3.1" and substitute "4.3.1".

* Table I, Add : "Plug, base closing 32 4.3.1 4.2.2.1"
(DEW. 12551752)
Examination for defects

"Base 32 4.3.1 4.2.2.1"
(Dwg. 12551751)
Examination for defects

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

"Spitback lead assembly 32 4.3.1 Visual"
(Dwg. 11834335)
Examination for defects

PAGE 9

Holder and Body Assembly: Delete: "(Dwg. 11834315)" and substitute "(Dwg. 11834318)".

TABLE 1. Delete: "3.3.1" and substitute '3.1.1".

PAGE 11

4.4.2.1 Major 102, 103 and 104, Delete: "3.3.1" and substitute "3.1.1".

Minor 201, Delete: "3.3.1" and substitute "3.1.1".

* 4.4.2.1 Delete in its entirety and substitute the following:

"4.4.2.1 Plug, base, closing 1 of 1 Dwg No. 12551752
Next higher Assembly 12551750

CRITICAL:	None defined	4.4.2		
MAJOR:				
101.	Large inside dia. max.	.40%	3.1.1	Gage
102.	Pitch, dia.	.40%	3.1.1	Gage
103.	Depth, large inside dia. min.	.40%	3.1.1	Gage
104.	Overall thickness minus rear flange	.40%	3.1.1	Gage
105.	Height, rear flange, max.	.40%	3.1.1	Gage
106.	Web thickness, min.	.40%	3.1.1	Gage
MINOR:				
201.	D.D. fully threaded	.65%	3.1.1	Visual/ Gage
202.	Dia., rear flange, min.	.65%	3.1.1	Gage
203.	Small inside dia., min.	.65%	3.1.1	Gage
204.	Chamfer 3 places	1.00%	3.1.1	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

PAGE 12

4.4.2.2, Major 101 AND 102, Delete: “3.3.1” and substitute "3.1.1”.

PAGE 13

4.4.2.3 Drawing number: Delete: “11820627” and substitute “9358016”.

Major 101 and 102, Delete: "3.3.1" and substitute "3.1.1".

Minor 201, Delete: “3.3.1” and substitute “3.1.1”.

PAGE 14 and 15

4.4.2.4, Major 102, Delete: "hold and body” and substitute “holder and body”.

Major 101 thru 112, Delete: “3.3.1” and substitute "3.1.1".

Minor 201 thru 205, Delete: "3.3.1" and substitute "3.1.1".

PAGE 16

4.4.2.5, Major 101, Delete: “3.3.1” and substitute "3.1.1”.

PAGE 17

4.4.2.6, Major 101 thru 106, Delete: “3.3.1” and substitute "3.1.1".

Minor 201 thru 202, Delete: “3.3.1” and substitute "3.1.1".

PAGE 18

4.4.2.7, Major 101 thru 107, Delete: “3.3.1” and substitute "3.1.1”.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

Minor 201 thru 202, Delete: “3.3.1” and substitute "3.1.1”.

PAGE 19

4.4.2.8, Minor 201, Delete: “presence or roller weight” and substitute "presence of ball weight”.

Major 101, Delete: “3.3.1” and substitute “3.1.1”.

Minor 201, Delete: “3.3.1” and substitute “3.1.1”.

PAGE 20

4.4.2.9, Major 101 thru 103, Delete: “3.3.1” and substitute “3.1.1”.

Minor 201, Delete: “3.3.1” and substitute "3.1.1”.

* 4.4.2.9A Should read as follows:

"4.4.2.9A Base 1 of 1 Dwg No. 12551751
Next higher No. 12551750

CRITICAL:	**None defined**	**4.4.2**		
MAJOR:				
101.	Dia, fornt flange, max.	.40%	3.1.1	Gage
102.	Overall thickness minus front flange, max.	.40%	3.1.1	Gage
103.	Pitch dia.	.40%	3.1.1	Gage
104.	Depth, large dia, min.	.40%	3.1.1	Gage
105.	Dia, large inside, min.	.40%	3.1.1	Gage
MINOR:				
201.	Dia., inside, min.	.65%	3.1.1	Gage
202.	D.D. fully threaded	.65%	3.1.1	Gage
203.	Chamfer 3 places	1.00%	3.1.1	Visual

PAGE 21 and 22

4.4.2.10, Critical 1, Delete “3.3.1” and substitute “3.1.1”.

Add Critical 2 and 3 as follows:

"2. Height *of* spitback assembly retaining crimp (min)/Note 4/100%/3.1.1/Auto/Gage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

3. Inside diameter of spitback assembly retaining crimp (max)/Note 7/100%/3.1.1/Auto/Gage".

Delete "Majors 101 and 102" in their entirety.

In catergory column, Changes Majors respectively:

From: Major 103, 104, 105, . . ., 119.
To: Major 101, 102, 103, . . ., 117.

Major 101 thru 107, Delete: "3.3.1" and substitute "3.1.1".

Major 107, Delete: "Form" and substitute "At".

Minor 201, Delete: "3.3.3" and substitute "3.4".

Next Higher Assembly, Delete: "11835825" and substitute "11825955".

* 4.4.2.10 Delete major 101. and 102.

Add Note 3/ as follows:

"3/ TV-T sample used in subsequent ballistics test and waterproofness test".

4.4.2.10 NOTES 1 and 2 should read:

"1. If assemblies are assembled on a qualified assembly machine, this check is performed 100% by the machine and the defects are automatically removed. If the machine fails verification, the assemblies are 100% x-ray checked with the critical defects manually removed and the lot then submitted for inspection verification of the x-ray sort.

2. If assemblies are hand built, the assemblies are 100% x-ray checked with the critical defects manually removed or are 100% inspected by an approved blast proof gage that will destroy the rotor assembly if it is in the unsafe position. The lot is then submitted for x-ray verification of the inspection. Sample size determined by .25 AQL (minimum sample size is 315) zero defects allowed. If the lot is rejected the assemblies will be 100% x-ray checked with the critical defects manually removed and the lot submitted for inspection verification of the x-ray sort."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

PAGE 24

Table II

Delete all “Vi and Vt" and substitute "Ri and Rt" wherever it appears.

Add footnote “6” to Target Reliability.

Add footnote “7” to Extended Range and Armor Plate.

Note 2: Delete “(N N)“ and substitute “divided”.

Delete "devided" and substitute “divided”.

In second sentence: Delete: “A” and substitute “at”.

PAGE 27

4.6: Delete: "Constant twist” and substitute “gain or progressive twist”.

Change the second statement from: Delete “Drawing 282000380” and substitute ‘28201629 or Government 11825969”; to: Delete “Drawing 282000380” and substitute “20201629 or Government 9390748”.

4.6.2: Delete: “15.0 ± .5 meters” and substitute “150 ± 1.0".

4.6.3: Delete: “.60 inch (16 gage)” and substitute “.060”.

4.6.5: Delete: "HEPD" and substitute "HEDP".

PAGE 28

6.2.8: Delete: "Profidions" and substitute "Provisions”.

PAGE 29

6.3.7: Delete: "firinf" and substitute “firing”.

6.3.8 Add new paragraph as follows:

“6.3.8 Defective test ammunition. If any fuze firing defect is found to have been caused by a defective cartridge and verified by the Government, the firing defect shall be considered a no-test. In such cases the test shall be repeated in whole or in part, as indicated."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity
Army-AR

(Project 1305-AD12)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.