INCH-POUND

MIL-P-70675 (AR)
AMENDMENT 1
26 July 1991

MILITARY SPECIFICATION

POWER SUPPLY ASSEMBLY, FOR MINES
M718A1/M741A1, SYSTEM

This Amendment forms a part of Military Specification MIL-P-70675(AR), dated 23 July 1988, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

3.3.1: Delete in it entirety and substitute the following paragraph:

"3.3.1 Non-activation voltage. Each battery cell shall be unactivated and measured as follows:

a. Maximum 40% Relative Humidity shall be no more than 5 millivolts.

b. Greater than 40% Relative Humidity shall be no more than 200 millivolts."

PAGE 7

4.4.2.1 Power supply molding:

Major 102: Delete "I.D. of bottom post (max)" and substitute "O.D. of bottom post (max)".

Major 111: Delete "Length of bottom post" and substitute "Distance from top of bridge to bottom of posts.

PAGE 8

4.4.2.1, Minor 207: Delete in its entirety.

Custodian:
Army-AR

Preparing activity
Army-AR

(Project 1345-A582)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.