MILITARY SPECIFICATION SHEET

VISOR ASSEMBLY, AVIATOR'S, SEVEN WAVELENGTH LASER PROTECTIVE, EEU-8/P

This specification is approved by the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation:
MIL-V-29591(AS)

REQUIREMENTS:

QUALIFICATION: Required.

USE: The visor assembly shall be used as a component of the HGU-68/P helmet assembly worn by fixed wing aircraft crew members.

DIMENSIONS

The visor assembly dimensions shall be as specified in Naval Air Systems Command Dwg. 3316AS100.

WINDBLAST RESISTANCE TEST

REQUIREMENT: When tested as specified below, the visor assembly shall provide facial and eye protection during windblast. The visor assembly shall not rise or loosen. The helmet and visor assembly shall not show evidence of material failure. The complete helmet assembly and oxygen mask retention system shall prevent helmet rotation greater than ± 5° and shall prevent helmet loss.

AMSC N/A FSC 8475
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:24Z
Check the source to verify that this is the current version before use.

TESTING: The helmet shell and liner assembly shall be custom fit and mounted on the windblast headform with the visor in the down and locked position. The lower edge of the visor lens shall follow the contour of the oxygen mask to provide eye protection during windblast. The helmet/visor assembly shall be exposed to windblast velocities of 600 ± 60 KEAS at each of the following attitudes in the order listed:

a. Head on/head up

b. Rotated 45° starboard/head up

c. Head on/tilted 45° aft

d. Rotated 45° port/tilted 45° aft

The time of exposure to the maximum range shall be 300 ± 50 ms, and the rise time to reach peak velocity shall be 125 ± 20 ms. The total windblast duration shall be at least 3.0 seconds. The helmet assembly and visor assembly shall pass the requirements given above.

Preparing Activity:
NAVY - AS
Project No. 8475-N228-01

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T00:24Z
Check the source to verify that this is the current version before use.