MIL-L-850D
18 February 1964
SUPERSEDING
MIL-L-00850C (SHIPS)
10 December 1962
MIL-L-850B
21 May 1957

MILITARY SPECIFICATION

LIFE PRESERVER, YOKE TYPE (FIBROUS GLASS) WITH REPLACEMENT TYPE COVER

This specification has been approved by the Department of Defense and is mandatory for use by the Departments of the Army, the Navy, and the Air Force.

1. SCOPE

1.1 This specification covers one type of life preserver with buoyant fibrous glass pads.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

L-P-375 - Plastic Film, Flexible, Vinyl Chloride.
V-F-106 - Fasteners, Slide, Interlocking.
V-T-276 - Thread, Cotton.
CCC-C-426 - Cloth, Cotton Drill.
CCC-T-191 - Textile Test Methods.

MILITARY

MIL-C-299 - Cloth, Cotton, Print.
MIL-P-699 - Paint, Deck, Gray, Outside.
MIL-W-530 - Webbing, Textile, Cotton, General Purpose, Natural or in Colors.
MIL-B-2766 - Batt, Fibrous Glass Lifesaving Equipment.
MIL-P-3454 - Packaging and Packing of Life Preservers.
MIL-G-16491 - Grommet, Metallic.

STANDARD

FEDERAL

FED-STD-751 - Stitches, Seams, and Stitchings.

DRAWINGS

FSC 4220

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:35Z
Check the source to verify that this is the current version before use.

BUREAU OF SHIPS
S3306-969942 - Yoke Type Life Preserver, Assembly.
S3306-969943 - Yoke Type Life Preserver, Collar and Details.
S3306-969944 - Yoke Type Life Preserver, Outer Cover Details (Inside and Outside Section).
S3306-969945 - Yoke Type Life Preserver, Insert Patterns.
S3306-969946 - Yoke Type Life Preserver, Insert Cover Patterns.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Preproduction sample. - Before production is started, preproduction samples as specified in 4.2 shall be submitted for testing as specified in 4.7 to determine conformance with this specification.

3.2 Material. -

3.2.1 Drill. - Drill shall conform to type I, class 3 of CCC-C-426. The color shall be deck-gray, formula No. 20, type I of MIL-P-699 (see 6.2). The drill shall be vat dyed and shall show good fastness to light, salt water, laundering and crocking.

3.2.2 Vinyl film. - The vinyl film shall be 0.0080 ± 0.0008 inch thick and shall conform to type II, class I of L-P-375.

3.2.3 Fibrous glass. - The fibrous glass shall conform to MIL-B-2766.

3.2.4 Print cloth. - The print cloth shall conform to type I, class 1 of MIL-C-299.

3.2.5 Webbing. - Webbing shall be 1-inch wide, equal in color and colorfastness to the cotton drill, and shall conform to type IIb of MIL-W-530.

3.2.6 Tie tape and reinforcing tape. - The preserver tie tape and reinforcing tape shall be made from 1 1/8-inch cotton tape. The tape shall weigh not less than 0.18 ounce per linear yard and have a minimum breaking strength of 180 pounds. The color shall reasonably match that of the drill and shall show fair fastness to light, salt water, and crocking.

3.2.7 Metal hardware. - Metal hardware shall be made from brass or corrosion-resisting steel and shall have a dull black "Military" finish. The spring of the collar and waist strap snap fasteners shall be made of phosphor bronze. Grommets shall conform to type III, class 3, size 1 of MIL-G-16491.

3.2.8 Slide fasteners. - Slide fasteners shall be nylong on nylon tape and conform to V-F-106 and shall be of type I, style 2, size LM, class A except that the tape width shall be 9/16 plus or minus 1/32 inches. The length of the slide fasteners shall be 16 inches for the collar section and 10 inches for each of the body sections. All metal pieces shall be enameled and shall have perforated pull tabs. Color of the tape shall acceptably match the color of the cotton drill specified.

3.3 Design. - The life preserver shall consist essentially of an outside cover, a collar, harness strap, metal hardware, fibrous glass pads and pad covers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:35Z
Check the source to verify that this is the current version before use.

3.3.1 Outer preserver cover. - The outer preserver cover shall be made from cotton drill (see 3.2.1).

3.3.2 Collar. - The collar shall be made from cotton drill (see 3.2.1).

3.3.3 Harness strap. - The harness strap shall be made of 1-inch cotton webbing (see 3.2.5) in accordance with the applicable drawings.

3.3.4 Fibrous glass pads. - There shall be four front pads (one upper and one lower pad each side of front) and one collar (or back) pad. The fibrous glass (see 3.2.3) shall be covered with print cloth (see 3.2.4).

3.3.5 Vinyl film envelope. - All pads shall be enclosed in a vinyl film envelope (see 3.2.2). Finished envelopes shall show no evidence of leakage when tested as specified in 4.7.2. Envelopes shall show an adhesion of not less than 8 pounds when tested as specified in 4.7.3.

3.3.6 Tape. - The preserver tie tapes and reinforcing tape shall be of the width and length shown on the applicable drawings (see 3.2.6).

3.3.7 Metal hardware. - Metal hardware shall be in accordance with applicable drawings (see 3.2.7).

3.3.8 Tag. - A tag of bleached print cloth, conforming to type III, class 1 of MIL-C-299, 2 1/2 by 3 1/2 inches, shall be sewed on the underside of the preserver as shown on the applicable drawing. The printing on the tag shall be in waterproof black ink.

3.4 Construction. - Fibrous glass life preservers shall conform to S3306-969942, S3306-969943, S3306-969944, S3306-969945 and S3306-969946.

3.5 Distribution of buoyant medium. - The fibrous glass shall be distributed as shown in table I.

Table I - Distribution of fibrous glass.

	Ounces
Collar pad	22 ± 1/4
Upper front pad	11 ± 1/4
Lower front pad	11 ± 1/4
Total Amount in preservers	66 ± 1 1/4

3.5.1 Buoyancy. - The completed pads including the sealed waterproof envelopes shall have the buoyancies specified in table II when tested as specified in 4.7.7.

Table II - Buoyancy of completed pads.

	Pounds
Collar pad	15.0 ± 0.5
Upper front pad	8.0 ± 0.5
Lower front pad	8.0 ± 0.5

Source: https://assist.dla.mil -- Downloaded: 202610-16T11:35Z
Check the source to verify that this is the current version before use.

3.6 Stitching. - All stitching shall be type 301 of FED-STD-751. Stitching of the cotton drill cover shall be done with type IB3, No. 20, 4-ply cotton thread equal in color to the cotton drill and conforming in physical characteristics and color fastness to V-T-276. Seaming of the print cloth pad covers shall be done with type IA1 or IA2, unbleached or white, No. 50, 3-ply cotton thread. Stitching in webbing and tapes and in webbing and tape attachments to drill shall be done with type IB3, No. 16, 4-ply cotton thread equal in color to the cotton drill and conforming in physical characteristics and color fastness to V-T-276.

3.7 Assembly. - The preservers shall be assembled in accordance with the following directions, with numbers and letters corresponding to numbers and letters shown on the drawing:

(l) Pattern description. - The preserver is fabricated from the pattern pieces listed below. S3306-969944 shows, full size, the pieces necessary for the inside and ouside sections of the front body outer covers. The outer collar sections, quick-release placket and hardware are shown on S3306-969943. Full sized patterns for the print cloth inserts are detailed on S3306-969945. Full sized patterns for the vinyl film insert covers are presented on S3306-969946. Since the preserver is essentially bilaterally symmetrical in form, some of the singularly presented patterns represent the left as well as the right of the preserver. In these cases the piece is cut and then turned to the reverse side to form a mirror image. This provides, in the outer cover of the preserver, a means of obtaining the opposite pattern pieces from the original and insures that all fabric parts are cut with the same surface weaves exposed. In the patterns representing the pad inserts, the collar insert is made from three pieces; the upper front insert and the lower front insert are made from one piece, respectively. The insert covers of vinyl sheeting require one pattern only for each respective pad cover.

S3306-969944:

(1) Outside preserver section, OP, used for right and left pieces.
(2) Inside preserver section, IP, used for right and left pieces.
(3) Preserver gusset, PG, used for right and left pieces.
(4) Reinforcing section RS-1, used for right and left pieces.
(5) Reinforcing section RS-2, used for right and left pieces.
(6) Manufacturer's tag, one piece.

S3306-969943:

(1) Outside collar section, OC, used for right and left pieces.
(2) Inside collar section, IC, one piece.
(3) Collar gusset, CG, one piece.
(4) Release placket, RP-1, one piece for left side only.
(5) Dot-type fastener consisting of socket, plate, post stud and stud plate, four sets.
(6) "Dee" ring, four required.
(7) Reinforcing patches, RS-4, 4 pieces for inside and outside collar section.
(8) Slider fly, SF-1, 1 piece, used on collar.
(9) Slider fly, SF-2, 2 pieces, used on right and left preserver sections.
(10) Slider protection patch, RS-3, 3 pieces, used on collar, right and left preserver sections.

S3306-969945:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:35Z
Check the source to verify that this is the current version before use.

(1) Insert collar gusset, section ICG, one piece.
(2) Insert inside collar section, section IIC, one piece.
(3) Insert outside collar section, section IOC, one piece
(4) Insert upper front pad, section IUF, four pieces.
(5) Insert lower front pad, section ILF, four pieces.

S3306-969946:

(1) Collar insert cover, section CIC, two pieces.
(2) Upper front insert cover, section UFIC, four pieces.
(3) Lower front insert cover, section LFIC, four pieces.

(II) Assembly directions. -

(II) a. Outside preserver cover. -

(1) On the reverse side of each OP left and right piece, separately attach the corresponding RS-1 reinforcing strip between the points indicated by (P).
(2) On the reverse side of each OP left and right piece, separately attach the corresponding RS-2 reinforcing strip between the points indicated by (P-1).
(3) On pattern section OP, with the right face of the cloth up, form top and bottom gussets by folding point (P-2) on point P-3, with the right faces of the cloth together, and sew to point (P-4).
(4) On pattern section OP, left side only, with the right face of the cloth up, attach the assembled (see release placket RP-1 subassembly directions) release placket RP-1, between the points indicated by (P-5).
(5) Take a 12-inch piece of 1-1/8 inch-tape on the right face of each side of the OP section over the RS-2 reinforcing strip at the points (P-11) as indicated. These ties provide a means of fastening the preserver at the front of the collar.
(6) On the right face of the cloth of the IP section used for the left side of the preserver, attach the manufacturer's tag between the points indicated by (P).
(7) With the right faces together, join the inside and outside preserver section by stitching along the hem line from (P-6) to (P-8).
(8) Continue joining the inside and outside preserver sections by stitching from (P-9) to (P-10) on the right body side and from (P-9) to (P-7) on the left body side.
(9) Each slider fly section SF-2 shall be turned under 1/4 inch at each end and hemmed. The fly section shall be folded lengthwise, with the turned under ends facing, so that the long edges coincide, and shall be stitched to a 10 inch slide fastener with the long ends running concurrently with one edge of the slide fastener tape. Stitch each slide fastener-fly section assembly into a preserver body section by turning under the raw edges and stitching from (P-3) to (P-9),
(10) The slider protection patches, RS-3 shall be turned under 1/4 inch on 3 sides, excluding the selvage, and hemmed. Place the patches over the open end of the slide fasteners, stitching along the line (S-2) on both the inside and outside preserver sections, leaving the selvage edge toward the slide fastener, open. A sufficient fullness to provide for the easy covering of the slider shall be allowed.
(11) Insert preserver gussets PG as follows: (a) With the edge (e) of the IP section and the edge (e) of the PG section coinciding with the lines (S) superimposed so that the right faces of the cloth are together at the stitch line (S), join the gusset to the IP section from (P-6) to (P-7). The operation is repeated for the other PG and IP

Source: https://assist.dla.mil -- Downloaded: 202610-16T11:35Z
Check the source to verify that this is the current version before use.

combination. (b) With the edge (e-1) of the OP section and the edge (e-1) of the PG section coinciding, and with the lines (S-1) superimposed so that the right faces of the cloth are together at stitch line (S-1), join the gussets to the OP section from (P-6) to (P-7). The operation is repeated for the other PG and OP combination.

(12) The edges of the OP and IP sections in the areas from (P-7) to (P-10) of the right preserver section shall be turned back and stitched.

(13) Place reinforcement patch RS-4 on right outside collar section, OC, in area marked (P-7) and stitch in place along lines (S-3). Repeat for left outside collar section with additional reinforcement patch RS-4.

(14) Form the full outside collar section by superimposing the left and right pieces of OC, right faces of the cloth together and with the edges (e) coinciding by adding stitch line (S). Turn back the right outside collar section and stitch down with one row of stitches.

(15) Place reinforcement patches RS-4 on inside collar section, IC, in areas marked (P-8) and stitch in place along lines (S-4).

(16) With the right faces of the inside collar section assembly and collar gusset, CG, facing stitch along the seam line from (P-1) to (P-a) and from (P-2) to (P-b).

(17) The slider fly section SF-1 shall be turned under 1/4 inch at each end and hemmed. The fly section shall be folded lengthwise, with the turned under ends facing, so that the long edges coincide, and shall be stitched to the 16 inch slide fastener with the long edges running concurrently with one edge of the slide fastener tape. Stitch the slide fastener fly assembly into the inside collar and collar gusset assembly by turning under the raw edges and stitching from (P-1) to (P-2).

(18) One slider protection patch RS-3 prepared in operation (10) above shall be placed over the end of the slide fastener by making the stitch line (S-2), leaving the selvage edge toward the slide fastener open. A sufficient fullness to provide for the easy covering of the slider is to be allowed.

(19) With the right faces of the inside collar section assembly and the outside collar section assembly joined in operation (14), stitch along the seam line from (P-3) to (P-b).

(20) With the right faces of the collar gusset and outside collar section facing, and with the edges (e-1) coinciding, stitch along the line (S-1).

(21) Complete assembly of the inside and outside collar sections by stitching along the stitch line from (P-a) to (P-10).

(22) Stitch the neck area closed along the line from (P-9) to (P-4).

(23) Place the two pieces of folded webbing (see release placket webbing; subassembly directions) parallel to one another and approximately 1/8 inch apart, so that the outer edges of the two pieces so placed pass through reference points (P-5) and (P-6) and the raw ends of the webbing coincide with the edge of inside collar section IC; complete stitching from points (P-3) to (P-4); turn the complete collar assembly rightside out, flatten and double stitch the webbing firmly in place.

(24) Reinforce inside collar to outside collar and collar gusset attachment by adding a row of stitches from (P-4) to (P-9) and from (P-10) to (P-a), along line (S-1) to (P-b), from (P-b) concluding at (P-3).

(25) Stitch down the edge of the inside collar, outside collar assembly from (P-9) to (P-10). Trim the edges close to the seam line to permit a close fit when the collar is slipped into the body section. The stitched end of the collar is then slipped into the stitched-under end if the OP and IP sections, operation (12), and the two joined by two rows of top stitching 1/4 inch apart. The closure shall be finished with a double row of top stitching parallel and close to each outer edge extending 1-1/2 inches on either side of the attachment seams. This attachment is shown in section B-B- on S3306-969942.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:35Z
Check the source to verify that this is the current version before use.

(26) A 9-1/2-inch piece of 1-inch webbing is bound for a distance of 1-3/4 inches with a double row of stitching over the inside neck stitch line of the collar. This operation is repeated with the other end of the webbing being attached to the correspondingly opposite point at the inside neck stitch line. This forms a resting tape for the back of the neck when the preserver is worn.

(27) A 70-inch piece of 1-inch webbing is folded in half to give a double 35-inch length. About 1-1/2 inches from the fold, the double webbing is joined to form a small loop. The loose ends are separately attached in two places indicated by points (P-12) and (P-13) on the OP right and left sections over the reinforcing strip RS-1. This forms the leg straps and the small loop affords an engagement with the body strap.

(28) The body strap is formed from two pieces of 1-inch webbing, one 18 inches and one 70 inches in length. The 18-inch strip is folded over so that one end extends 3 inches past the other. Two dot fasteners, with the socket sides placed on the outside of the long fold are placed on a line through the middle of the webbing 4 inches and 6 inches from the end, with the dot portion of the sockets pointed toward the open end. Two double tubular rivet studs are placed 1 inch and 3 inches from the other end of the webbing so that they will exactly engage the sockets previously placed on the long fold when the webbing is folded over flat on itself. Double dee rings are slipped over the socket end of the webbing and the dot-type fasteners engaged. The double dee rings are secured at the fold of the doubled-over webbing by placing a box stitch 1 inch long, and 1/2 inch from the fold. The short end on which the studs were placed, is finished with a metal tip. The long end of the subassembly is finished by doubling under 1-1/2 inches of the webbing and securing a dee ring in the fold by a 1-inch box stitch or suitable bar tack. The main portion of the body strap is formed by folding over 4 inches of one end of the 70-inch piece of webbing and stitching 1/8 inch around. Two grommets are placed midway between the edges of the webbing 1 inch and 3 inches, respectively, from the folded end. The other end of the 70-inch piece is folded over 1-1/2 inches and a single dee ring fastened by box stitching or bar tacking. The 70-inch piece of webbing is engaged through the double dee ring of the smaller subassembly in such a way that the single dee-ringed end can be used to adjust the length of the completed body strap.

(29) The completed body strap assembly is passed through the loop formed at the juncture of the leg straps and stitched to the loop at a point 31 inches from the doubled-over grommeted end of the body strap. Care must be taken in this operation to insure that when the preserver is in use, the grommeted end of the body strap is properly stitched to the leg strap loop, so that it can be brought around the left side of the preserver and engaged to the stud and socket combination with no twisting of any of the harness straps.

(II) b. Bouvant pad inserts. -

(1) With the edges (e) and the stitch lines (S) of the sections IIC and IOC coinciding, stitch along (S) from (P-1) to (P-2).

(2) Attach the collar gusset ICG to the IOC section of the IOC, IIC combination by making the edges (e-1) and the stitch line (S-1) coincide and stitching along (S-1) from (P-1) to (P-2).

(3) Attach the other edge of the collar gusset ICG to the IIC and its combined pieces by making the edges (e-2) and the stitch lines (S-2) coincide and stitching from (P-1) to (P-3) and (P-2) to (P-4). This provides an opening from (P-3) to (P-4) for inserting buoyant filling material.

(4) The final closure of the collar pad is made by sewing along (S-3) from (P-3) to (P-4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:35Z
Check the source to verify that this is the current version before use.

after filling material has been added.

(5) The upper front inserts are made by superimposing two IUF sections so that points (P) and (P-1) coincide and stitch along (S) from (P) to (P-1). This provides an opening from (P-1) to (P) for the insertion of buoyant medium.

(6) The lower front inserts are made in the same fashion employing the similar reference points and seams shown in the ILF drawing.

(7) The final closures of both front inserts are made by sewing along (S-1) from (P-1) to (P).

(II) c. Vinyl outer pad covers. All vinyl outer pad covers are fabricated in the same general manner. Two of each of the section CIC for the collar, section UFIC for the upper front and section LFIC for the lower front are superimposed upon one another, respectively. Each cover is first sealed from point (P) to point (P-1) along seam line (S), thus providing an opening from (P-1) to (P) for the placement of the print cloth covered inserts. The final closure, in all cases, is made by completing seal (S-1) from (P-1) to (P). Care must be exercised at this point that sufficient air is exhausted from the vinyl covers to provide for easy insertion into the drill preserver cover. Overcompression must also be avoided as the consequent loss in pad displacement will adversely affect the buoyancy. Note: No greater compression should be used than would give a minimum net buoyancy of 15.0 pounds for the collar pad and 8.0 pounds for both upper and lower front pads.

(II) d. Release placket, RP-1; subassembly. -

(1) Fold over cut edge (e) 1/2 inch, with the reverse side of the cloth in, and hem.

(2) Fold the piece thus formed, with the reverse side of the cloth in, so that cut edge (e-1) coincides with a line (P) to (P-1).

(3) Again fold the piece, with the reverse side of the cloth in so that the fold formed in (2) coincides with the selvage edge (e-2).

(4) Stitch a seam 1/8 inch from the edge around the entire periphery of the placket.

(5) On this semifinished piece attach two post studs (see drawing), stud bodies up, at points (P-3).

(6) At points (P-4) the socket and plate combinations are placed, plate sides up, and the socket parts in such a position that the dot marks are nearest the open end of the release placket when the assembly is attached to the left front part of the preserver.

(II) e. Release placket, webbing; subassembly. -

(1) A 6-1/2 inch piece of 1-inch webbing is folded over on itself so that the cut ends coincide and stitched along either side 1/8 inch from the edge.

(2) A grommet is placed midway from either edge 1-1/2 inches from the folded end of the webbing. Two pieces are needed to complete the subassembly.

3.8 U.S. Coast Guard approval. - When specified in 6.1, all preservers shall be approved by the U. S. Coast Guard.

3.9 Workmanship. - The workmanship and finish (such as turn-under of raw ends of webbing and tape) shall be first class in every respect.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - Unless otherwise specified in the contract or purchase order,

Source: https://assist.dla.mil -- Downloaded: 202610-16T11:35Z
Check the source to verify that this is the current version before use.

the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 When inspection is conducted at the contractor's plant, all tests specified herein shall be conducted by the contractor under the surveillance of the inspector. Contractors not having laboratory facilities satisfactory to the inspector shall engage the services of a commercial testing laboratory acceptable to the inspector. The contractor shall furnish test reports, in duplicate, showing quantitative results of all tests and analyses required by this specification, and signed by the Director, or his authorized assistant, of the laboratory in which the tests were conducted. These reports shall be furnished the inspector. The furnishing or maintaining of test reports or records shall not be construed as waiving the witnessing of tests by the inspector.

4.2 Preproduction tests. - Prior to regular production, preproduction tests shall be conducted by the Material Laboratory, New York Naval Shipyard, Brooklyn 1, New York, and shall consist of all the tests specified in this specification including the examination to determine conformance to the construction requirements. Samples of all materials used in the fabrication of the life preserver shall be examined and tested to ascertain their conformance to the applicable specifications or to the requirements for the material as specified herein.

4.2.1 Samples for preproduction. - The following samples shall be submitted:

(a) Three complete life preservers.
(b) Two square yards of vinyl film.
(c) Two square yards of each type of cloth used.
(d) Three yards of each type of tape and webbing used.
(e) Two complete sets of buoyant pads.
(f) Two sets of all hardware used.
(g) One cone of each type thread used.
(h) Three sets of each length of slide fasteners.

4.2.2 Preproduction samples shall be plainly identified by securely attached durable tags marked with the following information:

Samples for preproduction test.
Name of product, together with complete identifying data such as manufacturer's designation number.
Name of manufacturer.
Contract or order number.

4.3 Sampling. -

4.3.1 Lot. - For the purpose of sampling for examination and test, a lot shall consist of not more than 3,000 life preservers.

4.3.2 Sampling for quality conformance inspection. -

4.3.2.1 Sampling for visual and dimensional examination. - A random sample of life preservers

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:35Z
Check the source to verify that this is the current version before use.

shall be selected in accordance with table III from each inspection lot of material offered for examination of visual and dimensional characteristics with lot acceptance based on the following sampling inspection requirements.

Table III. Sampling for visual and dimensional examination
AQL (approx.) = 0.65 percent defective.

Number of life preservers in inspection lot	Number of life preservers in sample	Acceptance number (defectives)	Rejection number (defectives)
110 or under	15	0	1
111 to 300	25	0	1
301 to 500	35	0	1
501 to 800	50	1	2
801 to 1300	75	1	2
1301 to 3000	110	2	3

4.3.2.2 Sampling for quality conformance tests. - A random sample of life preservers shall be selected from each lot in accordance with table IV and shall be subjected to the tests specified in 4.5.

Table IV. Sampling for quality conformance tests.

Number of life preservers or body strap assemblies in lot	Number of life preservers for test of operation of snap fasteners	Number of life preservers for pad immersion test	Number of life preservers for pad seam and distribution of buoyant medium test
110 or under	7	5	3
111 to 500	10	7	5
501 to 1300	15	10	7
1301 to 3000	25	15	10

4.3.3 Sampling for production check test. - From the first lot offered for delivery under a contract or order, and thereafter from every fifth lot, 2 life preservers shall be selected and forwarded to the laboratory designated by the bureau or agency concerned.

4.4 Visual and dimensional examination. - Each of the sample life preservers selected in accordance with 4.3.2.1 shall be visually and dimensionally examined to verify compliance with this specification. Any life preserver in the sample containing one or more visual or dimensional defects shall not be offered for delivery, and if the number of defective life preservers in any sample exceeds the acceptance number for that sample, this shall be cause for rejection of the lot represented by the sample.

4.5 Quality conformance test. - Each of the sample life preservers selected in accordance with 4.3.2.2 shall be tested in accordance with 4.7.2, 4.7.3, 4.7.4, 4.7.5, 4.7.6 to verify compliance with this specification. Any sample life preserver which does not meet the requirements for these characteristics shall cause rejection of the lot represented by the sample.

4.6 Production check test. - Each sample selected in accordance with 4.3.3 shall be subjected to

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:35Z
Check the source to verify that this is the current version before use.

the tests specified in 4.7 and inspected for conformance with all requirements of this specification other than those specified in section 5. Acceptance of the first lot offered for delivery under a contract or order shall be withheld until a test report indicating that the sample has satisfactorily passed the tests is received. Thereafter, except as hereinafter specified, acceptance and rejection of lots shall normally be on the basis of 4.4 and 4.5 and acceptance shall not be withheld pending receipt of test reports. However, upon receipt of a test report indicating that the sample has not passed the tests, additional samples shall be selected from every subsequent lot offered for delivery and subjected to the test or tests wherein failure was observed. Lots shall then be accepted only upon receipt of a test report indicating that the samples so selected have satisfactorily passed the test. This additional testing shall be discontinued and inspection returned to the normal basis of 4.4 and 4.5 when 4 successive lots have been accepted.

4.7 Test procedures. -

4.7.1 All tests not herein described shall be in accordance with the methods specified in CCC-T-191; method 5660 shall be used for all lightfastness tests.

4.7.2 Pad immersion test. - The completed front and collar pads, including the sealed waterproof envelopes, shall be held beneath the surface of a tank of water, compressing to create a moderate pressure within the pad. Any leakage shall be determined by noting the escape of air bubbles.

4.7.3 Pad seam test. - One-inch strips cut across and perpendicular to the seams of the vinyl film envelopes shall be pulled apart at a rate of separation of the clamping jaws of 12 inches per-minute.

4.7.4 Operation of snap fasteners. - The waist strap and collar snap fasteners shall be opened and closed five times. The fasteners shall be capable of easy opening and positive closure.

4.7.5 Slide fasteners. - The slide fasteners in the collar section and each of the body sections shall be opened and closed five times. The fastener slide shall be capable of moving freely and easily separating and closing the two halves.

4.7.6 Distribution of buoyant medium test. - The front and collar pads from each sample preserver shall be weighed after removal of the vinyl film to determine compliance with 3.5.

4.7.7 Buoyancy test. - The completed front and collar pads, including the sealed waterproof envelopes, shall be respectively subjected to buoyancy tests. In this test, the pad shall be placed in a cage of adequate size and of sufficient weight to submerge the pad. This assembly shall be suspended from a direct reading scale, in fresh water, at room temperature, with the top of the cage 2 inches beneath the surface of the water. The scale reading shall be taken as soon as practicable, and the buoyancy calculated as the apparent weight of the cage and pad subtracted from the previously determined underwater weight of the assembly without the pad.

4.8 Examination of preparation for delivery. - The packaging, packing, and marking of life preservers shall be subject to examination to determine compliance with the requirements of Section 5 of this specification.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking. - Life preservers shall be packaged by level A or C, packed by level A, B, or C, and marked in accordance with MIL-P-3454, as specified (see 6.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:35Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. - Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) If Coast Guard Approval is required (see 3.8).
(c) Applicable levels of packaging and packing (see 5.1).

6.2 Color chip. - Color chip may be obtained from Code 305, Norfolk Naval Shipyard, Portsmouth, Virginia. When requesting, specify for what purpose color chip is desired.

6.3 Preproduction. -

6.3.1 Invitations for bids should provide that the Government reserves the right to waive the requirement for preproduction samples as to those bidders offering a product which has been previously procured or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending procurement.

Custodians:
Army - MO
Navy - Ships

Preparing activity:
Navy - Ships
(Project 4220-0058)

Reviewer:
Army - MO
Navy - SH

Note: Review/user information is current as of the date of the document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:35Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
BUREAU OF SHIPS
WASHINGTON 25, D. C.

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
NAVY DEPARTMENT

CHIEF, BUREAU OF SHIPS
SPECIFICATIONS AND STANDARDIZATION BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 20261O-16T11:35Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION		
ORGANIZATION	CITY AND STATE	
CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

   ☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 APR 62 1426 REPLACES NAVSHIPS FORM 4063, WHICH IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:35Z
Check the source to verify that this is the current version before use.