MILITARY SPECIFICATION

RESISTOR NETWORK, FIXED, FILM,
ESTABLISHED RELIABILITY,
STYLE RZR50, 8 PIN SIP

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the detail requirements for style RZR50, 8 pin single in-line package (SIP) resistor network. This style is available in all characteristics and resistance tolerances F, G, and J.


1.2 Part or Identifying Number (PIN). Resistor networks covered by this specification shall be identified by a PIN which shall consist of the basic number of this specification and a coded number. The PIN shall be in the following form:

M874 — Military specification number


H05F1002CS — Coded number

The coded number shall be derived in accordance with MIL-R-874.


1.2.1 Schematics. The schematic of the resistor network shall be identified by a single letter in accordance with the drawings below. The resistor element R_{ref} shall be the reference resistor element used in determining the ratio accuracy (when applicable).



SCHEMATIC "H"



SCHEMATIC "G"



SCHEMATIC "C"

Benefical comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be US Army Laboratory Command, ATTN: SLCET-R-S, Fort Monmouth, NJ 07703-5302, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5905

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:40Z
Check the source to verify that this is the current version before use.

1.2.1.1 Standard resistance values. The standard resistance values and the resistance value designators for the "H" schematic are as specified in table I.

TABLE I. Standard resistance values.

Resistance designator	R1 (ohms)	R2 (ohms)	Resistance designator	R1 (ohms)	R2 (ohms)
A001	82	130	A010	330	470
A002	120	200	A011	330	680
A003	130	210	A012	1.5k	3.3k
A004	160	260	A013	3.0k	6.2k
A005	180	240	A014	180	270
A006	180	390	A015	270	270
A007	220	270	A016	560	560
A008	220	330	A017	560	1.2k
A009	330	390	A018	620	2.7k

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-R-874 - Resistor Networks, Fixed, Film, Established Reliability, General Specification for.
MIL-R-39032 - Resistors, Packaging of.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Aveue, Philadelphia, PA 19120-5099.)


2.2 Order of precedence. In the event of a conflict between the text of this document and references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Associated detail specifications. The individual item requirements shall be in accordance with MIL-R-874, and as specified herein.

3.2 Design and construction. The resistor shall be of the design, construction, and physical dimensions specified on figure 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:40Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm
.003	0.08	.027	0.69
.004	0.10	.035	0.89
.008	0.20	.040	1.02
.009	0.23	.050	1.27
.012	0.30	.052	1.32
.015	0.38	.076	1.93
.017	0.43	.100	2.54
.020	0.51	.135	3.43
.025	0.64	.342	8.69
.026	0.66	.783	19.89

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance are ±.005 (.13 mm).
4. The picturization of the styles above is given as representative of the envelope of the item. Slight deviations from the outline shown, which are contained within the envelope and do not alter the functional aspects of the device, are acceptable.
5. Terminal centerline to centerline measurements made at a point of emergence of the lead from the body.
6. Measurement made at point of emergence of the lead from the body.
7. Pin 1 locator shall be a dot, notch, stripe, or numeral 1 adjacent to pin number 1 in the shaded area; also, additional marking may be placed on the top edge where the bevel may be located.
8. If the standoffs are located on the body, a minimum of two standoffs are required as illustrated. As an option, additional standoffs may be located on the body of the resistor network. If leads with standoffs are used, standoffs on the body are not required.

FIGURE 1. RZR50 style resistors.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:40Z
Check the source to verify that this is the current version before use.

3.3 *Power rating*. The power rating shall be as specified in table II, based on a full load operation at an ambient temperature of 70°C. For operation at temperatures higher than 70°C, derate in accordance with MIL-R-874.

TABLE II. Power ratings.

Schematic	Characteristic	Element power rating (watts)	Network power rating (watts)
C	H	0.2	1.4
	K	0.2	1.4
	M	0.2	1.4
G	H	0.2	0.8
	K	0.2	0.8
	M	0.2	0.8
H	H	0.11	1.32
	K	0.11	1.32
	M	0.11	1.32

3.4 Power conditioning. The power applied for power conditioning for schematics "C", "G", and "H" shall be 1.5 times rated power.

3.5 *Voltage rating*. The maximum continuous working voltage for each style shall not exceed 100 volts dc or ac rms.

3.6 Resistance. Minimum and maximum resistance values shall be as specified in table III.

TABLE III. Resistance values.

Resistance tolerance	Characteristic	Minimum resistance (ohms)	Maximum resistance (megohm)
F (±1.0 percent)	H, K, M	10.0	1
G (±2.0 percent)	K, M	10.0	1
J (±5.0 percent)	K, M	10.0	1

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-R-874.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-R-39032.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:40Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The notes specified in MIL-R-874 are applicable to this specification.

6.2 Acquisition requirements. Acquisition documents must be in accordance with MIL-R-874.

6.3 PIN. PIN is a new term encompassing previous terms used in specifications such as part number, type designator, identification number, etc. (see 1.2).

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AR, MI
Navy - AS, OS
Air Force - 11, 17
DLA - ES

User activities:
Army - AT, AV, ME
Navy - CG, MC
Air Force - 19

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5905-1154-5)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:40Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

U.S. GOVERNMENT

(Fold along this line)

DEPARTMENT OF THE ARMY

US Army Laboratory Command
Fort Monmouth, NJ 07703

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Laboratory Command
ATTN: SLCET-R-S
Fort Monmouth, NJ 07703

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:40Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-R-874/5	Resistor Network, Fixed, Film, Established Reliability, Style RZR50, 8 Pin Sip

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(FOLD ON THIS LINE.)

(FOLD ON THIS LINE. CUT ALONG THIS LINE.)

U.S. GOVERNMENT

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T11:40Z
Check the source to verify that this is the current version before use.