MIL-C-38302A(USAF)
AMENDMENT 1
14 SEP 85

MILITARY SPECIFICATION

COMPUTER, BOMBING, FLIGHT DIRECTOR CP-734A/AJB-7

This amendment forms a part of Military Specification MIL-C-38302A(USAF) dated 7 Nov 1968 and is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Add new paragraph 2.1:
"2.1 Government documents."

Renumber existing paragraph "2.1" to "2.1.1" and change preamble to read as follows:
"2.1.1 Specifications, standards and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation form a part of this specification to the extent specified herein."

Under "SPECIFICATIONS Federal" delete "QQ-P-416". Add "PPP-B-601 Boxes, Wood Cleated-Plywood" and "PPP-B-636 Box Shipping, Fiberboard"

Under "SPECIFICATIONS Military" change title of MIL-C-5541 to read "Chemical Conversion Coating on Aluminum Alloys"; Add "MIL-M-7793 Meter Time Totalizing"; Add "MIL-C-83488 Coating, Aluminum, Ion Vapor Deposited".

Under "STANDARDS Military" delete "MIL-STD-100" and substitute "DOD-STD-100".

Add boxed paragraph to bottom center:

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145-5990 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

PAGE 2

Under "STANDARDS Military" add "MIL-STD-889 Dissimilar Metals"; delete "MS17322" and "MS33586"; Change title of "MS3116" to read "Connector Plug, Electric, Series 1, Solder Type, Straight Bayonet Coupling".

FSC 1280

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:21Z
Check the source to verify that this is the current version before use.

Add the following at conclusion of paragraph 2.1.1:

"Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting office.

PAGE 3

Add paragraph 3.3.6:

"3.3.6 Reclaimed materials. Reclaimed materials shall be used to the maximum extent possible."

PAGE 5

In paragraph 3.5.e. delete "10g's" and "15 g's" and substitute "9 g's" and "13.5 g's" respectively.

In paragraph 3.7 line 2 delete "MS17322-6" and substitute "MS7793/6-002".

PAGE 13

Delete paragraph 3.17.2 and substitute:

"3.17.2 Steel parts. Steel parts shall be coated with ion vapor deposited aluminum, where practicable, in accordance with MIL-C-83488, type I or II as applicable and of a class that is adequate to achieve the degree of protection required. Other protective coating in lieu of MIL-C-83488, may be used if demonstrated to be satisfactory and approved by the cognizant engineering activity. Cadmium plating must be avoided when satisfactory alternative processes can be used."

PAGE 32

In paragraph 4.6.4 delete "502" and substitute "502.1".

In paragraph 4.6.5 delete "501" and substitute "501.1".

Delete paragraph 4.6.9 and substitute:

"4.6.9 Temperature-altitude. The temperature altitude test shall be conducted in accordance with method 504.1 category 6 of MIL-STD-810 except the altitude shall be 80,000 feet in step 6, a temperature of 85°C shall be maintained for 4 hours in lieu of 16 hours and in step 8, the temperature shall be 85°C. Thermocouples shall be installed to permit temperature measurement throughout the test at appropriate points."

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:21Z
Check the source to verify that this is the current version before use.

PAGE 33

In paragraph 4.6.11 delete "516" and substitute "516.2".

Delete paragraph 4.6.12 and substitute:
"4.6.12 Vibration failure. The vibration failure test shall be conducted in accordance with MIL-STD-810 method 514.2 equipment catetory b.1, curve c, except that at 1 g, the frequency shall be extended to .40 inch double amplitude and maintained at this amplitude until the frequency is reduced to 5 Hz. The computer shall be operating during the test."

Delete paragraph 4.6.13 and substitute:
"4.6.13 Acceleration. The acceleration test shall be conducted in accordance with MIL-STD-810 method 513.2 procedure I and II, except during the operational test the g-level in the down direction shall be 3.3 g's."

Delete paragraph 4.6.14 and substitute:
"4.6.14 Vibrated endurance. The vibration endurance test shall be conducted in accordance with MIL-STD-810, Method 514.2, equipment category b.1, curve D, except that at 1 g, the frequency shall be extended to .40 inch double amplitude and maintained at this amplitude until the frequency is reduced to 5 Hz. During vibration, the computer shall not be operating."

Change subparagraphs of 4.6.14 to read as follows:
"a. Rain: Method 506.1 procedure I, except that the rainfall rate shall be 5 $\pm$ 1 and 12 $\pm$ 1 inches per hour, respectively. The wind source shall be turned off as soon as 40 miles per hour wind velocity is obtained."

"b. Humidity: Method 507.1, procedure I, except in step 2 the temperature shall be 71°C."

"c. Fungus: Method 508.1, procedure I."

"d. Salt foG: Method 509.1, procedure I."

"e. Dust: Method 510.1, procedure I."

"f. Explosion: Method 511.1, procedure I."

PAGE 35

Add paragraph 4.7:
"4.7 Inspection and test. Tests of methods of preservation and packaging shall be accomplished in accordance with Section 4 of MIL-P-116 to insure compliance with Section 5 of the specification."

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:21Z
Check the source to verify that this is the current version before use.

Delete Section 5 and substitute:

"5. PACKAGING

5.1 Preservation - packaging. Preservation - packaging shall be Level A or C as specified.

5.1.1 Level A.

5.1.1.1 Cleaning. Units shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. Units shall be dried in accordance with process D-4 of MIL-P-116.

5.1.1.3 Preservation application. Not applicable.

5.1.1.4 Unit packaging. Unless otherwise specified by the procuring activity, each computer, bombing, flight director CP-734A/AJB-7, shall be packaged in quantity unit packs of one each in accordance with Method IIc of MIL-P-116. Each unit shall be overboxed in PPP-B-636 carton. Carton shall be large enough to allow for application of sufficient cushioning material between container and bag, of a type, density, and thickness to insure shock transmission does not exceed peak values in G's established for the computer when completed packs are subjected to the rough handling drop tests of MIL-P-116.

5.1.2 Level C. Units shall be clean, dry, and individually packaged in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from supply source to the first receiving activity.

5.2 Packing. Packing shall be level A, B, or C as specified.

5.2.1 Level A. Units packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-601, Style A or B, class overseas, unless otherwise specified by the procuring activity. Insofar as practical, exterior shipping container shall be of uniform shape, size, and of minimum tare and cube, consistent with the protection required.

5.2.2 Level B. Transmitters packaged as specified in 5.1.1 shall be packed in weather-resistant class exterior shipping containers conforming to PPP-B-636. Other requirements as specified in 5.2.1 above are applicable.

5.2.3 Level C. Packing shall be applied which affords adequate protection during domestic shipment from the supply source to the first domestic receiving activity for immediate use. This level shall conform to applicable carrier rules and regulations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:21Z
Check the source to verify that this is the current version before use.

5.3 Marking. In addition to any special marking required by the contract or order, each unit package and shipping container shall be marked in accordance with MIL-STD-129."

Custodian:
Air Force-99

Review Activity:
Air Force-84

Preparing activity:
Air Force-71

Project number:
1280-F021

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:21Z
Check the source to verify that this is the current version before use.