NOT MEASUREMENT SENSITIVE

A-A-52413(AT)
18 January 1993

COMMERCIAL ITEM DESCRIPTION

HOSE, RUBBER; OIL SUCTION, WIRE-REINFORCED

The General Service Administration has authorized the use of this commercial item description as a replacement for MIL-H-52544B(AT) which is canceled.

1.0 Abstract. This commercial item description (CID) covers two types of bulk wire-reinforced hydraulic suction hose (see 1.1) for use in hydraulic suction lines. Operating temperatures in excess of the rated temperatures (see 1.1) may materially reduce the life of the hose.

1.1 Classification. Hoses shall be of the following types:

Type I - Operating temperature range from -40°F to 200°F.
Type II - Operating temperature range from -40°F to 250°F.

2.0 Salient characteristics.

2.1 Material. Hose shall be as specified herein. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this CID. The use of recovered material made in compliance with regulatory requirements is acceptable providing that all requirements of this CID are met (see 5.4).

2.1.1 Tube. The tube of the hose shall be seamless oil-resistant synthetic rubber.

2.1.2 Cover. The cover of the hose shall be seamless ozone and oil resistant synthetic rubber.

2.2 Design and construction. Type I hose shall conform to SAE J517. Type II hose shall conform to SAE J517, except hose shall be capable of an operating temperature range of -40°F to 250°F. The maximum operating pressure for each hose size shall be in accordance with SAE J517 series 100R4.

Beneficial comments, recommendations, additions, deletions clarifications, etc. and any other data which may improve this document should be sent by letter to: U.S. Army Tank-Automotive Command, ATTN: AMSTA-GDS, Warren, MI 48397-5000.

AMSC N/A FSC 4720

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:09Z
Check the source to verify that this is the current version before use.

2.3 Age. The hose shall be manufactured not more than thirty two calendar quarters (8 years) prior to date of delivery to the Government.

2.4 Length. Unless otherwise specified (see 5.2), bulk hose shall be furnished in lengths of 13.7 meters (m) (45 feet) or longer except that not more than 25 percent may be furnished in lengths between 7.6 m (25 feet) and 13.4 m (44 feet) and not more than an additional 25 percent may be furnished in lengths between 4.6 m (15 feet) and 7.3 m (24 feet).

2.5 Size. The size of the hose shall conform to SAE J517 series 100R4 (see 5.2).

2.6 Identification and marking. Identification and marking shall be in accordance with SAE J517. In addition, type II hose shall have the maximum operating temperature of 250°F appropriately identified and marked.

2.7 Workmanship. Workmanship shall be in accordance with the manufacture of a high quality hose. This shall be evidenced by the absence of defects detrimental to hose serviceability or appearance, such as, hose shall be clean and free from oil, grease, dirt, or other foreign material, both internally and externally.

3.0 Quality assurance provisions.

3.1 Responsibility for inspection. The contractor is responsible for the performance of all inspections (examinations and tests).

3.2 Contractor certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this commercial item description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. Items with known defects shall not be submitted for Government acceptance. The Government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4.0 Preservation, packaging, packing, labeling, and marking. Preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order (see 5.2).

5.0 Notes.

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

5.1 Address for obtaining copies of referenced documents.

5.1.1 Non-Government publications. SAE J517 "Hydraulic Hose", is available from The Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096.

5.2 Ordering data. Acquisition documents must specify the following:

a. Title, number, and date of this CID.
b. Length of hose, when a specific length is required (see 2.4).
c. Size of hose required (see 2.5).
d. Issue of the DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 5.1.1).
e. Selection of applicable level and packaging requirements (see 4.0).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:09Z
Check the source to verify that this is the current version before use.

5.3 Cross-reference data. Hoses conforming to type II of this document are interchangeable/substitutable with hoses conforming to MIL-H-52544B(AT).

5.4 Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

5.5 Metric product. Hoses that are to metric dimensions will be considered on the following basis:

a. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of Federal Standard No. 376, and all other requirements of this commercial item description are met.

b. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch/pound units, a request shall be made to the contracting officer to determine if the product is acceptable.

c. The contracting officer has the option of accepting or rejecting the product.

Custodian:
Army - AT

Review activity:
DLA - CS

Preparing activity:
Army - AT

(Project 4720-0033)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:09Z
Check the source to verify that this is the current version before use.