INCH-POUND

MIL-F-14902A (AR)
AMENDMENT 1
31 May 2000

MILITARY SPECIFICATION

FIN, ASSEMBLY, 60MM, M2

MIL-F-14902A was inactivated after 31 January 1996 for new design

This amendment forms a part of MIL-F-14902A (AR), dated 23 November 1973, and is approved for use by the U.S. Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1, SPECIFICATIONS, MILITARY: Add:

"MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for ".

Under STANDARDS, delete the following:

"FEDERAL
FEDERAL TEST METHOD
Standard No. 151 – Metals, Test Methods"

Under STANDARDS, MILITARY: Delete:

"MIL-STD-109 - Quality Assurance Terms and Definitions.
MIL-STD-1168 - Lot Numbering Of Ammunition.
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes."

PAGE 2

Add new paragraph 2.2 as follows:

"2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

AMSC N/A **FSC 1310**

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:05Z
Check the source to verify that this is the current version before use.

ASTM METHOD E-18 - Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103).

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using federal agencies.)"

4.1, Delete in its entirety and substitute:

"4.1 Responsibility for Inspection and Standard Quality Assurance Provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification."

4.1.1: Delete in its entirety and substitute:

"4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material."

4.2, After heading "Initial production inspection": Add: "(First Article)".

4.2.1, First paragraph: Delete: "(see 6.3)".

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:05Z
Check the source to verify that this is the current version before use.

PAGE 4

4.2.2, Last sentence: Delete in its entirety and substitute: "See MIL-A-48078".

4.2.3, End of paragraph: Add: "See MIL-A-48078".

4.3.1: Delete in its entirety and substitute:

"4.3.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078."

PAGE 5

4.3.2: Delete in its entirety and substitute:

"4.3.2 Examination. See MIL-A-48078. Unless otherwise specified, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II."

Add new paragraph 4.3.2.1.1 as follows:

"4.3.2.1.1, Fin Canted (see dwg. 12972526 covering a detail of dwg. 9207612).

CATEGORIES	DEFECTS	METHOD OF INSPECTION
CRITICAL:	None defined	
MAJOR:		
101	Fin blade(s) canted in improper direction	Visual
102	Improper fin blade cant angle	Gage (CD)
103	Improper height of fin blade cant	Gage (CD)
MINOR:	None defined"	

PAGE 7

4.3.2.3, Major 101: Delete in its entirety and substitute:

"101 Fin blade(s) damaged, distorted or mislocated (functional) ... Gage (CD)".

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:05Z
Check the source to verify that this is the current version before use.

PAGE 7 (cont)

4.3.2.4, Major 102: Delete in its entirety and substitute:

"102 Fin blade(s) damaged, distorted or mislocated (functional) ... Gage (CD)".

PAGE 8

4.4.2: Delete: "Federal Test Method Standard No. 151, Method 243." and substitute: "ASTM E-18".

Add the following at the end of the paragraph:

"Prior to performing the hardness test, removal of the decarburized zone is recommended. Decarburized layers up to .006 depth maximum, may be removed from each side of the fin blade. Machining two (2) flats, 180 degrees apart on cartridge container surface prior to testing is permitted and may aid in obtaining accurate, consistent results."

PAGE 9

6.1: Delete in its entirety and substitute:

"6.1 Ordering data. See MIL-A-48078."

6.2: Delete in its entirety and substitute:

"6.2 Submission of inspection equipment designs for approval. See 6.2.3 of MIL-A-48078. Submit designs as required to: "Commander, U.S. Army Armament, Research, Development and Engineering Center (ARDEC), ATTN: AMSTA-AR-QAA-C, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423, in the contract. Unless otherwise specified, Data Item DI-R-1714 will apply."

PAGE 10

6.3: Delete in its entirety.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1310-0593)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:05Z
Check the source to verify that this is the current version before use.