MIL-I-14925A (AR)
AMENDMENT 2
28 DECEMBER 1982
SUPERSEDING
AMENDMENT 1
11 April 1975

MILITARY SPECIFICATION

IGNITER ASSEMBLY, M76

LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-I-14925A (PA) dated 29 March 1974 and is approved for use by the U. S. Army Armament Research and Development Command and is available for all Departments and Agencies of the Department of Defense.

PAGE 6

* 4.3.1 At end of paragraph add the following: "In addition, inspection lots of igniter assemblies shall contain igniter launch motor bodies from not more than one lot interfix number from one manufacturer."

PAGE 7

* 4.3.2.2 Under the category CRITICAL add:

"SPECIAL

1. Inspection for melt index. See paras. 4.3.3.2.6 & 4.4.4

2. Inspection for density. See paras. 4.3.3.2.7 & 4.4.5"

PAGE 9

Add the following:

* "4.3.3.2.6 Melt index of body, igniter launch Motor. One body shall be selected at beginning and one at end from each day's continuous production run from each mold cavity and tested in accordance with procedure in 4.4.4. Failure of one or more bodies to meet the requirement shall be cause for rejection of the day's production represented by the sample."

FSC 1336

Source: https://assist.dla.mil -- Downloaded: 202640-18T05:06Z
Check the source to verify that this is the currentversion before use.

PAGE 9

* "4.3.3.2.7 Density of body, igniter launch Motor. One body shall be selected at beginning and one at the end from each day's continuous production run from each mold cavity and tested in accordance with procedure in 4.4.5. Failure of one or more bodies to meet the requirement shall be cause for rejection of the day's production represented by the sample.

PAGE 10

Under para. 4.4.3

delete: in its entirety

add: 4.4.3 Ballistic Functioning. - The sample igniters shall be conditioned at -25°F minus 5°F and +125°F plus 5°F for a period of 4 hours minimum and shall be installed in nozzle dwg. 9225158. The nozzle-igniter shall be assembled to the case dwg. 9225157 with a free volume of 24.7 cubic inches. The free volume shall be obtained by installing a simulated propellant in the case with a volume of 19.1 cubic inches. The sample shall be fired within 5 minutes after removal from the conditioning unit. Ballistic results shall be recorded to determine compliance with the requirements. This test shall be performed using a current of 8±.5 amperes.

PAGE 10

Add the following:

* "4.4.4 Body, igniter launch motor melt index. This test shall be performed in accordance with Dwg. # 9221073 and ASTM D1238-79."

* "4.4.5 Body, igniter launch motor density. This test shall be performed in accordance with Dwg. #9221073 AND ASTM D 792-66."

* NOTE: The margins of this amendment are marked with an asterisk to indicate where changes from previous amendments were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian
Army-AR

Preparing Activity
Army-AR

Project No. 1336- A447

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:06Z
Check the source to verify that this is the current version before use.