MIL-M-14926B (PA)
29 March 1974
SUPERSEDING
MIL-M-14926A (MU)
12 May 1971

MILITARY SPECIFICATION

MOTOR, ROCKET, LAUNCH, M114 PARTS FOR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not normally covered by the drawings and provides quality assurance provisions for the fabrication of parts and packing of one type of rocket motor designated as Motor, Rocket, Launch M114.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-636	Box, Fiberboard
PPP-F-320	Fiberboard, Corrugated and Solid Sheet Stock (Container Grade) and Cut Shapes
TT-I-558	Ink, Marking Stencil, Opaque, for Nonporous Surfaces (Metals, Glass, etc.)

FSC: 1336

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-C-2439	Container, Ammunition, Fiber, Spirally Wound
MIL-P-3420	Packaging Materials, Volatile Corrosion Inhibitor, Treated, Opaque
MIL-I-6868	Inspection Process, Magnetic Particle

STANDARDS

FEDERAL

FED-STD-151	Metal, Test Methods

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168	Lot Numbering of Ammunition
MIL-STD-1169	Packaging, Packing and Marking for Shipment of Inert Ammunition Components
MIL-STD-1235	Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

PICATINNY ARSENAL

PRODUCT AND PACKING DRAWINGS

9225160	Metal Parts Assembly TOW Launch Motor - M114

INSPECTION EQUIPMENT DRAWINGS

9225616	Hydrostatic Test
9246460	Ring, Plain

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

2.2 Other Publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

AMERICAN SOCIETY FOR TESTING MATERIALS

ASTM B 117 Method of Salt Spray (Fog) Testing

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia 3, Pennsylvania.)

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Components and Assemblies. The components and assemblies shall comply with all requirements specified on drawing (dwg.) 9225160 and with all requirements of applicable standards and specifications.

3.3 Salt Spray Test. The case and nozzle, after application of protective finish, shall show no signs of corrosion when subjected to salt spray.

3.4 Dimensional Stability of Case. The case shall not exhibit any deformation exceeding drawing dimensions as a result of hydrostatic test.

3.5 Case Surface Integrity. There shall be no evidence of cracklike indications on the surfaces of the case.

3.5.1 Evidence of Magnetic Particle Inspection. At the successful completion of magnetic particle inspection, the case shall be marked with the letter "M" adjacent to the hydrostatic test mark, using contrasting ink in accordance with TT-I-558.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

3.6 Chamber Internal Burst Pressure.

3.6.1 First Article. Each individual launch motor case burst as part of the first article shall withstand a minimum internal pressure of 20,500 pounds per square inch gage (psig). In addition, the mean of the first article sample minus (-) 4.353 standard deviations shall yield a value of 20,500 psig minimum (min.).

3.6.2 Production. Each case tested shall withstand a minimum internal pressure of 21,000 psig.

3.7 Workmanship. All parts and assemblies shall be fabricated in a thorough, workmanlike manner. The parts shall be free of burrs, sharp edges, warpage, dirt, rust and other foreign matter. The cleaning method used shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agents. Surface coatings shall be continuous, except for scratches not exposing base metal.

3.8 First Article Inspection. This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection. Unless otherwise specified in the contract or order, the supplier is responsible for the performance of all of the inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Submission of Product. At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.

b. Drawing and specification number and date, together with an identification and date of changes thereto.

c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.

d. Number of items in the lot.

e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First Article Inspection

4.2.1 Submission. The contractor shall submit a first article sample to a Government approved facility as designated by the Contracting Officer (See 6.4) for evaluation in accordance with the provisions of 4.2.2. The first article sample shall consist of ten (10) complete sets of parts which have been produced by the contractor or furnished by a supplier, and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same sources of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including statements of findings of tests and examinations and certificates of conformance for materials(See 4.1.1c). A sample containing known defects will not be submitted unless speci-

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:07Z
Check the source to verify that this is the current version before use.

fically authorized by the Contracting Officer. A first article sample, or portion thereof, as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days, or whenever a change occurs in manufacturing process, material used, drawings, specification or source of supply such as to significantly affect product uniformity as determined by the Government.

4.2.2 Inspections to be Performed. Each component will be subjected by the Government to any or all of the examinations and tests specified in 4.3.2 and 4.3.3 of this specification, and to any or all requirements of the applicable drawings.

4.2.3 Rejection. If any assembly fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an assembly or component in the sample to comply with any of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article or portion thereof. Until a first article sample is accepted, the contractor is in no way authorized by the Government to initiate regular production unless otherwise directed by the Contracting Officer.

4.3 Inspection Provisions

4.3.1 Lot Formation. The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn, and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision, and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specification, or drawing, not affecting safety, performance, interchangeability or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each inspection lot of complete launch motor assemblies shall contain parts from not more than one interfix lot number from one manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

4.3.2 Examination. The examinations listed in the following subparagraphs shall be performed on inspection lots (See 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for Critical Defects (and Major Defects, when so specified) shall be 100 percent. Sampling plans for Major and Minor Defects shall be in accordance with MIL-STD-105, except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of Major and Minor Defects listed, the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each Major Defect and an AQL of 0.65 percent for each Minor Defect. When this method is elected, it shall be applied to all of the Major and Minor Defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Case-Launch Motor (See dwg. 9225157, covering a detail of dwg. 9225160).

Categories	Defects	Method of Inspection
Critical:		
1.	Aft end thread minor diameter, maximum (max.)	Gage
2.	Aft end thread, full thread, min.	Gage
3.	Evidence of hydrostatic test mark missing	Visual
4.	Evidence of magnetic particle inspection mark missing	Visual
Major:	AQL 1.00 Percent	
101.	Aft end thread minor diameter	Gage
102.	True position of aft end minor thread diameter to Datums A and B	Gage
103.	Perpendicularity of aft face with Datums A and B	Gage
104.	Perpendicularity of forward end shoulder with Datums A and B	Gage
105.	Length from forward end to shoulder	Gage
106.	Large inside diameter forward end	Gage
107.	Small inside diameter forward end	Gage
108.	Forward end thread pitch diameter	Gage
109.	Straightness of case outside diameter	Gage
110.	Aft end thread pitch diameter	Gage
111.	Presence of chamfer at small inside diameter forward end	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

Minor:	AQL 2.50 Percent	
201.	Forward end thread major diameter, min.	Gage
202.	Forward end thread relief diameter	Gage
203.	Depth of large diameter cavity forward end, min.	Gage
204.	Length forward end thread relief diameter	Gage
205.	Evidence of poor workmanship (See 3.7)	Visual

4.3.2.2 Nozzle-Launch Motor (See dwg. 9225158, covering a detail of dwg. 9225160).

Categories	Defects	Method of Inspection
Critical:		
1.	Throat diameter, min.	Gage
2.	Thread major diameter, min.	Gage
Major:	AQL 1.00 Percent	
101.	Thread pitch diameter	Gage
102.	Throat diameter, max.	Gage
103.	True position of thread minor diameter with Datums A and C	Gage
104.	Perpendicularity of case butting shoulder with Datum A and C	Gage
105.	Location of exit cone basic diameter	Gage
106.	Thread relief diameter, max.	Gage
107.	Length to case butting shoulder	Gage
108.	Length of thread relief	Gage
109.	Thickness of case butting flange	Gage
110.	Diameter of butting flange, min.	Gage
Minor:	AQL 2.50 Percent	
201.	Thickness of exit cone wall	Gage
202.	Overall length	Gage
203.	Exit cone outside diameter, min.	Gage
204.	Length of exit cone flange, min.	Gage
205.	Evidence of poor workmanship (See 3.7)	Visual

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:07Z
Check the source to verify that this is the current version before use.

4.3.2.3 Support, Propellant (see dwg. 9225159, covering a detail of dwg. 9225160).

Categories	Defects	Method of Inspection
Critical:	None defined.	
Major:	AQL 1.00 Percent	
101.	Shank diameter	Gage
102.	Shank step diameter	Gage
103.	Shank step diameter chamfer, max.	Gage
104.	Perpendicularity of shank step face with shank diameter	Gage
105.	Perpendicularity of aft face with shank diameter	Gage
106.	Length of full thread, min.	Gage
107.	Thread pitch diameter	Gage
108.	Thickness of pin retention segments	Gage
109.	True position of pin retention slots	Gage
110.	Width of pin retention slot	Gage
Minor:	AQL 2.50 Percent	
201.	Thread major diameter, min.	Gage
202.	Overall length, min.	Gage
203.	Length to shank step, min.	Gage
204.	Symmetry of pin retention segment w/slot	Gage
205.	Concentricity of outside diameter of pin retention segment with shank diameter	Gage
206.	Evidence of poor workmanship (See 3.7)	Visual

4.3.3 Testing

4.3.3.1 First Article Sample (See 4.2.1). The assemblies and components submitted as the first article sample shall be tested as specified below after having been examined for requirements as specified in 4.2.2. Rejection and resubmission shall be in accordance with 4.2.3.

4.3.3.1.1 Salt Spray Test (See 3.3 and 4.3.3.2.1).

4.3.3.1.2 Dimensional Stability of Case (See 3.4 and 4.3.3.2.2).

4.3.3.1.3 Hydrostatic Test of Case (See dwg. 9225157 and 4.3.3.2.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

4.3.3.1.4 Magnetic Particle Inspection of Case (See 3.5 and 4.3.3.2.4).

4.3.3.1.5 Burst Test of Case (See 3.6.1) Major Defect. Eight (8) cases shall be subjected to the test as specified in 4.4.5.1, using equipment in accordance with 4.3.4. Any individual case or any group of 8 cases considered to be the first article sample failing to meet the requirements shall be cause for rejection of the first article sample.

4.3.3.1.6 Residual Magnetization (See dwg. 9225157 and 4.3.3.2.6)

4.3.3.1.7 Wall Thickness Examination of Case (See dwg. 9225157 and 4.3.3.2.7).

4.3.3.2 Production

4.3.3.2.1 Salt Spray Test (See 3.3) Major Defect. One (1) test specimen per heat treat batch shall be subjected to the test as specified in 4.4.1, using equipment in accordance with 4.3.4. Failure of the test specimen to comply with the requirement shall reject the heat treat batch represented by the specimen.

4.3.3.2.2 Dimensional Stability of Case (See 3.4) Critical Defect. This examination shall be performed 100 percent as specified in 4.4.2, using equipment in accordance with 4.3.4. Any case failing to comply with the requirements shall be classed defective and shall be removed from the lot.

4.3.3.2.3 Hydrostatic Test of Case (See dwg. 9225157) Critical Defect. This test shall be performed 100 percent as specified in 4.4.3, using equipment in accordance with 4.3.4. Any case failing to comply with the requirements shall be classed defective and shall be removed from the lot.

4.3.3.2.4 Magnetic Particle Inspection of Case (See 3.5) Critical Defect. This test shall be performed 100 percent as specified in 4.4.4, using equipment in accordance with 4.3.4. Any case failing to comply with the requirements shall be classed defective and shall be removed from the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

4.3.3.2.5 Internal Burst Pressure Test of Case (See 3.6.2) Major Defect. One (1) launch motor case shall be randomly selected from each heat treated batch and tested as specified in 4.4.5.2, using equipment in accordance with 4.3.4. The case failing to comply with the requirements shall be cause for rejection of all the cases in that heat treated batch.

4.3.3.2.6 Residual Magnetization (See dwg. 9225157) Major Defect. This test shall be performed 100 percent as specified in 4.4.6, using equipment in accordance with 4.3.4. Any case failing to meet the requirement shall be removed from the lot.

4.3.3.2.7 Wall Thickness Examination of Case (See dwg. 9225157) Major Defect. This examination shall be performed 100 percent as specified in 4.4.7, using equipment in accordance with 4.3.4. Any case failing to comply with the requirements shall be classed defective and shall be removed from the lot.

4.3.4 Inspection Equipment. Inspection equipment required to perform the inspection prescribed in this specification is identified in the Examination (4.3.2) and Test Method (4.4) paragraphs herein. See 6.3 for details concerning responsibilities for inspection equipment design and approval.

4.4 Test Methods and Procedures

4.4.1 Salt Spray Test. The test specimen shall be cut from scrap items, or made from the same steel, heat treated in the same batch as the items and surface finished by the same process. The specimen shall have an external surface of four (4) square inches, minimum. The test specimen shall be used only once and discarded. The test specimen shall be subjected to a 5 percent salt spray test as described in FED-STD-151, Method 811. As an alternate, the 5 percent salt spray test specified in ASTM B117 may be used. Exposure time for the test shall be two (2) hours.

4.4.2 Dimensional Stability of Case. Dimensional examination of the overall length, outside diameter (functional) for total length of case; outside diameter, minimum, for distance indicated (See Note 6 of dwg. 9225157) and the inside diameter shall be performed on the case prior to and after hydrotest. The functional examination shall be performed with ring gage dwg. 9246460.

Source: https://assist.dla.mil -- Downloaded: 202640-18T05:07Z
Check the source to verify that this is the current version before use.

4.4.3 Hydrostatic Test of Case. The case shall be internally pressurized to the pressure, maintained for the time and the test repeated for the number of cycles and pressure between cycles as specified on dwg. 9225616. If water is used as the pressure media, extreme care should be taken to prevent rust. If oil is used as the pressure media, the case will be cleaned of all oil after the test.

4.4.4 Magnetic Particle Inspection. After successful completion of the dimensional stability examination, the case shall be subjected to the magnetic particle inspection in accordance with MIL-I-6868. The continuous wet fluorescent process shall be utilized. Magnetization shall be circular and longitudinal. Observations shall be made for crack-like indications.

4.4.5 Burst Test. The case shall be tested at ambient temperature. During the test a plug that simulates the nozzle throat area and transfers the load to the forward attachment area shall be used. Sealing of the thread is permissible.

4.4.5.1 First Article Testing. The pressure causing burst of the case shall be determined by internally pressurizing the case.

4.4.5.2 Production Testing. The case shall be subjected to an internal pressure of 21,000 psig minimum.

4.4.6 Residual Magnetization. The residual magnetization of the case shall be taken by contacting the surface of the part with the probe of an appropriate meter. The probe shall be run along the entire length of the part on two sides 180 degrees apart at a rate which will permit adequate registration. This examination shall take not less than 20 seconds per launch motor case.

4.4.7 Wall Thickness Examination of Case. The wall thickness of the case shall be examined from the forward thickness transition to the aft thickness transition.

5. PREPARATION FOR DELIVERY

5.1 Packing. Level C. Motor metal parts shall be packaged, packed and marked in accordance with MIL-STD-1169 and the following instructions:

Source: https://assist.dla.mil -- Downloaded: 202640-18T05:07Z
Check the source to verify that this is the currentversion before use.

Each Motor Case with Nozzle Assembled shall be wrapped separately in VCI paper conforming to MIL-P-3420, Type I, Class 3, Style A requirements. The wrapped motor shall be inserted into a fiber tube constructed in accordance with requirements cited in paragraph 3.3 of MIL-C-2439. Approximate size of VCI paper for the Motor shall be 17 by 8 inches. Tube size shall be approximately 17 1/8 inches long by 2 3/16 inches inside diameter with minimum 3/32 inch wall thickness. Alternatively, the tube may be lined with the prescribed VCI paper in lieu of wrapping the motor.

Twenty-four (24) packaged motor s shall be packed in a 25 space fiber box, meeting the requirements of PPP-B-636 for a V3c box. A plain fiberboard pad constructed of PPP-F-320, Type CF, Class Domestic, Variety SW, Grade 275 board shall be inserted on the inside bottom of the box and on top of the box contents. Box size shall be approximately 11 7/8 by 11 7/8 by 17 1/2 inches depth inside dimensions. Pad size shall be equal to the inside length and width of the box less 1/16 inch. Closure shall be in accordance with MIL-STD-1169 or by application of 2 inch wide tape, PPP-T-76, over all top and bottom seams of box with approximately 3 inch extension of tape onto end panels and around corners.

Twenty-four (24) support assemblies shall be packaged in one or more sealed moisture-proof bags. The support assemblies shall then be placed in a fiber tube, as described above, and the tube placed in the 25th space of the box with the packaged motor assemblies.

6. NOTES

6.1 Intended Use. The Motor, Rocket, Launch M114 covered by this specification is intended for use in the TOW Guided Missile, BGM71.

6.2 Ordering Data. Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data Cards. Data cards shall be prepared for each lot in accordance with the information specified in MIL-STD-1167.

c. Inspection equipment design requirements (See 4.3.4 and 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

6.3 Inspection Equipment Designs.-Inspection equipment designs are of two types - Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs are designated by Drawing Numbers (under the "Method of Inspection" headings in Section 4). Design responsibility for all other inspection equipment is assigned to the contractor. Equipment to be designed by the contractor is designated "CD". The contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified, however, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.3.2 and 6.3.3, should he elect to do so.

6.3.1 SIE Designs.-SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.

b. A source control drawing or a specification control drawing, as defined in MIL-STD-100.

c. An envelope drawing, as defined in MIL-STD-100, which establishes the criteria which a detail design shall meet. When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.

6.3.2 Contractor Designs.-Contractor designs are required for all inspection equipment for which SIE designs are not specified, and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is cataloged and available for purchase by the general public). Contractor designs shall include appropriate operating instructions, calibration procedures and maintenance procedures. Commercial equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government, and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commerical equipment, or with SIE designs if not otherwise covered thereby (See 6.3.1 c). Designs shall be of the category and form (per MIL-D-1000) specified in the Contract Data Requirements Lists DD Form 1423). The contractor is referred to MIL-HDBK-204, "Inspection Equipment Design" for guidance. The specification number and other specific identifying information from Section 4 of this specification shall be referenced on each contractor design, together with the component or assembly drawing number and revision letter to which the specific design applies.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

6.3.3 Submission of Designs for Approval.-Contractor designs shall be approved by the Government prior to fabricating or procuring the equipment. Designs shall be submitted for approval to Picatinny Arsenal, ATTN: SARPA-QA-A-R, Dover, New Jersey, 07801, in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements List (DD Form 1423) or in the contract. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will normally be accomplished within one month after receipt.

6.4 Submission of First Article Sample. Instructions as to the submission and location for testing and evaluation of the first article sample shall be obtained from the Contracting Officer. Upon receipt of such request, the Contracting Officer shall advise Picatinny Arsenal and instructions will be issued accordingly. All inquiries should be forwarded to:

Commander
Picatinny Arsenal
ATTN: SARPA-QA-I-Q
Dover, New Jersey 07801

6.5 Definitions

6.5.1 Contractor. Unless otherwise specified, the word "Contractor", used throughout this specification, shall mean any supplier or producer of items or material to the Government. This shall include commercial contractors, sub-contractors, Government-Owned, Contractor-Operated (GOCO) and Government-Owned, Government-Operated (GOGO) plants.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1336-A225

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
Picatinny Arsenal
ATTN: SARPA-AD-E-C-3
Dover, NJ 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the docum DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.