INCH-POUND

MIL-M-14926C(MI)
30 June 1989
SUPERSEDING
MIL-M-14926B(PA)
29 March 1974

MILITARY SPECIFICATION

MOTOR, ROCKET, LAUNCH, M114
PARTS FOR

This specification is approved for use by the U.S. Army Missile Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements not normally covered by the drawings and provides quality assurance provisions for the fabrication of parts and packing of one type of rocket motor designated as Motor, Rocket, Launch M114.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplements thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Missile Command, ATTN: AMSMI-RD-SE-TD-ST, Redstone Arsenal, AL 35898-5270, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1336

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-F-320	-	Fiberboard: Corrugated and Solid, Sheet Stock (Container Grade) and Cut Shapes
PPP-T-76	-	Tape, Packaging, Paper (For Carton Sealing)

MILITARY

MIL-C-2439	-	Container, Ammunition, Fiber, Spirally Wound
MIL-P-3420	-	Packaging Materials, Volatile Corrosion Inhibitor Treated, Opaque
MIL-P-5501/7	-	Caps and Plugs, Protective, Dust and Moisture Seal (Cap-Plug, General Purpose)
MIL-I-43553	-	Ink, Marking, Epoxy Base
MIL-P-46002	-	Preservative Oil, Contact and Volatile Corrosion-Inhibited

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168	-	Ammunition Lot Numbering
MIL-STD-1169	-	Packaging, Packing and Marking for Shipping of Inert Ammunition Components
MIL-STD-1235	-	Single- and Multi-level Continuous Sampling Procedures and Tables for Inspection by Attributes, Functional Curves of the Continuous Sampling Plan
MIL-STD-1949	-	Inspection, Magnetic Particle

(Unless otherwise indicated, copies of the federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

Picatinny Arsenal

9225157	-	Case Launch Motor
9225158	-	Nozzle Launch Motor
9225159	-	Support Propellant

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

9225160 - Metal Parts Assembly TOW Launch Motor - M114
9225616 - Hydrostatic Test
9246460 - Ring, Plain

(Copies of the drawings are available from the Commander, Picatinny Arsenal, NJ 07801.)

U.S. Army Missile Command

13348305 - Metal Parts Assembly TOW Launch Motor - M114
13349876 - Launch Motor

(Copies of the drawings are available from the Commander, U.S. Army Missile Command, ATTN: AMSMI-RD-SE-TD-ST, Redstone Arsenal, AL 35898-5270.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.4.

3.2 Materials. Materials shall be in accordance with applicable drawings and specifications.

3.3 Components and assemblies. The components and assemblies shall comply with all requirements specified on drawing 9225160 and all requirements of applicable standards and specifications.

3.4 Case.

3.4.1 Dimensional stability. The case shall not exhibit any deformation greater than drawing dimensions as a result of hydrostatic test (see 4.6.1.1 and 4.6.2.1).

3.4.2 Surface integrity. There shall be no evidence of cracklike indications or surface flows, including but not limited to laps, slivers, seams, roll-in scale, or tool marks on the case surface (see 4.7.3).

3.4.3 Magnetic particle inspection. At the successful completion of magnetic particle inspection, the case shall be marked with the letter "M" adjacent to the hydrostatic test mark, using contrasting ink in accordance with MIL-I-43553 (see 4.6.1.3, 4.6.2.3, and 4.7.3).

3.5 Performance.

3.5.1 Chamber internal burst pressure.

3.5.1.1 First article. Each individual launch motor case burst as part of the first article shall withstand a minimum internal pressure of 20,500

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

pounds per square inch gage (psig). In addition, the mean of the first article sample minus 4.353 standard deviations shall yield a value of 20,500 psig minimum (see 4.6.1.4).

3.5.1.2 Production units. Each case tested shall withstand a minimum internal pressure of 21,000 psig (see 4.6.2.4).

3.6 Workmanship. All parts and assemblies shall be fabricated in a thorough, workmanship manner. The parts shall be free of burrs, sharp edges, warpage, dirt, rust and other foreign matter. The cleaning method used shall not damage any part, nor shall the cleaning agents contaminate any part. Surface coatings should be continuous, except for scratches not exposing base metal.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of know defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspections. Inspections shall include the examinations and tests classified in 4.2.a on 10 complete sets of parts (see 3.1).

4.3.1 First article submission inspection. The contractor shall submit a first article sample to an approved Government facility designated by the Contracting Officer (see 6.2) for evaluation in accordance with the provisions

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

of 4.5 and 4.6. The first article sample shall consist of 10 complete sets or parts that have been produced by the contractor or furnished by a supplier, and that have been manufactured using the same production processes, procedures, and equipment that will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same sources of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to ensure that it conforms to the requirements of the contract, and if specified in the contract or purchase order, submit a record of this inspection with the sample, including statements of findings of tests and examinations and certificates of conformance for materials (see 4.3.1.1.1). A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days, or whenever a change occurs in manufacturing process, material used, drawings, specifications, or source of supply that significantly affect product uniformity as determined by the Government.

4.3.1.1 Government rights to documentation. The contractor shall furnish the Government if specified in the contract or purchase order, a statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or when commercial specifications are referenced in any of the contractual documents, and that the certificates of conformance are on file and available for review.

4.3.1.2 First article rejection. If any assembly fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon failure of an assembly or component in the sample to comply with any of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article or portion thereof. Until a first article sample is accepted, the contractor is in no way authorized by the Government to initiate regular production unless otherwise directed by the Contracting Officer.

4.4 Quality conformance inspection. Quality conformance inspections shall be as specified in table I.

TABLE I. Quality conformance inspection.

Inspection	Requirement paragraph	Test paragraph
Materials	3.2	4.5
Dimensional stability	3.4.1	4.6.1.1
Surface integrity	3.4.2	4.7.3
Magnetic particle inspection	3.4.3	4.6.1.3
Chamber internal burst pressure	3.5.1	4.6.1.4
Workmanship	3.6	4.5

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

4.4.1 Lot formation. The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn, and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision, and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specification, or drawing, not affecting safety, performance, interchangeability or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each inspection lot of complete launch motor assemblies shall contain parts from not more than one interfix lot number from one manufacturer.

4.4.2 Submission of product. At the time the completed lot of product is submitted to the Government for acceptance, and if specified in the contractor purchase order (see 6.2), the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.

b. Drawing and specification number and date, together with an identification and date of changes thereto.

c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.

d. Number of items in the lot.

e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.4.3 Inspection equipment. Inspection equipment required to perform the inspection prescribed in this specification is identified in the examination (4.5) and test method (4.7) paragraphs herein. See 6.4 for details concerning responsibilities for inspection equipment design and approval.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

4.5 Examinations. Each motor shall be examined for compliance with the requirements specified in 3.2 through 3.6. The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.4.1) of the components or assemblies designated in the applicable paragraph headings. Examinations for Critical Defects (and Major Defects, when so specified) shall be 100 percent. Sampling plans for Major and Minor Defects shall be in accordance with MIL-STD-105, except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQLs designated herein to the groups of Major and Minor Defects listed, the contractor may elect to apply AQLs to individual defects using an AQL of 0.40 for each Major Defect and an AQL of 0.65 for each Minor Defect. When this method is elected, it shall be applied to all of the Major and Minor Defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

4.5.1 Case-Launch Motor (see dwg. 9225157 or 13349876 covering a detail of dwg. 9225160 or 13348305) and table II.

TABLE II. Classification of defect, case-launch motor.

Categories	Defects	Method of Inspection
Critical:		
1.	Aft end thread minor diameter, maximum (max.)	Gage
2.	Aft end thread, full thread, min.	Gage
3.	Evidence of hydrostatic test mark missing	Visual
4.	Evidence of magnetic particle inspection mark missing	Visual
Major:	AQL 1.00	
101.	Aft end thread minor diameter	Gage
102.	Position of aft end minor thread diameter to Datums A and B	Gage
103.	Perpendicularity of aft face with Datums A and B	Gage
104.	Perpendicularity of forward end shoulder with Datums A and B	Gage
105.	Length from forward end to shoulder	Gage
106.	Large inside diameter forward end	Gage
107.	Small inside diameter forward end	Gage
108.	Forward end thread pitch diameter	Gage
109.	Straightness of case outside diameter	Gage
110.	Aft end thread pitch diameter	Gage
111.	Presence of chamfer at small inside diameter forward end	Visual
Minor:	AQL 2.50	
201.	Forward end thread major diameter, min.	Gage
202.	Forward end thread relief diameter	Gage
203.	Depth of large diameter cavity forward end, min.	Gage
204.	Length forward end thread relief diameter	Gage
205.	Evidence of poor workmanship (see 3.6)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

4.5.2 Nozzle-launch motor (see dwg. 9225158, covering a detail of dwg. 9225160 or 13348305) and table III.

TABLE III. Classification of defect, nozzle-launch motor.

Categories	Defects	Method of Inspection
Critical:		
1.	Throat diameter, min.	Gage
2.	Thread major diameter, min.	Gage
Major:	AQL 1.00	
101.	Thread pitch diameter	Gage
102.	Throat diameter, max.	
103.	Position of thread minor diameter with Datums A and C	Gage
104.	Perpendicularity of case butting shoulder with Datums A and C	Gage
105.	Location of exit cone basic diameter	Gage
106.	Thread relief diameter, max.	Gage
107.	Length to case butting shoulder	Gage
108.	Length of thread relief	Gage
109.	Thickness of case butting flange	Gage
110.	Diameter of butting flange, min.	Gage
Minor:	AQL 2.50	
201.	Thickness of exit cone wall	Gage
202.	Overall length	Gage
203.	Exit cone outside diameter, min.	Gage
204.	Length of exit cone flange, min.	Gage
205.	Evidence of poor workmanship (see 3.6)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

4.5.3 Support propellant (see dwg. 9225159, covering a detail of dwg. 9225160 or 13348305) and table IV.

TABLE IV. Classification of defect, support propellant.

Categories	Defects	Method of Inspection
Critical:	None defined.	
Major:	AQL 1.00	
101.	Shank diameter	Gage
102.	Shank step diameter	Gage
103.	Shank step diameter chamfer, max.	Gage
104.	Perpendicularity of shank step face with shank diameter	Gage
105.	Perpendicularity of aft face with shank diameter	Gage
106.	Length of full thread, min.	Gage
107.	Thread pitch diameter	Gage
108.	Thickness of pin retention segments	Gage
109.	Position of pin retention slots	Gage
110.	Width of pin retention slot	Gage
Minor:	AQL 2.50	
201.	Thread major diameter, min.	Gage
202.	Overall length, min.	Gage
203.	Length to shank step, min.	Gage
204.	Position of pin retention segment w/slot	Gage
205.	Position of outside diameter of pin retention segment with shank diameter	Gage
206.	Evidence of poor workmanship (see 3.6)	Visual

4.6 Testing.

4.6.1 First article sample (see 4.3.1). The assemblies and components submitted as the first article sample shall be tested as specified below after having been examined for requirements as specified in 4.5 and 4.6. Rejection and resubmission shall be in accordance with 4.3.1.2.

4.6.1.1 Dimensional stability of case (see 3.4.1 and 4.6.2.1).

4.6.1.2 Hydrostatic test of case (see dwg. 9225157 and 4.6.2.2).

4.6.1.3 Magnetic particle inspection of case (see 3.4.3 and 4.6.2.4).

4.6.1.4 Burst test of case (see 3.5.1.1) Major Defect. Eight cases shall be subjected to the test as specified in 4.7.4 using equipment in accordance with 4.4.3. Any individual case or any group of eight cases considered to be the first article sample failing to meet the requirements shall be cause for rejection of the first article sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

4.6.1.5 Residual magnetization (see dwg. 9225157 and 4.6.2.5).

4.6.1.6 Wall thickness examination of case (see dwg. 9225157 or 13349876 and 4.6.2.6).

4.6.2 Production.

4.6.2.1 Dimensional stability of case (see 3.4.1) Critical Defect. This examination shall be performed 100 percent, as specified in 4.7.1, using equipment in accordance with 4.4.3. Any case failing to comply with the requirements shall be classed defective and shall be removed from the lot.

4.6.2.2 Hydrostatic test of case (see dwg. 9225157 or 13349876) Critical Defect. This test shall be performed 100 percent, as specified in 4.7.2, using equipment in accordance with 4.4.3. Any case failing to comply with the requirements shall be classed defective and shall be removed from the lot.

4.6.2.3 Magnetic particle inspection of case (see 3.4.3) Critical Defect. This test shall be performed 100 percent, as specified in 4.5, using equipment in accordance with 4.4.3. Any case failing to comply with the requirements shall be classed defective and shall be removed from the lot.

4.6.2.4 Internal burst pressure test of case (see 3.5.1.2) Major Defect. One launch motor case shall be randomly selected from each heat treated batch and tested, as specified in 4.7.4.2, using equipment in accordance with 4.4.3. The case failing to comply with the requirements shall be cause for rejection of all the cases in that heat treated batch.

4.6.2.5 Residual magnetization (see dwg. 9225157 or 13349876) Major Defect. This test shall be performed 100 percent, as specified in 4.7.5, using equipment in accordance with 4.4.3. Any case failing to meet the requirement shall be removed from the lot.

4.6.2.6 Wall thickness examination of case (see dwg. 9225157) .Major Defect. This examination shall be performed 100 percent, as specified in 4.7.6, using equipment in accordance with 4.4.3. Any case failing to comply with the requirements shall be classed defective and shall be removed from the lot.

4.7 Test methods and procedures.

4.7.1 Dimensional stability of case.

4.7.2 Hydrostatic test of case. The case shall be internally pressurized to the pressure, maintained for the specified time, and the test repeated for the number of specified cycles and pressure between cycles, as specified on dwg. 9225616. If water is used as the pressure medium, extreme care should be taken to prevent rust. If oil is used as the pressure medium, the case will be cleaned of all oil after the test.

4.7.3 Magnetic particle inspection. After successful completion of the dimensional stability examination, the case shall be subjected to the magnetic

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

particle inspection in accordance with MIL-STD-1949. The continuous wet fluorescent process shall be used. Magnetization shall be circular and longitudinal. Observations shall be made for crack-like indications. Cases showing evidence of crack-like indications on the surface shall be rejected (see 3.4.3).

4.7.4 Burst test. The case shall be tested at ambient temperature. During the test a plug that simulates the nozzle throat area and transfers the load to the forward attachment area shall be used. Sealing of the thread is permissible.

4.7.4.1 First article testing. The pressure-causing burst of the case shall be determined by internally pressurizing the case.

4.7.4.2 Production testing. The case shall be subjected to an internal pressure of 21,000 psig minimum.

4.7.5 Residual magnetization. The residual magnetization of the case shall be taken by contracting the surface of the part with the probe of an appropriate meter. The probe shall be run along the entire length of the part on two sides 180 degrees apart at a rate which will permit adequate registration. This examination shall take not less than 20 seconds per launch motor case.

4.7.6 Wall thickness examination of case. The wall thickness of the case shall be examined from the forward thickness transition to the aft thickness transition.

4.8 Packaging inspection. The preservation, packing, and marking shall be inspected to verify conformance to the requirements of Section 5.

5. PACKAGING

5.1 Preservation. The preservation oil shall meet the requirements of MIL-P-46002. The threads on the head end of the cap shall be protected by cap-plug per MIL-C-5501/7, part number M5501/7-F14.

5.2 Packing. Packing shall be Level C, as specified (see 6.2). Motor metal parts shall be preserved as specified in 5.1, packaged, packed, and marked in accordance with MIL-STD-1169 and the following instructions:

5.2.1 Wrapping of motors. Each motor case with nozzle assembled shall be wrapped separately in volatile corrosion inhibitor (VCI) paper conforming to MIL-P-3420, Type I, Class 3, Style A requirements. The wrapped motor shall be inserted into a fiber tube constructed in accordance with requirements cited in paragraph 3.3 of MIL-C-2439. Approximate size of VCI paper for the Motor shall be 17 by 8 inches. Tube size shall be approximately 17.125 inches long by 2.1875 inches inside diameter with minimum 0.094 inch wall thickness. Alternatively, the tube may be lined with the prescribed VCI paper in lieu of wrapping the motor.

5.2.2 Packing of motors. Twenty-four packaged motors shall be packed in a 25 space fiber box, meeting the requirements of PPP-B-636 for a V3c box. A

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

plain fiberboard pad constructed of PPP-F-320, Type CF, Class Domestic, Variety SW, Grade 275 board shall be inserted on the inside bottom of the box and on top of the box contents. Box size shall be approximately 11.875 by 11.875 by 17.50 inches depth inside dimensions. Pad size shall be equal to the inside length and width of the box less 0.0625 inch. Closure shall be in accordance with MIL-STD-1169 or by application of two inch wide tape in accordance with PPP-T-26, over all top and bottom seams of box with approximately three inch extensions of tape onto end panels and around corners.

5.2.3 Packaging of motors. Twenty-four support assemblies shall be packaged in one or more sealed moisture-proof bags. The support assemblies shall then be placed in a fiber tube, as described above, and the tube placed in the 25th space of the box with the packaged motor assemblies.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The Motor, Rocket, Launch M114, covered by this specification is intended for use in the TOW Guided Missile, BOM71.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Data Cards. Data cards shall be prepared for each lot in accordance with the information specified in MIL-STD-1167.

c. Inspection equipment design requirements (see 4.4.3 and 6.4).

d. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.1.2).

e. When first article is required (see 3.1 and 6.3).

f. Instructions for submission of first article sample.

g. When certification is required (see 4.4.2).

h. Level of packing (see 5.2).

6.3 First article. When a first article inspection is required, the items should be a first article sample. The first article should consist of 10 complete sets of parts, 10 of each subassembly and 10 of each component identified by a drawing or part number. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior government approval is presently appropriate for the pending contract.

6.4 Inspection equipment designs. Inspection equipment designs are of two types - Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs are designated by drawing numbers in the paragraph heading in section 4. Design responsibility for all other inspection equipment is assigned to the contractor. Equipment to be designed by the contractor is designated "CD." The contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified, however, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.4.2 and 6.4.3, should he elect to do so.

6.4.1 SIE designs. SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.

b. A source control drawing or a specification control drawing.

c. An envelope drawing which establishes the criteria which a detail design shall meet. When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.

6.4.2 Contractor designs. Contractor designs are required for all inspection equipment for which SIE designs are not specified, and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is cataloged and available for purchase by the general public.) Contractor designs shall include appropriate operating instructions, calibration procedures, and maintenance procedures. Commercial equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government, and may include illustrations and engineering data. Designs shall be used with commercial equipment, or with SIE designs if not otherwise covered thereby (see 6.4.1c). Designs shall be of the category and form specified in the Contract Data Requirements List (DD Form 1423). The specification number or other specific identifying information from section 4 of this specification shall be referenced on each contractor design, together with the component or assembly drawing number and revision letter to which the specific design applies.

6.4.3 Submisssion of designs for approval. Contractor designs shall be approved by the Government prior to fabricating or procuring the equipment. Designs shall be submitted for approval in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements List (DD Form 1423) or in the contract. Partial submission of the inspection equipment designs is permissible and encouraged. However, the complete date for design review will be based on the date of the final submission of designs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

6.5 Metrication. Whenever inch/pound dimensions are used in this document, metric equivalents in accordance with FED-STD-376 are acceptable.

6.6 Subject term (key word) listing.

Engine
Initiate
Propellant device

6.7 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army - MI

Preparing Activity:
Army - MI

(Project 1336-A583)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.