INCH-POUND

MIL-M-14926D (MI)
13 September 1991
SUPERSEDING
MIL-M-14926C (MI)
30 June 1989

MILITARY SPECIFICATION

MOTOR, ROCKET, LAUNCH, M114
PARTS FOR

This specification is approved for use by the U.S. Army Missile Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements not normally covered by the drawings and provides quality assurance provisions for the fabrication of parts and packing of one type of rocket motor designated as Motor, Rocket, Launch M114.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Missile Command, ATTN: AMSMI-RD-SE-TD-ST, Redstone Arsenal, AL 35898-5270 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1336

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-F-320	-	Fiberboard: Corrugated and Solid, Sheet Stock (Container Grade) and Cut Shapes
PPP-T-76	-	Tape, Packaging, Paper (For Carton Sealing)

MILITARY

MIL-C-2439	-	Container, Ammunition, Fiber, Spirally Wound
MIL-P-3420	-	Packaging Materials, Volatile Corrosion Inhibitor Treated, Opaque
MIL-P-5501/7	-	Caps and Plugs, Protective, Dust and Moisture Seal (Cap-Plug, General Purpose)
MIL-I-43553	-	Ink, Marking, Epoxy Base
MIL-P-46002	-	Preservative Oil, Contact and Volatile Corrosion-Inhibited

STANDARDS

MILITARY

MIL-STD-1168	-	Ammunition Lot Numbering
MIL-STD-1169	-	Packaging, Packing and Marking for Shipping of Inert Ammunition Components
MIL-STD-1949	-	Inspection, Magnetic Particle

(Unless otherwise indicated, copies of the federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Ave., Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

ARMY

9225157	-	Case Launch Motor
9225158	-	Nozzle Launch Motor
9225159	-	Support Propellant

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

9225160	-	Metals Parts Assembly TOW Launch Motor - M114
9225616	-	Hydrostatic Test
9246460	-	Ring, Plain
13348305	-	Metal Parts Assembly TOW Launch Motor - M114
11349876	-	Launch Motor

(Copies of the drawings and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Materials. Materials shall be in accordance with applicable drawings and specifications.

3.3 Components and assemblies. The components and assemblies shall comply with all requirements specified on drawing 9225160 and all requirements of applicable standards and specifications.

3.4 Case.

3.4.1 Dimensional stability. The case shall not exhibit any deformation greater than drawing dimensions as a result of hydrostatic test (see 4.6.1.1 and 4.6.2.1).

3.4.2 Surface integrity. There shall be no evidence of cracklike indications or surface flaws including but not limited to laps, slivers, seams, roll-in scale, or tool marks on the case surface (see 4.7.3).

3.4.3 Magnetic particle inspection. At the successful completion of magnetic particle inspection, the case shall be marked with the letter "M" adjacent to the hydrostatic test mark, using contrasting ink in accordance with MIL-I-43553 (see 4.6.1.3, 4.6.2.3, and 4.7.3).

3.5 Performance.

3.5.1 Chamber internal burst pressure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

3.5.1.1 First article. Each individual launch motor case burst as part of the first article shall withstand an internal gage pressure of not less than 20,500 pounds force per square inch (lbf/in^2). In addition, the mean of the first article sample minus 4.353 standard deviations shall yield a value of not less than 20,500 lbf/in^2 (see 4.6.1.4).

3.5.1.2 Production units. Each case tested shall withstand an internal gage pressure of not less than 21,000 lbf/in^2 (see 4.6.2.4).

3.6 Workmanship. All parts and assemblies shall be fabricated in a thorough, workmanlike manner. The parts shall be free of burrs, sharp edges, warpage, dirt, rust and other foreign matter. The cleaning method used shall not damage any part, nor shall the cleaning agents contaminate any part. Surface coatings should be continuous, except for scratches not exposing base metal.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

4.3 First article inspections. Inspections shall include the examinations and tests classified in 4.2.a on 10 complete sets of parts (see 3.1).

4.3.1 First article submission inspection. The contractor shall submit a first article sample to an approved Government facility designated by the contracting officer (see 6.2) for evaluation in accordance with the provisions of 4.5 and 4.6. The first article sample shall consist of 10 complete sets or parts that have been produced by the contractor or furnished by a supplier, and that have been manufactured using the same production processes, procedures, and equipment that will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same sources of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to ensure that it conforms to the requirements of the contract and if specified in the contract or purchase order, submit a record of this inspection with the sample, including statements of findings of tests and examinations and certificates of conformance for materials (see 4.3.1.1). A sample containing known defects will not be submitted unless specifically authorized by the contracting officer. A first article sample shall also be submitted whenever there is a lapse in production for a period greater than 90 days, or whenever a change occurs in manufacturing process, material used, drawings, specifications, or source of supply that significantly affects product uniformity as determined by the Government.

4.3.1.1 Government rights to documentation. If specified in the contract or purchase order, the contractor shall furnish the Government a statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or when commercial specifications are referenced in any of the contractual documents, and that the certificates of conformance are on file and available for review.

4.3.1.2 First article rejection. If any assembly fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon failure of an assembly or component in the sample to comply with any of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article or portion thereof. Until a first article sample is accepted, the contractor is in no way authorized by the Government to initiate regular production unless otherwise directed by the contracting officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection. Quality conformance inspections shall be as specified in table I.

TABLE I. Quality conformance inspection.

Inspection	Requirement paragraph	Test paragraph
Materials	3.2	4.5
Dimensional stability	3.4.1	4.6.1.1
Surface integrity	3.4.2	4.7.3
Magnetic particle inspection	3.4.3	4.6.1.3
Chamber internal burst pressure	3.5.1	4.6.1.4
Workmanship	3.6	4.5

4.4.1 Lot formation. In this specification the term "inspection lot" is an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn, and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Changes to the process, specification, or drawing, not affecting safety, performance, interchangeability or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each inspection lot of complete launch motor assemblies shall contain parts from not more than one interfix lot number from one manufacturer.

4.4.2 Submission of product. At the time the completed lot of items deliverable under this contract is submitted to the Government for acceptance, and if specified in the contract or purchase order (see 6.2), the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification

b. Drawing and specification number and date, together with an identification and date of changes thereto

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review. The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

d. Number of items in the lot

e. Date submitted.

4.5 Examinations. Each motor shall be examined for compliance with the requirements specified in 3.2 through 3.6. The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.4.1) of the components or assemblies designated in the applicable paragraph headings. Examinations for Critical Defects (and Major Defects, when so specified) shall be 100 percent. Sampling plans for Critical and Major Defects shall be in accordance with Table II.

TABLE II. Sampling plan.

Lot Size	Sample Size
2 to 13	All
14 to 150	13
151 to 280	20
281 to 500	29
501 to 1200	34
1201 to 3200	42
3201 to 10,000	50
10,001 to 35,000	60
35,001 to 150,000	74
150,001 to 500,000	90
500,001 and over	102
In all cases: Acceptance number is ZERO Rejection number is ONE	

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

4.5.1 Case-launch motor (see drawing 9225157 or 13349876 covering a detail of drawing 9225160 or 13348305) and table III.

TABLE III. Classification of defects, case-launch motor.

Categories	Defects	Method of inspection	Sampling plan (tables)
Critical:			
1.	Aft end thread minor diameter, maximum (max.)	Gage	All
2.	Aft end thread, full thread, minimum (min.)	Gage	All
3.	Evidence of hydrostatic test mark missing	Visual	All
4.	Evidence of magnetic particle inspection mark missing	Visual	All
Major:			
101.	Aft end thread minor diameter	Gage	II
102.	Position of aft end minor thread diameter to Datums A and B	Gage	II
103.	Perpendicularity of aft fence with Datums A and B	Gage	II
104.	Perpendicularity of forward end shoulder with Datums A and B	Gage	II
105.	Length from forward end to shoulder	Gage	II
106.	Large inside diameter forward end	Gage	II
107.	Small inside diameter forward end	Gage	II
108.	Forward end thread pitch diameter	Gage	II
109.	Straightness of case outside diameter	Gage	II
110.	Aft end thread pitch diameter	Gage	II
111.	Presence of chamfer at small inside diameter forward end	Visual	II

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

4.5.2 Nozzle-launch motor (see drawing 9225158, covering a detail of drawing 9225160 or 13348305) and table IV.

TABLE IV. Classification of defects, nozzle-launch motor.

Categories	Defects	Method of inspection	Sampling plan (tables)
Critical:			
1.	Throat diameter, min.	Gage	All
2.	Thread major diameter, min.	Gage	All
Major:			
101.	Thread pitch diameter	Gage	II
102.	Throat diameter, max.		
103.	Position of thread minor diameter with Datums A and C	Gage	II
104.	Perpendicularity of case butting shoulder with Datums A and C	Gage	II
105.	Location of exit cone basic diameter	Gage	II
106.	Thread relief diameter, max.	Gage	II
107.	Length to case butting shoulder	Gage	II
108.	Length of thread relief	Gage	II
109.	Thickness of case butting flange	Gage	II
110.	Diameter of butting flange, min.	Gage	II

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

4.5.3 Support propellant (see drawing 9225159, covering a detail of drawing 9225160 or 13348305) and table V.

TABLE V. Classification of defects, support propellant.

Categories	Defects	Method of inspection	Sampling plan (tables)
Critical:	None defined.		
Major:			
101.	Shank diameter	Gage	II
102.	Shank step diameter	Gage	II
103.	Shank step diameter chamfer, max.	Gage	II
104.	Perpendicularity of shank step face with shank diameter	Gage	II
105.	Perpendicularity of aft face with shank diameter	Gage	II
106.	Length of full thread, min.	Gage	II
107.	Thread pitch diameter	Gage	II
108.	Thickness of pin retention segments	Gage	II
109.	Position of pin retention slots	Gage	II
110.	Width of pin retention slot	Gage	II

4.6 Testing.

4.6.1 First article sample (see 4.3.1). The assemblies and components submitted as the first article sample shall be tested as specified below after having been examined for requirements as specified in 4.5 and 4.6. Rejection and resubmission shall be in accordance with 4.3.1.2.

4.6.1.1 Dimensional stability of case (see 3.4.1 and 4.6.2.1).

4.6.1.2 Hydrostatic test of case (see drawing 9225157 and 4.6.2.2).

4.6.1.3 Magnetic particle inspection of case (see 3.4.3 and 4.6.2.4).

4.6.1.4 Burst test of case (see 3.5.1.1) Major Defect. Eight cases shall be subjected to the test as specified in 4.7.4. Any individual case or any group of eight cases considered to be the first article sample failing to meet the requirements shall be cause for rejection of the first article sample.

4.6.1.5 Residual magnetization (see drawing 9225157 and 4.6.2.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

4.6.1.6 Wall thickness examination of case (see drawing 9225157 or 13349876 and 4.6.2.6.

4.6.2 Production.

4.6.2.1 Dimensional stability of case (see 3.4.1) Critical Defect. This examination shall be performed 100 percent, as specified in 4.7.1. Any case failing to comply with the requirements shall be classed as defective and shall be removed from the lot.

4.6.2.2 Hydrostatic test of case (see drawing 9225157 or 13349876) Critical Defect. This test shall be performed 100 percent, as specified in 4.7.2. Any case failing to comply with the requirements shall be classed as defective and shall be removed from the lot.

4.6.2.3 Magnetic particle inspection of case (see 3.4.3) Critical Defect. This test shall be performed 100 percent, as specified in 4.7.3. Any case failing to comply with the requirements shall be classed as defective and shall be removed from the lot.

4.6.2.4 Internal burst pressure test of case (see 3.5.1) Major Defect. One launch motor case shall be randomly selected from each heat treated batch and tested, as specified in 4.7.4.2. Any case failing to comply with the requirements shall be cause for rejection of all the cases in that heat treated batch.

4.6.2.5 Residual magnetization (see drawing 9225157 or 13349876) Major Defect. This test shall be performed 100 percent, as specified in 4.7.5. Any case failing to meet the requirements shall be removed from the lot.

4.6.2.6 Wall thickness examination of case (see drawing 9225157) Major Defect. This examination shall be performed 100 percent, as specified in 4.7.6. Any case failing to comply with the requirement shall be classed as defective and shall be removed from the lot.

4.7 Test methods and procedures.

4.7.1 Dimensional stability of case. Dimensional examination of the overall length, outside diameter (functional) for total length of case; outside diameter, minimim, for distance indicated (see Note 6 of drawing 9225157 or 13349876) and the inside diameter shall be performed on the case prior to and after hydrotest. The functional examination shall be performed with ring gage drawing 9246460.

4.7.2 Hydrostatic test of case. The case shall be internally pressurized to the pressure, maintained for the specified time, and the test repeated for the number of specified cycles and pressure between cycles, as specified on drawing 9225616. If water is used as the pressure medium,

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

extreme care should be taken to prevent rust. If oil is used as the pressure medium, the case shall be cleaned of all oil after the test.

4.7.3 Magnetic particle inspection. After successful completion of the dimensional stability examination, the case shall be subjected to the magnetic particle inspection in accordance with MIL-STD-1949. The continuous wet fluorescent process shall be used. Magnetization shall be circular and longitudinal. Observations shall be made for crack-like indications. Cases showing evidence of crack-like indications on the surface shall be rejected (see 3.4.3).

4.7.4 Burst test. The case shall be tested at ambient temperature. During the test a plug that simulates the nozzle throat area and transfers the load to the forward attachment area shall be used. Sealing of the thread is permissible.

4.7.4.1 First article testing. The pressure-causing burst of the case shall be determined by internally pressurizing the case.

4.7.4.2 Production testing. The case shall be subjected to an internal pressure of not less than 21,000 lbf/in^2.

4.7.5 Residual magnetization. The residual magnetization of the case shall be taken by contacting the surface of the part with the probe of an appropriate meter. The probe shall be run along the entire length of the part on two sides 180 degrees apart at a rate which will permit adequate registration. This examination shall take not less than 20 seconds per launch motor case.

4.7.6 Wall thickness examination of case. The wall thickness of the case shall be examined from the forward thickness transition to the aft thickness transition.

4.8 Inspection of packaging. The sampling and inspection of the preservation, packaging, and container marking shall be in accordance with the requirements of MIL-STD-1169.

5. PACKAGING

5.1 Preservation. The preservation oil shall meet the requirements of MIL-P-46002. The threads on the head end of the cap shall be protected by a cap-plug in accordance with MIL-C-5501/7, part number M5501/7-F14.

5.2 Packing. Packing shall be Level A or B as specified (see 6.2). Motor metal parts shall be preserved as specified in 5.1, packaged, packed, and marked in accordance with MIL-STD-1169 and the following instructions:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

5.2.1 Wrapping of motors. Each motor case with nozzle assembled shall be wrapped separately in volatile corrosion inhibitor (VCI) paper conforming to MIL-P-3420, Type I, Class 3, Style A requirements. The wrapped motor shall be inserted into a fiber tube constructed in accordance with requirements cited in paragraph 3.3 of MIL-C-2439. Approximate size of VCI paper for the motor shall be 17 by 8 inches. Tube size shall be approximately 17.125 inches long by 2.1875 inches inside diameter with not less than a 0.094 inch wall thickness. Alternatively, the tube may be lined with the prescribed VCI paper in lieu of wrapping the motor.

5.2.2 Packing of motors. Twenty-four packaged motors shall be packed in a 25-space fiber box, meeting the requirements of PPP-B-636 for a V3c box. A plain fiberboard pad constructed of PPP-F-320, Type CF, class domestic, variety SW, Grade 275 board shall be inserted on the inside bottom of the box and on top of the box contents. The box size shall be approximately 11.875 by 11.875 by 17.50 inches depth inside dimensions. Pad size shall be equal to the inside length and width of the box less 0.0625 inches. Closure shall be in accordance with MIL-STD-1169 or by application of two inch wide tape in accordance with PPP-T-76, over all top and bottom seams of the box with approximately 3 inch extensions of tape onto end panels and around corners.

5.2.3 Packaging of motors. Twenty-four support assemblies shall be packaged in one or more sealed moisture-proof bags. The support assemblies shall then be placed in a fiber tube, as described above, and the tube placed in the 25th space of the box with the packaged motor assemblies.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The Motor, Rocket, Launch M114, covered by this specification is intended for use in the TOW Guided Missile, BOM71.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of the specification

b. Data Cards. Data cards shall be prepared for each lot in accordance with the information specified in MIL-STD-1167.

c. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1)

d. When first article is required (see 3.1 and 6.3)

e. Instructions for submission of first article sample

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

f. When certification is required (see 4.4.2)

g. Level of packing (see 5.2).

6.3 First article. When first article inspection is required, the contracting officer should provide specific guidance to offerers whether the item(s) should be a first article sample, a first production item, or a number of items to be tested as specified in 4.3. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.4 Metrication. Metric equivalents in accordance with FED-STD-376 are acceptable for use in this specification.

6.5 Subject term (keyword) listing.

Engine
Ignition device
Propellant device

6.6 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army - MI

Preparing Activity:
Army - MI

(Project 1336 - A616)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-M-14926D (MI)	910913

3. DOCUMENT TITLE
MOTOR, ROCKET, LAUNCH, M114 PARTS FOR

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
COMMANDER U.S. ARMY MISSILE COMMAND	(1) Commercial (205) 876-6980	(2) AUTOVON 746-6980
c. ADDRESS (Include Zip Code) ATTN: AMSMI-RD-SE-TD-ST REDSTONE ARSENAL, AL 35898-5270	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD FORM 1426 89 OCT

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:07Z
Check the source to verify that this is the current version before use.