MILITARY SPECIFICATION

PROJECTILE, 8 INCH, M509A1
METAL PARTS ASSEMBLY

This amendment forms a part of Military Specification MIL-P-14895E (AR), dated 25 April 1983, and is approved for use by the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.3.2.1: Delete in its entirety.

PAGES 17 AND 18

4.4.2.3: Delete in its entirety and substitute new pages 17 & 18.

PAGE 19

4.4.2.4, Major 101: Delete in its entirety.

PAGE 20

4.4.2.5, Title: Delete "(Prior to final machining of boat-tail)".

Critical: Delete "None defined" and replace with the following:

"1. Metal defective - 100% 3.4.1 4.5.3.2"

Under Special Category: Delete Special "b" in its entirety and add the following:

"c. Base threads damaged or not full - 100% 3.1 Visual"

Majors 104 and 105: Delete in their entirety.

FSC 1320

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:04Z
Check the source to verify that this is the current version before use.

PAGE 22

4.4.2.5, Major 127: Delete "undercut".

PAGE 23

4.4.2.5, Major 138: Delete in its entirety.

Major 140: Delete "undercut".

Major 147: Delete in its entirety.

Add the following under Major:

"148. Depth from rear face to basic diameter forward of base thread	.40	3.1	Gage
149. Min. depth of full form base thread	.40	3.1	Gage
150. True position of rear counterbore to base thread	.40	3.1	Gage
151. Straightness of a diametral element of the rear surface	.40	3.1	Gage
152. Pitch diameter of base thread	.40	3.1	Gage
153. Minor diameter of base thread, max.	.40	3.1	Gage
154. Runout of base thread pitch diameter with bourrelets and rear surface	.40	3.1	Gage
155. Runout of boat-tail with bourrelets and rear surface	.40	3.1	Gage
156. Location of index mark with keyway	.40	3.1	Gage
157. Length from rear end to outside basic diameter on boat-tail	.40	3.1	Gage
158. Diameter of rear counterbore	.40	3.1	Gage"

PAGE 24

4.4.2.5, Minor Category: Add the following:

"212. Location of marking	.65	3.1	Gage
213. Marking missing, incorrect or illegible	.65	3.1	Visual
214. Protective coating incomplete or damaged	.65	3.1	Visual"

PAGE 25

4.4.2.6: Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 9343032
4.4.2.3	Base				NEXT HIGHER ASSEMBLY 10551896
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Metal defective		100%	3.1	4.5.9
Special					
a	Threads damaged or not full		100%	3.1	Visual
Major					
101	Forward runout on boat-tail with pitch diameter of thread and shoulder		.40	3.1	Gage
102	Rear runout on boat-tail with pitch diameter of thread and shoulder		.40	3.1	Gage
103	Straightness of a diametral element of shoulder		.40	3.1	Gage
104	Length from shoulder to forward basic diameter on boat-tail		.40	3.1	Gage
105	Length from shoulder to rear basic diameter on boat-tail		.40	3.1	Gage
106	Length from front face to shoulder		.40	3.1	Gage
107	Length from front face to end of thread relief groove		.40	3.1	Gage
108	Depth of wrench hole (2 places)		.40	3.1	Gage
109	Width of o-ring groove		.40	3.1	Gage
110	Thickness through base web		.40	3.1	Gage
111	Diameter of flat		.40	3.1	Gage
112	Diameter of o-ring groove		.40	3.1	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9343032
4.4.2.3	Base				NEXT HIGHER ASSEMBLY 10551896
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
113	True position of flat to thread pitch diameter		.40	3.1	Gage
114	Pitch diameter of thread		.40	3.1	Gage
115	Major diameter of thread		.40	3.1	Gage
116	Yield strength and percent elongation	*		3.6.2	4.5.1.5
117	Protective finish	*		3.1	4.5.8
118	Microstructure	*		3.1	4.5.6
Minor					
201	Depth from cavity basic diameter to bottom of cavity		.65	3.1	Gage
202	Length from rear surface to shoulder		.65	3.1	Gage
203	Diameter of thread relief groove		.65	3.1	Gage
204	Width of thread relief groove		.65	3.1	Gage
205	Presence and location of wrench holes		.65	3.1	Visual/Func. Gage
206	Radii or chamfers missing		.65	3.1	Visual
207	Surface finish improper		.65	3.1	Visual
208	Burr		.65	3.1	Visual
209	Coating incomplete or damaged		.65	3.1	Visual
210	Coating on excepted surfaces		.65	3.1	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:04Z
Check the source to verify that this is the current version before use.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1320-A758)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:04Z
Check the source to verify that this is the current version before use.