[METRIC]
A-A-3102
May 23, 1997

COMMERCIAL ITEM DESCRIPTION
PAPER, TABULATING MACHINE CONTINUOUS FLAT FOLD

The General Services Administration has authorized the use of this commercial item description as a replacement for UU-P-546 which is cancelled.

1. **SCOPE** This description covers tabulating forms for use on automatic data processing equipment equipped with a sprocket feed mechanism.

2. **CLASSIFICATION** Tabulating forms covered by this commercial item description shall be of the following two types and styles.

Type I - Single copy

Type II -Multi-copy
Style A -Carbon interleaved
Style B -Chemical Transfer Carbonless
Style C -Chemical Self-imaging Carbonless

3. SALIENT CHARACTERISTICS

3.1 Materials:

3.1.1 Paper: The paper shall be at least 95 percent bleached chemical pulp, with not more than 5 percent unbleached and/or groundwood pulp. The paper shall be tested in accordance with TAPPI T401 for fiber composition. For "Designated Carbonless Forms" only and provided that all other requirements are met, the paper may be made from a minimum 40 percent bleached chemical pulp and a maximum 60 percent groundwood, when tested in accordance with TAPPI T401 for fiber composition. No polychlorinated biphenyol's (PCB'S) shall be added or used during the manufacture of the paper or in any coating operation of the base paper. As evidence of compliance, the contractor shall submit a certificate stating that no polychlorinated biphenyls have been added or used during the manufacturing or converting operations.

Beneficial comments, recommendations, additions, deletions, clarifications etc. Any data, which may improve this document, should be sent to:

General Service Administration
Federal Supply Service,
Engineering Branch (2FYEE)
26 Federal Plaza, New York, NY 10278.

FSC 7530

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:29Z
Check the source to verify that this is the current version before use.

3.1.1.1 Basis weight: The basis weight of the paper shall be as specified in the Ordering Data and shall be expressed as g/m^2 (lbs, 17x22-500). The basis weight tolerance shall be ± 5% unless otherwise specified in the Ordering Data. Basis weight shall be tested in accordance with TAPPI T410.

3.1.1.2 Sizing: The paper shall be suitably sized for writing on with ink without spreading or feathering. Conformance shall be determined by testing in accordance with section 5.6.2.

3.1.1.3 Color: Unless otherwise specified in the Ordering Data, the color of the paper shall be white.

3.1.1.4 Brightness: The brightness shall be 75% minimum for single and carbon interleaved forms and 78% minimum for carbonless forms, unless otherwise specified in the Ordering Data. Testing for brightness shall be in accordance with TAPPI T452.

3.1.1.5 Dimensions: The tabulating forms shall be furnished in the size(s) specified in the Ordering Data. The width shall be the overall form width in inches including the marginal aligning strips. The length shall be the distance in inches between the horizontal perforated tear lines. Form tolerances: A tolerance of 1.588 mm (± 1/16 inch) shall be allowed on the width of the forms. The length shall not vary by more than 0.794 mm (± 1/32 inch) from the specified length. The length of a strip of forms whose total length is nearest to 304.801 cm (120 inches) shall not vary by more than 2.381 mm (± 3/32 inch) from the specified length of a single form time the number of forms in the strip.

3.1.2 Carbon leaves: The carbon leaves for type II, style A, tabulating paper sets shall be a continuous strip, black, of good quality, and with the necessary graded sensitivity to ensure clear, legible copies on all parts of the set, when processed on a (sprocket feed) printers,decollators and others forms handling equipment. The carbon coating may cover only the area between marginal aligning strips or extend to the edge of the carbon tissue, at the contractor's option.

3.1.2.1 Carbon Paper Tolerances: The width of the carbon paper shall be specified in the Ordering Data. When full width carbons are specified, they shall extend the full width of the form. The carbon paper shall extend not more than 0.794 mm (1/32 inch) beyond either vertical edge nor be less than 1.588 mm (1/16 inch) narrower than the form. When carbons are specified to be short on one or both margins, the location of the carbon paper edge and the tolerances permitted shall be as specified in the Ordering Data. The length of the carbons shall not vary from the actual form length by more than 0.397 mm (±1/64 inch) and the length of the carbons for a continuous length of sets closes to 304.801 cm (120 inches) shall not vary from the length of the forms by more than 1.588 mm (±1/16 inch).

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:29Z
Check the source to verify that this is the currentversion before use.

3.2 Assembly of forms: All forms shall be marginally punched and flat folded. When specified forms shall be furnished with vertical perforations and punched holes for filing. Multi-part sets shall be joined by one of the methods specified in the Ordering Data. A form set shall be that material between two consecutive horizontal perforations.

3.2.1 Perforations: All perforations shall be clean cut and sufficiently deep to permit easy separation but do not tear in ordinary handling or in feeding through the machine.

3.2.1.1 Marginal aligning strips: Forms shall include marginal aligning strips of not less than 9.525 mm (3/8 inch) nor more than 15.875 mm (5/8 inch)on the left and right sides, with or without vertical tear-line perforations, as specified in the Ordering Data. Width of the aligning strips within these limitations shall be at the supplier's option, unless otherwise specified in the Ordering Data.

3.2.1.2 Vertical tearline perforations: The location of the vertical tearlines and whether parts and carbons or parts only are to be perforated shall be as specified in the Ordering Data. When vertical tearline perforations are specified, the cut and uncut portions shall ensure straight and proper tears.

3.2.1.3 Horizontal tearline perforations: Horizontal tearline perforations shall be positioned 6.350 mm (1/4 inch) above the center of the top marginal aligning holes. The horizontal tearline perforations shall be positioned at a 90^0 angle to a vertical line through the center of all marginal aligning holes in either margin. The perforations shall be cut through both forms and carbons. The cut and uncut portions shall ensure straight and proper tears.

3.2.1.4 Microperforations: Perforations of all single part forms shall contain a minimum of 50 ties per inch for the vertical and horizontal tearlines, unless otherwise specified in the Ordering Data. Conformance shall be determined in accordance with section 5.5.

3.2.2 Punching:

3.2.2.1 Marginal punching: Tabulating paper in accordance with this specification shall be punched in the right and left aligning margins with round holes 3.969 mm $\pm$ 0.397 mm (5/32 inch +/- 1/64 inch) in diameter, except that the holes adjacent to the top and bottom horizontal tearline perforations in both margins shall be 4.763 mm $\pm$ 0.397 mm (3/16 inch $\pm$ 1/64 inch) or 3.969 mm $\pm$ .3969 mm (5/32 $\pm$ 1/64 inch). The bottom marginal holes of a form shall be located 6.350 mm $\pm$ 0.794 mm (1/4 inch $\pm$ 1/32 inch) above the horizontal tearline perforation and all holes shall be set 6.350 mm $\pm$ 0.397 mm (1/4 inch $\pm$ 1/64 inch) or -0.795 mm (-1/32 inch) from the edge of the form, measured to the center of the hole. Hole shall be spaced vertically 12.700 mm $\pm$ 0.397 mm (1/2 inch $\pm$ 1/64 inch), center to center, for

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:29Z
Check the source to verify that this is the current version before use.

full length of the forms and identically located on all copies of all sets throughout each pack of forms. The marginal holes shall extend in a straight line parallel to the sides of the continuous strip, perpendicular to the horizontal perforations. Holes punched in carbons shall not be less than the actual size of the holes punched in the form and not greater than 5.556 mm (7/32 inch) in diameter. Carbons shall be punched in the margins and flush with the edge of the form. Carbons positioned between and extending from the inner edge of the marginal holes on one side of the form to the inner edge of the form holes on the opposite margins shall not be punched. Holes in carbons shall be centered with the corresponding holes in the form. All holes must be clean cut and the forms, as delivered, completely free of waste.

3.2.2.2 File punching: When specified in the Ordering Data, prepunched holes 6.350 mm ± 1.588 mm (1/4 inch +/- 1/16 inch) in diameter shall be located at the top, bottom, or top and bottom of each set, 15.875 mm ± 3.175 mm (5/8 inch ± 1/8 inch) from the horizontal perforation measured to the center of the hole. The number of holes and distance between holes shall be as specified, with a tolerance of ± 1.588 mm (+/-1/16 inch). Unless otherwise specified in the Ordering Data, the holes shall be equidistant from the vertical edges of the form when the perforated margin portion is removed.

3.2.3 Joining: Type II forms shall be joined in the marginal aligning strip by one of the following methods as specified in the Ordering Data.

3.2.3.1 Temporary joining: Temporary joining shall include crimping or fugitive gluing. This joining is fastening which permits gravity or mechanical separation of parts and carbon leaves, as applicable, without the necessity of first stripping off the fastened marginal aligning strip.

3.2.3.1.1 Crimping: Crimping is a method of joining in which the forms are die embossed or cut in one or both marginal aligning strips thereby interlocking the parts and carbons. Carbon interleaves shall be fastened by at least one prong of a four prong crimp in one margin and by at least one prong of the crimp in the opposite margin. Crimps shall be spaced at not more than 76.200 mm (3 inch) intervals and shall fall not closer than 9.601 mm (3/8 inch) to the horizontal tearlines.

3.2.3.1.2 Fugitive gluing: Fugitive gluing is a method of pasting a carbon to the back of the preceding part with a special glue that will hold sufficiently so keep the carbon in place on the printer and release when forms pass over a carbon decollator. Forms shall also be crimped in both margins with at least two prongs. Crimps shall be spaced at not more than 76.200 mm (3 inch) intervals and shall not fall closer than 9.525 mm (3/8 inch) to the horizontal tearline.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:29Z
Check the source to verify that this is the current version before use.

3.2.3.2 Permanent joining: Permanent joining shall include firm gluing, or a flexible stub. A fastening which requires stripping off the fastened marginal aligning strip before separating parts and carbon leaves.

3.2.3.2.1 Firm gluing: Firm gluing is a method in which adhesive is applied within the marginal aligning strips in such a manner that the forms are tightly held. A combination of fanfolding and firm gluing, open on one side, may be furnished.

3.2.3.2. Flexible stub: Flexible stub is a method of construction in which adhesive is applied within the marginal aligning strip(s) and the strip(s) is constructed in such a manner as to allow parts and carbons to move and adjust to each other as the sets pass through the machine.

3.2.3.3 Combination joining: Combination joining shall include any combination of temporary and permanent fastening. It requires stripping off the fastened marginal aligning strip before separating parts and carbon leaves.

3.2.4 Printing: Tabulating paper forms shall be printed as specified in the Ordering Data. Printing may consist of horizontal lines or alternate shaded areas as follows:

3.2.4.1 Line printing: When specified, horizontal lines shall be printed on the face of each part in the form set with black, gray, or green ink. There shall be 2, 3 or 6 lines per inch as specified in the Ordering Data. All horizontal lines shall be positioned at a 90^0 angle to a vertical line through the center of all marginal aligning holes in either margin. Discontinuities in broken lines shall not exceed 3.175 mm (1/8 inch). The last line of a set need not be printed if it falls on a horizontal perforation.

3.2.4.1.1 Two lines per inch: When two lines per inch are specified, the lines shall be alternatively heavy and light or broken. The first line shall be heavy and 12.7000 mm (1/2 inch) below the horizontal perforation. All lines shall be 12.7000 mm (1/2 inch) apart.

3.2.4.1.2 Three lines per inch: When three lines per inch are specified, the first and second lines shall be light or broken and the third line shall be heavy. Every third line thereafter shall be heavy. The first line shall be 8.458 mm (1/3 inch) below the horizontal perforation. All lines shall be 8.458 mm (1/3 inch) apart.

3.2.4.1.3 Six lines per inch: When six lines per inch are specified, the first and fourth lines shall be heavy and the second, third, fifth, and sixth lines shall be light or broken. Every first and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:29Z
Check the source to verify that this is the current version before use.

fourth line thereafter shall be heavy. The first line shall be 1.588 mm (1/6 inch) below the top horizontal perforation. All lines shall be 1.588 mm (1/6 inch) apart.

3.2.4.2 Green Bar Format: When specified in the Ordering Data, forms shall be printed with alternate tinted light green and white bars, in lieu of line printing. As specified, there shall be 2, 3, 6 or 8 alternating white and green bars per inch, beginning with a white bar. The width of the bars shall be 12.700 mm (1/2"), 8.458 mm (1/3"), 1.588 mm $\pm$ 0.794 mm (1/6" +/- 1/32") or 3.175 mm (1/8"), as applicable. The color of the tinted portion shall be such to permit printed numerals or characters to be readily distinguishable on all parts of a form.

3.2.5 Single Part Sets: Type I sets shall consist of a continuous strip of paper, conforming to 3.2, flat folded at the horizontal tear-line perforations to produce the number of single part sets specified in the Ordering Data. Unless otherwise specified, the basis weight of the paper shall be 75 g/m^2 (20 lbs).

3.2.6 Carbon Interleave Sets: Type II, Style A sets shall consist of two or more continuous strips of paper conforming to 3.1.1, interleaved with a continuous strips of carbon paper conforming to 3.1.2 The number of strips (parts) comprising a multi-part set shall be specified in the Ordering Data. The sets shall be flat folded at the horizontal tearline to produce the number of multi-part sets specified in the Ordering Data. Unless otherwise specified in the Ordering Data. The basis weight of paper and carbon interleaves shall be as selected by the contractor to insure compliance with the performance requirements in 5.6.1. The method of joining shall be as specified in the Ordering Data.

3.2.7 Chemical Transfer Carbonless Sets: Type II, Style B sets shall consist of 2 to 6 strips of surface coated papers. The coatings shall be chemically reactive materials so that the impact of the printer type face on the top part of a multi-part set shall develop images of the imprinted characters on subsequent underlying parts. The top sheet shall be coated on the back(CB) and the bottom sheet shall be coated on the front (CF). Middle parts shall be coated front and back (CFB). The front and back surface coatings shall be the same color. The number of strips (parts) comprising a multi-part set shall be as specified in the Ordering Data. The sets shall be flat folded at the horizontal tearline to produce the number of multi-part sets specified in the Ordering Data. Unless otherwise specified in the Ordering Data. The basis weight of the paper shall be as selected, by the contractor, to insure compliance with the performance requirement in 5.6.1.

3.2.8 Chemical Self-imaging Carbonless Sets: Type II, Style C, sets shall consist of two to six strips of pressure activated, self-imaging paper. The self-imaging paper shall be fabricated to ensure that the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:29Z
Check the source to verify that this is the current version before use.

impact of the printer type face on the top part of multi-part sets shall develop images of the imprinted characters on subsequent underlying parts. The number of strips (parts) comprising a multi-part set shall be as specified in the Ordering Data. The sets shall be flat folded at the horizontal tear-line to produce the number of multi-part sets specified in the Ordering Data, Unless otherwise specified in the Ordering Data, the basis weight of the paper shall be as selected by the contractor, to insure compliance with the performance requirement in 5.6.1.

3.3 Forms continuity: Each strip shall have no more than one break per shipping container with not less than 100 continuous forms in any broken strip. Not more than 10 percent of the shipping containers shall contain broken strips. No splices shall be permitted.

3.4 Workmanship: The forms shall be clean and free from dirt, foreign matter, tears, wrinkles, creases, folds (other than at the horizontal tearline), paper dust, lint, or grit or other defects which adversely affect appearance or serviceability.

4. REGULATORY REQUIREMENT

4.1 Certification: The contractor shall certify that the regulatory requirements for recovered materials shall be as specified in the Ordering Data and applicable solicitation. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4.2 Bleaching: To obtain an acceptable brightness, in accordance with the performance standards of this document, a chemical bleaching process may be used. When specified in the ordering data (See Ordering Data), the bleaching process shall not include the use of chlorine, chlorine dioxide, or other chlorine compounds. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4.3 Labeling: The recycled content shall be marked on the product or unit pack.

5. QUALITY ASSURANCE PROVISIONS

5.1 Product Conformance: The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specification, standards and quality assurance practices and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:29Z
Check the source to verify that this is the current version before use.

Suppliers are encouraged to use quality control (QC) techniques that exhibit control over their processes (e.g. (Statistical Process Control) SPC techniques) as defined in American National Standards Institute (ANSI)/American Society for Quality Control (ASQC) ANSI/ASQC, Z1.1, Z1.2 and Z1.3 (ASQC) B.1, B.2 and B.3 that systematically reduce excess variations. Objective evidence shall be available that demonstrates overall measurement adequacy techniques and controls. These techniques shall ensure quality levels equal to, or greater than, those cited in applicable technical document or, herein. End item inspection/testing may be used by the offeror or the Government representative, as a means to determine the effectiveness of the in process quality controls. In process controls shall not be substituted for end item performance testing. For those characteristics for which there are no such controls, or for end item performance test, lot by lot sampling for inspection/test shall be required. Sampling shall be in accordance with the (ANSI/ASQC) Z1.4, Sampling procedures and Tables for inspection by Attributes.

5.2 Paper Component Testing: Each lot of paper used in the manufacture of the tabulating forms shall be sampled and tested for basis weight and fiber analysis, color and brightness in accordance with the methods specified in the Table I.

Table I

Characteristic	Test Method	
Basis Weight	TAPPI	T 410
Fiber Composition	TAPPI	T 401
Color	TAPPI	T 524
Brightness	TAPPI	T 452

5.2.1 Writing quality: Characters shall be written on one part (chosen alternately from specimen to specimen) of a set with a one percent aqueous solution of Acid Red 1 Color Index Number 18050 or Acid Green 3 Color Index Number 42085. The characters shall be clear cut and shall not feather. The Acid Red 1 or the Acid Green 3 may be obtained from Pylam products, International Dyestuffs Corp., Sandoz, Incorporated and Ciba-Geigy Chemical Corp.

5.3 Examination for dimensional defects: The sample unit for this examination shall be a continuous strip of forms whose length comes closest to 304.80 cm (120 inches). The inspection level shall be S-1 and the acceptable quality level shall be 2.5 percent defective. The examination for length of a continuous strip shall be made on the entire sample unit. All other dimensional examinations shall be made on one set.

5.4 Microperforations: Microperforations shall be examined as follow:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:29Z
Check the source to verify that this is the current version before use.

Randomly, select a sample consisting of two attached sheets. Carefully examine the vertical perforations along each side of the sheets and the horizontal perforations between the two sheets. There shall be no more than two ties (the uncut area between perforated cuts) in succession which exceed 0.794 mm (1/32 of an inch) each in length for each of the sheets examined.

The number of ties per inch of the vertical perforations on the right side margin is determined by using a magnifier having a minimum magnification of ten and a measuring device capable of measuring to 0.397 mm (1/64 inch), or smaller. Align the center of one of the ties to the center of one of the markings on the device. Mark of an inch length of perforation, and count the number of ties within that length. Repeat the above procedure for the vertical perforations on the left side margin and for one of the horizontal perforations. Shall not be less than the required and specific number of ties per inch for any of the perforations examined.

5.5 End Item Tests: The end item shall be tested for performance and capability of being copied and writing quality. The sample unit for performance testing shall be 100 (one-hundred) complete sets and for writing quality testing shall be five complete sets. The inspection level shall be S-1, with an AQL of 2.5 percent defective. Tabulating paper in accordance with this Commercial Item Description shall be constructed to provide satisfactory processing on all properly adjusted printers (sprocket feed type), decollators, and other forms handling equipment. Color and brightness must be done on an End Item Test bases only for TYPE II Multi-copy that included for Style A, Style B and Style C.

5.5.1 Performance: Tabulating paper in accordance with this Commercial Item Description shall be constructed to provide satisfactory processing on all properly adjusted printers (sprocket feed type), decollators, and other forms handling equipment. All parts of multi-part forms shall produce legible copies immediately after printing. (A) Feed 100 complete sets of the tabulating paper through any printer designed to accommodate the paper type. The printer shall be maintained and adjusted in accordance with the manufacturer's instructions to accommodate the applicable number of parts in the papers. To be considered acceptable:
1. There shall be no paper caused jams or interruptions.
2. The printing on each part of the paper shall be immediate and clearly legible.

The government reserves the right to direct the supplier to perform the testing, using any commonly available printer rated at a designated speed. Furthermore, the government reserves the right to require the test to be performed on commonly available printers with different designated speed ratings during the contract period. If so directed, the supplier shall be provided reasonable time to make

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:29Z
Check the source to verify that this is the current version before use.

suitable test arrangements, consistent with the timely performance of delivery requirements.

6. **PACKAGING, PACKING, LABELING AND MARKING** packaging, packing, labeling and marking shall be as specified in the contract or order.

7. **NOTES**

7.1 Referenced Documents: The issue of the referenced documents in effect on the date of the solicitation for offers or request for proposals shall be used to determine conformance with the requirements of this Commercial Item Description.

7.1.1 TAPPI test methods are available from: Technical Association of the Pulp and Paper Industry, Technology Park/Atlanta, P.O. Box 105113, Atlanta, GA 30348 (404) 446-1400

7.1.2 ANSI/ASQC is available from: American Society for Quality Control,P.O.BOX 3005,611 E. Wisconsin Avenue, Milwaukee,WI 53201-4606

7.2 Ordering Data: Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

1) Type, style, color and size required.
2) Type of equipment on which forms are to be used.
3) Basis weight of paper, color and brightness.
4) Whether vertical tearline perforations and location is required.
5) Location, center to center distance of filing holes, as applicable.
6) Number of parts for type II set and method of jointing.
7) Width and tolerance of carbon leaves.
8) Whether line or bar printing is required.
9) Specific, packaging, packing, marking and palletization.
10) If microperforations are not required for 91/2" x11" forms.
11) Whether bleaching without use of chlorine, chlorine dioxide, or hypochlorite is required.

8. **List of NSN'S**

7530-00-011-8509	7530-00-531-7922	7530-00-551-9506
7530-00-052-7918	7530-00-731-5363	7530-00-551-9507
7530-00-052-7919	7530-00-800-0996	7530-00-551-9508
7530-00-052-7922	7530-00-838-9129	7530-00-551-9509
7530-00-052-7921	7530-01-028-7105	7530-00-682-6849

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:29Z
Check the source to verify that this is the current version before use.

7530-00-057-9487	7530-01-029-1157	7530-00-682-6851
7530-00-144-9600	7530-01-029-1158	7530-00-682-6853
7530-00-144-9601	7530-01-030-1420	7530-00-761-1861
7530-00-144-9602	7530-01-057-0167	7530-00-761-1862
7530-00-144-9606	7530-01-068-5255	7530-00-761-1863
7530-00-144-9618	7530-01-338-0625	7530-00-761-1864
7530-00-144-9630	7530-01-343-2123	7530-00-761-1865
7530-00-144-9652	7530-00-038-6487	7530-00-761-1866
7530-00-144-9661	7530-00-052-7921	7530-00-761-1867
7530-00-145-0414	7530-00-052-7922	7530-00-761-1869
7530-00-145-0415	7530-00-068-1658	7530-00-762-2441
7530-00-145-0416	7530-00-082-2409	7530-00-904-3225
7530-00-145-0417	7530-00-175-6078	7530-00-916-4167
7530-00-145-0418	7530-00-180-5923	7530-00-995-2586
7530-00-145-0419	7530-00-180-5924	7530-01-015-9464
7530-00-185-6751	7530-00-249-4840	7530-01-027-4023
7530-00-185-6752	7530-00-249-4845	7530-01-045-5870
7530-00-185-6754	7530-00-249-4846	7530-01-123-3296
7530-00-185-6757	7530-00-271-8917	7530-01-188-0437
7530-00-249-4842	7530-00-271-8919	7530-01-207-3806
7530-00-249-4843	7530-00-273-9232	7530-01-212-7525
7530-00-249-4844	7530-00-406-1295	7530-01-216-4263
7530-00-249-4847	7530-00-428-4203	7530-01-243-6644
7530-00-264-3703	7530-00-464-0622	7530-01-379-8529
7530-00-356-9521	7530-00-551-9505	7530-01-434-0042
7530-01-434-0043	7530-01-434-1267	7530-01-436-7060

Military Interests:
Activity:
DOD has waived coordination of this document

Preparing

GSA -FSS

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:29Z
Check the source to verify that this is the currentversion before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:29Z
Check the source to verify that this is the current version before use.