[METRIC]
A-A-2015C
December 10, 1991
SUPERSEDING
A-A-2015B
June 1, 1989

COMMERCIAL ITEM DESCRIPTION

CREDENZA (STEEL, CONTEMPORARY STYLE)

The General Services Administration has authorized the use of this Commercial Item Description in preference to Interim Federal Specification AA-C-001919.

Salient characteristics. These characteristics concisely describe the essential physical and functional/performance features of the commercially available item.

Design. The credenzas shall be contemporary style designed for heavy duty, office use. Drawer fronts shall overlap pedestal fronts.

Styles.

Style A - Consisting of 4 sections.
Two sections, each containing one storage drawer and one letter size, file drawer. One double section with an adjustable shelf and two hinged or sliding doors. One section containing three storage drawers. Overall dimensions 1900 mm W X 500 mm D X 750 mm H.

Style B - Consisting of 3 sections.
Two sections, each containing one storage drawer and one letter size, file drawer. One double section with an adjustable shelf and two hinged or sliding doors. Overall dimensions 1500 mm W X 500 mm D X 750 mm H.

Style C - Consisting of 1 double section.
One double section with an adjustable shelf and two hinged or sliding doors. Overall dimensions 755 mm W X 500 mm D X 750 mm H.

Style D - Consisting of 2 sections and a kneespace.
Two sections, each containing one storage drawer and one letter size, file drawer separated by a kneespace with a back panel (double width). Overall dimensions 1500 mm W X 500 mm D X 750 mm H.

Notes: 1 - Unless otherwise specified, dimensions shall have a tolerance of ± 25 mm.
2 - Height shall be measured with glides fully retracted.

FSC 7110

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:18Z
Check the source to verify that this is the current version before use.

General construction.

Laminated tops. The credenza shall have a particleboard top with a self-edged, high pressure laminated plastic face and a backing sheet to produce a balanced sandwich construction. Alternatively, the top may be steel with a self-edged, high pressure laminated plastic face. The simulated walnut grain of the laminated plastic tops shall match GSA Standard Sample No. FSS-L-01002. Alternatively, the manufacturer may provide his equivalent, commercial, walnut grain laminated plastic, subject to contracting officer approval. Overall thickness of the top shall be 25 mm, minimum.

Locks. The locks shall be of the disk or pin tumbler type, having not less than four disks or pin tumblers, and shall be operated by a grooved key. The locks shall have not less than 125 key changes. No one key shall open more than one unit, up to a minimum of 125 units consecutively produced. All locks in a single credenza shall be keyed alike. Two keys shall be furnished with each credenza.

Drawers. The drawers shall have stops to prevent accidental removal but allow removal without the use of tools. The minimum inside clear dimensions shall be as specified in Table I. File and storage drawers shall be welded construction with double wall drawer fronts. The storage drawer body shall be constructed to accommodate partitions. Each storage drawer shall have a minimum of one partition. The storage drawers shall be suspended on telescoping ball bearing slides, rollers, or nylon glides. The slides, glides, or rollers shall promote smooth quiet operation and prevent metal to metal contact between suspension members. The file drawers shall be on full progressive suspensions or telescoping ball bearing slides. The file drawer shall have a spring-activated follower block which operates smoothly. Bumpers shall cushion drawer stops in both closed and extended positions. All storage drawer fronts and file drawer fronts shall extend the width of the section with the drawer front overlapping the front edge of the case. (Necessary clearance shall be allowed between drawer fronts.

TABLE I
minimum inside clear dimension

Drawer type	Width	Height	Depth
Storage Drawer	300 mm	114 mm	280 mm
File Drawer	300 mm	254 mm	356 mm

Drawer and door pulls. The drawer and door pulls shall be recessed. The finish shall be polished, chrome plate on steel or die-cast zinc, or polished, anodized aluminum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:18Z
Check the source to verify that this is the current version before use.

Adjustable shelf. The shelf shall be formed on all four sides. Shelf adjusting devices shall not be visible on the exterior of the case. Shelf supports shall be provided.

Legs. Legs shall be a minimum 25 mm square, polished finish, stainless or chromium plated steel. They shall have adjustable glides and the exposed length shall be a minimum 175 mm from the base frame to the bottom of the fully retracted glides.

Finish. The finish shall be semi-gloss, baked enamel. The colors shall match Fed. Std. No. 595 - black (27040) and parchment within the range delimited by (26586) and (26405). Alternatively, the manufacturer may provide his equivalent, commercial, black or parchment baked enamel finish, subject to contracting officer approval.

Identification label. The label shall have the contractor's name or trademark, contract number, National Stock Number (if specified), and month, and year of manufacture legibly marked in permanent dark ink. The label shall be affixed to the back of the credenza and shall not be removable by hand without defacement after being affixed for four hours.

Workmanship. The workmanship shall be of the quality to produce finished credenzas acceptable in appearance, function and serviceability and prevent potential hazard to personnel or their clothing.

Quality assurance provisions. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements specified herein. Sampling for inspection shall be performed in accordance with MIL-STD-105, unless an equal or better plan is approved by the contracting officer or his/her representative. A lot shall consist of units of one style and color. The sample shall be one each. Inspection levels and AQL's shall be as follows:

For fit, finish and all other workmanship - Level II, AQL 6.5 defects per hundred units.

For packaging, packing and marking - Level S-2, AQL 4.0 percent defective.

Any failure to meet the dimensions, color, identification label or performance requirements shall cause rejection of the lot.

Performance.

ANSI/BIFMA. Each credenza shall comply with the requirements of BIFMA Desk Products Standard X5.5-1989, with the following exceptions.

Exceptions to BIFMA American National Standard X5.5-1989:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:18Z
Check the source to verify that this is the current version before use.

Section 13.2.2, 13.2.3, 14, 15, 16, 17, 18, and 19 are not applicable.

Level test for top. The test unit shall be located on a flat surface. Place a steel straight-edge on edge, diagonally (corner to corner) across the top. The length of the straight-edge shall be greater than the diagonal length of the top. There shall be no gap between the straight-edge and top greater than 3 mm at any point along the diagonal length of the top. This test shall be performed along both diagonals of the top before and after performing the top loading test specified in BIFMA.

Chromium plating test. Plated samples shall be tested for corrosion in accordance with the 5 percent neutral salt spray at 35°C in accordance with ASTM Test Method B117. Test period shall be not less than 48 hours. After the specified exposure is completed, the specimen shall be visually examined to assure that the plating shows no evidence of peel, chip, uneven color, powder film, pits, or stain. Widely scattered spots of corrosion are permitted, however, none of these spots shall exceed 1.6 mm along the greatest dimension.

Regulatory Requirement. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Preservation, packaging, packing, labeling, and marking. The preservations, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Standards. The issues of ANSI/BIFMA X5.5, MIL-STD-105, and Fed. Std. No. 595 in effect on the date of the solicitation shall be used to determine compliance with the stated requirements.

Notes.

Purchasers should specify style and color.

Plastic laminate panel. A sample panel of the decorative plastic laminate sheet is available from the General Services Administration, Federal Supply Service, National Furniture Center, Engineering Division, Washington, DC 20406.

Color panel. A sample of the baked enamel finish referenced in Fed. Std. No. 595 is available from the General Services Administration, Business Center, Federal Supply Service, Washington, DC 20407 or the Business Service Center in the nearest General Services Administration Regional Offices.

Federal Standard No. 595 is available from the General Services Administration Business Service Centers in Boston, MA; New York,

Source: https://assist.dla.mil -- Downloaded: 20261O-26T08:18Z
Check the source to verify that this is the current version before use.

NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Houston, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.

ANSI/BIFMA standard. Copies of the ANSI/BIFMA Standard X5.5 is available from the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.

ASTM Test Method. Copies of the ASTM Test Method B-117 are obtainable from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

MIL-STD-105. Copies of MIL-STD-105 are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:18Z
Check the source to verify that this is the current version before use.