| INCH-POUND |

A-A-50501
18 July 1991

COMMERCIAL ITEM DESCRIPTION

AUGER MACHINES, PIPE AND SEWER CLEANER: GASOLINE-ENGINE-DRIVEN, TRAILER MOUNTED

The General Services Administration has authorized the use of this Commercial Item Description as a replacement for military specification MIL-A-28672B(YD) which is cancelled.

Abstract. This Commercial Item Description (CID) covers three sizes of gasoline-engine-driven, trailer mounted auger machines using sectional rods for unclogging and cleaning of pipes and sewers.

Salient Characteristics.

1. The three sizes of auger machines covered by this CID are:

   a. Size 1 - Minimum capacity 500 feet.
   b. Size 2 - Minimum capacity 800 feet.
   c. Size 3 - Minimum capacity 1,000 feet.

2. The auger machine shall be fully hydraulic and be provided with, as a minimum, the following controls, valves, gages, and accessories. All controls shall be mounted on a control panel which is situated such that the operator can observe the equipment operation while manipulating the controls.

   a. Variable speed rotation, 0 to not less than 150 revolutions per minute.
   b. Clockwise and counterclockwise rotation.
   c. Push and pull rod travel actuator.
   d. Automatic obstruction response sensor.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 4940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

e. Adjustable full time hydraulic pressure relief valve for controlling rod travel pressure limit.
f. Automatic footage counter which shall limit rod travel to a predetermined distance.
g. Safety brake.
h. Accessories.

TABLE I. Accessories.

Item No.	Quantity (each)	Description	Furnished on Size 1	2	3
1	1	Hose rod guide, 7 feet	X	X	X
2	1	Hose rod guide, 18 feet	X	X	X
3	1	Rod guide bell	X	X	X
4	1	Rod guide brace	X	X	X
5	1	Auger, 3 inch	X	X	X
6	1	Auger, 4 inch	X	X	X
7	1	Auger, 6 inch	X	X	X
8	1	Auger, 8 inch		X	X
9	1	Square bar corkscrew, 4 inch	X	X	X
10	1	Square bar corkscrew, 6 inch	X	X	X
11	1	Square bar corkscrew, 8 inch	X	X	X
12	1	Square bar corkscrew, 10 inch			X
13	1	Cutter, minimum 3 blades, 4 inch	X	X	X
14	1	Cutter, minimum 3 blades, 6 inch	X	X	X
15	1	Cutter, minimum 3 blades, 8 inch		X	X
16	1	Cutter, minimum 3 blades, 10 inch			X
17	1	Heavy duty root saw, 4 inch	X	X	X
18	1	Heavy duty root saw, 6 inch	X	X	X
19	1	Heavy duty root saw, 8 inch		X	X
20	1	Heavy duty root saw, 10 inch			X
21	2	15/16 inch assembly tools	X	X	X
22	2	15/16 inch assembly handles	X	X	X
23	1	15/16 inch rod pick up tools	X	X	X

3. The electric start gasoline engine shall include the manufacturer's standard fuel tank and filter system and be provided an ignition switch, choke, and throttle mounted on the control panel.

4. The two wheeled cart type trailer chassis on which the auger is mounted shall meet all DOT Federal Motor Carrier Safety Regulations and shall be provided with retractable landing leg with caster type landing wheel, leveling jacks, and a standard commercial lunette ring for towing with a motor vehicle.

5. The equipment shall be provided with suitably located instruction plates describing any special or important procedures to be followed in operating and servicing. The plates, made of a material which will last and remain legible for the life of the equipment, shall be securely affixed to the equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

6. The color of finish coat, conforming to FED-STD-595, shall be as specified in the contract or order.

Contractor Certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this CID and the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Metric Products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of FED-STD-396, and all other requirements of this CID are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent possible.

QUALITY ASSURANCE PROVISIONS

1. Responsibility for inspection. The contractor is responsible for the performance of all inspection requirements as specified herein. The Government reserves the right to perform any of the inspections set forth where such inspections are deemed necessary to ensure that the equipment(s) conforms to the prescribed requirements and operate satisfactorily.

2. First article inspection. When specified, one sample (a complete unit) shall be subjected to a first article inspection. The first article may be either a first production unit or a unit selected at random from the supplier's current inventory. The inspection shall consist of examination, performance test, and road test.

3. Quality conformance inspection. The quality conformance inspection shall be conducted on each unit intended to be supplied to the Government. The inspection shall consist of examination, engine and hydraulic system test, and packaging inspection.

4. Inspection requirements. Failure to pass any element of the following inspection shall constitute cause for rejection.

   a. Examination. This element shall encompass all visual examinations and dimensional measurements. The equipment(s) shall be checked for conformance to the manufacturer's own design and specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

b. Performance test. Before testing, the contractor shall prepare a maintenance schedule. Unless otherwise specified in the maintenance schedule, the auger shall operate as specified herein without maintenance. The auger shall demonstrate its ability to clear blockages at 25 percent, 50 percent, 75 percent, and 100 percent of the maximum rod travel distance. At the maximum rod travel distance, the blockage shall be increased as necessary to demonstrate proper operation of the automatic obstruction response sensor. The equipment(s) shall perform satisfactorily without any malfunction.

c. Road test. The equipment, with all necessary attachments and accessories, shall be towed by a vehicle at a speed of not less than 50 mph on a straight run and at a speed of not less than 35 mph through a curve marked for that speed run on paved road to demonstrate towing, turning, and tracking ability. The equipment shall show no evidence of instability.

d. Engine and hydraulic system test. The auger shall be operated for not less than one hour with the engine being stopped and started and the controls operated as many times as necessary to determine ease of operation, effectiveness, and responsiveness, and that the engine and rod actuating mechanism operate promptly and with neither restriction nor malfunction.

e. Packaging inspection. The equipment(s) shall be inspected to verify conformance to the packaging requirements.

Preservation, packaging, packing, labeling, and marking. Preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

CID based part identification numbers. The following part identification numbering procedure is for government purposes and does not constitute a requirement for the contractor.

Part identification designation A - 50501 - X
Designates a CID
CID Number
Size

Notes.

1. Acquisition requirements. Acquisition documents should specify the following:

   a. Purchaser should specify size.
   b. Purchaser should specify a complete list of accessories if other than those indicated herein.
   c. Purchaser should specify color of finish coat required.
   d. Purchaser should specify preservation, packaging, packing, labeling, and marking requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

2. Federal Motor Carrier Safety Regulations are available from the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402.

3. Federal Standards are available from Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

MILITARY INTERESTS:

Custodian:

Navy - YD

Review Activity:

DLA - CS

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA - FSS

PREPARING ACTIVITY:

Navy - YD

(Project 4940-0601)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.