INCH-POUND
A-A-50526C
February 21, 1995
SUPERSEDING
A-A-50526B
January 12, 1988

# COMMERCIAL ITEM DESCRIPTION

# HAT, SERVICE: WITH CHIN STRAP

The General Services Administration has authorized the use of this commercial item description.

1. SCOPE This commercial item description covers requirements for a felt hat with chin strap intended for wear by male military personnel of the Department of Defense

## 2 SALIENT CHARACTERISTICS

2 1 Salient characteristics The hat shall be of fur felt in campaign style with "Montana" peak crown having a leather chin strap with sliding keeper and buckle The hat shall have a double thick, stiff, flat brim 3 inches wide Each hat shall have grosgrain ribbon and bow trim, securely sewn with concealed hand stitching, four round eyelets in the crown for ventilation and two oblong eyelets in the brim for the chin strap The eyelets shall be made of brass and enameled, in a shade closely matching the shade of the hat

2 2 Material

2.2.1 Felt The felt shall be from a fur mixture composed of only virgin cut furs The finished felt shall have a bursting strength of not less than 170 pounds and shall weigh no less than 25 ounces per square yard The finished hat shall weigh between 7 and 9 ounces, depending on size.

2 2 2 Color The color of the felt shall be Army/Marine Corps olive drab shade 441, and Air Force blue shade 1571 Shades shall match the standard samples when viewed under filtered tungsten lamps that approximate artificial daylight and that have a correlated color temperature of 7500 (± 200) K, with illumination of 100 (± 20) foot candles Shades shall be a good match to the standard samples under incandescent lamplight at 2300 (± 200) K The shades shall be obtained by metallic dyeing or acid dyeing and shall show (good) colorfastness to light after 80 hours of fade-ometer testing (Method 5660 of FED-STD-191) wet dry cleaning (Method 5662 of FED-STD-191), and perspiration (Method 5680 of FED-STD-191)

Beneficial comments recommendations, additions, deletions, clarifications, etc and any data which may improve this document should be sent to Defense Personnel Support Center, Clothing and Textiles Directorate, Attn DPSC-FQSE, 2800 South 20th Street, Philadelphia, PA 19145-5099

AMSC N/A FSC 8405

DISTRIBUTION STATEMENT A. *Approved for public release; distribution is unlimited.*

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

2 2 3 Sweatband The sweatband shall be full grain, vegetable-tanned leather. The sweatband shall not be less than 1-1/2 inches wide, 5/128 inch thick, and shall be brown or black in shade An oil silk or plastic interlining not less than 1 inch wide shall be zigzag-sewn between the sweatband and the hat. The ends of the sweatband shall be butted with zigzag or other ornamental offset stitch type

2.2.4 Chin strap, with keeper. Each hat shall have a black leather chin strap and keeper. The chin strap shall be approximately 29 inches long by 3/8 inch wide with finished (black dyed) edges The chin strap shall be thick enough to weigh 4 5 to 5 5 ounces The sliding keeper shall be approximately 1/16 inch thick and shall conform in width to the width of the chin strap. The strap shall be pointed at the leading end and shall have nine holes centered on the strap, 1/2 inch apart

2 2 5 Chin strap buckle The buckle shall be a tongue-type, center-bar type made of rust-resistant 1/32 inch thick steel It shall measure overall approximately 3/4 inch long by 9/16 inch wide and shall have openings measuring 3/8 inch wide

2 2 6 Grosgrain ribbon Each hat shall have a 12-ligne grosgrain ribbon hat band and bow trim The ribbon and bow shall be dyed to match or approximate the shade of the olive drab hat fur or black for the Air Force blue or maroon hat fur The bow shall measure 3-1/2 (+ 1/8) inches and shall be centered on the left side, as the hat is worn The ribbon and bow shall have good fastness to light after 80 hours exposure (Method 5660 of FED-STD-191), perspiration (Method 5680 of FED-STD-191), and wet dry cleaning (Method 5622 of FED-STD-191) and shall meet the following requirements

Width overall, including selvages
12 ligne (± 1/2) ligne
Weight per gross yard, minimum
30 ounces
Filling threads per inch, minimum 68
Total warp ends, full width,
including selvages, minimum 236
Yarn ply warp 1
Yarn ply filling 2
Denier warp 154 (± 8)
Equivalent - count 36's
Weave Gosgrain
Material warp Viscose rayon
Material filling Mercerized cotton

2 2 7 Thread All sewing applications (butting sweatband, edge stitching brim, ribbon band assembly, bow, interlining to sweatband, and reed covering tacking) shall use multi-filament nylon, soft or bonded finish thread, with a minimum breaking strength of 2 8 pounds Hats using olive drab felt shall be sewn with Olive Drab T-1, CA 66023 dyed thread (DoD Standard Color Card for Sewing Threads ) Thread shades for hats using Blue 1571 felt should be referred to the Air Force The dyed thread shall show good fastness to light after 80 hours exposure (Method 5660), perspiration (Method 5680), and wet dry cleaning (Method 5622)

2 3 Sizes The hats shall be manufactured in the standard regular oval in the following commercial 1/8-inch sizes and head measurements

| Size of Hat | Head Measurement | Height of Crown | Size of Hat | Head Measurement | Height of Crown |
|---|---|---|---|---|---|
| 6-1/2 | 20-1/2 | 4-15/16 | 7-1/4 | 22-3/4 | 5-5/16 |
| 6-5/8 | 20-7/8 | 5 | 7-3/8 | 23-1/8 | 5-3/8 |
| 6-3/4 | 21-1/4 | 5-1/16 | 7-1/2 | 23-1/2 | 5-7/16 |
| 6-7/8 | 21-5/8 | 5-1/8 | 7-5/8 | 23-7/8 | 5-1/2 |
| 7 | 22 | 5-3/16 | 7-3/4 | 24-1/4 | 5-9/16 |
| 7-1/8 | 22-3/8 | 5-1/4 | | | |

The tolerances for the above head measurements are + 1/4 - 1/8 inch



Source: https://assist.dla.mil - Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

2 4 Label A commercial-type label is acceptable, provided that an additional printed cloth label containing the contractor's name, contract number, size and National Stock Number (NSN) is caught on the stitching of the commercial label The commercial label shall include fiber and care information

2 5 Label/tag Each item shall be individually bar-coded with the type VIII, class 17 label/tag of DDD-L-20 This label/tag shall be located so that it is completely visible on the item when it is folded and/or packaged as specified and so that it causes no damage to the item.

3. **REGULATORY REQUIREMENTS** The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with Public Law 94-580; and in accordance with paragraph 23 403 of the Federal Acquisition Regulation (FAR).

## 4 QUALITY ASSURANCE

4.1 Certification The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices The Government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for, under the provisions of the contract. Reliance on contractor quality assurance systems shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract

4 2 Visual examination Each hat shall be examined for the defects listed below in accordance with ANSI/ASQC-Z1 4

4 3 Defects Any hole, cut, tear, color not as specified, any part shaded, any spot or stain (outside); raw edges, open seams, thread ends not removed, or loose tension resulting in loose seams; any material defects, distorted parts or poor workmanship, any component part omitted, label missing, incorrect, or illegible, measurement of item not as specified, bar code omitted or not readable by scanner, human-readable interpretation (HRI) omitted or illegible, bar code not visible on folded, packaged item, bar code causes damage to the item, any items not packaged in accordance with the contract or purchase order

4 4 Market acceptability criteria The item offered must have been sold to the commercial market or to the Government, and the contractor shall certify and provide supporting documentation as to its serviceability and the long term (five years) availability of all necessary maintenance and logistics support parts and materials.

4 5 Warranty The item offered shall include the standard warranty given to the commercial market beginning with the date of delivery of the individual items.

## 5 PACKAGING

The preservation, packing, and marking shall be as specified in the contract or purchase order

## 6 NOTES

6 1 Source of Government documents Copies of military and Federal documents are available from

Standardization Documents Order Desk
Bldg 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

6 2 Sources of non-Government documents

ANSI/ASQC-Z1 4 Sampling Procedures & Table for Inspection by Attributes

(Applications for copies should be addressed to American National Standards Institute 11 West 42nd Street New York, NY 10036 )

ASTM Manual

(Applications for copies should be addressed to American Society For Testing Materials, 1916 Race Street, Philadelphia PA 19103-1187.)

AATCC Manual

(Applications for copies should be addressed to American Association of Textile Chemists and Colorists, P.O. Box 12215, Research Triangle Park, NC 27709-2215.)

6.3 Renovation capability Manufacturers should maintain/offer renovation capability to include replacing outside trim, sweatband and cleaning and blocking of the hat

6 4 This commercial item description replaced MIL-H-19448.

MILITARY INTERESTS
Custodian
Navy - MC
Air Force - 45
Army - GL

Review Activity

Army - MD
Air Force - 01, 32
Other - SO

CIVIL AGENCY COORDINATING ACTIVITY.
GSA - FSS

PREPARING ACTIVITY
DLA - CT

Project No 8405-0195



Source: https://assist.dla.mil - Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.