COMMERCIAL ITEM DESCRIPTION

TRUNKS, GENERAL PURPOSE

The General Services Administration has authorized the use of this Commercial Item Description (CID).

This commercial item description covers general purpose trunks for wear by male and female military personnel.

Salient characteristics

Design. The trunks shall be a boxer style with a covered elastic waistband and a concealed drawcord, bound V-notch at outer leg seam, double lapped and double stitched seams except for the notch binding and hem.

Sizes. The trunks shall be available in sizes Extra-small (24-26); Small (28-30); Medium (32-34); Large (36-38) and Extra-large (40-42). The finished dimensions shall be as stated in Table I.

Materiel

Trunks. The basic material shall be a minimum of 50% cotton and the balance polyester, twill, 6.5 to 7.5 ounces per square yard and olive green color.

Elastic. The elastic cotton webbing shall comply with the measurements required in Table I.

Drawcord. The drawcord shall be of proper length to accommodate the waist and hips.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this Document should be addressed to the Commanding General (PSE-C), Marine Corps Research, Development and Acquisition Command, Washington, D.C. 20380-0001, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this Document or by letter.

FSC 8415

Distribution Statement A. Approval for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

TABLE I

Finished Measurements

Dimension		X-Small	Small	Med	Lge	X-Lge	Tolerance
Waist-Relaxed	1/	10	11	12	13	14	±1/2
Waist-Maximum	2/	18	19	20	21	22	±1/2
Front Seam	3/	10	10-1/2	11	11-1/2	12	±1/2
Back Seam	4/	13	14	14-1/2	15	15-1/2	±1/2
Side Seam	5/	8-1/2	9-1/2	10	10-1/2	11	±1/2
Inseam	6/	5	6	6-1/2	7	7-1/4	±1/2

1/ Measure from folded side to folded side along top edge of waist.
2/ Measure from folded side to folded side along top edge of waist with waistband stretched taut.
3/ Measure from top of waist along front rise to the folded edge of inseam.
4/ Measure from top of waist along back rise to the folded edge of inseam.
5/ Measure from top of waist along side seam to the top edge of V-Notch.
6/ Measure from leg opening to leg opening along crotch seam.

Thread. The thread shall be cotton or polyester/cotton and dyed an olive green shade.

Labels. Each pair of trunks shall have a printed label attached on the inside center back waist containing the size, National Stock Number (NSN), contract number and contractor's name.

Workmanship. After completion, the trunks shall be thoroughly cleaned and all loose threads, lint and foreign matter removed. The trunks shall be uniform in quality and shall be free from irregularities or defects which adversely affect performance, reliability or durability.

Contractor certification. The contractor shall certify and maintain inspection records indicating the product offered meets the salient characteristics of this CID, and that the product conforms to the producers' own drawing, specifications, standards and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Quality assurance provisions:

Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified in this CID.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

The Government reserves the right to perform any of the inspections set forth in the specifications where such action is deemed necessary to assure that supplies and services conform to prescribed requirements. The contractor is responsible for insuring that components and materials used were manufactured, examined and conform with the requirements as specified in this CID.

Sampling. The finished trunks shall be sampled for inspection in accordance with MIL-STD-105. Except where otherwise specified the inspection level shall be S-2, AQL 6.5 percent defective. A lot shall be the quantity of trunks of the same size submitted for inspection at one time. A sample unit shall be one pair of trunks.

Inspection of the end item

Visual examination. The end item trunk shall be visually examined for defects in accordance with Table II.

TABLE II
Visual-Examination

Examine	Defect
Basic fabric, color	Hole, tear, slub, etc., that may develop into a hole. Not an olive green shade.
Elastic waistband	Fullness not evenly distributed in stitching elastic waistband to top of trunk.
	Drawcord caught in stitching other than center back seam. (Prevents adjustment of drawcord to fit waist.)
Leg bottom	Hem uneven. V-notch binding twisted or distorted in any way.
Label	Omitted.
Seams and stitching	Seam twisted, puckered or pleated seriously affecting appearance.
	Thread breaks not secured by backtacking.
	Open seam over 1/4 inch.
	Raw edges over 1/2 inch.
Buttonholes (drawcord)	Omitted.
	Constructed through outside of trunks.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

Inspection for preparation and delivery. An inspection shall be made to determine whether the packaging, packing, and marking comply with the requirements of the contract or purchase order. Examination for defects shall be in accordance with Table III. For examination of interior packaging, the sample unit shall be one shipping container fully prepared for delivery. Sampling shall be in accordance with MIL-STD-105. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an AQL of 4.0 defects per hundred units.

TABLE III
Preparation for delivery defects.

Examine	Defects
Markings	Omitted; incorrect; illegible; improper size, location sequence, or method of application.
Materials	Any component missing, damaged, or not conforming to applicable requirements stated herein.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, or distortion of container.
Contents	Quantity of container is more or less than required. Gross weight exceeds requirements of the box specifications.

Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling and marking

Each pair of trunks shall be folded in half along the length. The bottom and side (where necessary in larger sizes) shall be folded in so that the trunks measure approximately 11-1/2 by 7-1/2 inches. Five pairs of trunks of one size only shall be neatly stacked with each pair reversed end to end and secured at each end with cotton tape or twine to form a bundle. Four bundles (twenty pair) of trunks shall then be packed in a snug fitting container made of fiberboard conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Containers shall be sealed in accordance with good commercial practices.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

In addition to any special marking required by the contractor or purchase order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129.

Palletization. Trunks, packed as specified, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be number 3 in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course.

Notes

Ordering data. The purchasers should select the preferred options permitted herein and include the following in procurement documents.

(a) Title, number, and date of the CID.
(b) Size(s) required.
(c) When palletization is required.

Military Standards are available from the Commander, Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.

Review Activity
DLA-CT

Civil Agency Coordinating Activities
GSA-FSS

Preparing Activity
Navy-MC

Project No. 8415-0669

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.