INCH-POUND
A-A-50527B
July 3,1996
SUPERSEDING
A-A-50527A
August 16, 1994

COMMERCIAL ITEM DESCRIPTION

TRUNKS, GENERAL PURPOSE

The General Services Administration has authorized the use of this commercial item description by all federal agencies.

1. SCOPE. This commercial item description covers the requirements for general purpose trunks for wear by male and female military personnel.

2. CLASSIFICATION. The trunks shall be available in the following sizes:

Extra-Small	(XSM)	(26-28)	Large	(LG)	(38-40)
Small	(SM)	(30-32)	Extra-Large	(XLG)	(42-44)
Medium	(MED)	(34-36)	Extra-Extra Large	(XXLG)	(46-48)

3. SALIENT CHARACTERISTICS

3.1 Description. The trunks shall be a boxer-style with a covered elastic waistband and a concealed drawcord, bound V-notch at outer leg seam, double-lapped and double-stitched seams except for the notch binding and hem, and a 5 inch by 5 inch back patch pocket on the right side with a button closure. The patch pocket shall be 3-1/2 inches (± 1/2 inch) from the top of the waist band to the top of the pocket and 1-1/2 inches (± 1/2 inch) from the side seam to the edge of the pocket. The trunks shall have a liner with elasticized leg openings.

3.2 Material

3.2.1 Basic material. The basic material shall be 100 percent woven nylon, weighing 2.8 ounces per square yard when tested in accordance with ASTM-D-3776 Option C, having a 110 x 68 yarn count when tested in accordance with ASTM-D 3775, and shall be 55 to 57 inches wide. The samples shall be conditioned as directed in ASTM-D-1776 prior to testing. The yarns shall be 70 denier, 2 ply texturized nylon. The color shall be olive green shade 3452. The dyed cloth shall show a minimum rating of "4" when tested for colorfastness to combined laundering and bleaching (after 3 wash and dry cycles) in accordance with AATCC 61, Test 4A. The soap solution shall contain 0.5 percent soap P-S-1792, Soap, Laundry, Type I, classes 1 or 2; and 0.2 percent sodium metasilicate, O-S 604, Sodium Metasilicate, Technical, Type I. The bleach solution shall have 1.0 percent of available chlorine. The specimen shall weigh 4.0 grams.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: Defense Personnel Support Center, Clothing and Textiles Directorate, Attn: DPSC-FNS, 2800 South 20th Street, Philadelphia, PA 19145-5099.

AMSC N/A FSC 8415

DISTRIBUTION STATEMENT A. *Approved for public release; distribution is unlimited.*

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

The dyed cloth shall show a minimum rating of 4 when tested for colorfastness to light when tested in accordance with AATCC 16, option A. When a color change equal to Step 4 on the Grey Scale is evident in either sample being evaluated or the standard sample, exposure shall be continued for the additional number of hours at which the color change was apparent. Specimens which do not show a color change until 80 AFU's shall be returned to the machine for a total exposure period not to exceed 140 hours.

3.2.2 Liner. The fabric for the liner shall be 100 percent tetra-channel polyester fiber or equal, plain weave, weighing 4.0 to 4.5 ounces per linear yard (50 to 60 inches wide) when tested in accordance with ASTM-D-3776, Option C, and the color shall be gray or natural. The samples shall be conditioned as directed in ASTM-D-1776 prior to testing. The size of the liner shall be suitable for the trunks.

3.3 Elastic. The elastic webbing for the waistband shall be white, 2 inch wide cotton, polyester, or a cotton/polyester blend. The weight of the webbing shall be 1.25 ounces per linear yard with a minimum thickness of 0.048 inch. The elastic webbing for the leg openings of the liner shall be white, 1/4 inch wide, weighing a minimum of 0.28 ounces per linear yard, with a minimum thickness of 0.16 inch. Both elastics shall have a maximum of 50 percent elongation when tested in accordance with ASTM-D-4964. The elastic shall comply with the finished measurements in Table I. Test procedure for weight shall be in accordance with ASTM-D-3776, Option C and test for thickness shall be in accordance with ASTM-D-1777. The samples shall be conditioned as directed in ASTM-D-1776 prior to testing. A thickness gauge of the dead-weight type equipped with a dial graduated to read directly to 0.0001 inches shall be used. The presser foot shall be circular, with a diameter of 0.375 $\pm$ 0.0001 inches and with the moving parts weighted to apply a total load of 3.4 $\pm$ 0.1 pounds per square inch to the specimen. The anvil shall be not less than 0.250 inches in diameter. The presser foot and anvil surface shall be planed to within 0.0001 inches and shall be parallel to each other to within 0.0001 inches. The micrometer shall be capable of repeating its reading to 0.00005 inches at zero setting or on a steel gauge block.

3.4 Drawcord. The drawcord shall be of a proper length to accommodate the waist and hips. The braid for the tubular drawcord shall be cotton, polyester, or polyester/cotton in a solid or flat construction in an olive green shade and approximately 3/16 inch in diameter/width. The dyed cord shall have a minimum rating of "4" for colorfastness to light, laundering (after 3 wash and dry cycles), and crocking when tested in accordance with AATCC 16 (see paragraph 3.2.1), AATCC 61-test 3A, and AATCC 8 respectively, and shall have a minimum breaking strength of 75 pounds when tested in accordance with ASTM-D-5034. The specimen must be dried after each of the three laundering cycles. The soap solution shall contain 0.5 percent by weight, P-D-245, Detergent, Laundry, and Hand Dishwashing (Granular) Type II, in water hardness not over 50 parts per million. The weight of the specimen shall be 4.0 $\pm$ 0.5 grams and the rotating time shall be 30 minutes with ten stainless steel balls in each cylinder. The cord shall be knotted at each end.

3.5 Binding. The binding for the leg opening shall be made from the basic cloth, and shall finish 5/16 to 3/8 inch in width on the outside.

3.6 Thread. The thread shall be cotton or spun polyester, or cotton- covered polyester dyed to an olive green shade. The cotton thread shall be 2, 3, or 4 ply, having a minimum breaking strength of 1.5 pounds. The polyester thread shall be 3 ply, having a minimum breaking strength of 2.2 pounds. The cotton-covered polyester thread shall be 2 ply or 3 ply, having a minimum breaking strength of 2.6 pounds. The tests for breaking strength shall be in accordance with ASTM-D-2256.

3.7 Labels. A commercial-type label is acceptable, provided that an additional printed cloth label containing the contractor's name, contract number, size and National Stock Number (NSN) is

Source: https://assist.dla.mil - Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

caught on the stitching of the commercial label. The commercial label shall include fiber and laundering information.

3.8 Label/tag. Each item shall be individually bar-coded with a paper tag for personal clothing items. The paper tag shall be standard bleached sulfate having a basis weight of 100 pounds. The paper used for the tags shall have a smooth finish to accept thermal transfer and direct printing. The tags shall have a hole and shall be attached to each item by a fastener, clearly legible and readable by a scanner. The bar coding element shall be a 13 digit national stock number (NSN). The bar code type shall be a medium to high code density and shall be located so that it is completely visible on the item when it is folded and/or packaged as specified and so that it causes no damage to the item.

3.9 Finished measurements. The finished measurements of the trunks shall be as indicated in Table I.

TABLE I. Finished measurements (inches)

Dimension	26-28 XSM	30-32 SM	34-36 MED	38-40 LG	42-44 XLG	46-48 XXLG
Waist Relaxed 1/	9	10	12	14	16	18
Waist Maximum 2/	15	17	19	21	23	25
Front Seam 3/	11-1/2	12	12-1/2	13	13-1/2	14
Back Seam 4/	14	14-1/2	15	15-1/2	16	16-1/2
Side Seam 5/	11	12	13	14	15	16
Inseam 6/	3-1/2	4	4.5	5	5.5	6
Thigh 7/	12	12-1/2	13	13-1/2	6	14-1/2
Tolerance on all measurements is ± 1/2 inch						

1/ Measure from folded side to folded side along top edge of waist.
2/ Measure from folded side to folded side along top edge of waist with waistband stretched taut.
3/ Measure from top waist along front rise to the intersection of inseam.
4/ Measure from top of waist along back rise to the intersection of inseam.
5/ Measure from top of waist along side seam to bottom of leg at lower front cover of notch.
6/ Measure from the crotch seam to end of leg.
7/ Measurement from the crotch seam to top of notch at side seam.

4. REGULATORY REQUIREMENTS. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. QUALITY ASSURANCE PROVISIONS

5.1 Product Conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be a similar product that is offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

5.2 Market acceptance criteria. The item offered, or a generic equivalent, must have been sold to the commercial market or to the Government for at least two years.

5.3 Visual examination. Each pair of trunks shall be examined for the defects listed below and in accordance with ANSI/ASQC-Z1.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

5.3.1 Defects. Any hole, cut, tear, or color not as specified; any spot or stain (outside); thread ends not removed; label missing, incorrect, or illegible; measurement of components not as specified; bar code omitted or not readable by scanner; human-readable interpretation (HRI) omitted or illegible; bar code not visible on folded, packaged item; bar code causes damage to the item; fullness of elastic waistband not distributed evenly; drawcord caught in stitching other than center back seam; hem uneven, binding twisted or distorted; seam twisted, puckered, or pleated affecting appearance; thread breaks not secured by bartacking; open seams; raw edges; buttonhole for drawcord omitted or constructed through outside of trunks; size of buttonhole not corresponding with drawcord/width; any component or requirement not as specified; any item not packaged in accordance with the contract or purchase order.

5.5 Acceptance criteria. Acceptance shall be as specified in the contract or purchase order.

6. PACKAGING

6.1 Preservation, packing, and marking. The preservation, packing, and marking shall be as specified in the contract or purchase order.

7. NOTES

7.1 Source of Government documents. Copies of military and Federal documents are available from:

Standardization Documents Order Desk
700 Robbins Avenue, Bldg. 4D
Philadelphia, PA 19111-5094

7.2 Source of non-Government documents.

ASTM TEST METHODS

(Applications for copies should be addressed to American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.)

AATCC Test Methods

(Applications for copies should be addressed to American Association of Textile Chemists and Colorists (AATCC), P.O. Box 12215, Triangle Park, NC 27709-2215.)

ANSI/ASQC Z1.4 - Sampling Procedures and Table for Inspection by Attributes

(Applications for copies should be addressed to the American National Standards Institute, 11 42nd Street, New York, NY 10036.)

MILITARY INTERESTS:

Custodian:
Navy-MC

CIVIL AGENCY COORDINATING ACTIVITY
GSA - FSS

PREPARING ACTIVITY:
DLA - CT

Project 8415-0079

Source: https://assist.dla.mil - Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.