A-A-50529
29 September 1988

COMMERCIAL ITEM DESCRIPTION

SHOES, WOMEN'S, DRESS, BLACK, POROMERIC

The General Services Administration has authorized the use of this Commercial Item Description (CID).

This commercial item description covers women's black hi-gloss poromeric shoes for wear by military personnel.

Salient characteristics

Design. The shoes shall be a moccasin toe blucher oxford with full flat welt around heel construction, three eyelets, cambrelle vamp and tongue lining, leather quarter lining, composition soles and rubber heels.

Sizes. The shoes shall be available in whole and half sizes, 3 through 10, 11, and 12 and furnished in widths AAAAA, AAAA, AAA, AA, A, B, C, D, E, and EE inclusive, or as an option, may be provided in narrow, medium, wide, and extra wide.

Materiel

Uppers. The upper shall be cut from hi-gloss poromeric material. The poromeric material shall be approximately 0.060 inch thick.

Outsole. The outsole shall be 10(±1/2) irons thick having a smooth tread design.

Beneficial comments (recommendations, additions, deletions, and any pertinent data) which may be of use in improving this Document should be addressed to the Commanding General (PSE-C), Marine Corps Research, Development, and Acquisition Command, Washington, D.C. 20380-0001, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this Document or by letter.

FSC 8435

Distribution Statement A. Approval for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

Heels. The molded rubber full heels shall be of a commercial washer or plastic core type construction, 5/8 to 3/4 inch in height, with smooth or textured tread. The rubber shall be synthetic, black in color, of a non-marking composition and shall have an abrasion index of not less than 90.

Insoles. The insoles may be leather or synthetic and cut to properly fit the shoe.

Shank. The shank may be made from reinforced steel or fused fiberglass. The shank shall conform to the contractor's last.

Counters. The counters shall be of a stiffening material to reinforce the heel to prevent sagging and loss of shape.

Eyelets. The flat flange type eyelets shall not be visible on the outside of shoe.

Laces. The round laces shall be nylon and in a black shade. The length of the laces shall be a minimum of 20 inches.

Lasts. The shoes shall be made with the contractor's lasts, standard patterns, dies and markers.

Workmanship. After completion, the shoes shall be thoroughly cleaned and all foreign matter removed. The shoes shall be uniform in quality and shall be free from irregularities or defects which adversely affect performance, reliability or durability.

Contractor certification. The contractor shall certify and maintain inspection records indicating that the product offered meets the salient characteristics of this CID, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Quality assurance provisions:

Responsibility for inspection. Unless otherwise specified in the contract of purchase order, the contractor is responsible for the performance of all inspection requirements as specified in the CID. The Government reserves the right to perform any of the inspections set forth in the specifications where such action is deemed necessary to assure that supplies and services conform to prescribed requirements. The contractor is responsible for insuring that components and materials used were manufactured, examined, and conform with the requirements as specified in this CID.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

Sampling. The finished shoes shall be sampled for inspection in accordance with MIL-STD-105. Except where otherwise specified the visual inspection level shall be S-2, AQL 6.5 percent defective. A lot shall be the quantity of shoes submitted for inspection at one time. A sample unit shall be one pair of shoes.

Inspection of the end item

Visual examination. The end item shoes shall be visually examined for defects in accordance with Table I.

Table I

Visual Examination

Examine	Defects
Pairing	Not properly mated, i.e., not right and left of the same size, color or appearance.
Poromeric	Any cut, tear, hole or abrasion.
Seams and stitching	Open seams; needle holes or needle chews; grinning seam, i.e., thread exposed; broken stitch, one or more skipped stitches, two or more consecutive.
Eyelets	Not the correct number. Not the same number of eyelets on each side.
Insole	Short or long.
Heel	Heel not finished properly.
Lining	Wrinkled or torn.

Inspection for preparation and delivery. An inspection shall be made to determine whether the packaging, packing, and marking comply with the requirements of the contract or purchase order. Examination for defects shall be in accordance with Table II. For examination of interior packaging, the sample unit shall be one shipping container fully prepared for delivery. Sampling shall be in accordance with MIL-STD-105. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an AQL of 4.0 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:43Z
Check the source to verify that this is the current version before use.

Table II

Preparation for delivery defects.

Examine	Defects
Markings	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Material	Any component missing, damaged, or not conforming to applicable requirements stated herein.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, or distortion of container.
Contents	Quantity of container is more or less than required. Gross weight exceeds requirements of the box specifications.

Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling and marking

Each shoe shall be wrapped in a sheet of regular grade commercial tissue paper. Each mated pair of shoes shall then be packaged in a one piece or two piece shoe box. Six pairs of shoes of one size and width only shall be packed in a snug fitting container made of fiberboard conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Containers shall be sealed in accordance with good commercial practices and reinforced with pressure-sensitive adhesive filament tape.

In addition to any special marking required by the contract or purchase order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129.

Palletization. Shoes, packed as specified, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

Pallet type shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be number 3 in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course.

Notes

Ordering data. The purchasers should select the preferred options permitted herein and include the following in procurement documents.

(a) Title, number, and date of the CID.
(b) Size(s) required.
(c) When palletization is required.

Military standards are available from the Commander, Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.

Military Interests:

Custodians
Navy-MC
Air Force-11

User Activities
Air Force - 45

Review Activities
DLA - CT
Air Force - 82
Air Force - 99

Civil Agency Coordinating Activities
GSA-FSS

Preparing Activity
Navy-MC

Project No. 8435-0055

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:43Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.