[METRIC]

A-A-563A
May 13,1994
SUPERSEDING
A-A-563
May 6,1981

COMMERCIAL ITEM DESCRIPTION

RULER, PLASTIC (DESK)

The General Services Administration has authorized the use of this Commercial Item Description, for all Federal agencies.

1. SCOPE:

This commercial item description covers a plastic desk ruler with an inch scale and a metric scale.

2. Salient Characteristics:

A. The rulers shall be fabricated of plastic suitable for the purpose intended. The plastic shall be clear and colorless or a neutral color (e.g., white, light yellow, etc.).

B. The material used for marking the graduations and figures shall be waterproof, black in color, and of a good commercial quality.

C. The rulers shall have square corners. The top surface shall be of the two-bevel type. The bottom surface may be undercut along each edge fo the full length of the ruler. The bottom surface shall be flat.

D. Dimensions and tolerances shall be as specified in Table I.

Beneficial comments, recommendations, additions, deletions, clarification, ect. and any data which may improve this document should be sent to:

General Services Administration
Engineering Division (2FYEE), Rm. 20-130
26 Federal Plaza
New York, NY 10278

DISTRIBUTION STATEMENT A: Approved for public release: distribution is unlimited.

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.

E. The permissible departure of each working edge, of the rulers from straight-edge, measured at points of maximum departure, shall not exceed 0.08 cm (1/32) inch.

Note. Permissible departure from a straightedge refers to the distance between two lines parallel to the length of the ruler, one line touchi point on the edge of the ruler at maximum bulge, the other line touchi points on the edge where there is a Maximum depression.

Table I. Dimensions and tolerances

Length cm/inch	Width Min. cm/inch	Width Max. cm/inch	* Thickness cm/inch
30.5 + 0.08 cm (12 + 1/32- 0)IN.	2.7 cm (1-1/16)IN.	3.0 cm (1-3/16)IN.	0.38 ± 0.05 cm (0.150 ± .020)IN.

* This dimension shall be measured at the point of maximum ruler thickness.

F. The permissible departure of the bottom surface of the rulers fr straightedge, measured at point of maximum departure, shall not 0.08 cm (1/32) inch (see note above).

G. Graduations on both scales shall be accurate to within 0.04 cm (1/64) inch. The total accumulated error, for each scale, shall not exceed 0.16 cm (1/16) inch.

H. The graduations shall be located at the outer edges of the beveled sides of the ruler. Each graduation shall be marked in black waterproof ink or paint. The length of each different graduation marking for each scale, shall be as in Table II.

I. The inch scale shall contain not less than 191 clearly visible graduations. The ends of the ruler may serve as the graduation at each end of the scale.

J. The metric scale shall contain not less than 301 clearly visible graduations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.

Table II Length of graduation markings

Scale	Graduations	Length minimum
Metric	1 Millimeter	0.20 cm (5/64) IN.
Metric	5 Millimeters	0.28 cm (7/64) IN.
Metric	10 Millimeters	0.44 cm (11/64) IN.
Inch	1/16 inch	0.16 cm (1/16) IN.
Inch	1/8 inch	0.20 cm (5/64) IN.
Inch	1/4 inch	0.28 cm (7/64) IN.
Inch	1/2 inch	0.36 cm (9/64) IN.
Inch	1 inch	0.44 cm (11/64) IN.

K. The figures shall not be less than 0.24 cm (3/32) inch in height. Figures 1 through 12 for the inch scale and 1 through 30 for the metric scale, shall be located adjacent to the appropriate inch graduation and centimeter graduation, respectively, and toward the center of the ruler as measured on the ruler width. Figures, for eac scale, shall read from left to right. All figures shall he marked in black water proof ink or paint and shall be easily read.

L. Workmanship. All surfaces of the ruler shall be smooth. Rulers shal be free from any defects and imperfections which may affect appearanc or serviceability.

3. Quality Assurance

Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Excep as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the government. The Governmen reserves the right to perform any of the inspections set forth in the Commercial Item Description, where such inspections are deemed necessa to assure that supplies and services conform to the prescribed requirements.

Contractor Certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The government reserves t right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of th contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.

A. Each lot of scales shall be inspected for conformance to the requirements herein. Sampling for inspection shall be in accordance with MIL-STD-105 using the plans specified below.

B. Visual and dimensional characteristics - Inspection Level S-2 with an Acceptable Quality Level (AQL) of 4.0 percent defective. The sample unit shall be one scale.

4. Preparation for delivery

Packaging, packing and marking shall be as specified in the contract or purchase order.

5. Regulatory Requirements

The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable in accordance with paragraph 23.403 of the Federal Acquisition Regulation.

6. Application for copies of technical documents referenced herein:

The issue date in effect on date of invitation for bids or request for proposal shall apply.

A. Military Specifications:

MIL-STD-105 - Sampling Procedures and Table for Inspection by Attributes.

Available from: Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094

B. Federal Acquisition Regulation:

Available from: Superintendent of Documents, Government Printing Office (GPO), Washington, DC 20402

7. Ordering Data:

Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

1) Packaging, packing and marking.

No Official DOD Interest
Has Been Registered

Preparing Activity:
GSA/FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.