INCH-POUND

MIL-B-49436/4A(ER)
29 March 1991
SUPERSEDING
MIL-B-49436/4(ER)
3 August 1983

MILITARY SPECIFICATION SHEET

BATTERY, RECHARGEABLE, SEALED NICKEL CADMIUM BB-557/U

This specification is approved for use by LABCOM, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-49436





FIGURE 1. FRONT VIEW.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.


Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.



INCHES	MM
.120	3.0
.250	6
.718	18.2
.734	18.6
.750	19.0
1.032	26.2
1.437	36.5
4.125	104.7

FIGURE 2. TOP VIEW

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.






FIGURE 3. BATTERY CONNECTOR INTERFACE

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

DRAWING NOTES

1. All dimensions are in inches.
2. Tolerances on decimals: ± 0.031 inch.
3. Dimensioning shall be per USAS-144.5 Y14.5 1966.
4. Stencil (or equivalent) schematic, identificaion and charging instructions as shown. Color marking white.
5. Face of connector shall be flush to 0.031 inch below top of battery.
6. Manufacturer shall fill in applicable information in parenthesis.
7. See Figure 2 for top view.
8. Pressure relief valve shall be located under connector. It shall release gas before case damage is incurred.
9. See Figure 3 for connector-battery interface. The main connector key shall be oriented as shown in Figure 2. The two connector mounting screws shall be corrosion resistant steel, Class 303, Condition A in accordance with ASTM A 484.
10. Holes A shall be .154 ±.002 dia x .34 ±.02 deep for a 4-40 UNC-2A insert. Insert to be flush or below surface.
11. The lettered holes of table I are shown in approximate positions in Figure 3. The holes shall be .136 ±.002 diameter. Marking of holes not required.
12. Each required SC-C-179495 connector wire shall be provided with a hole (see table I and figure 3) and pre-fitted with a neoprene rubber grommet of 50 ±5 durometer in accordance with MIL-R-3065 to furnish a watertight seal around the connector wires.
13. Pressure relief valve mounted in hole B has a typical height of 0.42 from base on connector well.

TABLE I. CONNECTOR WIRE COLOR CODE

HOLE C	HOLE D	HOLE E	HOLE F
BLACK/WHITE	BLACK	WHITE/RED	RED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Rated capacity (C_5):	1.0 AH
Voltage (Nominal):	24 Volts
Weight (Maximum):	0.77 Kg (1.7 lbs)
Connector:	Floating type per SC-C-179495
Number and type of cells:	20 sealed "4/5A" size cells or equal
Charge rate for testing and on battery (C/5 for 6-7 hrs):	0.20 amps

Discharge Rates	5 Second Voltage (V)	Final Voltage(V)	Current (Amps)
C/5	-	20.0	0.2
C_5	-	20.0	1.0
$3C_5$	22.0	20.0	3.0
$5C_5$	-	20.0	5.0

Test	Discharge Rate	Capacity Requirement(AH)
Full Capacity Discharge	C_5	.90
Cycle Life, 224 cycles	C_5	.67
Overcharge, 24 hours	C_5	.90
High Rate Discharge	$3C_5$	.72
Low Temperature Discharge at -30°C (-22°F)	C_5	.40
Retention of Charge 7 days at 51°C (124°F)	C_5	.50
Pulse Discharge 5 amps, 5 seconds on, 25 seconds off, continuously to 20 Volts	$6C_5$	.70
Vibration	C/5	.95

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

NOTES - 1. Unless otherwise specified, all values are minimum.
2. All charges and discharges shall be performed on fully assembled batteries through the terminals.

CUSTODIAN:
ARMY-ER

REVIEWER:
ARMY-CR, AV, GL

PREPARING ACTIVITY:
ARMY-ER

(PROJECT 6140-A731)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.