MIL-C-60913(AR)
AMENDMENT 3
14 MAY 1984
SUPERSEDING
AMENDMENT 2
30 April 1975

MILITARY SPECIFICATION

CHARGE, PROPELLANT, INCREMENT
XM185 (M185) (MADE FROM PROPELLANT M9)

This Amendment forms a part of Military Specification MIL-C-60913(PA), dated 15 May 1967, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.1: Delete "XM652" and substitute "M301A3".

2. Specifications:

Delete the following:

MIL-B-3106
MIL-B-13239

Add the following Specification:

"MIL-F-50499 - Filler, Sheet Form (for use in ammunition containers)".

PAGE 2

2. Drawings:

Delete the following Army drawings:

"20-4-619 Marking Diagram
7548645 Cartons, Packing ...
7549033 Container, Metal ...".

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:05Z
Check the source to verify that this is the current version before use.

Add the following Army drawing:

"9241693 - Packing of Fiberboard Cartons for Shipment of Propellant Increments".

2. Publications:

Delete the following:

"Army

ET-9220706 Equipment Tabulation".

PAGE 3

2.2: Other Publications: Delete entire paragraph "Code of Federal Regulations" and substitute the following new paragraph:

"Code of Federal Regulations, Title 49 - Transportation, Parts 0-190. (The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C., 20402. Orders should specify 49 CFR 0-190 (latest revisions))."

PAGE 4

4.1.2: Delete entire paragraph "Government verification".

PAGE 5

4.2.2.1, Bag, propellant (see dwg. 9220707 covering a detail of dwg. 9220706)": Delete Minor defect "203 Location of button hole (2 places ... Gage 01003".

PAGE 6

4.2.2.2, Charge, Propellant Increment (see dwg. 9220706):

Add the following two new minor defects:

"205 Distance between outer edge of Button holes Gage 02006
206 Symmetry of outer edge of Button hole and outer edge of bag (2 places) Gage 02007".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:05Z
Check the source to verify that this is the current version before use.

PAGE 8

4.2.4, Inspection Equipment: Delete First Sentence: "Equipment Tabulation Number ET-9220706 identifies the inspection equipment required to perform the examinations and tests prescribed in this section."

* 5.1.1: Delete in its entirety and substitute the following:

"5.1.1 Level A. Propellant increments shall be packed in heat sealed barrier bags complying with Type I, Class E, of MIL-B-117. The barrier bag size shall be 22 1/2 inches long by 22 1/2 inches wide, nominal. Approximately 15 pounds of propellant shall be packed in each bag and closed by means of heat sealing. Two heat sealed bags shall be packed in a wooden box (Suggested inside box dimensions 14 1/2" by 14 1/2" by 7 1/4") conforming to Grade A, Type I, Class 1 or 3 of MIL-B-2427. Both ends, sides, top, and bottom of the wooden box shall be lined with 1/16 inch thick solid water resistance sheet material conforming to MIL-F-5049. The box shall be closed and strapped in accordance with MIL-B-2427. The net weight shall not exceed 30 pounds of propellant."

* 5.1.1.1: Add the following new paragraph:

"5.1.1.1 Alternative Level A. Propellant increments shall be packed in propellant packing boxes M17, M18, M24 or M25 complying with dwgs. 76-4-56, 76-4-59, 76-4-46 and 7549033 respectively. In lieu of air pressure test, two 4-MIL conductive polyolefin or polyethylene bags can be used for all containers listed herein. Each bag must be individually tied and shall be a lay flat style bag made of conductive material in accordance with 5.1.2.1."

PAGE 9

* 5.1.2: Delete in its entirety and substitute the following:

"5.1.2 Level B. Propellant increments shall be packed in a fiberboard carton conforming to requirements for Carton No. 1 referenced on dwg. 7548645. The liner shall be a lay flat style bag made of conductive material in accordance with 5.1.2.1."

* 5.1.2.1: Add the following new paragraph:

"5.1.2.1 Liners. Liners shall be made of conductive polyethylene or polyolefin sheet with a thickness of .004

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:05Z
Check the source to verify that this is the current version before use.

inch minimum, surface resistivity shall not exceed 1000 ohms per centimeter, when tested in accordance with Methods 4041 and 5052 of FED-STD-406. Electrostatic bleed-off shall not exceed 2.00 seconds when tested in accordance with Method 4046 of FED-STD-101. The liner shall be closed by rolling down the top and taped (with pressure tape made in accordance with PPP-T-97 or MIL-T-43036) to prevent unrolling or it may be heat sealed. Details not specified herein shall comply with PPP-B-26."

* 5.1.3: Delete in its entirety.

* 5.1.3.1: Delete in its entirety.

* 5.2.1: Delete in its entirety and substitute the following:

"5.2.1 Level A. Exterior containers shall be marked in accordance with dwg. 8796522. The dot marking shall be "Propellant explosive Class A."

* 5.2.2: Delete in its entirety and substitute the following:

"5.2.2 Alternative Level A. The M17, M18, and M24 containers shall be marked in accordance with dwg. 8858848. The M25 container shall be marked in accordance with dwg. 8858577."

* 5.2.3: Delete in its entirety and substitute the following:

"5.2.3 Level B. The fiberboard carton or other container shall be marked in accordance with dwg. 9241693."

* The margins of this Amendment are marked with an asterisk to indicate where changes, additions, modifications, corrections, deletions from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-A277)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:05Z
Check the source to verify that this is the current version before use.