INCH-POUND

MIL-DTL-55302/145C
22 March 2005
SUPERSEDING
MIL-C-55302/145B
17 November 1988

DETAIL SPECIFICATION SHEET

# CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES, RECEPTACLE WITH PIN CONTACTS, 2 FEMALE KEYING GUIDES, 2.114 INCHES LENGTH, FOR PRINTED WIRING BOARDS (.100 INCH SPACING)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-55302.





FIGURE 1. Connector, receptacle (.100 inch spacing).

AMSC N/A FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.


| Inches | mm | Inches | mm |
|---|---|---|---|
| .006 | 0.15 | .142 | 3.61 |
| .012 | 0.30 | .153 | 3.89 |
| .016 | 0.41 | .189 | 4.80 |
| .0229 | 0.582 | .200 | 5.08 |
| .024 | 0.61 | .248 | 6.30 |
| .0244 | 0.620 | .252 | 6.40 |
| .050 | 1.27 | .305 | 7.45 |
| .071 | 1.80 | .317 | 8.05 |
| .100 | 2.54 | 1.800 | 45.72 |
| .122 | 3.10 | 2.114 | 53.70 |

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ± .005 (0.13 mm).
4. Standoffs are located between each cable hole and between each hole and contact hole set.

FIGURE 1. Connector, receptacle (.100 inch spacing) - Continued.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.





NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ± .005 (0.13 mm).

| Inches | mm |
|---|---|
| .004 | 0.10 |
| .030 | 0.76 |
| .050 | 1.27 |
| .060 | 1.52 |
| .070 | 1.78 |
| .100 | 2.54 |
| .106 | 2.69 |
| .118 | 3.00 |
| .200 | 5.08 |
| .240 | 6.10 |
| .320 | 8.13 |
| 1.80 | 45.7 |


FIGURE 2. Recommended hole patterns.




Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.





SUBPART A
FLEXIBLE CABLES





SUBPART B
SEMIRIGID CABLES





SUBPART C
90° FLEXIBLE CABLES





SUBPART D
90° SEMIRIGID CABLES




SUBPART E
90° PCB MOUNTING CABLES




SUBPART F
VERTICAL MOUNTING PCB





SUBPART G
SOLDER POSTS TWISTED BRAID

FIGURE 3. Coaxial configurations.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.




| Inches | mm | Inches | mm |
|---|---|---|---|
| .020 | 0.51 | .138 | 3.51 |
| .03 | 0.8 | .139 | 3.53 |
| .063 | 1.60 | .155 | 3.94 |
| .071 | 1.80 | .157 | 3.99 |
| .076 | 1.93 | .158 | 4.01 |
| .079 | 2.01 | .165 | 4.19 |
| .094 | 2.39 | .177 | 4.50 |
| .095 | 2.41 | .185 | 4.70 |
| .100 | 2.54 | .189 | 4.80 |
| .110 | 2.79 | .271 | 6.88 |
| .122 | 3.10 | .303 | 7.70 |
| .126 | 3.20 | .317 | 8.05 |
| | | .374 | 9.50 |

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ± .005 (0.13 mm).

FIGURE 3. Coaxial configurations – Continued.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.





FIGURE 4. Contact and keying arrangements.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.





FIGURE 5. Connector terminations.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.


| Inches | mm | Inches | mm | Inches | mm |
|---|---|---|---|---|---|
| .010 | 0.25 | .063 | 1.60 | .177 | 4.50 |
| .014 | 0.36 | .100 | 2.54 | .200 | 5.08 |
| .020 | 0.51 | .118 | 3.00 | .217 | 5.51 |
| .025 | 0.64 | .126 | 3.20 | .236 | 5.99 |
| .056 | 1.42 | .155 | 3.94 | .490 | 12.45 |
| .062 | 1.57 | .173 | 4.39 | | |

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ± .005 (0.13 mm).
4. Solder tail accepts no. 22 AWG wire.
5. Crimp contact accepts no. 22-26 AWG wire.
6. Contact with .025 $inch^2$ (0.64 $mm^2$) wrappost.


FIGURE 5. Connector terminations - Continued.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.




FIXED MOUNT




FLOATING MOUNT

| Inches | mm | Inches | mm |
|---|---|---|---|
| .004 | 0.10 | .374 | 9.50 |
| .008 | 0.20 | .809 | 20.55 |
| .116 | 2.95 | .900 | 22.86 |
| .187 | 4.75 | 1.618 | 41.10 |
| .197 | 5.00 | 1.800 | 45.72 |

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance is ± .005 (0.13 mm).
4. Floating mount panel thickness .085 (2.15 mm) maximum.

FIGURE 6. Recommended panel cutouts .



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Dimensions and configurations: See figures 1 through 6.

Contact identification: See figure 4.

Contact retention: Coaxial and power: 11.25 pounds minimum.
Signal: 4 pounds minimum.

| Mating and unmating force (per contact): | Coaxial | Power | Signal |
|---|---|---|---|
| (Min) | 7.2 ounces | 3.6 ounces | 0.7 ounce |
| (Max) | 36 ounces | 18 ounces | 3.6 ounces |

Values for each connector to be addition of contacts according to contact type.

Contact resistance: 12 milliohms maximum.

Dielectric withstanding voltage:

Sea level: 1,000 V rms, 60 Hz.

High altitude: 300 V rms, 60 Hz.

Current rating:

Power contacts: 25 amperes at 25°C.

Coaxial contacts: .5 ampere at 25°C.

Signal contacts: 3 amperes at 25°C.

Keying: Moldings and mounting hardware provide 16 or 36 polarizing positions according to choice of 4 or 6 way capability. Keys are constructed in accordance with MIL-DTL-55302/154. Connectors are supplied with hex pins in the “1” and “A” positions, except for 1/4-turn locking styles, which are keyed in “F” and “6” positions. When required, connectors can be easily keyed to desired position by using a simple wrench.

Hood types: In accordance with MIL-DTL-55302/155.

Mounting hardware: In accordance with MIL-DTL-55302/154.


Mating connectors: In accordance with MIL-DTL-55302/150.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.

Part or Identifying Number (PIN): Consists of the letter M, the basic number of the specification sheet, and a dash number compiled as follows:

Example:




Changes from previous issue: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-55302, this document references the following:

MIL-DTL-55302/150
MIL-DTL-55302/154
MIL-DTL-55302/155



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force – 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-4490-000)

Review activities:
Army – AR, AT, AV, CR4, MI
Navy – AS, MC, OS, SH
Air Force – 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:52Z
Check the source to verify that this is the current version before use.