
INCH-POUND
MIL-PRF-55339/29B
w/AMENDMENT 2
28 September 2023
SUPERSEDING
MIL-PRF-55339/29B
w/AMENDMENT 1
15 November 2019

PERFORMANCE SPECIFICATION SHEET

ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, IN-LINE, (WITHIN SERIES SMA PLUG TO SMA PLUG), CLASS 2

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-55339.



Reference	Series	Contact
A	SMA	Pin

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. All undimensioned pictorial representations are for reference purposes only.
4. Interface dimensions shall be in accordance with MIL-STD-348.
5. Three holes .016 (0.41 mm) minimum diameter, equally spaced, are required for safety wiring after mating. Location on coupling nut optional.

FIGURE 1. General configuration jack-plug-jack.

AMSC N/A
FSC 5935
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:06Z
Check the source to verify that this is the current version before use.

DESIGN AND CONSTRUCTION:

General configuration: See figure 1.

Impedance: 50 ohms, nom.

Working voltage: Sea level – 335 Vrms.
70,000 feet – 85 Vrms.

Frequency range: 0 to 18.0 GHz.

Temperature range: -65° to +165°c.

PERFORMANCE

Dimensions: See figures 1.

Center contact retention: Axial force – 6 lb, min.
Torque – Not applicable.

Force to engagement and disengage: Longitudinal force – Not applicable.
Torque – 2 in. lb, max.

Coupling proof torque: 15 in, lbs, min.

Mating characteristics: See MIL-STD-348 for dimensions.

Permeability: <2.0.

Seal:
Pressurized – Not applicable.
Weatherproof – Not applicable.

Insulation resistance: MIL-STD-202-302, test condition B. 5,000 megohms, min.

VSWR: 1.10 + .008 F(GHz) at .5 to 18.0 GHz.

VSWR procedure.

The VSWR shall be measured in accordance with the following procedure or a method acceptable to the Government.

Part should be tested using a Network Analyzer with the Time Domain (TDR) option installed. This is essential to allow the effect of the adapters to be “gated” out. The recommended network analyzer systems include suitable equipment with NIST traceability or equivalent. All gating will be completed in accordance with the procedures stated by the network analyzer manufacturer with the following time domain settings:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:06Z
Check the source to verify that this is the current version before use.

TABLE I. Suggested Time Domain Settings.

Transform Mode 1/	Gate Type	Gate Shape 2/	Start Gate Time (ps)	Stop Gate Time (ps)
Low-pass	Bandpass	Minimum, Normal, Wide	End of Adapter 3/ – Rise Time of Gate 4/	End of Device Under Test + Rise Time of Gate

1/ The low-pass mode will have a higher resolution than the band-pass mode.

2/ Each shape specified will not be smaller than the minimum gate span to ensure the response has the correct start and stop times.

3/ "Port Extension" is also used for detection to move the measurement plane after calibration is complete.

4/ The minimum window is used for best resolution.

5/ The maximum window is used for best dynamic range.

The printer/plotter and the computer should be any unit compatible to the system. The test adapters will utilize the following frequency bands:

Frequency	VSWR
500 MHz	1.055
1 GHz	1.055
5 GHz	1.075
10 GHz	1.100
15 GHz	1.125
18 GHz	1.140
26 GHz	1.180
40 GHz	1.25
50 GHz	1.30
65 GHz	1.375

50-ohm precision air lines may also be used on both sides of the device under test.

Calibration of the system should be performed using the manufacturer's calibration kits and the recommended calibration procedures. The frequency range shall be DC to 65 GHz. The VSWR calibration test setup shall be verified using the manufacturers verification kits. The calibrated system VSWR shall be less than 1.02 + .001F (F in GHZ).

The VSWR of the DUT shall be measured using the procedures described in the manufacturer's operating instructions. The time domain shall then be used to remove the effects of the test adapter with the recommended settings as mentioned above.

The output shall be generated using the appropriate printer/plotter.

RF leakage (total): -60 dB, max, between 2 to 3 GHz, min

RF insertion loss: (.06 $\sqrt{F\ (GHz)}$ dB max tested at 6 GHz).

Durability: 500 cycles minimum at 12 cycles/min maximum. The connector shall meet the mating characteristics and force to engage and disengage requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:06Z
Check the source to verify that this is the current version before use.

Dielectric withstanding: MIL-STD-202-301. Test voltage -1,500 Vrms, min (sea level).

Contact resistance (milliohms, max)

Contact	Initial	After
Center	4.0	6.0
Outer	2.0	Not applicable

Vibration, high frequency: Interruptions – 1 µs, max. MIL-STD-202-204, test condition D.

Shock: MIL-STD-202-213, test condition I.

Thermal shock: MIL-STD-202-107, test condition C.

Moisture resistance: MIL-STD-202-106. 200 megohms, min.

Corona level: Voltage – 250 V, min.
Altitude – 70,000 feet, min.

RF high potential withstanding voltage: RF voltage – 670 Vrms, min.
Frequency – 5 MHz, min.

Salt spray (corrosion): MIL-STD-202-101, test condition B.

Coupling mechanism retention force: 60 lb, min.

Marking: As specified in MIL-PRF-55339.

Part or Identifying Number (PIN):

M55339/29-30101 without safety wire holes, -30001 with safety wire holes
M55339/29-40101 without safety wire holes, -40001 with safety wire holes

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents: In addition to MIL-PRF-55339, this document references the following:

MIL-STD-202-101
MIL-STD-202-106
MIL-STD-202-107
MIL-STD-202-204
MIL-STD-202-213
MIL-STD-202-301
MIL-STD-202-302
MIL-STD-348

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:06Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force – 85
DLA – CC

Preparing activity:
DLA - CC

Review activities:
Army – AR, AT, EA
Navy – AS, MC, OS
Air Force – 19

(Project 5935-2023-077)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:06Z
Check the source to verify that this is the current version before use.