MILITARY SPECIFICATION

PERISCOPE, TANK: M35E1

This amendment forms a part of Military Specification MIL-P-48450A(MU) dated 15 March 1976.

PAGE 3

Paragraph 3.4.3.1 - Delete and substitute:

"3.4.3.1 Vibration "A". This requirement shall be met with the image intensifier tube and reticle projector lamp energized by the application of +24 ± 6.0 VDC to Contact 11733497 (Reference Drawing 11733401). The vibration input to the periscope shall be at the interface of the periscope and mount. Vibration shall be applied along each of three mutually perpendicular axes of the periscope. The vibration shall be shall be sinusoidal as follows:

a. A frequency of 5 Hertz(Hz), the acceleration shall be .5 G ± 10%.

b. During a frequency sweep of 5 to 9 Hz, increase acceleration linearly from .5 G to 1.5 G's ± 10%.

c. During a frequency sweep of 9 to 500 Hz, maintain constant acceleration of 1.5 G's ± 10%.

d. During a frequency sweep of 500 to 9 Hz, maintain constant acceleration of 1.5 G's ± 10%.

e. During a frequency sweep of 9 to 5 Hz, decrease acceleration linearly from 1.5 G's to .5 G ± 10%.

f. At 5 Hz, the acceleration shall be .5 G ± 10%.

The frequency of applied vibration shall be swept logarithmically in 15 minute ± 1 minute sweep cycles for a total of two hours per axis . There shall be no failure or flicker of light emission from the image intensifier tube nor the reticle projector lamp during vibration and the periscope shall show no evidence of physical failure subsequent to vibration. Following the vibration test the persicope shall meet the requirements of 3.6.3.2, 3.6.4.1, 3.6.9, 3.6.2, 3.6.3.1, 3.6.3.1.1, 3.6.3.1.2, 3.6.5, 3.6.6, 3.6.6.1, 3.6.7, 3.6.8, 3.2, 3.1, 3.5 and then each module (see 3.1) shall meet their own respective post-vibration test requirements."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:27Z
Check the source to verify that this is the current version before use.

Paragraph 3.4.3.2 - Delete and substitute:

"3.4.3.2 Vibration "B" - This requirement shall be met with the image intensifier tube and reticle projector lamp energized by the application of +24 ± 6.0 VDC to Contact 11733497 (Reference Drawing 11733401). The vibration input to the periscope shall be at the interface of the periscope and mount. Vibration shall be applied along each of three mutually perpendicular axes of the periscope. The vibration shall be sinusoidal as follows:

a. At a frequency of 5 Hertz(Hz), the acceleration shall be 1.0 G ± 10%.

b. During a frequency sweep of 5 to 500 Hz, maintain constant acceleration of 1.0 G ± 10%.

c. During a frequency sweep of 500 to 5 Hz, maintain constant acceleration of 1.0 G ± 10%.

d. At 5 Hz, acceleration shall be 1.0 G ± 10%.

The frequency of applied vibration shall be swept logarithmically in 15 minute ± 1 minute sweep cycles for a total of 15 minutes ± 1 minute along each of the three mutually perpendicular axes (total vibration time 45 minutes ± 3 minutes). There shall be no failure or flicker of light emission from the image intensifier tube nor the reticle projector lamp during vibration and the periscope shall show no evidence of physical failure subsequent to vibration. Following the vibration test the periscope shall meet the requirements of 3.6.3.2, 3.6.4.1, 3.6.9, 3.6.2, 3.6.3.1, 3.6.1.1, 3.6.3.1.2, 3.6.5, 3.6.6, 3.6.6.1, 3.6.7, 3.6.8, 3.2, 3.1, 3.5 and then each module (see 3.1) shall meet their own respective post-vibration test requirements".

PAGE 4

Paragraph 3.4.3.3 - Delete and substitute:

"3.4.3.3 Shock. This requirement shall be met with the image intensifier tube and reticle projector lamp energized by the application of +24 ± 6.0 VDC to Contact 11733497 (Reference Drawing 11733401). The shock input to the periscope shall be at the interface of the periscope and mount. The periscope shall be subjected to 24 cumulative shocks consisting of three each at 35 G's ± 10%, then 20 G's ± 10% applied in each direction along each of the two mutually perpendidular horizontal axes (all four sides). The shock pulse shall have a half sine wave with a time duration of 3 ± .2 milliseconds. The periscope shall also be subjected to six cumulative shocks consisting of three each at 35 G's ± 10%, then 20 G's ± 10% applied in one direction along the vertical axis (normal operating position of

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:27Z
Check the source to verify that this is the current version before use.

the periscope only). The shock pulse shall have a half sine wave with a time duration of 18 + 3 milliseconds. Subsequent to shock, there shall be no failure or flicker of light emission from the image tube nor the reticle projector lamp. The periscope shall also show no evidence of physical failure. Following the shock test, the periscope shall meet the requirements o 3.6.3.2, 3.6.4.1, 3.6.9, 3.6.2, 3.6.3.1, 3.6.3.1.1, 3.6.3.1.2, 3.6.5, 3.6.6, 3.6.6.1, 3.6.7, 3.6.8, 3.2, 3.1, 3.5 and then each module (see 3.1) shall meet their own respective post-shock test requirements."

PAGE 5

Paragraph 3.6.1.a, Line 1 - Delete "four" and substitute "three".

PAGE 6

Paragraph 3.6.3.1.1, Line 3 - Delete "0.2 mil" and substitute "1.0 mil"

Custodian:

Army-AR

Preparing Activity:

Army-AR

Project No. 1240-A735

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:27Z
Check the source to verify that this is the current version before use.