MILITARY SPECIFICATION

POWER CONTROL C: 10526593

This amendment forms a part of Military Specification MIL-P-60213(MU), dated 4 March 1965.

Paragraph 3.4.3.1, line 3: Delete "(Part No. 10525850)" and substitute "(Part Nos. 9144277 and 10525850)".

Paragraph 3.4.3.2, line 3: Delete "(Part No. 10525850)" and substitute "(Part Nos. 10525850 and 10525855)".

Paragraph 3.4.4.1: Delete first sentence in its entirety.

Following paragraph 4.1.1, add paragraphs 4.1.2, 4.1.2.1 and 4.1.2.2.

"4.1.2 First article (initial production) approval.- The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of three (3) units manufactured in the same manner using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

4.1.2.1 Government testing.- When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.1.2.2 Contractor testing.- When the contractor is responsible for conducting first article approval tests, the sample shall be inspected and a record of this inspection, including certificates of conformance for materials shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection."

Paragraph 4.2.3: Add the following sentence: "No lots shall be accepted until control samples have been satisfactorily tested."

FSC 1220

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:18Z
Check the source to verify that this is the current version before use.

Paragraph 4.3.2: Delete first sentence and substitute:

"The units shall be selected at random by a Government representative as control samples from each three (3) months production or portion thereof as follows:

3 units per first 100 produced
5 units per 200
7 units per 300
9 units per 400
10 units per 500
12 units per 700
15 units per 1000
and 2 units for each 100 items produced in excess of 1000."

Paragraph 4.4.1.1, item 4, Description Column: Delete "reverse current" and substitute "current rating".

Paragraph 4.5.1.3.2: Delete in its entirety and substitute:

"4.5.1.3.2 Operating.- This test shall be conducted in accordance with the humidity test defined in Procedure III of MIL-F-13926, except that the humidity shall be maintained at 92 to 97 percent for the 24 hour period, and the test shall cease at the end of that period (Method 106 of MIL-STD-202 shall be excluded). Throughout the test period, the board shall be capable of performing the tests of 4.5.13 through 4.5.15 to determine compliance with 3.3.4.1. In order to demonstrate this capability, the tests of 4.5.13 and 4.5.15 shall be performed a minimum of once each 6 hours of the 24 hour period. The final test shall be conducted during the final portion of the 24 hour period."

Paragraph 4.5.1.4: Delete in its entirety and substitute:

"4.5.1.4 Salt spray.- This test shall be conducted in accordance with the salt spray test defined in Method 101, Condition B of MIL-STD-202 using a 5 percent salt solution. At the end of the exposure period, salt deposits shall be removed from the board by a gentle wash, not exceeding 30 minutes, in running water not warmer than 100°F, using a soft hair brush or plastic-bristle brush. The board shall then be air dried in a controlled environment at 72° ± 5°F and a relative humidity of 30 to 50 percent for a period of 24 hours. The board shall be inspected visually for any physical damage, then tested in accordance with 4.5.3 through 4.5.15, excluding 4.5.10, to determine compliance with 3.3.6."

Paragraph 4.5.1.5: Delete "3.4.3" and substitute "3.4.7"; delete "4.5.2.2 inclusive" and substitute "4.5.15 inclusive, excluding 4.5.10".

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:18Z
Check the source to verify that this is the current version before use.

Paragraph 4.5.5.1, Table IX, Column C, line 14: Delete "plus 1.2" and substitute "plus 1.6"; Line 16: Delete "plus 0.6" and substitute "plus 0.8".

Table XI: Delete "4.10.2" in three places and substitute "4.4.1.1".

* Table XII: Add to the columns:

"Column A	Column B	Column C
Pin 11B	Pin 28B	VDC minus 1.29 ± 0.13"

Table XX, delete in its entirety and substitute the following:

"TABLE XX

Resistance Value	Ordnance Number	Resistance Value	Ordnance Number
2,200 ohms	10526094	10,000 ohms	10526599
2,700 ohms	10526095	12,000 ohms	10526032
3,300 ohms	10525856	15,000 ohms	10526033
3,900 ohms	10526096	18,000 ohms	10526042
4,700 ohms	10526098	22,000 ohms	10526044
5,600 ohms	10526099	27,000 ohms	10525898
6,800 ohms	10526100	33,000 ohms	10526638
8,200 ohms	10526028	47,000 ohms	10526029"

Paragraph 4.5.12(a), Table XXIII, Column C, line 2: Delete "plus 2.0 Vdc minimum" and substitute "plus 0.5 Vdc minimum".

Paragraph 4.5.12(a), Table XXV, Column C, line 2: Delete "plus 2.0 Vdc minimum" and substitute "plus 0.5 Vdc minimum".

*The outside margin has been marked to indicate where an addition to the previous amendment has been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in this notation. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notation and relationship to the last previous amendment.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A193

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:18Z
Check the source to verify that this is the current version before use.