MIL-R-81628B (AS)
AMENDMENT 2
8 March 1979
SUPERSEDING
AMENDMENT 1
1 MARCH 1976

MILITARY SPECIFICATION

RADIO SET AN/ARC-143B

This amendment forms a part of Military Specification MIL-R-81628B (AS) of 1 April 1974, and has been approved by the Naval Air Systems Command, Department of the Navy.

Page 28, paragraph 3.5.1.5.9.3.1.: Delete and substitute

"3.5.1.5.9.3.1 Level - For a 1000 microvolt signal deviated 20 KHz peak at a modulation rate of 1000 Hz, the FM data output shall be 2.81 volts rms ±1dB. Under service conditions, the FM output shall be 2.8 volts rms +3, -2dB in response to the same input signal at ambient temperatures below 20°C."

Page 28, paragraph 3.5.1.5.9.3.6.: Delete and substitute

"3.5.1.5.9.3.6 Response - From 300 to 3000 Hz, the audio response to an input signal deviated 20 KHz shall not vary more than ±2dB with a reference of 1000 Hz."

Page 31, paragraph 3.5.1.7.1.: Delete and substitute

"3.5.1.7.1 RF Power Output - The transmitter shall be capable of producing into a 50 ohm resistive load 30 watts of AM carrier power, ± 2 db, -0 and 100 watts of FM carrier power, ± 2 db, -0 under standard and service conditions. Automatic level control shall be used to limit the variation in output power to within 2 db peak-to-peak across the frequency band."

Page 33, paragraph 3.5.1.7.6.2.1.: Delete and substitute

"3.5.1.7.6.2.1 Level - The FM modulator shall be adjusted for a peak deviation of ±20 KHz with an input signal level of 2.81 volts rms ± 1 dB at a modulation frequency of 1000 Hz."

Page 33, paragraph 3.5.1.7.6.2.2.1.: Delete and substitute

"3.5.1.7.6.2.2.1 Frequency - From 300 Hz to 3000 Hz, the input signal required to produce 20 KHz deviation shall not vary more than ±2dB from that of a 1000 Hz reference."

Project No. 5821-N139

FSC 5821

Preparing Activity:Navy-AS

Source: https://assist.dla.mil -- Downloaded: 202640-23T05:49Z
Check the source to verify that this is the current version before use.